

CENTAFLEX-A TYPE 1-S

HIGHLY FLEXIBLE INDUSTRIAL COUPLINGS & DIMENSIONAL BLUEPRINT DATA

Description: The CENTAFLEX-A Type 1-S represents a specialized high-elasticity variation incorporating compact flange coupling hubs and optimized adapter pins. Engineered explicitly for dynamic shaft connections within close-proximity spaces, it supports straightforward blind axial plug-in installations while managing high torque spikes and continuous systemic resonances safely.

KEY PERFORMANCE ADVANTAGES

- **Compact Blind Plugging Optimization:** Offers high structural adaptability across a smaller length footprint (\$L_1\$, \$C_1\$), allowing rapid maintenance swaps without decoupling the engine block or prime mover.
- **Elite Shock Absorbing Properties:** Efficiently absorbs heavy alternating torsional load oscillations, safeguarding transmission gearboxes and pump components from early fatigue.
- **Multi-Directional Deflection Capacity:** Neutralizes severe axial displacements and misalignment tolerances smoothly across heavy alternating industrial environments.

DIMENSIONAL SPECIFICATIONS (SIZES 1 - 600)

Below is the complete engineering matrix for the **CENTAFLEX-A Type 1-S** industrial sequence:

Size	Dimensions [mm]										T _K	Y	Mass Moments [kgm ²]		Mass [kg]	
	A	B ₁	C ₁	d _{1max}	d ₃	E	L ₁	M ₁	N ₁	S			J ₁	J ₂	m ₁	m ₂
1	24	7	26	19	56	22	24	M 6	30	2	44	2x180°	0.00004	0.00003	0.06	0.13
2	24	8	32	26	85	20	28	M 8	40	4	68	2x180°	0.00011	0.00016	0.10	0.26
4	28	8	34	30	100	24	30	M 8	45	4	80	3x120°	0.00023	0.00027	0.15	0.35
8	32	10	46	38	120	28	42	M 10	60	4	100	3x120°	0.0007	0.0008	0.29	0.79
12	32	10	46	38	122	28	42	M 10	60	4	100	4x90°	0.0010	0.0008	0.32	0.85
16	42	12	56	48	150	36	50	M 12	70	6	125	3x120°	0.0019	0.0021	0.50	1.26
22	42	12	56	48	150	36	50	M 12	70	6	125	4x90°	0.0026	0.0023	0.60	1.35
25	46	14	61	55	170	40	55	M 14	85	6	140	3x120°	0.0036	0.0025	0.80	1.96
28	46	14	61	55	170	40	55	M 14	85	6	140	4x90°	0.0046	0.0030	0.90	2.10
30	58	16	74	65	200	50	66	M 16	100	8	165	3x120°	0.0083	0.0060	1.3	1.1
50	58	16	74	65	200	50	66	M 16	100	8	165	4x90°	0.0106	0.0072	1.7	1.2
80	65	16	75.5	65	205	61	66	M 16	100	9.5	165	4x90°	0.0119	0.0132	1.7	3.8
90	70	20	88	85	260	62	80	M 20	125	8	215	3x120°	0.0294	0.0213	2.7	2.3
140	70	20	88	85	260	62	80	M 20	125	8	215	4x90°	0.0368	0.0251	3.4	2.6
200	80	20	102	105	300	72	94	M 20	145	8	250	4x90°	0.0596	0.0471	4.2	3.7
250	85	20	108	115	340	77	100	M 20	160	8	280	4x90°	0.091	0.086	5.0	5.5
400	105	28	135	120	370	95	125	M 24	170	10	300	4x90°	0.204	0.154	9.6	8.2
600	125	30	170	140	470	110	155	M 27	200	15	380	4x90°	0.569	0.363	16.5	13.3

* Note: Specifications are subject to continuous refinement and manufacturing tolerance margins.

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited
Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com
Web: www.jinharsh.com