

CENTAFLEX-A TYPE 1

HIGHLY FLEXIBLE INDUSTRIAL COUPLINGS & FULL DIMENSIONAL BLUEPRINT DATA

Description: The CENTAFLEX-A Type 1 configuration features a premium elastomeric coupling hub layout engineered with specific adapter spacing pins (B_1 , C_1 clearances). Optimized for simple blind-fit mounting arrangements, it offers extensive dynamic elasticity along with simplified positioning constraints across heavy multi-shaft generator architectures and pump groups.

KEY PERFORMANCE ADVANTAGES

- **Blind-Fit Mounting Optimization:** Standardized structural parameters ($\$L_1$, $C_1\$$) enable convenient axial plugging during mounting without requiring complex component decoupling.
- **High-Fidelity Vibration Dampening:** Efficiently absorbs extreme torsional shock spikes, extending the operational lifespan of downstream gearboxes and shafts.
- **Broad Misalignment Adaptability:** Handles severe concurrent combinations of radial, axial, and angular shaft displacement anomalies.

DIMENSIONAL SPECIFICATIONS (SIZES 1 - 800)

Below is the calibrated blueprint matrix for the **CENTAFLEX-A Type 1** industrial series line:

Size	Dimensions [mm]													Mass Moments [kgm²]		Mass [kg]			
	A	B ₁	C ₁	d _{1max}	d ₃	E	L ₁	M ₁	N ₁	S	x ₁	x ₂	x ₆	T _K	Y	J ₁	J ₂	m ₁	m ₂
1	24	7	26	19	56	22	24	M 6	30	2	-	-	-	44	2x180°	0.00002	0.00003	0.04	0.13
2	24	8	32	26	85	20	28	M 8	40	4	-	-	-	68	2x180°	0.00009	0.00016	0.08	0.26
4	28	8	34	30	100	24	30	M 8	45	4	-	-	-	80	3x120°	0.00020	0.00027	0.13	0.35
8	32	10	46	38	120	28	42	M 10	60	4	-	-	-	100	3x120°	0.0006	0.0008	0.25	0.79
12	32	10	46	38	122	28	42	M 10	60	4	-	-	-	100	4x90°	0.0007	0.0008	0.28	0.85
16	42	12	56	48	150	36	50	M 12	70	6	5	18	4	125	3x120°	0.0015	0.0021	0.40	1.26
22	42	12	56	48	150	36	50	M 12	70	6	5	18	4	125	4x90°	0.0019	0.0023	0.50	1.35
25	46	14	61	55	170	40	55	M 14	85	6	5	18	5	140	3x120°	0.0027	0.0042	0.60	1.96
28	46	14	61	55	170	40	55	M 14	85	6	5	18	5	140	4x90°	0.0034	0.0047	0.70	2.10
30	58	16	74	65	200	50	66	M 16	100	8	5	20	5	165	3x120°	0.0065	0.0100	1.0	3.4
50	58	16	74	65	200	50	66	M 16	100	8	5	20	5	165	4x90°	0.0081	0.0112	1.3	3.4
80	65	16	75.5	65	205	61	66	M 16	100	9.5	5	20	5	165	4x90°	0.0095	0.0132	1.4	3.8
90	70	20	88	85	260	62	80	M 20	125	8	8	25	5	215	3x120°	0.0237	0.0327	2.2	6.3
140	70	20	88	85	260	62	80	M 20	125	8	8	25	5	215	4x90°	0.0286	0.0364	2.7	6.6
200	80	20	102	105	300	72	94	M 20	145	8	8	25	5	250	4x90°	0.0481	0.0696	3.4	9.3
250	85	20	108	115	340	77	100	M 20	160	8	10	30	6	280	4x90°	0.081	0.121	4.5	12.7
400	105	28	135	120	370	95	125	M 24	170	10	10	40	6	300	4x90°	0.155	0.212	7.5	18.9
600	125	30	170	140	470	110	155	M 27	200	15	10	60	5	380	4x90°	0.464	0.502	13.8	32.1
800	145	22	182	165	545	128	165	M 22	230	17	-	-	-	370/470	4x90°	0.586	0.888	20.1	49.2

* Note: All operational measurements are subject to standard application tolerances.

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited
Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com
Web: www.jinharsh.com