

CENTAFLEX-A TYPE 2-S

HIGHLY FLEXIBLE INDUSTRIAL COUPLINGS & DUAL-HUB COMPACT SPECIFICATIONS

Description: The CENTAFLEX-A Type 2-S design integrates an advanced dual-hub adapter profile with compressed distance dimensions (L_2 , L_3 spans). Tailored specifically for specialized high-speed multi-shaft arrangements, it yields elite torsional vibration dampening alongside highly stable structural torque isolation under constrained envelope constraints.

KEY PERFORMANCE ADVANTAGES

- **Compact Dual-Hub Design:** Optimizes clearance profiles to facilitate robust overlapping shaft fittings within heavily restricted coaxial housing spaces.
- **High alternating load capacity:** Built with premium precompressed rubber variants to manage ongoing multi-directional misalignment spikes effortlessly.
- **Resonance Tuning Stability:** Reliably decouples continuous torsional oscillation spikes from downline gearboxes, ensuring extended system operational lifespans.

DIMENSIONAL SPECIFICATIONS (SIZES 1 - 600)

Below is the complete engineering matrix extracted for the **CENTAFLEX-A Type 2-S** series layout:

Size	Dimensions [mm]											Mass Moments [kgm²]		Mass [kg]		
	A	B	d _{1max}	d _{2max}	d ₃	E	L ₁	L ₂	L ₃	N ₁	N ₂	S	J ₁	J ₂	m ₁	m ₂
1	24	7	19	25	56	22	24	24	50	30	36	2	0.00011	0.00003	0.24	0.13
2	24	8	26	38	85	20	28	28	60	40	55	4	0.00052	0.00016	0.57	0.26
4	28	8	30	45	100	24	30	30	64	45	65	4	0.00102	0.00027	0.83	0.35
8	32	10	38	55	120	28	42	42	88	60	80	4	0.0029	0.00008	1.63	0.79
12	32	10	38	55	122	28	42	42	88	60	80	4	0.0032	0.0008	1.66	0.85
16	42	12	48	70	150	36	50	50	106	70	100	6	0.0084	0.0021	2.96	1.26
22	42	12	48	70	150	36	50	50	106	70	100	6	0.0091	0.0023	3.0	1.35
25	46	14	55	85	170	40	55	55	116	85	115	6	0.0156	0.0042	4.13	1.96
28	46	14	55	85	170	40	55	55	116	85	115	6	0.0165	0.0047	4.2	2.10
30	58	16	65	100	200	50	66	66	140	100	140	8	0.0371	0.0100	7.1	3.4
50	58	16	65	100	200	50	66	66	140	100	140	8	0.0393	0.0112	7.5	3.4
80	65	16	65	100	205	61	66	66	141.5	100	140	9.5	0.0406	0.0132	7.5	3.8
90	70	19	85	110	260	62	80	80	168	125	160	8	0.1155	0.0327	14.1	6.3
140	70	19	85	110	260	62	80	80	168	125	160	8	0.1225	0.0364	14.7	6.6
200	80	19	105	110	300	72	94	90	192	145	160	8	0.1996	0.0696	19.0	9.3
250	85	19	115	130	340	77	100	100	208	160	195	8	0.350	0.121	27.0	12.7
400	105	25	120	140	370	95	125	125	260	170	200	10	0.643	0.212	40.0	18.9
600	125	28	140	180	470	110	155	155	325	200	280	15	1.914	0.502	80.2	32.1

* Note: Structural traits comply with standardized industrial engineering tolerances.

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited
Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com
Web: www.jinharsh.com