

CENTAFLEX-A TYPE 2

HIGHLY FLEXIBLE INDUSTRIAL COUPLINGS & DUAL-HUB DIMENSIONAL SPECIFICATIONS

Description: The CENTAFLEX-A Type 2 layout features an enhanced dual-flanged hub architecture engineered to span extended distance spaces (L_2, L_3 clearances). Outfitted with deep complementary guide bores (d_{1max}, d_{2max}), it delivers exceptional torque balancing and vibration damping stability across severe dual-shaft adapter interfaces.

KEY PERFORMANCE ADVANTAGES

- **Dual-Hub Geometry Integration:** Provides optimized dual clearance bores (N_1, N_2) allowing secure overlapping connections onto independent primary and secondary industrial shafts.
- **Superior Torsional Stiffness Balancing:** Dampens heavy rotating vibration waves and natural resonance spikes across high-load pump modules and generator drive systems.
- **Extensive Multi-Directional Misalignment Mitigation:** Easily accommodates combined severe radial, axial, and angular shaft displacement variances under continuous operations.

DIMENSIONAL SPECIFICATIONS (SIZES 1 - 800)

Below is the official recorded blueprint matrix for the **CENTAFLEX-A Type 2** configuration sequence:

Size	Dimensions [mm]											Mass Moments [kgm²]		Mass [kg]		
	A	B	d _{1max}	d _{2max}	d ₃	E	L ₁	L ₂	L ₃	N ₁	N ₂	S	J ₁	J ₂	m ₁	m ₂
1	24	7	19	25	56	22	24	24	50	30	36	2	0.00009	0.00003	0.22	0.13
2	24	8	26	38	85	20	28	28	60	40	55	4	0.00050	0.00016	0.55	0.26
4	28	8	30	45	100	24	30	30	64	45	65	4	0.00099	0.00027	0.81	0.35
8	32	10	38	55	120	28	42	42	88	60	80	4	0.0028	0.0008	1.59	0.79
12	32	10	38	55	122	28	42	42	88	60	80	4	0.0029	0.0008	1.62	0.85
16	42	12	48	70	150	36	50	50	106	70	100	6	0.0080	0.0021	2.86	1.26
22	42	12	48	70	150	36	50	50	106	70	100	6	0.0084	0.0023	2.90	1.35
25	46	14	55	85	170	40	55	55	116	85	115	6	0.0147	0.0042	3.93	1.96
28	46	14	55	85	170	40	55	55	116	85	115	6	0.0153	0.0047	4.00	2.10
30	58	16	65	100	200	50	66	66	140	100	140	8	0.0353	0.0100	6.8	3.4
50	58	16	65	100	200	50	66	66	140	100	140	8	0.0368	0.0112	7.1	3.4
80	65	16	65	100	205	61	66	66	141.5	100	140	9.5	0.0382	0.0132	7.2	3.8
90	70	19	85	110	260	62	80	80	168	125	160	8	0.1098	0.0327	13.6	6.3
140	70	19	85	110	260	62	80	80	168	125	160	8	0.1143	0.0364	14.0	6.6
200	80	19	105	110	300	72	94	90	192	145	160	8	0.1881	0.0696	18.2	9.3
250	85	19	115	130	340	77	100	100	208	160	195	8	0.341	0.121	26.5	12.7
400	105	25	120	140	370	95	125	125	260	170	200	10	0.594	0.212	37.9	18.9
600	125	28	140	180	470	110	155	155	325	200	280	15	1.810	0.502	77.5	32.1
800	145	28	165	230	545	128	165	165	347	230	325	17	2.652	0.888	95.3	49.2

* Note: Component dimensional traits are subject to standard manufacturing tolerance guidelines.

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited
Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com
Web: www.jinharsh.com