

CENTAFLEX-A TYPE 3

HIGHLY FLEXIBLE FLYWHEEL COUPLINGS & COMPLETE SAE J620 SPECIFICATIONS

Description: The CENTAFLEX-A Type 3 configuration is explicitly engineered for direct adaptation onto standardized engine flywheels complying with industrial **SAE J620** footprints. Outfitted with robust flange backing setups (\$D_J\$, \$D_A\$, \$D_T\$), it acts as a premier dynamic link to dampen intense crankshaft torsional stress oscillations and eliminate angular resonance variations across high-capacity drive applications.

DIMENSIONAL SPECIFICATIONS (SIZES 8 - 90)

Size	SAE J620	Dimensions [mm]												Z	Dimensions [mm]			Mass Moments [kgm²]		Mass [kg]	
		A	B	C ₁	C ₂	C ₃	d _{1max}	d ₃	D _J	D ₂	D _A	D _T	E		L ₁	N ₁	S	J ₁	J ₂	m ₁	m ₂
8	6.5	32	10	46	6	52	38	120	180	9	215.9	200	6x60°	28	42	60	4	0.0135	0.0008	2.45	0.79
	7.5				6	52			190		241.3	222.3	8x45°					0.0198		2.95	
12	6.5	32	10	46	6	52	38	122	180	9	215.9	200	6x60°	28	42	60	4	0.0136	0.0008	2.48	0.85
	7.5				6	52			190		241.3	222.3	8x45°					0.0135		2.48	
16	6.5	42	12	56	6	62	48	150	180	9	215.9	200	6x60°	36	50	70	6	0.0155	0.0021	2.9	1.26
	7.5				6	62			190		241.3	222.3	8x45°					0.0224		3.5	
22	6.5	42	12	56	6	62	48	150	180	9	215.9	200	6x60°	36	50	70	6	0.0157	0.0023	3.9	1.35
	7.5				6	62			190		241.3	222.3	8x45°					0.0228		4.5	
25	7.5	46	14	61	6	67	55	170	190	9	241.3	222.3	6x60°	40	55	85	6	0.0255	0.0042	4.5 4.6	1.96
	8				6	67			200	11	263.5	244.5	6x60°					0.0338			
	10				10	71			260	11	314.3	295.3	8x45°					0.0897			
28	7.5	46	14	61	6	67	55	170	190	9	241.3	222.3	6x60°	40	55	85	6	0.0324	0.0047	8.7 10.7	2.10
	8				6	67			200	11	263.5	244.5	6x60°					0.0345			
	10				10	71			260	11	314.3	295.3	8x45°					0.0904			
30	10	58	16	74	10	84	65	200	270	11	314.3	295.3	8x45°	50	66	100	8	0.1039	0.0100	8.9	3.40
	11.5				10	84			310		352.4	333.4	8x45°					0.1568		10.9	
50	10	58	16	74	10	84	65	200	270	11	314.3	295.3	8x45°	50	66	100	8	0.1054	0.0112	9.0	3.40
	11.5				10	84			310		352.4	333.4	8x45°					0.1583		11.0	
80	10	65	16	75.5	10	85.5	65	205	270	11	314.3	295.3	8x45°	61	66	100	9.5	0.1068	0.0132	10.2	3.80
	11.5				10	85.5			310		352.4	333.4	8x45°					0.1597		12.6	
90	10	70	19	88	10	98	85	260	270	11	314.3	295.3	8x45°	62	80	125	8	0.1292	0.0327	10.7	6.30
	11.5				10	98			310		352.4	333.4	8x45°					0.1882		13.1	

DIMENSIONAL SPECIFICATIONS (SIZES 140 - 800)

Size	SAE J620	Dimensions [mm]												Z	Dimensions [mm]			Mass Moments [kgm ²]		Mass [kg]	
		A	B	C ₁	C ₂	C ₃	d _{1max}	d ₃	D _J	D ₂	D _A	D _T	E		L ₁	N ₁	S	J ₁	J ₂	m ₁	m ₂
140	10				10	98			270	11	314.3	295.3	8x45°					0.1337			
	11.5	70	19	88	10	98	85	260	310	11	352.4	333.4	8x45°	62	80	125	8	0.1931	0.0364	10.7	13.1
	14				10	98			405	13	466.7	438.2	8x45°					0.5450			6.6
200	11.5	80	19	102	10	112	105	300	310	11	352.4	333.4	8x45°	72	94	145	8	0.2116	0.0696	13.8	22.4
	14				10	112			405	13	466.7	438.2	8x45°					0.5639			9.3
250	14	85	19	108	10	118	115	340	405	13	466.7	438.2	8x45°	77	100	160	8	0.533	0.121	21.3	12.7
400	14	105	25	135	10	145	120	370	405	13	466.7	438.2	8x45°	95	125	170	10	0.698	0.212	27.1	18.9
600	18	125	28	170	20	190	140	470	450	17	571.5	542.9	6x60°	110	155	200	15	2.234	0.502	56.6	77.3
	21				20	190			560		673.1	641.4	12x30°					4.055			32.1
800	21	145	28	182	15	197	165	545	560	17	673.1	641.4	12x30°	128	165	230	17	3.325	0.888	66.9	49.2

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited
 Authorized India Partner: CENTA Power Transmission | Regal Rexnord

Email: crm@jinharsh.com
Web: www.jinharsh.com