

CENTAFLEX-A TYPE G

HIGHLY FLEXIBLE CARDAN / SPACER COUPLINGS & DIMENSIONAL SPECIFICATIONS

Description: The CENTAFLEX-A Type G configuration is an elongated spacer coupling setup engineered specifically for bridging variable shaft spans (*L* variants). Utilizing a multi-joint design with integrated companion flanges, it provides absolute torsional oscillation dampening over long distances, making it highly effective for cardan-style drive tracks and heavy hydraulic machinery alignments.

KEY PERFORMANCE ADVANTAGES

- **Customizable Variable Distance Spanning:** The spacer length (\$L\$) is fully adaptable to custom system configurations, enabling long coaxial bridges without critical vibration risks.
- **High Deflection Absorption:** Dual elastomeric elements isolate severe structural misalignments across parallel, angular, and axial vectors.
- **Systemic Resonance Protection:** Safely tunes away critical engine frequency build-ups, protecting high-capacity gearboxes, industrial pumps, and marine tracks.

DIMENSIONAL SPECIFICATIONS (SIZES 1 - 600)

Below is the complete engineering matrix compiled for the **CENTAFLEX-A Type G** spacer coupling series:

Size	Dimensions [mm]											
	A	B	d _{2max}	d ₃	d _{4max}	L	L ₂	L ₄	N ₁	N ₂	N ₃	S
1	24	7	25	56	25	*	24	24	30	36	36	2
2	24	8	38	85	38	*	28	28	40	55	55	4
4	28	8	45	100	45	*	30	30	45	65	65	4
8	32	10	55	120	55	*	42	42	60	80	80	4
12	32	10	55	122	55	*	42	42	60	80	80	4
16	42	12	70	150	70	*	50	50	70	100	100	6
22	42	12	70	150	70	*	50	50	70	100	100	6
25	46	14	85	170	85	*	55	55	85	115	115	6
28	46	14	85	170	85	*	55	55	85	115	115	6
30	58	16	100	200	100	*	66	66	100	140	140	8
50	58	16	100	200	100	*	66	66	100	140	140	8
80	65	16	100	205	100	*	66	66	100	140	140	9.5
90	70	19	110	260	110	*	80	80	125	160	160	8
140	70	19	110	260	110	*	80	80	125	160	160	8
200	80	19	110	300	110	*	90	90	145	160	160	8
250	85	19	130	340	130	*	100	100	160	195	195	8
400	105	25	140	370	140	*	125	125	170	200	200	10
600	125	28	180	470	180	*	155	155	200	280	280	15

* Dimension L complies with customer-defined specifications.
Note: Mass moments of inertia and total mass listings are available upon direct corporate request.

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited

Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com

Web: www.jinharsh.com