

CENTAFLEX-B Flexible Link Shafts

Type B-G and B-H-G Flexible U/J Spacer Shafts | Industrial Pump Components

PRODUCT OVERVIEW & EXTENSION SCOPE

The **CENTAFLEX-B Bauform B-G (and B-H-G)** is an extended variable-length spacer coupling system featuring an integrated central tube configuration. Engineered specifically for centrifugal pump drives and applications matching standard **DIN 740** guidelines, it features drop-out removable center sections to simplify seal replacement and machine maintenance without requiring the realignment of driving or driven components.

KEY APPLICATION ENGINEERING BENEFITS

- **ISO & DIN 740 Dimensional Matching:** Standardized lengths (\$L_3^{**}\$, \$L_4^{**}\$) correspond precisely to standardized centrifugal pump spacer envelopes.
- **Removable Center Spacer:** Radially split elements allow quick plug-in replacement of the flexible inserts, reducing plant downtime.
- **High Variable Misalignment Tolerance:** Dual articulation planes handle large parallel and angular offsets while protecting connected pump packing boxes or mechanical seals from stress.

TECHNICAL DIMENSIONS & SPECIFICATIONS

Dimensional properties and geometric metrics catalog for standard CENTAFLEX-B spacer configurations.

Size Grösse	d ₁ min [mm]	d ₁ max [mm]	d ₃ [mm]	E [mm]	L ₁ [mm]	N [mm]	R [mm]	S ±1 [mm]	L ₃ * [mm]	L ₄ * [mm]	Order Code Bestellbezeichnung
72	9	30	72	14	28	50	45	6	100	140	CF-B-(H)-72-G-L=*
76	12	30	76	16	30	50	45	6	100	140	CF-B-(H)-76-G-L=*
98	12	38	98	24	42	61	60	6	100	140	CF-B-(H)-98-G-L=*
120	15	48	120	28	50	71	70	6	100	140	CF-B-(H)-120-G-L=*
138	15	55	138	30	55	86	85	6	140	180	CF-B-(H)-138-G-L=*
165	20	65	165	36	65	100	100	8	180	250	CF-B-(H)-165-G-L=*
185	30	80	185	45	80	115	115	10	180	250	CF-B-(H)-185-G-L=*

* The measurements L₃ and L₄ correspond to ISO dimensions for couplings with removable spacers for centrifugal pump drives.
* Die Maße L₃ und L₄ entsprechen den genormten Abmessungen für Kupplungen mit ausbaubarem Zwischenstück für Kreiselpumpenantriebe nach DIN 740.
Note: The measurement L denotes non-standard lengths. Please always state the measurement required (L₃, L₄ or L) on inquiries or orders. Dimensions in [mm].

Procurement, Boring Retrofits & Technical Engineering (India):

For finished bore modifications, customized non-standard spacer tube lengths (\$L\$), or formal quotations, please contact:

Jinharsh Industrial Solutions Private Limited
Email: crm@jinharsh.com | Web: www.jinharsh.com