

CENTAFLEX-B Taper Bush Couplings

Type B-T and B-H-T with Taper Bush Integration | Hubs A-B, A-A, and B-B

PRODUCT OVERVIEW & TAPER LOCKING SYSTEM

The **CENTAFLEX-B Taper Bush Variant (Bauform B-T / B-H-T)** integrates the highly resilient torsional dampening capabilities of the standard series with the operational convenience of a standardized locking mechanism. Designed to optimize component replacement, this variant utilizes standard industrial taper bushes, allowing secure, backlash-free mounting onto commercial shafts without the need for specialized custom boring or matching tooling configurations.

VERSATILE MODULAR HUB CONFIGURATIONS

To accommodate diverse mounting envelopes and shaft combinations, this series features three distinct interlocking hub pairings:

- **Hubs / Nabe A-B:** Combines an internally mounted taper locking mechanism with an extended outward-facing shoulder profile.
- **Hubs / Nabe A-A:** Utilizes dual inward-facing taper locking bush mechanisms for ultra-compact axial spatial layouts.
- **Hubs / Nabe B-B:** Employs dual outward-protruding shoulder configurations to handle extended keyway engagements cleanly.

TECHNICAL DIMENSIONS & SPECIFICATIONS

Dimensional parameters, taper bush numbering assignments, and geometric metrics catalog for Type B-T configurations.

Size Grösse	d ₃ [mm]	N [mm]	S ±1 [mm]	Hub / Nabe A		Hub / Nabe B		L _A [mm]	L _B [mm]	L _{AB} [mm]	L _{AA} [mm]	L _{BB} [mm]	L _T [mm]	E _A [mm]	E _B [mm]	Order Code Bestellbezeichnung
				bush	d ₁ range	bush	d ₂ range									
72	72	50	6	—	—	1108	10–28	—	35	—	—	76	22	—	21	CF-B-(H)-72-T*
76	76	50	6	—	—	1108	10–28	—	35	—	—	76	22	—	21	CF-B-(H)-76-T*
98	98	61	6	1108	10–28	1210	11–32	22,5	40	68,5	51	86	25	4,5	22	CF-B-(H)-98-T*
120	120	71	6	1210	11–32	1610	14–42	26	43	75	58	92	25	4	21	CF-B-(H)-120-T*
138	138	86	6	1610	14–42	2012	18–50	26	52	84	58	110	32	1	27	CF-B-(H)-138-T*

* Please insert the required hub type combination, e.g. A-B, A-A or B-B into the order suffix placeholder.
* Hier gewünschte Nabenbauform einsetzen, z.B. A-B, A-A oder B-B.
Note: Please state required finish bore d₁ and d₂. Tolerance H7, keyway according to DIN 6885/1. Otherwise, hubs are supplied prebored. We reserve the right to alter details and dimensions without notice. Dimensions in [mm].

Procurement, Bush Selections & Technical Engineering Support (India):

For finished bore custom tolerance checks (H7), matching keyway positioning (DIN 6885/1), or quick-ship taper locking bush supply, contact:

Jinharsh Industrial Solutions Private Limited

Email: crm@jinharsh.com | Web: www.jinharsh.com