

CENTAFLEX-CO Series Couplings

Highly Durable Torsional Flywheel Couplings / Flanges to SAE J620

ROBUST FLYWHEEL INTEGRATION

The CENTAFLEX-CO series features heavy-duty elastomeric elements optimized to establish robust connections with diesel and gas engine flywheels matching standard **SAE J620** parameters. Built for high operational durability within small to medium packaging configurations, these systems isolate harmful structural resonance spikes and safely manage compound alignment errors to shield secondary equipment like multi-pump drives, auxiliary gearboxes, and generator components.

KEY APPLICATION ENGINEERING BENEFITS

- **SAE J620 Matching:** Drop-in alignment options tailored for 6½", 7½", 8", and 10" engine flywheel mount configurations.
- **Advanced Vibration Damping:** High-performance compression element block setups mitigate torsional stress spikes, minimizing mechanical wear.
- **Compact Assembly Dimensions:** Space-efficient hub configurations (\$L^{*}\$) enable straightforward housing installations within crowded engine compartments.

DIMENSIONS & TECHNICAL DATA

Exact physical measurements, mass criteria, and structural inertia profiles for standard CENTAFLEX-CO assemblies.

size Grösse	SAE J620	A [mm]	B [mm]	C ₁ [mm]	C ₂ [mm]	E [mm]	d ₁ max. [mm]	d ₂ [mm]	L* [mm]	N [mm]	weight m [kg]	Moments of inertia J [kgm²]	
												J _{pri}	J _{sec}
35	6½"	36	12	12	38	152	48	50	40	60	1,58	0,0040	0,0001
35	7½"	36	12	12	38	152	48	50	40	60	1,66	0,0059	0,0001
35	8"	36	12	12	38	152	48	50	40	60	1,75	0,0082	0,0001
40	6½"	36	12	12	38	152	48	50	40	60	1,68	0,0041	0,0002
40	7½"	36	12	12	38	152	48	50	40	60	1,76	0,0060	0,0002
40	8"	36	12	12	38	152	48	50	40	60	1,85	0,0083	0,0002
45	8"	43	12	12	48	172	55	60	50	70	2,52	0,0095	0,0003
50	8"	43	12	12	48	172	55	60	50	70	2,61	0,0096	0,0004
55	8"	56	12	12	60	216	60	65	62	80	3,65	0,0131	0,0006
55	10"	56	12	12	60	216	60	65	62	80	3,90	0,0206	0,0006
60	8"	56	12	12	60	216	60	65	62	80	3,80	0,0135	0,0009
60	10"	56	12	12	60	216	60	65	62	80	4,05	0,0209	0,0009

* Standard hub length shown; alternative hub lengths are fully customizable and available upon inquiry.
* Standardnabenlänge, abweichende Längen sind lieferbar.
Engineering Note: Dimensional parameters align with standard application configurations. Precise shaft tolerances and custom finished bore configurations should be coordinated with our application engineering division prior to installation.

Procurement, Retrofitting & Custom Engineering Support (India):

For specialized engineering assessments, custom dynamic torsional values, or procurement inquiries, contact:
Jinharsh Industrial Solutions Private Limited
Email: crm@jinharsh.com | Web: www.jinharsh.com