

CENTAFLEX-H

TORSIONALLY STIFF & HIGHLY FLEXIBLE INDUSTRIAL COUPLINGS

Product Overview: The CENTAFLEX-H series consists of specialized, torsionally stiff yet components-flexible couplings designed primarily for diesel-driven hydrostatic drives, main pump systems, and complex hydraulic building tracks. Engineered to operate cleanly above critical resonance speeds, its premium material formulation controls progressive torsional stiffness criteria while maintaining minor structural installation margins.

KEY PERFORMANCE ADVANTAGES

- Multi-Bauform Structural Adaptation:** Readily adaptable across distinct assembly configurations, including Type 1 (standard flanged), Type 2 (dual hub spaces), Type 3 (flywheel configuration), and Type 4 formats.
- Progressive Torsional Stiffness Tuning:** Features carefully mapped variable load values ($\$C_{\{Tdyn\}}$) to securely shift dangerous shaft vibration peaks outside active running zones.
- High Thermal & Environmental Stability:** Formulated to maintain reliable operational properties under continuous elevated operating temperatures within heavy machine compartments.

TECHNICAL SPECIFICATIONS & PERFORMANCE DATA (SIZES 8 - 400)

Below is the official recorded data matrix for the CENTAFLEX-H series:

Size Grösse	Nominal Torque	Maximum Torque	Max Speed	Dynamic Torsional Stiffness ($\$C_{\{Tdyn\}}$ imes $10^4\$$) [Nm/rad]				Relative Damping
	T_{KN} [Nm]	T_{Kmax} [Nm]	n_{max} [min ⁻¹]	$0.25\ T_{KN}$	$0.50\ T_{KN}$	$0.75\ T_{KN}$	$1.0\ T_{KN}$	ψ^p
8	100	280	6500	0,65	0,84	1,3	2,3	0,5
16	200	560	5500	1,7	2,2	2,9	3,6	0,5
25	350	875	5000	3,2	5,3	8,0	12,0	0,5
30	500	1400	4000	3,5	4,4	6,0	8,8	0,5
50	800	2000	4000	6,7	11,5	16,5	26,2	0,5
90	950	2200	4000	11,6	16,1	21,0	35,0	0,5
110	1200	2500	4000	15,5	22,5	29,0	40,0	0,5
140	1600	4000	3600	17,2	23,0	29,5	44,0	0,5
160	2000	4000	3600	26,4	38,1	50,2	73,0	0,5
400	4000	10000	2500	80,9	131,0	188,0	275,0	0,5

Note: Torque ratings are specified in Newton-meters [Nm]. Dynamic torsional stiffness values are expressed as $\$C_{\{Tdyn\}}$ imes $10^4\$$ [Nm/rad].

PROCUREMENT, CONFIGURATION FITTING & TORSIONAL VIBRATION ANALYSIS SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited

Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com

Web: www.jinharsh.com