

CENTAFLEX-X SERIES

HIGHLY FLEXIBLE SHAFT COUPLINGS & MULTI-CONFIGURATION DIMENSIONS

Product Description: The CENTAFLEX-X series features high-elasticity industrial couplings uniquely built to optimize versatile geometry setups including **X-1 / X-1-S** standard flanges, **X-2 / X-2-S** dual-hub variants, and **X-G / X-G-S** extended spacer combinations. Purpose-engineered for zero-backlash torque transmission, it isolates continuous alternating load stress waves and accommodates intense multi-directional shaft misalignments.

KEY CONFIGURATION ADVANTAGES

- **X-1 / X-1-S Integration:** Short, compact profile configuration featuring specialized bolt clearances (\$M\$) for rapid space-saving adapter assemblies.
- **X-2 / X-2-S Integration:** Outfitted with dual guide hub extensions supporting broad minimum and maximum shaft bore adaptability (\$d_1, d_2\$).
- **X-G / X-G-S Integration:** Extended cardan/spacer assembly format optimized to bridge long distance configurations (\$L_4, L_5, L_6\$) safely while tuning out harmonic engine frequencies.

TECHNICAL SPECIFICATIONS & BAUGROESSEN MATRIX

Below is the complete architectural dimensional layout for the **CENTAFLEX-X Sizes 1 to 90**:

CF-X Size	A	B	C	d ₁		d ₂		d ₃	d ₄	F	L ₁	L ₂	L ₃	L ₄ *	L ₅ *	L ₆	S	M	N ₁	N ₂	R	T _K / Division
				min	max	min	max															T _K / Teilung
1	18	7	25	8	19	8	25	56	57	12	24	24	49	100	140	to be stated upon order Bitte bei Bestellung angeben	1	M6	30	36	30	44 / 2x180°
2	24	8	32	10	28	12	38	85	88	14	28	28	60	100	140		4	M8	40	55	40	68 / 2x180°
4	25	8	32.5	12	30	15	45	100	100	14.5	30	30	62.5	100	140		2.5	M8	45	65	45	80 / 3x120°
8	30	10	45	12	38	18	55	120	125	17	42	42	87	100	140		3	M10	60	80	60	100 / 3x120°
16	35	12	53	15	48	20	70	150	155	21	50	50	103	100	140		3	M12	70	100	70	125 / 3x120°
25	40	14	58	15	55	20	85	170	175	23	55	55	113	140	180		3	M14	85	115	85	140 / 3x120°
30	50	16	71	20	65	25	100	200	205	30	66	66	137	140	180		5	M16	100	140	100	165 / 3x120°
90	65	19	90	30	85	30	110	260	260	34	80	80	170	-	-		10	M20	125	160	125	215 / 3x120°

* Structural metrics \$L_4\$ and \$L_5\$ adapt to standard technical defaults. Dimension \$L_6\$ must be finalized based on customer specification profiles.
Note: Exact mass moments of inertia parameters are readily accessible upon direct corporate validation.

PROCUREMENT, CONFIGURATION FITTING & VIBRATION ANALYSIS SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited
Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com
Web: www.jinharsh.com