

CENTALINK

HIGH-FLEXIBILITY LINK COUPLINGS & DRIVE SHAFT SYSTEMS

Product Description: The CENTALINK series comprises premier, highly flexible link couplings and intermediate drive shafts designed for demanding power transmission tasks. Built to accommodate immense misalignments—specifically across long spanning links—its segmented arrangement allows outstanding isolation of torsional stress fields and natural frequency resonance tuning.

KEY PERFORMANCE ADVANTAGES

- **Exceptional Displacement Tolerance:** Offers deep relief across significant axial, radial, and angular shaft displacement spans without inducing heavy reaction loads.
- **Adaptable Tube Spanning:** Highly scalable dynamic configurations allow integration with long customized structural tube links (\$ ext{C}_{ ext{tube}}\$ parameters).
- **Zero Backlash Performance:** Segmented link components ensure a highly uniform, constant velocity layout optimized for heavy industrial gearboxes and marine thrust systems.

TECHNICAL SPECIFICATIONS & PERFORMANCE MATRIX

Below is the updated performance tracking matrix compiled for the **CENTALINK Sizes 48 to 88** (omitting non-quantified spatial displacement criteria):

CENTALINK Size	Nominal Torque	Max. Torque	Continuous Vibr. Torque at 10 Hz	Dyn. Torsional Stiffness*		Allowable Axial Shaft Displ.	Axial Stiffness	Angular Stiffness (per linkset)	Max. Speed
	[kNm]	[kNm]	[kNm]	of links [kNm/rad]	of tube [kNm/rad]	[mm]	[kN/mm]	[kNm/grad]	[min ⁻¹]
48	3,3	8,25	1,32	400	305	± 20	0,11	0,05	2400
50	4,0	10,00	1,60	580	976	± 20	0,11	0,07	2400
55	5,0	12,50	2,00	770	976	± 20	0,14	0,08	2400
60	6,5	16,25	2,60	970	976	± 20	0,18	0,12	2400
65	7,5	18,75	3,00	1300	1190	± 20	0,18	0,15	2300
67	9,0	22,50	3,60	1800	2370	± 20	0,18	0,22	2300
68	11,0	27,50	4,40	2200	2370	± 20	0,22	0,26	2100
69	15,5	38,75	6,20	3900	4150	± 20	0,25	0,40	2100
70	16,0	40,00	6,40	2800	2370	± 26	0,26	0,36	2100
71	20,5	51,25	8,20	6000	4150	± 26	0,29	0,74	2100
72	25,0	62,50	10,00	4500	6650	± 26	0,31	0,58	1800
75	30,0	75,00	12,00	7000	10300	± 26	0,37	0,92	1800
76	43,0	107,50	17,20	12500	26350	± 26	0,43	1,44	1800
77	58,0	145,00	23,20	21000	54500	± 26	0,49	2,45	1500
78	44,0	110,00	17,60	12500	10300	± 36	0,44	1,14	1500
80	62,0	155,00	24,80	20000	12600	± 36	0,55	2,00	1500
84	95,0	237,50	38,00	40000	54500	± 36	0,65	4,00	1300
86	125,0	312,50	50,00	58000	54500	± 36	0,76	6,10	1200
88	150,0	375,00	60,00	76000	54500	± 36	0,87	8,10	1100

* Dynamic Torsional Stiffness calculations correspond to a standard tube length *L* in [mm] based on the sizing parameters:
 $C_{Tdyn} = C_{links} + C_{L}(C_{tube})$ $C_{Tdyn} = C_{links} \cdot C_{tube} \cdot L \cdot C_{links} + C_{tube}$

PROCUREMENT, SPANNING CUSTOMIZATION & VIBRATION ANALYSIS SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited

Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com

Web: www.jinharsh.com