Extension.GUI

Class FXMLTestResultsDocumentController

```
java.lang.Object
   └─ Extension.GUI.FXMLTestResultsDocumentController
```

All Implemented Interfaces:

javafx.fxml.Initializable

```
public class FXMLTestResultsDocumentController
extends java.lang.Object
implements javafx.fxml.Initializable
```

Used by the FXML document to control the test results GUI

Version:

April2015

Author:

Miguel Roman-Roman, Wei Huang, Di Tran, Josh Gillham, Nathan Witt, Thomas Macari

---

Constructor Summary

[FXMLTestResultsDocumentController](#)()

Method Summary

void	[initialize](#)(java.net.URL url, java.util.ResourceBundle rb) Used to initialize this GUI
void	[runTest](#)() Gets the results from running the JUnit tests then formats the failures and prints it to the text area.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

---

Constructor Detail

FXMLTestResultsDocumentController

```
public FXMLTestResultsDocumentController()
```

Method Detail

initialize

```
public void initialize(java.net.URL url,
                       java.util.ResourceBundle rb)
```

Used to initialize this GUI

---

runTest

`public void runTest()`

Gets the results from running the JUnit tests then formats the failures and prints it to the text area.