A Brief Guide to the changes Package

September 22, 2026

This short guide demonstrates how to use the changes package in LaTeX to track and display edits in a collaborative document.

Basic Usage

First, define the authors who will be making changes using the \definechangesauthor command. Each author is assigned a unique ID and a color for their changes.

```
\definechangesauthor[name={Alice}, color=blue]{alice}
\definechangesauthor[name={Bob}, color=red]{bob}
```

Examples

1. Adding Text

```
This is \added[id=alice]{a new sentence} added by Alice.
```

Output: This is a new sentence[alice] added by Alice.

2. Deleting Text

```
This sentence \deleted[id=bob]{contains redundant information}.
```

Output: This sentence ~~contains redundant information~~[bob].

3. Replacing Text

```
He \replaced[id=alice]{revised the manuscript}{wrote the paper}.
```

Output: He revised the manuscript~~wrote the paper~~[alice].

4. Commenting

```
\comment[id=bob]{Consider rephrasing this paragraph.}
```

Output (as footnote):

[bob 1] Consider rephrasing this paragraph.

Final Mode

To hide all tracked changes and show only the final version of the text, load the package with:

```
\PassOptionsToPackage{final}{changes}
\usepackage{paper-utils}
```

Print list of changes

```
\listofchanges[style=<style>, title=<title>, show=<type>]
```

List of Changes

Added (alice): a new sentence 1
Deleted (bob): contains redundant information 1
Replaced (alice): revised the manuscript 1
Commented (bob): Consider rephrasing this paragraph. 2