A Brief Guide to the `minted` package

Jacopo Massa

September 22, 2026

Options

Be sure to set the options `tabsize` and `gobble` in the preamble, as shown below.

```
\usepackage[minted=true,tabsize=4,gobble=1]{paper-utils}
```

`tabsize` (default: 4) sets the number of spaces per tab character.
`gobble` (default: 4) sets the number of characters to remove from the beginning of each line of code. This is useful for removing leading whitespace in indented code blocks.

In the `paper-utils` package, there are two environments for including code: `code` (for unnumbered code blocks) and `codenum` (for numbered ones).

`code` environment

```
application(AppId, [Functions], [Services]).
```

`codenum` environment

```
1 fogBrain(App, NewPlacement) :-
2     deployment(App, Placement, AllocHW, AllocBW),
3     reasoningStep(App, Placement, AllocHW, AllocBW, NewPlacement).

4 fogBrain(App, Placement) :-
5 placement(App, Placement).
```

To use options (e.g., `firstnumber=1`), use the starred version of the environment, i.e., `codenum*`.

"`.localSettings.yaml`" file

If you use `latexIndent` on your local machine, you can copy the `.localSettings.yaml` file from the `packages` folder to the directory where your `.tex` files are located. This will deactivate the auto-indentation of the `code` and `codenum` environments.