

Lab Report

Lab Report

Time Spent: 00:13

Score: 0/14 (0%)

Not Passed

Passing Score: 14/14 (100%)

TASK SUMMARY

Required Actions & Questions

Isolate traffic with the **net 192.168.0.0** filter.

Q1 What is the effect of the **net 192.168.0.0** filter in Wireshark?

Your answer:

Correct answer: Only packets with either a source or destination address on the 192.168.0.x network are displayed.

Isolate traffic with the **host 192.168.0.45** filter.

Q2 What is the effect of the **host 192.168.0.45** filter in Wireshark?

Your answer:

Correct answer: Only packets with 192.168.0.45 in either the source or destination address are displayed.

Isolate traffic with the **ip.src==192.168.0.45** filter.

Q3 What is the effect of the **ip.src==192.168.0.45** filter in Wireshark?

Your answer:

Correct answer: Only packets with 192.168.0.45 in the source address are displayed.

Isolate traffic with the **ip.dst==192.168.0.45** filter.

Q4 What is the effect of the **ip.dst==192.168.0.45** filter in Wireshark?

Your answer:

Correct answer: Only packets with 192.168.0.45 in the destination address are displayed.

Isolate traffic with the **tcp.port==80** filter.

Q5 What is the effect of the **tcp.port==80** filter in Wireshark?

Your answer:

Correct answer: Only packets with port 80 in either the source or destination port are displayed.

Isolate traffic with the **eth contains 11:12:13** filter.

Q6 What is the effect of the **eth contains 11:12:13** filter in Wireshark?

Your answer:

Correct answer: Only packets with 11:12:13 in either the source or destination MAC address are displayed.

Isolate traffic with the **tcp contains password** filter.

Q7 What is the captured password?

Your answer:

Correct answer: hippophobia

EXPLANATION

Complete this lab as follows:

1. Start a Wireshark capture.
 - a. From the Favorites bar, select **Wireshark**.
 - b. Maximize the window for easier viewing.
 - c. Under Capture, select **enp2s0**.
 - d. Select the **blue fin** to start a Wireshark capture.
2. Apply the **net 192.168.0.0** filter.
 - a. In the *Apply a display filter* field, type **net 192.168.0.0** and press **Enter**.
Look at the source and destination addresses of the filtered packets.
 - b. Select the **red square** to stop the Wireshark capture.
 - c. In the top right, select **Answer Questions**.
 - d. Answer Question 1.

3. Apply the **host 192.168.0.45** filter.
 - a. Select the **blue fin** to start a Wireshark capture.
 - b. In the *Apply a display filter* field, type **host 192.168.0.45** and press **Enter**.
Look at the source and destination addresses of the filtered packets.
 - c. Answer Question 2.
4. Apply the **ip.src==192.168.0.45** filter.
 - a. In the *Apply a display filter* field, type **ip.src==192.168.0.45** and press **Enter**.
Look at the source and destination addresses of the filtered packets.
 - b. Answer Question 3.
5. Apply the **ip.dst==192.168.0.45** filter.
 - a. In the *Apply a display filter* field, type **ip.dst==192.168.0.45** and press **Enter**.
Look at the source and destination addresses of the filtered packets.
 - b. Answer Question 4.
6. Apply the **tcp.port==80** filter.
 - a. In the *Apply a display filter* field, type **tcp.port==80** and press **Enter**.
Look at the source and destination addresses of the filtered packets.
 - b. Answer Question 5.
7. Apply the **eth contains 11:12:13** filter.
 - a. In the *Apply a display filter* field, type **eth contains 11:12:13** and press **Enter**.
Look at the source and destination addresses of the filtered packets.
 - b. Answer Question 6.
8. Apply the **tcp contains password** filter.
 - a. In the *Apply a display filter* field, type **tcp contains password** and press **Enter**.
 - b. Select the **red box** to stop the Wireshark capture.
 - c. Locate the password.
 - d. Answer Question 7.
 - e. Select **Score Lab**.