

Lab Report

Lab Report

Time Spent: 00:13

Score: 0/4 (0%)

Not Passed

Passing Score: 4/4 (100%)

TASK SUMMARY

Required Actions & Questions

Filter for ICMP packets

Run ping

Run hping3 for ICMP flood

Q1 What is the main difference between a normal ICMP (ping) request and an ICMP flood? (Select two).

Your answer:

Correct answer: With an ICMP flood, the ICMP packets are sent more rapidly., With an ICMP flood, all packets come from the same source.

EXPLANATION

Complete this lab as follows:

1. Use Wireshark to capture and analyze a ping to *192.168.10.10*.
 - a. From the Favorites bar, select **Wireshark**.
 - b. Under Capture, select **enp2s0**.
 - c. Select the **blue fin** to start a Wireshark capture.
 - d. From the Favorites bar, select **Terminal**.
 - e. From the Terminal, type **ping 192.168.10.10** and press **Enter**.
 - f. After some data exchanges, press **Ctrl + c** to stop the ping process.
 - g. From Wireshark, select the **red box** to stop the Wireshark capture.
 - h. In the *Apply a display filter* field, type **icmp** and press **Enter**.
Notice the number of packets captured and the time between each packet being sent.
2. Use Wireshark to capture and analyze an ICMP flood.
 - a. Select the **blue fin** to start a new Wireshark capture.
 - b. From the Terminal, type **hping3 --icmp --flood 192.168.10.10** and press **Enter** to start a ping flood against CorpServer2.
 - c. From Wireshark, select the **red box** to stop the Wireshark capture.
Notice the type, number of packets, and time between each packet being sent.
 - d. From the Terminal, type **Ctrl + c** to stop the ICMP flood.
3. Answer the questions.
 - a. In the top right, select **Answer Questions**.
 - b. Answer the questions.
 - c. Select **Score Lab**.