

Lab Report

Lab Report

Time Spent: 00:06

Score: 0/4 (0%)

Not Passed

Passing Score: 4/4 (100%)

TASK SUMMARY

Required Actions

Change the password for the admin account to **Donttre@donme**.

Create and configure a new pfSense user **Show Details**

Set a 20 minute session timeout for pfSense.

Enable anti-lockout for HTTP

EXPLANATION

Complete this lab as follows:

1. Access the pfSense management console.
 - a. From the taskbar, select **Google Chrome**.
 - b. Maximize the window for better viewing.
 - c. In the Google Chrome address bar, enter **198.28.56.22** and then press **Enter**.
 - d. Enter the pfSense sign-in information as follows:
 - Username: **admin**
 - Password: **pfsense**
 - e. Select **SIGN IN**.
2. Change the password for the default (admin) account.
 - a. From the pfSense menu bar, select **System > User Manager**.
 - b. For the admin account, under Actions, select the **Edit user** icon (pencil).
 - c. For the Password field, change to **Donttre@donme**.
 - d. For the Confirm Password field, enter **Donttre@donme**.
 - e. Scroll to the bottom and select **Save**.
3. Create and configure a new pfSense user.
 - a. Select **Add**.
 - b. For Username, enter **lyoung**.
 - c. For the Password field, enter **C@nyouGuess!t**.
 - d. For the Confirm Password field, enter **C@nyouGuess!t**.
 - e. For Full Name, enter **Liam Young**.
 - f. For Group Membership, select **admins** and then select **Move to Member of list**.
 - g. Scroll to the bottom and select **Save**.
4. Set a session timeout for pfSense.
 - a. Under the *System* breadcrumb, select **Settings**.
 - b. For Session timeout, enter **20**.
 - c. Select **Save**.
5. Disable the webConfigurator anti-lockout rule for HTTP.
 - a. From the pfSense menu bar, select **System > Advanced**.
 - b. Under webConfigurator, for Protocol, select **HTTP**.
 - c. Select **Anti-lockout** to disable the webConfigurator anti-lockout rule.
 - d. Scroll to the bottom and select **Save**.