

Lab Report

Lab Report

Time Spent: 00:07

Score: 0/2 (0%)

Not Passed

Passing Score: 2/2 (100%)

TASK SUMMARY

Lab Questions

Perform a decoy scan

Q1 From the results of the decoy scan, which IP address is most likely that of the attacker?

Your answer:

Correct answer: 192.168.0.47

EXPLANATION

Complete this lab as follows:

1. Start a Wireshark capture for the enp2s0 interface.
 - a. From the Favorites bar, select **Wireshark**.
 - b. Under Capture, select **enp2s0**.
 - c. From the upper-left menu, select the *blue fin* to start a scan.
2. Run **nmap** (from Terminal or Zenmap) to disguise the source IP address.
 - From Zenmap:
 - a. From the Favorites bar, select **Zenmap**.
 - b. In the Command field, type **nmap -D RND:5 192.168.0.10**
 - c. Select **Scan**.
 - d. As soon as Nmap completes, immediately stop Wireshark by selecting the *red box*.
 - From Terminal:
 - a. From the Favorites bar, select **Terminal**.
 - b. At the prompt, type **nmap -D RND:5 192.168.0.10** and press **Enter**.
 - c. As soon as Nmap completes, immediately stop Wireshark by selecting the *red box*.
3. Analyze the Wireshark data.
 - a. Maximize the Wireshark window for easier viewing.
 - b. From Wireshark, scroll through the results until you see **192.168.0.10** in the *Destination* column.
 - c. Under Source, view the different IP addresses used to disguise the scan.
 - d. In the top right, select **Answer Questions**.
 - e. Answer the question.
 - f. Select **Score Lab**.