

Lab Report

Lab Report

Time Spent: 00:07

Score: 0/5 (0%)

Not Passed

Passing Score: 5/5 (100%)

TASK SUMMARY

Required Actions & Questions

Discover and enable the onboard wireless adapter

Scan for wireless access points

Q1 What is MOST likely to be the rogue access point's ESSID?

Your answer:

Correct answer: GreatDonuts

Q2 What is the rogue access point's average signal power?

Your answer:

Correct answer: -94

Q3 What frequency channel is the rogue access point using?

Your answer:

Correct answer: 10

EXPLANATION

Complete this lab as follows:

1. Start the wireless interface in monitor mode.
 - a. From the Favorites bar, select **Terminal**.
 - b. At the prompt, type **airmon-ng** and press **Enter** to view and find the name of the wireless adapter.
 - c. Type **airmon-ng start wlp1s0** and press **Enter** to put the adapter in monitor mode.
 - d. Type **airmon-ng** and press **Enter** to view the new name of the wireless adapter.
2. Display a list of detected access points.
 - a. Type **airodump-ng wlp1s0mon** and press **Enter** to scan for wireless access points.
 - b. After a few seconds, press **Ctrl + c** to stop the scan.
 - c. In the top right, select **Answer Questions**.
 - d. Answer the questions.
 - e. Select **Score Lab**.