


FR-8 · Channel (top + 2 sides)

11 ga 0.120" (3.04 mm) · HR steel sheet A1011 CS · flat blank 6.209" × 12.000" · ≈ 1.79 lb each · QTY 1 FR + 1 FL = 2 per vehicle


FLAT PATTERN (as laser-cut, marked side up)



NOTES

- 1. Laser cut from the *_cut.dxf file (1:1, inch). The DXF governs the geometry; dimensions here are for checking.
 - 2. Bend allowance (K = 0.44, inside radius = t) is already in the flat. Bend on the orange lines; UP = toward you when the part lies as drawn.
 - 3. Holes marked DRILL LATER (red dashed) are not laser cut — drill after bending/welding.
 - 4. Deburr all edges, remove dross.
 - 5. Right part (FR) shown. Left part (FL) = mirror: cut *_FL_cut.dxf, bend the same UP/DOWN.
- * 90° bends, R = t; relief cut at B

FORMED PART (after bending)



BEND TABLE

Bend	Angle	Direction	Inside R	Order	Bend line position
B1	90.0°	UP (toward)	R=t 0.120	1	X = 1.771
B2	90.0°	UP (toward)	R=t 0.120	2	X = 4.438

FILES

- FR-8_FR_cut.dxf (right, qty 1 / vehicle)
- FR-8_FL_cut.dxf (left = mirror, qty 1 / vehicle)
- FR-8_ref.dxf (reference: + bend lines, drill-later)

FR-8Channel (top + 2 sides)	HR steel sheet A1011 CS 11 ga 0.120" (3.04 mm)	Units: inch · NOT TO SCALE	Sienna WAV frame	REV A
FR-8 · Channel (top + 2 sides)	QTY 1 FR + 1 FL = 2 per vehicle	Tol.: cut ±0.010" · bend ±1° · IR = t	2026-10-03	SHEET 1/1