

Worksheet 1 in R

Worksheet for R Programming

Instructions:

- Use RStudio or the RStudio Cloud accomplish this worksheet. + Save the R script as *RWorksheet_lastname#1.R*. **DONE**
- Create your own *GitHub* repository and push the R script as well as this pdf worksheet to your own repo. **DONE**

Accomplish this worksheet by answering the questions being asked and writing the code manually.

Using functions:

`seq()`, `assign()`, `min()`, `max()`, `c()`, `sort()`, `sum()`, `filter()`

1. Set up a vector named `age`, consisting of 34, 28, 22, 36, 27, 18, 52, 39, 42, 29, 35, 31, 27, 22, 37, 34, 19, 20, 57, 49, 50, 37, 46, 25, 17, 37, 42, 53, 41, 51, 35, 24, 33, 41.
 - a. How many data points?
- 34
 - b. Write the code and its output.

```
> length(age)
[1] 34
```

2. Find the reciprocal of the values for `age`.

Write the R code and its output.

```
> rcp_age <- 1/age
```

```
> rcp_age
```

```
[1] 0.02941176 0.03571429 0.04545455 0.02777778 0.03703704 0.05555556
[7] 0.01923077 0.02564103 0.02380952 0.03448276 0.02857143 0.03225806
[13] 0.03703704 0.04545455 0.02702703 0.02941176 0.05263158 0.05000000
[19] 0.01754386 0.02040816 0.02000000 0.02702703 0.02173913 0.04000000
[25] 0.05882353 0.02702703 0.01923077 0.01886792 0.02439024 0.01960784
[31] 0.02857143 0.04166667 0.03030303 0.02439024
```

3. Assign also `new_age <- c(age, 0, age)`.

What happen to the `new_age`?

- a zero is added to the values of `age`

```
[1] 34 28 22 36 27 18 52 39 42 29 35 31 27 22 37 34 19 20 57 49 50 37 46 25 17 37 52 53 41 51 35 24 33
41 0 34 28 22 36 27 18 52 39 42 29 35 31 27
[49] 22 37 34 19 20 57 49 50 37 46 25 17 37 52 53 41 51 35 24 33 41
```

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

4. Sort the values for age.

Write the Rcode and its input

```
> age_srt <- sort(age)
> age_srt
[1] 17 18 19 20 22 22 24 25 27 27 28 29 31 33 34 34 35 35 36 37 37 37 39 41 41 42 46 49 50 51 52 52 53 57
```

5. Find the minimum and maximum value for age.

Write the Rcode and its output

```
> miniAge <- min(age)
> miniAge
[1] 17

> maxAge <- max(age)
> maxAge
[1] 57
```

6. Set up a vector named data, consisting of 2.4, 2.8, 2.1, 2.5, 2.4, 2.2, 2.5, 2.3, 2.5, 2.3, 2.4, and 2.7.

a. How many data points?

- 12 data points

b. Write the Rcode and its output

```
> data <- c(2.4,2.8,2.1,2.5,2.4,2.2,2.5,2.3,2.5,2.3,2.4,2.7)
> data
[1] 2.4 2.8 2.1 2.5 2.4 2.2 2.5 2.3 2.5 2.3 2.4 2.7
```

7. Generates a new vector for data where you double every value of the data. | What happen to the data?

```
- > data *2
[1] 4.8 5.6 4.2 5.0 4.8 4.4 5.0 4.6 5.0 4.6 4.8 5.4
```

8. Generate a sequence for the following scenario:

8.1 Integers from 1 to 100

```
> seq(1:100)
[1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36
[37] 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72
[73] 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100
```

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

8.2 Numbers from 20 to 60

```
> seq(20,60)
```

```
[1] 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52  
53 54 55 56 57 58 59 60
```

8.3 Mean of numbers from 20 to 60

```
> mean(20:60)
```

```
[1] 40
```

8.4 Sum of all numbers from 51 to 91

```
> sum(51:91)
```

```
[1] 2911
```

8.5 Integers from 1 to 1000

```
> seq(1:1000)
```

```
[1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15  
[16] 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30  
[31] 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45  
[46] 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60  
[61] 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75  
[76] 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90  
[91] 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105  
[106] 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120  
[121] 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135  
[136] 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150  
[151] 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165  
[166] 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180  
[181] 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195  
[196] 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210  
[211] 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225  
[226] 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240  
[241] 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255  
[256] 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270  
[271] 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285  
[286] 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300  
[301] 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315  
[316] 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330  
[331] 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345  
[346] 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360
```

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

[361] 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375
[376] 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390
[391] 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405
[406] 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420
[421] 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435
[436] 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450
[451] 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465
[466] 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480
[481] 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495
[496] 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510
[511] 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525
[526] 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540
[541] 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555
[556] 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570
[571] 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585
[586] 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600
[601] 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615
[616] 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630
[631] 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645
[646] 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660
[661] 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675
[676] 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690
[691] 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705
[706] 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720
[721] 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735
[736] 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750
[751] 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765
[766] 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780
[781] 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795
[796] 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810
[811] 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825
[826] 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840
[841] 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855
[856] 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870
[871] 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885
[886] 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900
[901] 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915
[916] 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930
[931] 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945
[946] 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960
[961] 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975
[976] 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990
[991] 991 992 993 994 995 996 997 998 999 1000

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

- a. How many data points from 8.1 to 8.4?

Total Data points = 143

8.1 = 100 data points

8.2 = 41 data points

8.3 = 1 data point

8.4 = 1 data point

- b. Write the R code and its output from 8.1 to 8.4.

8.1

```
> data.frame(1:100)
```

X1.100

1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

8.2

```
> data.frame(20:60)
```

X20.60

1	20
2	21
3	22
4	23
5	24
6	25
7	26
8	27
9	28
10	29
11	30
12	31
13	32
14	33
15	34

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

16 35
17 36
18 37
19 38
20 39
21 40
22 41
23 42
24 43
25 44
26 45
27 46
28 47
29 48
30 49
31 50
32 51
33 52
34 53
35 54
36 55
37 56
38 57
39 58
40 59
41 60

8.3

```
data.frame(mean(20:60))  
mean.20.60.  
1      40
```

8.4

```
> data.frame(sum(51:91))  
sum.51.91.  
1    2911
```

c. For 8.5 find only maximum data points until 10

```
> max(1:10)  
[1] 10
```


Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

9. Print a vector with the integers between 1 and 100 that are not divisible by 3, 5 and 7 using filter option.

`filter(function(i) { all(i %% c(3,5,7) != 0) }, seq(100))` Write the R code and its output.

```
> filter(function(i) { all(i %% c(3,5,7) != 0) }, seq(100))
```

```
Error in attr("data", "tsp") <- c(start, end, frequency) :
```

```
object is not a matrix
```

```
> Filter(function(i) { all(i %% c(3,5,7) != 0) }, seq(100))
```

```
[1] 1 2 4 8 11 13 16 17 19 22 23 26 29 31 32 34 37 38 41 43 44 46 47 52 53 58 59 61 62 64 67 68 71 73  
74 76 79 82 83 86 88 89 92 94 97
```

10. Generate a sequence backwards of the integers from 1 to 100. Write the R code and its output.

```
> sqnc <- seq(100:1)
```

```
> sqnc
```

```
[1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29  
30 31 32 33 34 35 36
```

```
[37] 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63  
64 65 66 67 68 69 70 71 72
```

```
[73] 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99  
100
```

11. List all the natural numbers below 25 that are multiples of 3 or 5.

```
> sum((1:25)[((1:25)%%3==0) | ((1:25)%%5 == 0)])
```

```
[1] 168
```

Find the sum of these multiples.

a. How many data points from 10 to 11?

- 101 Data Points

b. Write the R code and its output from 10 and 11.

#10 output

```
> data.frame(100:1)
```

```
  X100.1
```

```
1    100
```

```
2     99
```

```
3     98
```

```
4     97
```

```
5     96
```

```
6     95
```

```
7     94
```

```
8     93
```

```
9     92
```

```
10    91
```

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

11	90
12	89
13	88
14	87
15	86
16	85
17	84
18	83
19	82
20	81
21	80
22	79
23	78
24	77
25	76
26	75
27	74
28	73
29	72
30	71
31	70
32	69
33	68
34	67
35	66
36	65
37	64
38	63
39	62
40	61
41	60
42	59
43	58
44	57
45	56
46	55
47	54
48	53
49	52
50	51
51	50
52	49
53	48
54	47

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

55	46
56	45
57	44
58	43
59	42
60	41
61	40
62	39
63	38
64	37
65	36
66	35
67	34
68	33
69	32
70	31
71	30
72	29
73	28
74	27
75	26
76	25
77	24
78	23
79	22
80	21
81	20
82	19
83	18
84	17
85	16
86	15
87	14
88	13
89	12
90	11
91	10
92	9
93	8
94	7
95	6
96	5
97	4
98	3

Name: Diana Marie Aguas
Course, Year, & Section: BSIT 2A

```
99    2
100   1
```

#11 output

```
> data.frame(sum((1:25)[((1:25)%%3==0) | ((1:25)%%5 == 0)]))
  sum..1.25....1.25...3....0.....1.25...5....0...
1                                168
```

12. Statements can be grouped together using braces '{' and '}'. A group of statements is sometimes called a block. Single statements are evaluated when a new line is typed at the end of the syntactically complete statement. Blocks are not evaluated until a new line is entered after the closing brace.

Enter this statement: { x <- 0+ x + 5 + }

Describe the output.

```
> { x <- 0+ x + 5 + }
Error: unexpected '}' in "{ x <- 0+ x + 5 + }"
- the closing brace is the error in this statement
```

13. Set up a vector named score, consisting of 72, 86, 92, 63, 88, 89, 91, 92, 75, 75 and 77. To access individual elements of an atomic vector, one generally uses the x[i] construction.

Find x[2] and x[3]. Write the R code and its output.

```
x[2] 86
x[3] 92
```

14. Create a vector a = c(1,2,NA,4,NA,6,7).

a. Change the NA to 999 using the codes print(a,na.print="-999").

```
> a = c(1,2,NA,4,NA,6,7)

> print(a, na.print = "-999")
[1] 1 2 -999 4 -999 6 7
```

b. Write the R code and its output. Describe the output.

```
> a = c(1,2,NA,4,NA,6,7)
> print(a, na.print = "-999")
[1] 1 2 -999 4 -999 6 7
```

-

15. A special type of function calls can appear on the left hand side of the assignment operator as in > class(x) <- "foo".

Follow the codes below:

```
name = readline(prompt="Input your name: ") age = readline(prompt="Input your age: ")
print(paste("My name is",name, "and I am",age ,"years old.")) print(R.version.string)
```

Name: Diana Marie Aguas

Course, Year, & Section: BSIT 2A

What is the output of the above code?

```
[1] "My name is Diana Marie Aguas and I am 19 years old."
```

```
> print(R.version.string)
```

```
[1] "R version 4.2.1 (2022-06-23 ucrt)"
```