Technical Specification draft

Large Model Specialized Computer Kernel Specification

Protocol revision: draft v1

Document status	Working draft for technical review
Language	English
Typesetting basis	ISO/IEC Directives, Part 2 inspired technical-specification structure
Document class	KOMA-Script scrbook
Website	https://github.com/dianzinao/lmsc-kernel-spec
Date	2026-04-26

Foreword

Contents

Foreword ii

0. Introduction and Scope 1
0.1 What LMSC Is . . . 1
0.2 Hard Layering Rules . . . 1
0.3 What This Specification Includes . . . 1
0.4 What This Specification Does Not Include . . . 1

1. Terminology 2

2. Normative Language 3

3. Architecture 4
3.1 Layering . . . 4
3.2 Data Flow . . . 4
3.3 Basic Principles . . . 4

4. Protocol Surface: Special Tokens and Grammar 6
4.1 Special Token List (Normative) . . . 6
4.1.1 Envelope Paired Tokens (8) . . . 6
4.1.2 Control Single Tokens (2) . . . 6
4.1.2a Rollback Envelope Semantics (Normative) . . . 6
4.1.3 Ref Element Paired Tokens (2) . . . 8
4.1.4 Key Token Family (Optional, Distribution-Defined K) . . . 8
4.1.5 Total . . . 8
4.2 Envelope Attributes . . . 8
4.3 Grammar (EBNF) . . . 10
4.4 Grammar Invariants (Normative) . . . 11
4.5 Role Semantics . . . 12

5. Atomic Operations 13
5.1 Categories and Counts . . . 13
5.2 A - Token Stream . . . 13
A1 - `logit_mask` . . . 13
A2 - `query_special` (Level-Dependent Optional) . . . 13
A3 - `token_rollback` . . . 13
A3 Level-Based Downgrade . . . 14
A4 - `token_inject` . . . 16
A5 - `session_fork` . . . 16
5.3 B - Envelope Structure . . . 17
B1 - `envelope_event` . . . 17
B2 - `dispatch` . . . 17
B3 - `envelope_emit` . . . 18
5.4 C - Scheduling . . . 19
C1 - `suspend` . . . 19
C2 - `resume` . . . 20
C3 - `abort` . . . 20
C4 - `preempt` . . . 20
C5 - `dispatcher_frame` . . . 20
5.5 D - Authorization . . . 21
D1 - `capability_check` . . . 21
D2 - `capability_grant` . . . 21
D3 - `capability_revoke` . . . 21
5.6 E - Program Table . . . 22
E - `program_table` . . . 22

5.7 F - State . . . 22
F1 - `kv` . . . 22
F2 - `blob` . . . 23
F3 - `ref` . . . 23
F4 - `region` . . . 24
5.8 G - Audit . . . 25
G1 - `audit_emit` . . . 25
5.9 H - I/O . . . 25
H1 - `fs` . . . 25
H2 - `net` . . . 25
H3 - `exec_sandbox` (Level-Dependent Optional) . . . 25
5.10 I - Time . . . 26
I1 - `clock` . . . 26

6. Inference Stack Integration Contract **27**
6.1 Three Hook Points . . . 27
6.2 Sampler Hook Contract . . . 27
6.3 Token Stream Hook Contract . . . 27
6.4 KV Cache Hook Contract . . . 28
6.5 Integration Levels (L0 /L1 /L2; Tier Aliases) . . . 28
6.5.1 L2 Invariant Downgrade Semantics . . . 28
6.5.1.1 Postconditions for Invalid L2 Rollback . . . 29
6.5.1.2 L2 Rollback Result Matrix . . . 30
6.5.1.3 L2 `I-ATTR-CLEAN` Byte-Level State Machine . . . 30
6.5.2 Streaming Downgrade for `envelope.emit` Under L2 . . . 31
6.6 Tokenizer Contract . . . 31

7. Syscall Interface **33**
7.1 Invocation Model . . . 33
7.2 Syscall Table . . . 33
7.3 Error Model . . . 34
7.4 Defense in Depth Validation . . . 34
7.5 ABI . . . 34

8. Program Model **35**
8.1 Manifest . . . 35
8.2 Handler Lifecycle . . . 36
8.3 Closed Action Set (7 Items) . . . 37
8.4 Namespace Isolation . . . 38
8.5 Dispatcher Frame . . . 38
8.6 Program Visibility . . . 39

9. State Model **40**
9.1 Five Classes of State . . . 40
9.2 Generation Marker (`gen` Attribute) . . . 40
9.3 Ref Resolution Chain . . . 40
9.4 Fork . . . 41
9.4.1 Boot Output and Fork . . . 42
9.4.2 Fork and Blob Refcount . . . 43
9.4.3 Restore Across Builds . . . 43

10. Scheduling and Session State Machine **44**
10.1 State Machine . . . 44
10.1.1 Outer-State Recovery Algorithm After Truncation . . . 45
10.1.2 Strict Protocol Mode and Auto Execute Scaffold . . . 45
10.2 Turn . . . 47
10.3 Concurrency . . . 48

11. Capability Model **49**
11.1 Capability Strings . . . 49
11.2 Three Pools . . . 49
11.3 Matching Rules . . . 49
11.4 Fixed-Only High-Risk Set . . . 49
11.5 Request Flow . . . 50

12. Required Programs **51**
12.1 `program` . . . 51
12.2 `capability` . . . 51
12.3 `runtime` . . . 52
12.3.1 `persona-refresh` Semantics . . . 53
12.4 `kv` . . . 54
12.5 Non-Replaceability . . . 54

13. Security Invariants **55**
13.1 Capability Three-Layer Verification . . . 55
13.2 Protocol Boundary Escaping (Corresponds to `I-EMIT-ESCAPE`) . . . 55
13.3 Rollback Boundaries . . . 56
13.4 Inject Boundaries . . . 59
13.5 Preempt Constraints . . . 59
13.6 Region Operations . . . 59
13.7 Audit Cannot Be Bypassed . . . 59
13.8 Sandbox Hard Constraints (If H3 Is Provided) . . . 60
13.9 Fork Safety . . . 60
13.10 Program Isolation . . . 60
13.11 Stack Depth . . . 60

14. Audit Log **62**
14.1 Record Structure . . . 62
14.2 Events Automatically Emitted by the Kernel . . . 62
14.2.1 Distribution Extensions and Model-Visible Projection . . . 63
14.2.2 Mutual-Exclusion Semantics of `rollback` and `rollback_error` . . . 64
14.3 Persistence . . . 64
14.4 Projection to the Model . . . 65

15. Error Code Registry **66**
15.1 Naming Rules . . . 66
15.2 Error Codes That **MUST** Be Defined (Minimum Enumeration) . . . 66
15.2.1 Error-Code Attribution (`origin`) . . . 68
15.3 Retryable Flag . . . 68

16. Conformance **69**
16.1 **MUST** . . . 69
16.1.1 Minimum Conformance Test Matrix . . . 71
16.2 **SHOULD** . . . 72
16.3 **MAY** . . . 72
16.4 Non-Conforming Examples . . . 73

17. Appendices **74**
Appendix A - Special Token Registry . . . 74
Appendix B - Capability Name Registry (Core) . . . 74
Appendix C - Action Registry . . . 75
Appendix D - Complete Syscall Method List . . . 75
Appendix E - Boot Output Schema . . . 76
Appendix H - Machine-Readable Artifact List . . . 76

Bibliography **78**

0. Introduction and Scope

0.1 What LMSC Is

LMSC is the **kernel** for large language models (LLMs). Its responsibilities are:

1. **Shape the token stream** -- constrain the model autoregressive process (logit masks, rollback, injection, snapshots);
2. **Host programs** -- provide loading, dispatch, authorization, state, and audit infrastructure for programs;
3. **Integrate with the inference stack** -- collaborate with the underlying inference engine through three hook points.

LMSC is **not** an Agent, chatbot, toolbox, or scaffold. It is only **mechanism**, not **policy**.

0.2 Hard Layering Rules

A conforming implementation **MUST** preserve the following layers under all circumstances:



Normative clauses MUST NOT reference across layers. The capabilities of required programs **MUST NOT** depend on the presence of any non-required program.

0.3 What This Specification Includes

- The special token set, envelope syntax, and attribute semantics of the session protocol;
- The signatures, preconditions, postconditions, and errors of atomic operations;
- The contracts for the three inference stack hook points;
- The system call table (excluding concrete language bindings);
- The program manifest format and handler lifecycle;
- The minimal instruction sets of the four required programs;
- The security invariants that the kernel **MUST** enforce;
- The audit log record structure;
- Error-code namespaces and semantics.

0.4 What This Specification Does Not Include

- Implementations of recommended programs (`think` /`memory` /`summarizer` /`lmchat` /...);
- Binding methods for concrete inference engines (vLLM /transformers /llama.cpp);
- Handler ABIs for specific programming languages;
- LoRA training-data formats;
- Frontend UI, Agent policy, or business logic.

---

1. Terminology

Term	Definition
kernel	The runtime core that implements this specification
inference stack	The LLM forward-computation engine (the host of the sampler, KV cache, and tokenizer)
session	A continuous context from kernel boot to termination, with independent context, kv, and blob namespaces
context	The complete token sequence of the current session (including interval markers that have been folded /dropped)
turn	The interval from leaving IDLE to the next IDLE; the unit of accounting for atomic operations and per-turn quotas
envelope	A structured fragment delimited by paired special tokens, with **four** kinds: `<lmsc_execute>` · `<lmsc_output>` ·`<lmsc_edit>` ·`<lmsc_rollback>` (pattern-string rollback)
StreamFrame	Progress metadata observed for an `envelope.emit` chunk: `{ chunk_index, total_chunks_hint?, stream_closed }`; defined in §8.2
EnvelopeChunk	The normalized payload for `on_envelope_chunk`, containing envelope kind /id /from /visibility /source path /frame /final token chunk
ChunkDecision	The return decision of `on_envelope_chunk`: `Continue`, `DetachObserver`, or `AbortEnvelope`
backpressure	In-session wait semantics when downstream consumption is slower than production on the `envelope.emit` Stream path; exceeding `STREAM_WRITE_TIMEOUT` triggers `E_EMIT_STREAM_BACKPRESSURE_TIMEOUT`
buffered /native	The two modes of `envelope_emit_stream` under L2: native is pull-based native consumption; buffered is the L2 downgrade semantics of buffering the full body and then injecting it once (§6.5.2)
control token	A pipelined single token, unpaired, representing an immediate instruction
special token	The general term for IDs reserved by the kernel
program	A user-space module registered on the kernel and responding to dispatch
handler	The executable part of a program, implementing lifecycle callbacks such as `dispatch`
manifest	Declarative metadata for a program
action	An executable action declared by a program to the kernel (a closed set of 7 entries; see §8.3)
capability	A fine-grained permission string
atomic primitive	The minimal indivisible capabilities provided by the kernel: 24 core entries + 2 optional entries (the 2 optional entries = `A2` + `H3`)
syscall	A function entry through which programs access atomic operations
dispatcher frame	One layer of the dispatcher stack, with an independent program lookup table and grammar constraints
region	A tagged token interval that can be edited as a whole (replaced or deleted)
ref	A generic reference element: `<lmsc_ref>kind: "...";id: "...";</lmsc_ref>`
blob	An immutable byte string addressed by content
boot output	The first `from="system"` output envelope injected by the kernel at session start
fork	A copy-on-write branch of the full session state (context + KV + metadata)

2. Normative Language

This document uses the keywords from [RFC 2119] and [RFC 8174]:

- **MUST**: absolute requirement;
- **MUST NOT**: absolute prohibition;
- **SHOULD**: strong recommendation;
- **MAY**: optional behavior.

The subject of ”the kernel **MUST**...” is a conforming implementation. The subject of ”a program **MUST**...” is a program deployed on a conforming kernel.

---

3. Architecture

3.1 Layering



3.2 Data Flow

Logits before sampling **MUST** first pass through the kernel's sampler hook, where the kernel applies logit masks, dispatcher frame constraints, and other pre-sampling restrictions. The token produced after sampling **MUST** pass through the token stream hook before append-to-context, where the kernel identifies envelopes, control tokens, refs, and rollback events. KV cache operations are driven directly by the kernel through the KV hook or the rollback truncate adapter, and do not pass through a model-observable path.

The required strength of the hooks above is determined by the access-level matrix in §6.5: L0 provides the Sampler /Token Stream /KV Cache hooks; L1 provides the Sampler and Token Stream hooks, and completes the truncation required by A3 through the rollback truncate adapter; L2 only requires Token Stream post-processing recognition and downgrades according to the post-hoc detection rules in §6.5.1.

Programs do not communicate directly with each other. Cross-program collaboration occurs through one of the following:

- Envelopes (program A's output is dispatched to program B);
- shared blob namespaces (explicit capability; see §5.7 F2). KV is isolated by program prefix `program:<name>/` by default (see §5.7 F1); **cross-program KV sharing is not defined by this specification**. A distribution **MAY** extend it without breaking P-1 /P-2 or §5.7 F1 isolation, but such extensions are distribution-level and do not constitute spec-level interoperable capabilities;
- ref resolution chains (a resolver registered by program B is called by the kernel when expanding a ref).

3.3 Basic Principles

P-1 - Minimal Kernel - The kernel **MUST NOT** implement any capability that can be constructed in user space by composing atomic operations.

P-2 - Mechanism, Not Policy - The kernel **MUST NOT** hard-code privileged policy; all policy goes through the capability authorization mechanism.

> **P-2 Boundary Note** - P-2 constrains business policies such as agent planning, tool selection, and business approval; it does not negate the kernel's own security baseline. The fixed-only capabilities in §11.4, the required programs in §12, and the non-substitutable fields in boot/runtime schemas are part of the capability mechanism and the boot security boundary itself; they are not privileged policy hard-coding prohibited by P-2.

P-3 - Single Path - Programs **MUST NOT** bypass syscalls to access the inference stack /KV cache /tokenizer reserved-id table.

P-4 - Frozen Token Set - The special token set is frozen at kernel build time and **MUST NOT** be added to or removed at runtime.

P-5 - No Cross-Layer Dependency - Normative clauses and the behavior of required programs **MUST NOT** depend on the presence of recommended or ecosystem programs.

---

4. Protocol Surface: Special Tokens and Grammar

4.1 Special Token List (Normative)

A conforming kernel **MUST** reserve independent IDs for the following tokens. The tokenizer **MUST** recognize them consistently with the kernel.

4.1.1 Envelope Paired Tokens (8)

Open	Close	Notes
`<lmsc_execute>`	`</lmsc_execute>`	Program dispatch
`<lmsc_output>`	`</lmsc_output>`	Result /input
`<lmsc_edit>`	`</lmsc_edit>`	Context edit
`<lmsc_rollback>`	`</lmsc_rollback>`	Pattern-string rollback (see §4.1.2a)

4.1.2 Control Single Tokens (2)

Token	Semantics	Primitive
`<|lmsc_abort|>`	Terminate the current envelope	C3
`<|lmsc_suspend|>`	Model-initiated suspension; the model path is equivalent to `suspend(External)` by default	C1

4.1.2a Rollback Envelope Semantics (Normative)

> **Single normative source for Pattern constraints -** This subsection is the **normative source of truth** for all syntax, semantics, length, reserved-literal, storm-limit, and other constraints on the rollback pattern body. §4.3 EBNF, §4.4 invariants, §5.2 A3, §13.3, and other locations are **references only** and **MUST NOT** introduce additional constraints that conflict with this subsection; if a conflict is found, this subsection prevails.

A model-generated `<lmsc_rollback>X</lmsc_rollback>` means: keep the content before the **most recent** occurrence of `X` that appears "before this envelope and within the rollback boundary (§4.4 `I-ROLLBACK-BOUND`)"; discard the rest, including this envelope itself.

When the kernel sees the `</lmsc_rollback>` close token, it executes the following steps (let `P` be the detokenized bytes of the pattern body):

1. Compute `candidate_context`: the detokenized byte stream from the rollbackable candidate lower bound of the current turn to immediately before the `<lmsc_rollback>` open; this candidate context **MAY** contain bytes that are not rollbackable because of structural boundaries, pinned regions, user input intervals, or `ROLLBACK_SEARCH_MAX_BYTES`.
2. Compute `allowed_window`: the closed interval in `candidate_context` that simultaneously satisfies `scope`, `I-ROLLBACK-BOUND`, pin/input hard boundaries, and `ROLLBACK_SEARCH_MAX_BYTES`; `effective_bound` **MUST** record the nearest boundary that was used.
3. `j:=last_index_of(candidate_context,P)`;
4. If `j=NOT_FOUND`: KV is unchanged; emit audit `kind=rollback`, with details containing `outcome=pattern_not_found`; the `token_rollback` syscall returns `E_ROLLBACK_PATTERN_NOT_FOUND`; the model path only emits audit and does not return an error to any caller.
5. If `j` exists but the matched interval `[j, j+len(P))` is not fully inside `allowed_window`: KV is unchanged; emit audit `kind=rollback`, with details containing `outcome=pattern_out_of_bound` and `effective_bound`; the `token_rollback` syscall returns `E_ROLLBACK_PATTERN_NOT_FOUND`; the model path only emits audit and does not return an error to any caller.
6. Otherwise: discard the entire token containing the first matched byte, leaving the KV cache tail before that token, and discard everything after it, including the rollback envelope itself; emit audit `kind=rollback` (details contain `outcome=truncated` /`pattern_bytes_len` /`truncated_tokens` /`effective_bound`).

> **Truncation granularity note** - ”Discard the entire token containing the first matched byte, leaving the KV tail before that token” is deliberate: the byte-level `last_index_of` hit position does not depend on the tokenizer, so the match result is predictable across tokenizers; however, the truncation boundary at ”the token containing the first matched byte” and the state restoration in §10.1.1 depend on tokenizer segmentation. Cross-implementation restoration consistency holds only under the §16.1 C-14 premise of ”the same tokenizer and the same kernel build”. Example: if the `W` in `Wait,` and the previous character form one token together, truncation also removes the remaining bytes of that token; training samples establish this behavior.

Constraints:

- The rollback envelope **MUST NOT** contain any reserved token in its body (any envelope open/close, `<|lmsc_abort|>` /`<|lmsc_suspend|>`, `<lmsc_ref>` /`</lmsc_ref>`, or key token); violation triggers `I-ROLLBACK-NO-NEST`;
- The body **MUST** be non-empty; empty body -> `E_ROLLBACK_PATTERN_EMPTY`;
- The detokenized byte length of the body **MUST** be $\leq$ `ROLLBACK_PATTERN_MAX_BYTES` (default **512**; see Appendix F); exceeding it -> `E_ROLLBACK_PATTERN_TOO_LONG`;
- Match search **MUST NOT** cross `I-ROLLBACK-BOUND`; search stops when it encounters a boundary;
- `ROLLBACK_STORM_LIMIT` (default 16 times /turn) remains in effect;
- **`ROLLBACK_PATTERN_MAX_BYTES` upper-bound enforcement** is level-specific:
  - **L0 /L1**: the kernel **MUST** use logit masks to ensure that, after a rollback envelope opens, a close token is produced within `ROLLBACK_PATTERN_MAX_BYTES` bytes. **Upper-bound handling (deterministic priority)**: when the next candidate token would make the rollback body byte count = `ROLLBACK_PATTERN_MAX_BYTES` and a close has not yet been produced, the kernel **MUST** select a path in the following order: (a) **prefer** to force-emit `</lmsc_rollback>` (forced close); (b) **only if** the forced close would simultaneously violate other invariants such as `I-ROLLBACK-NO-NEST` /`I-ROLLBACK-NO-ATTR` and therefore cannot legally close, downgrade to forcibly emitting `<|lmsc_abort|>` along the C3 abort path. The two paths **MUST NOT** be silently swapped by a distribution. Audit requirements: path (a) emits `kind=rollback`, with details that **MUST** contain `forced_close=true` and `effective_bound="pattern_max_bytes"`, and is then handled as an ordinary rollback pattern (search, hit /miss, KV truncation, `ROLLBACK_STORM_LIMIT` accounting, region cleanup); a rollback envelope whose body byte count exceeds `ROLLBACK_PATTERN_MAX_BYTES` **MUST NOT** be produced. Path (b) emits both `kind=rollback` (details contain `forced_close=true`, `forced_close_outcome="abort_fallback"`) and `kind=protocol_violation` (invariant=`I-ROLLBACK-BOUND`); KV is unchanged;
  - **L2**: without a sampler hook, the kernel **MUST** maintain a byte counter for the rollback envelope body in the token stream hook, accumulating from open; upon reaching `ROLLBACK_PATTERN_MAX_BYTES`, it immediately follows the C3 abort path and emits audit `kind=protocol_violation` (invariant=`I-ROLLBACK-BOUND`); L2 **MUST NOT** handle this by silent truncation or best-effort behavior.

A model-triggered rollback envelope and a program call to `token_rollback(pattern,scope)` (§5.2 A3) are **semantically equivalent** and share the constraints above.

The `scope` of the model path is inferred as follows:

- If, **before** the `<lmsc_rollback>` open, the current sampling position lies inside the body of some **non-rollback** envelope (i.e. the envelope stack contains at least one non-rollback envelope frame) -> `scope=Envelope`;
- Otherwise (the stack contains no non-rollback envelope, including the `GENERATING` case and the case where only the rollback envelope itself is on the stack) -> `scope=Turn`.

> **The rollback envelope does not participate in scope inference** - Even at the moment the `</lmsc_rollback>` close token is processed, when the rollback envelope is still on top of the envelope stack, scope inference **MUST** consider only the stack state **before** the rollback open; the rollback envelope itself **MUST NOT** count as a ”non-rollback envelope body”. This subsection is the normative source of truth for ”Model-path default scope inference” in §13.3; §13.3 and other locations are references only and **MUST NOT** introduce inference text that conflicts with this subsection.

The inferred result is written into the `search_scope` field in §14.2 rollback audit details; top-level `AuditRecord.scope` still only represents audit visibility and **MUST NOT** be reused for the rollback search range.

Examples (byte-level matching, tokenizer-independent):

- ASCII: `<lmsc_rollback>Wait,</lmsc_rollback>` truncates from the most recent occurrence of `Wait,`;
- Chinese: `<lmsc_rollback>` 结论： `</lmsc_rollback>` matches 结论： by its UTF-8 byte sequence;

- With newline: in `<lmsc_rollback> 结论: \n</lmsc_rollback>`, `\n` is a literal LF byte;
- Across token boundaries: the match unit is **bytes**, not tokens; how the tokenizer segments the pattern /context **does not** affect the hit result.

4.1.3 Ref Element Paired Tokens (2)

Open	Close	Form
`<lmsc_ref>`	`</lmsc_ref>`	The body uses the fixed micro-grammar `kind:"summary";id:"x";` (see §4.3)

> **Note** - `lmsc_ref` is not a "start-prefix" reserved token; like execute /output /edit /rollback, it is a complete pair of open/close reserved tokens. The ref body is parsed from the detokenized byte sequence between `<lmsc_ref>` and `</lmsc_ref>`, independent of how the ordinary tokenizer segments those bytes.

`<lmsc_ref>...</lmsc_ref>` is **not** an envelope: it has no dispatch semantics, does not enter the dispatcher frame stack, and the close token `</lmsc_ref>` does not trigger any dispatch. It only triggers F3 `ref.resolve` and replaces the resolved result inline. `RefOpen` /`RefClose` events (§6.3) are observable hooks for the token stream hook and differ from the dispatch semantics of `EnvelopeOpen/Close`. Its body **MUST** exactly conform to the ref micro-grammar (see §4.3 /`I-REF-CHARSET`).

4.1.4 Key Token Family (Optional, Distribution-Defined K)

Form: `<|key_<name>|>`. Typical examples: `key_tab`, `key_enter`, `key_esc`, etc. The concrete set is determined by the kernel build, and `runtime info` **MUST** expose the enabled list.

> **Key token semantic limitation** - Key token semantics are distribution-defined; this specification **does not** define their state-machine branches and **does not** define handler callbacks. The token stream hook handles them as `Chunk` events (**not** triggering any B2 /C-class or ref path); the literals involved are passed through unchanged.

4.1.5 Total

The reserved token count of a conforming kernel is 8 + 2 + 2 + K = **12 + K**. `runtime info` **MUST** return an accurate count. This specification enumerates reserved tokens as follows for tokenizer registry generation:

- Envelope open/close tokens: 4 pairs for a total of **8**: `<lmsc_execute>` /`</lmsc_execute>`, `<lmsc_output>` /`</lmsc_output>`, `<lmsc_edit>` /`</lmsc_edit>`, `<lmsc_rollback>` /`</lmsc_rollback>`;
- Control single tokens: 2: `<|lmsc_abort|>`, `<|lmsc_suspend|>`;
- Ref paired tokens: 2: `<lmsc_ref>`, `</lmsc_ref>` (see §4.1.3);
- Key tokens: K tokens (engineering reserved; see §4.1.4).

4.2 Envelope Attributes

An envelope open token is a complete reserved token from the §4.1 registry (for example, `<lmsc_output>`). Attributes **MUST NOT** be spliced into the open token literal. Attributes of non-rollback envelopes are maintained by the kernel as metadata, and when they need to be written into context they appear immediately after the open token as a **kernel-injected attribute header**. The attribute header uses ordinary tokenizer bytes and no reserved token.

The canonical form of the attribute header is:

```
@lmsc-attrs id="..." from="..." visibility="..."\n\n
```

There **MUST** be whitespace before the first attribute, and the attribute header ends with a blank line; only after the blank line does the envelope body begin. The attribute header is parsed as attributes only when the kernel has marked that byte interval as a `kernel-ownedattr_header`. If the model or a program generates the same literal in an ordinary body, it is treated only as body bytes and **MUST NOT** be promoted to attributes. The detokenized UTF-8 byte length of each attribute value **MUST** be $\leq$ `ATTR_VALUE_MAX_BYTES` (default 256; see Appendix F); on overflow, the kernel **MUST** reject that attribute header or syscall input and return `E_EMIT_ESCAPE_VIOLATION`.

The kernel generates or completes an attribute header at the following times:

- After the model generates a non-rollback envelope open token, the kernel injects a default attribute header (such as `id` and default `from="model"`) before entering body sampling;
- When `envelope.emit`, boot output, persona-refresh, or other kernel /program paths write an envelope, the kernel generates the attribute header from passed attrs or internal metadata;
- If an implementation accepts attributes in an open-tag form, it **MUST** first canonicalize them to this attribute header; the normative text, schemas, and tests use this attribute header as the source of truth.

> **Attribute-header injection atomicity (general rule)** - For any non-rollback envelope, the open token and the kernel-owned attribute header that immediately follows **MUST** be completed as an indivisible write unit: from the moment the open token is written to the moment the attribute header's terminating blank line is written, the kernel **MUST NOT** interleave any C1 (suspend) /C3 (abort) /C4 (preempt) control event; control events that arrive during this window **MUST** be queued and handled only after the attribute header is complete. The kernel **MUST NOT** allow program state or the inference stack to observe an intermediate state where "open is written but the attribute header is incomplete". This rule **covers every kernel attribute-header injection path** - including the default attribute header injected after a model-spontaneous open, `envelope.emit` /boot output /persona-refresh writes, auto execute scaffold injection (§10.1.2), and the canonicalization path when the implementation accepts open-tag-form attribute input - not only the scaffold submode. If the implementation decides for any reason to abandon the write, it **MUST** cancel and roll back the related decision **before** the open token is written, and **MUST NOT** emit a `kind=envelope_open` audit. §10.1.2 item 5 retains an equivalent but tighter event-queue rule for the scaffold submode (related to control-event priority arbitration); it does not conflict with this general rule, and on conflict this section prevails as the protocol-surface source of truth.
>
> **Note** - The `<lmsc_rollback>` envelope **carries no attributes**; its body directly carries the pattern sequence (see §4.1.2a /§4.3 EBNF). In the table below, values such as "all" in the `Applicable envelope` column **exclude** the rollback envelope.

The kernel **MUST** recognize the following core attributes (attributes not listed are passed through to programs):

Attribute	Applicable envelope	Values	Semantics
`id`	all	string	Unique identifier (kernel auto-completes a default)
`from`	execute /output /edit	`user` /`system` /`program:<name>` /`model`	Source
`visibility`	output /edit	`all` (default) /`model-only` /`user-only`	Visibility
`attention`	output	`free` (default) /`keep-summary` /`pin`	Retention policy
`confidence`	output /edit	`0.0`-`1.0`	Confidence
`schema`	output	string	Rendering schema name
`gen`	output	Free string (program-defined)	Generation marker; the kernel **does not interpret** it and only passes it through
`status`	output	string	Error code or `ok`; `ok` + empty body forms a short-circuit "ack"
`ref`	output	Same form as `id`	The ID used when this output is used as a ref source

For unknown attributes, the kernel **MUST** preserve and pass them through, and **MUST NOT** delete them.

> **Explanation** - The `gen` attribute uses a **free string**; the kernel performs no enum checking and triggers no state machine. Generation semantics are defined by the program itself, which conforms to P-5.
>
> **Explicit rule** - The **scope of `gen` is per-program**: the kernel **MUST NOT** compare `gen` strings across programs. The same `gen` spelling is not required to have the same semantics in program A and program B. If recommended programs need interoperability, a separate recommended-program document **SHOULD** provide an ecosystem-level vocabulary (not a normative-level constraint). Correspondingly, `region.tag.attrs.gen` is also per-program (the namespace of the owner program).
>
> **Length budget** - `gen` remains a free string, but it is subject to the unified attribute-value cap `ATTR_VALUE_MAX_BYTES`; recommended programs and distribution vocabularies **SHOULD** keep `gen` within 64 bytes so audit, diffs, and training samples remain stable.

4.3 Grammar (EBNF)

```
stream = { chunk | envelope | control | ref_element } ;
chunk = { ordinary_token } ;
envelope = execute_env | output_env | edit_env | rollback_env ;

(* envelope open tokens are complete reserved tokens; attributes are carried by the kernel-injected attribute header *)
execute_env = "<lmsc_execute>" , attr_header? , body , "</lmsc_execute>" ;
output_env = "<lmsc_output>" , attr_header? , body , "</lmsc_output>" ;
edit_env = "<lmsc_edit>" , attr_header? , body , "</lmsc_edit>" ;
rollback_env = "<lmsc_rollback>" , pattern_body , "</lmsc_rollback>" ;
attr_header = "@lmsc-attrs" , attrs , line_end , line_end ;
attrs = ws , attr , { ws , attr } ;
attr = ident , "=" , str_literal ;

(* lexical atomic definitions *)
ordinary_token = ? non-reserved token in the vocabulary, as output by the kernel tokenizer ? ;
ident = letter , { letter | digit | "_" | "-" } ;
str_literal = '"' , { str_char } , '"' ;
 (* double-quoted; MUST NOT span a newline; supports the two escapes \" and \\ *)
 (* each decoded str_literal has UTF-8 byte length <= ATTR_VALUE_MAX_BYTES; gen is recommended <= 64 bytes. *)
str_char = ( ? any Unicode character except '"' , '\\' , LF , CR , Tab (0x09) ? )
 | "\\\"" | "\\\\" ; (* Tab is excluded to avoid ambiguity at lexical boundaries of attribute values *)
ws = { " " | "\t" } ; (* attribute headers are inline and do not include newline; ws is required before the first attribute
↪  *)
line_end = "\n" | "\r\n" ;
 (* The trailing `line_end , line_end` in `attr_header` is two repetitions of `line_end`, equivalent to a single **blank
↪  line** at the end of attrs. `\r\n` is treated as a single `line_end` token and **MUST NOT** be split into two `line_end`
↪  tokens to fabricate a blank line. *)
letter = "A" .. "Z" | "a" .. "z" ;
digit = "0" .. "9" ;

body = { chunk | ref_element | control | rollback_env } ;
pattern_body = ordinary_token , { ordinary_token } ;
 (* non-empty; its detokenized byte sequence <= ROLLBACK_PATTERN_MAX_BYTES;
 and the byte sequence MUST NOT form the literal form of any reserved token
 (envelope open/close, <|lmsc_abort|>~/<|lmsc_suspend|>, <lmsc_ref>~/</lmsc_ref>, key literals).
 The check is performed **at byte level**: substring search is run over the detokenized
 UTF-8~/binary byte sequence of pattern_body, independent of how the tokenizer segments it.
 Violations are detected post-hoc by I-ROLLBACK-NO-NEST (enforced by logit mask in L0/L1). *)

ref_element = "<lmsc_ref>" , ref_body , "</lmsc_ref>" ;
ref_body = 'k','i','n','d',':',' ','"' , ref_value , '"',';'
 , 'i','d',':',' ','"' , ref_value , '"',';' ;
ref_value = ref_char , { ref_char } ;
ref_char = 'A'..'Z' | 'a'..'z' | '0'..'9'
 | '_' | '.' | ':' | '/' | '-' ; (* values are limited to the ASCII safe set *)

control = "<|lmsc_abort|>"
 | "<|lmsc_suspend|>"
 | key_token ;

key_token = "<|key_" , ident , "|>" ;
```

Specified - The body of `<lmsc_ref>...</lmsc_ref>` **MUST** exactly conform to:

`kind: "{kind}";id: "{id}";`

Where (`{kind}` /`{id}` are placeholders representing the actual value strings):

1. Field names are limited to `kind` and `id`;
2. The order is fixed: `kind` first, `id` second;
3. The character set of both values is limited to ASCII `[A-Za-z0-9_.:/-]`;
4. Additional fields **MUST NOT** be included, non-ASCII characters **MUST NOT** be used, and whitespace variants that deviate from this micro-grammar **MUST NOT** be used;
5. The values of `kind` and `id` **MUST NOT** be empty strings; the form `kind:"";` violates the EBNF (`ref_value` has at least 1 character) and is likewise treated as a micro-grammar violation.

A ref element that violates this micro-grammar or character-set constraint **MUST** be rejected by the kernel, which emits audit `kind=protocol_violation` (invariant=`I-REF-CHARSET`) and returns `E_REF_BODY_INVALID`.

The attribute headers of `<lmsc_execute>` /`<lmsc_output>` /`<lmsc_edit>` are **not subject** to this restriction: they are not on the fast path of streaming ref parsing and are parsed as kernel-owned attribute headers.

Explicit character prohibition - The `ref_char` character set above already implicitly excludes the double quote `"` and semicolon `;`, which are ref body delimiters themselves. This explicitly restates: the values of `kind` /`id` **MUST NOT** contain `"` or `;`. If an external system ID contains non-whitelisted characters (Chinese, spaces, Unicode punctuation, quotes, semicolons, etc.), the program **MUST** perform mapping/hash

processing at the `ref.bind` stage itself; the kernel **does not** provide an escaping mechanism. For any violating ref body, the kernel always returns `E_REF_BODY_INVALID`. See §9.3 for non-normative interoperability recommendations: prefer canonical IDs such as `base64url(no_padding(utf8_bytes))` or `sha256:<hex-prefix>`, and register the scheme /collision policy.

4.4 Grammar Invariants (Normative)

A conforming kernel **MUST** enforce the following grammar invariants. Enforcement modes are divided by level and invariant type:

- **A1 logit mask enforcement** (L0 /L1, at the sampler hook level): `I-ENV-PAIR`, `I-ENV-NO-SELF-NEST`, `I-CTRL-INSIDE-ENV`, `I-ROLLBACK-BOUND`, `I-ROLLBACK-NO-NEST`, `I-ABORT-SCOPED`, `I-ATTR-CLEAN`, `I-ROLLBACK-NO-ATTR`; plus the conditional invariant `I-STRICT-ENVELOPE-ONLY` (only included in the A1 enforcement set when `features.strict_protocol_mode=true` and `features.raw_text_outside_envelope="forbidden"`; see the end of this section and §10.1.2);
- **Syscall entry enforcement** (all levels): `I-EMIT-ESCAPE` (checked on `envelope.emit`, `net` -> envelope body rewriting, `region.edit`, and `ref.resolve` failure visible-text injection paths);
- **Post-hoc recognition + abort** (all levels, and under L2 the A1 group above is downgraded to this mode; see §6.5.1): `I-REF-CHARSET`. `I-REF-ANY` is a permissive invariant and has no violation form by itself; its legality is guaranteed by the ref-element exception in `I-CTRL-INSIDE-ENV` together with the body check in `I-REF-CHARSET`.

The entries are as follows:

- **I-ENV-PAIR** - Every envelope open **MUST** have a corresponding close; the session **MUST NOT** close before the close appears.
- **I-ENV-NO-SELF-NEST** - Envelopes of the same kind **MUST NOT** be directly nested (`<lmsc_execute>` **MUST NOT** be nested inside `<lmsc_execute>`).
- **I-CTRL-INSIDE-ENV** - Inside a non-rollback envelope, the only reserved tokens that **MAY** appear are: `<|lmsc_abort|>`, `<|lmsc_suspend|>`, a complete `<lmsc_ref>...</lmsc_ref>` ref element, and a **nested `<lmsc_rollback>` open** (the model initiates an undo inside an execute/output/edit body); the mask **MUST** reject other envelope open tokens. A `<lmsc_ref>` open /body /close **does not** enter the envelope stack and **does not** trigger B2 dispatch; its legality is constrained independently by `I-REF-ANY` and `I-REF-CHARSET`. L0 /L1 logit masks **MUST** allow `<lmsc_ref>` opens and legal ref-body continuation inside non-rollback envelope bodies, and **MUST NOT** misclassify them as forbidden envelope opens. Inside a **rollback envelope body**, reserved tokens **MUST NOT** appear (constrained by `I-ROLLBACK-NO-NEST`; in particular, `<|lmsc_suspend|>` and `<lmsc_ref>` **MUST NOT** appear inside a rollback envelope body to avoid carrying a partial pattern in a snapshot or triggering ref resolution).

  > **Disambiguation of the term "nested"** - In this entry, "nested `<lmsc_rollback>` open" means opening a new rollback envelope inside an execute /output /edit envelope body. This **MAY** occur (the rollback envelope then closes by itself and does not actually form a long-lived nested stack). What `I-ROLLBACK-NO-NEST` prohibits is any reserved token appearing inside the **body of the rollback envelope itself** (including another rollback open). The two uses of "nested" have different meanings and **MUST NOT** be conflated.

- **I-REF-ANY** - `<lmsc_ref>...</lmsc_ref>` **MAY** appear in any envelope body, and **MAY** also appear in an ordinary chunk.
- **I-ROLLBACK-BOUND** - The match search of `<lmsc_rollback>` **MUST NOT** cross the boundary of a closed envelope, the boundary of boot output, or the boundary of a dispatch declared with `rollback_safe:false`.
- **I-ROLLBACK-NO-NEST** - The body of `<lmsc_rollback>` **MUST NOT** contain any reserved token (any envelope open/close, `<|lmsc_abort|>` /`<|lmsc_suspend|>`, `<lmsc_ref>` /`</lmsc_ref>`, or key token). The kernel **MUST** enforce this through logit masks; if a post-hoc path identifies a violation, it **MUST** emit `kind=protocol_violation` and return `E_ROLLBACK_PATTERN_INVALID`.
- **I-ROLLBACK-NO-ATTR** - `<lmsc_rollback>` **MUST NOT** carry any attribute header or attribute metadata; L0 /L1 enforce this with logit masks, and under L2 it is handled by the same-named post-hoc detection item in §6.5.1. On violation, return `E_ROLLBACK_PATTERN_INVALID` and emit `protocol_violation` audit.

  > **L0 /L1 lookahead algorithm requirement** - The kernel **MUST** build a byte-level Aho-Corasick or equivalent trie over the **literal byte sequences** of all reserved tokens for multi-pattern lookahead in logit masks: after a candidate token is appended, if **any suffix** of the current rollback body accumulated byte sequence forms a non-empty prefix of any reserved token literal, the kernel **MUST** `hard_deny` that candidate token. This requirement covers the complete set of the four envelope open/close pairs,

<|lmsc_abort|> /<|lmsc_suspend|>, <lmsc_ref> /</lmsc_ref>, and all <|key_*|> literals. L2 does not apply this lookahead; it is handled instead by the post-hoc check in §6.5.1 item 5.

- **I-ABORT-SCOPED** - <|lmsc_abort|> is valid **only** inside an envelope. If it appears outside an envelope, the kernel **MUST** discard it (preferably by blocking it with a logit mask).
- **I-ATTR-CLEAN** - The kernel-owned attribute header ends at the blank-line boundary; the attribute header **MUST NOT** contain any special token literal, and the header prefix, separator before the first attribute, line ending, blank line, and attribute-value length cap **MUST** conform to §4.3 /§4.2.
- **I-EMIT-ESCAPE** - When injecting the bytes body of `envelope.emit`, rewriting a `net` response into an envelope body, injecting the `replacement` bytes of `region.edit`, or injecting visible text for `ref.resolve` failure, the kernel **MUST** escape reserved-token literal characters (§13.2).
- **I-REF-CHARSET** - The body of <lmsc_ref>...</lmsc_ref> **MUST** exactly conform to the micro-grammar `kind: "{kind}";id: "{id}";` ({kind} /{id} are placeholders); both values are limited to ASCII [A-Za-z0-9_.:/-] and **MUST NOT** be empty strings; violations **MUST** be rejected, emit `kind=protocol_violation`, and return `E_REF_BODY_INVALID`.
- **I-STRICT-ENVELOPE-ONLY** (**conditional invariant**, enabled only when `features.strict_protocol_mode=true` and `features.raw_text_outside_envelope="forbidden"`) - When the state is `GENERATING` and the envelope stack depth = 0, the next token sampled by the model **MUST** belong to the "legal LMSC protocol entry" set: one of <lmsc_execute> /<lmsc_output> /<lmsc_edit> /<lmsc_rollback> /<|lmsc_suspend|> /<lmsc_ref> open /EOS; any non-entry ordinary token is treated as a violation. <lmsc_ref> open is included in the entry set to stay consistent with `I-REF-ANY` (a ref **MAY** appear in any envelope body and in ordinary chunks); after the ref element closes the stack depth is still 0, and the immediately following token remains subject to this invariant. If that ref element was opened while this invariant was active and the stack depth was 0, a successful expansion result **MUST** also follow the strict top-level ref materialization rule in §9.3; the kernel **MUST NOT** write ordinary bytes returned by the resolver directly into context outside an envelope merely after `I-EMIT-ESCAPE`. L0 /L1 **MUST** enforce this in the sampler hook via logit mask before sampling; L2 detects violations post-hoc in the token stream hook and routes through `kind=protocol_violation` (invariant=`I-STRICT-ENVELOPE-ONLY`) the same way as §6.5.1 item 10, returning `E_PROTOCOL_VIOLATION`. When `raw_text_outside_envelope="audit-only"`, the invariant is **not** enforced, but the kernel **MUST** emit audit `kind=raw_text_outside_envelope` (which does not constitute a violation). When `raw_text_outside_envelope="allowed"` or `strict_protocol_mode=false`, the invariant is **not** active, preserving the existing compatibility behavior.

4.5 Role Semantics

For the three envelope kinds **`execute`** /**`output`** /**`edit`**, "**who initiated it**" is determined entirely by the `from` attribute in the attribute header (§4.2). The kernel **MUST NOT** hard-code roles by envelope kind: <lmsc_execute> defaults to `from="model"`, but it is legal for a program to write on behalf of the kernel with a kernel-owned attribute header carrying `from="program:flow"`.

The `rollback` envelope is the exception: <lmsc_rollback> **carries no attributes** (§4.2) and does not use the `from` mechanism; its role is determined implicitly by the generation path. When generated by model autoregression it is equivalent to `from="model"`; when a program explicitly calls A3 `token_rollback`, the audit records `source=program:<name>`. **The model path being "equivalent to `from=\"model\""` is only semantic attribution that treats it as model-initiated; no actual `from` attribute exists**. Any code parsing a rollback envelope **MUST NOT** try to read or infer its `from` field: that field does not exist and is structurally absent. Rollback-related audit **MUST NOT** use an `envelope_from` field; source attribution uses §14.2 `rollback_origin` or `AuditRecord.source`.

---

5. Atomic Operations

This section defines the kernel's minimal capability set. Each atomic operation gives: signature, preconditions, post-conditions, errors, and notes.

5.1 Categories and Counts

Class	Numbers	Core	Level-Dependent Optional
A - Token Stream	A1-A5	4	A2
B - Envelope Structure	B1-B3	3	--
C - Scheduling	C1-C5	5	--
D - Authorization	D1-D3	3	--
E - Program Table	E	1	--
F - State	F1-F4	4	--
G - Audit	G1	1	--
H - I/O	H1-H3	2	H3
I - Time	I1	1	--
Total		**24**	**2**

The **24** core primitives **MUST** be implemented; the two **level-dependent optional** primitives, **A2 and H3**, are determined by the §6.5 access level: L0 **MUST** provide both A2 and H3, L1 **MAY** provide them, and L2 **MAY** omit them.

5.2 A - Token Stream

A1 - `logit_mask`

```
logit_mask(mask: Mask) → ()
Mask := { hard_allow: Set<TokenId>?, hard_deny: Set<TokenId>?, bias: Map<TokenId, f32> }
```

- **Precondition**: the caller holds the `tokens.mask.direct` cap (fixed-only; by default only kernel internals and the inference stack adapter layer).
- **Postcondition**: applied to logits before the next sampling operation.
- **Errors**: `E_MASK_INVALID`.
- **Notes**: hard_deny takes precedence over bias; when hard_allow is non-empty, all other tokens **MUST** be treated as hard-denied.

A2 - `query_special` (Level-Dependent Optional)

```
is_special(id) → bool
name_of(id) → Option<string>
id_of(name) → Option<TokenId>
```

- **Precondition**: none.
- **Postcondition**: read-only; the returned mapping does not change during the session lifecycle.
- **Notes**: equivalent information is already returned in boot output; this primitive is a convenience API. Conforming L0 implementations **MUST** provide it; L1 implementations **MAY** provide it; L2 implementations **MAY** omit it. Programs **SHOULD** cache the token list from boot output in `on_load` and check `runtimeinfo.kernel.atomics` before calling it.

A3 - `token_rollback`

```
token_rollback(pattern: Bytes, scope: Scope) → Result<()>
Scope := Envelope | Turn
```

- **Preconditions**:
  - `I-ROLLBACK-BOUND` has not been violated;
  - `pattern` is non-empty and `len(pattern)≤ROLLBACK_PATTERN_MAX_BYTES` (default 512);
  - `pattern` **MUST NOT** contain the literal byte sequence of any reserved token (equivalent to `I-ROLLBACK-NO-NEST`);
  - The number of rollbacks in the current turn is < `ROLLBACK_STORM_LIMIT` (default 16);
  - The caller holds `tokens.rollback.explicit` (not granted by default; model-emitted `<lmsc_rollback>` envelopes use the kernel-internal equivalent path and do not use this cap).
- **Postconditions**:

  - Reverse-search for the most recent occurrence of `pattern` within the byte window allowed by scope;
  - On hit: discard the entire token containing the first matched byte, leaving the KV cache tail before that token (discarding the rollback envelope itself as well);
  - On miss (`pattern_not_found`) or if any byte of the hit interval is out of bounds (`pattern_out_of_bound`): leave KV unchanged;
  - Emit audit `kind=rollback`, with details containing `outcome` ∈ {`truncated`, `pattern_not_found`, `pattern_out_of_bound`} /`search_scope` /`pattern_bytes_len` /`truncated_tokens` (when `outcome=truncated`). Here `pattern_out_of_bound` distinguishes "pattern does not exist in the whole context" from "some byte in the matched interval falls outside the boundary". `search_scope` records the A3 argument or model-path inference, avoiding reuse of top-level `AuditRecord.scope` visibility semantics.
  - `ROLLBACK_STORM_LIMIT` counting follows the §13.3 rule: within a single turn, both **successful** (`outcome=truncated`) and **failed** (`pattern_not_found` /`pattern_out_of_bound`) attempts count toward the same counter, without distinction.
- **Errors**: `E_ROLLBACK_STORM` /`E_ROLLBACK_PATTERN_EMPTY`/ `E_ROLLBACK_PATTERN_NOT_FOUND`/ `E_ROLLBACK_PATTERN_TOO_LONG`/ `E_ROLLBACK_PATTERN_INVALID`.

A model-triggered `<lmsc_rollback>`⋯`</lmsc_rollback>` envelope and a program call to this primitive are **semantically equivalent**; both paths share the preconditions and invariants above. A miss on the model path does not report an error and only emits audit. **Model path `scope` inference**: current state `IN_ENVELOPE` -> `Envelope`; current state `GENERATING` -> `Turn`. The program-path syscall signature does not provide a default; the caller **MUST** pass `scope` explicitly. When a language binding or the kernel receives a defaulted/missing scope, it **MUST** reject the call and return `E_PROTOCOL_VIOLATION` or an equivalent binding-layer error.

> **V1 status of `tokens.rollback.explicit` -** This cap is listed as **fixed-only** (§11.4), but V1 grants it to no program (§12.3 default-holding table does not include it, and Appendix B also marks it `no,fixedonly`). This specification retains the `token_rollback` syscall interface as the kernel-internal equivalent path and as an entry point for a future major-version extension; in V1 there is **no legal program call path**. The current conforming paths that can produce KV truncation are model-generated `<lmsc_rollback>...</lmsc_rollback>` envelopes, or the kernel internally mapping that envelope close to the A3-equivalent flow.

V1 A3 path decision table:

Path	V1 status	Authorization and result
Model rollback envelope path	**MUST** support	The close of `<lmsc_rollback>...</lmsc_rollback>` triggers the kernel-internal A3-equivalent flow; no program cap participates
Kernel internal path	**MUST** support	The token stream hook /rollback parser **MAY** call the internal A3 semantics; it is not exposed to programs
Program syscall path `tokens.rollback(pattern,scope)`	**MUST** be unreachable	Programs **MUST NOT** hold `tokens.rollback.explicit` through `capabilities.granted` /`capabilities.requestable`; calls without the cap return `E_CAP_DENIED`, and a manifest /runtime state that claims the cap is requestable or already granted is non-conforming

> **Compatibility note**: if a future major version defines a program-initiated A3 path, it **MUST** also define callback return after rollback completion, reentry rejection, audit, and error-code rules. That path is not a V1 conformance test item.

A3 Level-Based Downgrade

A3 availability and downgrade semantics at different access levels:

Level /branch	`features.rollback_truncate_precision`	Rollback result	Enters §10.1.1 restoration algorithm?
L0	`byte`	Execute precise KV truncation after a hit; legal misses keep KV unchanged	Enters after a hit and completed truncation

Level /branch	features.rollback_truncate_precision	Rollback result	Enters §10.1.1 restoration algorithm?
L1	byte or token	Truncate through the rollback truncate adapter after a hit; the token branch discards the entire token containing the first matched byte, leaving the KV tail before that token	Enters after a hit and completed truncation
L2	byte or token	Post-hoc scan after the close event; truncate through the adapter after a hit; illegal rollback is cleaned up according to §6.5.1.1	Enters after a legal hit and completed truncation
L2	none	Does not perform physical truncation; **MUST** abort the current turn and emit protocol_violation or rollback_error (as determined by §6.5.1.1 /§14.2.2)	Does not enter; abort rollback takes precedence

The none branch is not ”low-precision restoration”; it is a fail-closed path when the rollback truncation precondition cannot be satisfied. Therefore it **MUST NOT** call the normal restoration algorithm in §10.1.1.

- **L0 /Tier-A**: as in the main text of this section; scope ∈ {Envelope, Turn} has complete semantics; pattern-string matching is implemented precisely by KV Hook + sampler mask; restoration state follows §10.1.1 with O(T) or O(1) snapshot.
- **Rollback truncate adapter**: any implementation that claims to support A3 truncation, even if it does not provide a full KV Hook, **MUST** declare a minimal truncation adapter through the inference stack adapter layer: truncate_to_token(pos) or truncate_to_byte(pos). This adapter only handles rollback truncation and is not equivalent to the A5 fork/restore/drop KV Hook. If physical truncation is completely unsupported, the implementation **MUST** declare features.rollback_truncate_precision=”none” and follow the abort fallback below.
- **L1 /Tier-B**: no full KV Hook, but the rollback truncate adapter **MUST** be supported. scope=Turn **MUST** be supported; scope=Envelope **MAY** have token-level truncation precision. If the inference stack adapter layer does not provide a byte-precise truncation API, an L1 implementation **MAY** run with boot output features.rollback_truncate_precision=”token” (unified with the L2 rule); the pattern search window still **MUST** be precise with respect to structural boundaries (**MUST NOT** approximate by the turn start as a worst case), and only truncation precision **MAY** be downgraded. On hit, audit details mark truncate_precision=token.
- **L2 /Tier-C**: no sampler hook and no full KV Hook. scope ∈ {Envelope, Turn} is determined by post-hoc scanning in the token stream hook; pattern matching is executed once at the </lmsc_rollback> close event; the kernel performs byte-precise or token-precise truncation through the rollback truncate adapter. If the adapter layer does not support byte-precise truncation, the L2 implementation **MUST** truthfully declare features.rollback_truncate_precision ∈ {byte, token} in boot output; an implementation declaring token **MUST** discard the entire token containing the first byte of the pattern when that byte falls in the middle of a token, leaving the KV tail before that token, and mark truncate_precision=token in audit details.

L2 fallback path when KV truncation is completely unsupported - If the inference stack adapter layer provides neither byte-precise nor token-level truncate APIs (meaning the kernel cannot complete any physical KV truncation under L2), the L2 implementation **MUST**: (1) declare features.rollback_truncate_precision=”none” in boot output; (2) when observing the </lmsc_rollback> close, perform no truncation and instead execute C3 abort for the current turn; (3) emit audit kind=protocol_violation (invariant=I-ROLLBACK-BOUND), with details containing truncate_fallback=”abort” and reason=”rollback_unsupported_truncate” (so the model can learn to stop generating it), and temporarily retain it in the model-visible projection of runtime audit tail; (4) **if this abort is triggered by the program path A3 or explicitly observed by a program**, return E_PROTOCOL_VIOLATION to the caller; the model path only emits audit and does not return an error to any caller (unified with the §6.5.1 L2 post-hoc invariant detection rule ”if the abort is observed as program-initiated”). **This C3 abort MUST ensure that the rollback envelope does not enter final stable context**; if an implementation cannot fully intercept it before the abort path, it **MUST** intercept at an earlier hook stage. L2 implementations **MUST NOT** silently ignore rollback that cannot be truncated; this fallback path **MUST** satisfy §16.1 C-11 for L2 post-hoc detection.

At all levels, A3 error-code semantics, out-of-bound handling (pattern_out_of_bound), audit emit rules, ROLLBACK_STORM_LIMIT, and related rules remain consistent. The implementation level does not affect the normative semantics of

A3; it only affects "how precisely those semantics are achieved".

A4 - token_inject

```
token_inject(tokens: Vec<TokenId>, position: Position) → Result<()>
Position := BeforeNextSample | AtEnvelopeClose
```

- **Preconditions**:
  - State **MUST** be one of { GENERATING, IN_ENVELOPE, DISPATCHING }; if the session is SUSPENDED, an ordinary A4 syscall **MUST** return E_INJECT_BAD_POSITION, with details preferably containing reason="suspended". C2 resume payload injection is part of C2's atomic restoration path and is not a direct A4 call while SUSPENDED;
  - All tokens are in the vocabulary;
  - If reserved tokens are included, the caller holds the tokens.inject.special cap (fixed-only);
  - Total length ≤ INJECT_MAX_TOKENS (default 4096);
  - The injection **MUST NOT** make the envelope stack exceed MAX_ENVELOPE_NEST; injections that would overflow the stack **MUST** return E_STACK_OVERFLOW;
  - An envelope close token **MUST NOT** be injected outside an envelope;
  - position=AtEnvelopeClose **MUST** be used only when the current envelope stack is non-empty and the stack top is not a rollback envelope; otherwise the kernel **MUST** return E_INJECT_BAD_POSITION;
  - **Token-sequence content invariant (applies to all positions)**: when the injection position lies inside a **non-rollback** envelope body (including the default position=AtEnvelopeClose case, and position=BeforeNextSample when the current stack top is a non-rollback envelope), the injected token sequence **MUST** satisfy §4.4 I-CTRL-INSIDE-ENV: the only reserved tokens permitted are <|lmsc_abort|>, <|lmsc_suspend|>, a complete <lmsc_ref>...</lmsc_ref> ref element, and a nested <lmsc_rollback> open; open /close tokens of any other envelope (including <lmsc_execute> /<lmsc_output> /<lmsc_edit> and same-kind nested open /close) **MUST NOT** be injected, even if the caller holds the tokens.inject.special cap. The kernel **MUST** validate the entire token sequence at the syscall entry (before sampling /KV write); on violation it **MUST** return E_INJECT_BAD_TOKEN, with details preferably containing reason="ctrl_inside_env_violation", and emit audit kind=protocol_violation (invariant=I-CTRL-INSIDE-ENV). Injection outside any envelope still follows existing rules such as "**MUST NOT** inject envelope close tokens"; rollback envelope bodies are already covered by the previous AtEnvelopeClose prohibition rule together with I-ROLLBACK-NO-NEST.
- **Position semantics**:
  - BeforeNextSample: insert before the next model sample; the insertion point is the current natural state-machine position;
  - AtEnvelopeClose: insert immediately **before** the matching close token of the current innermost open envelope, making the injected tokens part of that envelope body. This position **MUST NOT** be used for a rollback envelope body, to prevent program injection from breaking I-ROLLBACK-NO-NEST /I-ROLLBACK-BOUND checks for the rollback pattern.
- **Postcondition**: insert and update the KV cache; emit audit.
- **Errors**: E_INJECT_BAD_TOKEN /E_INJECT_BAD_POSITION /E_INJECT_CAP_DENIED /E_INJECT_TOO_LARGE /E_STACK_OVERFLOW.

A5 - session_fork

```
session.current_handle() → SessionHandle # current session handle; does not create a fork
session.fork() → SessionHandle # new session, shared KV prefix
session.restore(handle: SessionHandle) → Result<()> # switch to an already forked session
session.drop_fork(handle: SessionHandle)→ Result<()> # release a fork
```

- **Preconditions**:
  - The implementation level **MUST** be **L0** (A5 is unavailable under L1 /L2; calls return E_ATOMIC_UNSUPPORTED);
  - current_handle: the caller holds the session.fork cap; returns the SessionHandle for the current session, does not create a new fork, does not allocate a CoW snapshot, and does not count against fork depth /concurrency /memory quotas;
  - fork: **handlers in the session MUST NOT hold an in-progress streaming envelope.emit**; if this condition is violated, the kernel **MUST** return E_EMIT_STREAM_OPEN, with details containing at least open_stream_count, and **SHOULD** contain the list of unclosed envelope_id values that can be exposed; calling inside dispatch is legal: runtime admin fork (§12.3) depends on this path. (Cannot fork while streaming emit is unfinished.)
  - **Fork quota checks** (formally linked to Appendix F.3 normative constants and the errors registered in §15.2) - before allocating a CoW KV snapshot, the kernel **MUST** perform the following three checks, returning errors in this order. In concurrent scenarios, crossing through the gap between assignment and allocation **MUST** be guarded (quota check + CoW allocation **MUST** hold a mutex or equivalent semantics for the same root session):

1. **Depth**: if the fork-chain depth from the root session downward is ≥ `SESSION_FORK_MAX_DEPTH` (Appendix F.3; default 8), return `E_FORK_DEPTH_EXCEEDED`, audit details `reason="depth_limit"`;
2. **Concurrency**: if the total number of active (not `drop_forked`) forks of the current root session is ≥ `SESSION_FORK_MAX_CONCURRENT` (Appendix F.3; default 16), also return `E_FORK_DEPTH_EXCEEDED`, audit details `reason="concurrent_limit"`; both structural upper bounds reuse the same error code and are distinguished by the audit `reason` field; a separate error code is unnecessary (§15.1 class-A `E_FORK_` prefix convergence principle);
3. **Memory quota**: if the implementation sets `SESSION_FORK_MEM_LIMIT_MB` (Appendix F.3; default 1024, `null` means disabled), and **the estimate for this fork + accumulated CoW memory of currently active forks** exceeds that value, return `E_FORK_MEM_EXCEEDED` (quota exceeded); if depth /concurrency both pass and quota is sufficient (or disabled) but the underlying CoW allocation fails (physical OOM /address-space exhaustion), return `E_FORK_OOM` (physical allocation failure). The two are explicitly distinct.

– `restore` /`drop_fork`: the handle is valid.

- **Postconditions**:
  – `current_handle` returns the opaque handle of the current session; it does not change context /KV /audit cursor /dispatcher frame /fork quota state;
  – `fork` saves the complete context + KV cache (CoW reference) + kernel metadata (program table, kv refcount, capability set, audit cursor); returns a new SessionHandle, while the original session remains alive;
  – `restore` switches current execution to the target session, while the original session remains alive (the caller can explicitly release it with `drop_fork`);
  – `drop_fork` releases the corresponding CoW reference.
- **Errors**: `E_FORK_INVALID` /`E_EMIT_STREAM_OPEN` /`E_FORK_OOM` /`E_FORK_DEPTH_EXCEEDED` /`E_FORK_MEM_EXCEEDED` (trigger conditions are described in the precondition quota checks above; retryable classification is in §15.3).
- **Notes**: explicitly uses **fork semantics**. Supports tree-of-thought, OOM protection, and transactional dispatch.
- **`SessionHandle` type** - `SessionHandle` is an in-memory handle (opaque type); it is **not** serializable and **MUST NOT** be persisted across sessions; it is valid only during the current kernel instance lifecycle. `current_handle()` and `fork()` return the same kind of handle; a program can save the parent session handle before `restore(child)` and later use `restore(parent)` to return to the parent branch. Carrying the handle across processes /deployments **MUST** return `E_FORK_INVALID`.

5.3 B - Envelope Structure

B1 - `envelope_event`

```
(event, produced by the token stream hook)
on_envelope_open(kind, attr_header, id) → ()
on_envelope_close(kind, id) → ()
```

- **Postconditions**:
  – After open, the kernel associates or injects the kernel-owned attribute header; after the blank line ending the attribute header, it enters the body;
  – Close triggers B2 dispatch (if execute) or audit (if output/edit);
  – Stack depth ≤ `MAX_ENVELOPE_NEST` (default 4); when exceeded, the kernel **MUST** block open tokens through the logit mask.

B2 - `dispatch`

```
dispatch(envelope: Envelope) → DispatchResult
```

- **Preconditions**:
  – `envelope.kind=ExecEnv`;
  – **If the target program manifest declares `reentrant:false` and that program already has an active dispatch** (within the same session, not yet returned or aborted, including a dispatch in `SUSPENDED` state that has not yet resumed), the kernel **MUST** reject and return `E_DISPATCH_REENTRY`. A dispatch in `SUSPENDED` state is still considered an active dispatch and is subject to the same constraint.
- **Postconditions**:
  1. Parse the first token sequence of the body as `argv`;
  2. `program_table.lookup(argv[0])` -> handler;
  3. `cap.check(program.capabilities_required)`;
  4. Call `handler.dispatch(ctx,args)`;
  5. Write audit.

- **Errors**: `E_UNKNOWN_PROGRAM` /`E_CAP_DENIED` /`E_HANDLER_PANIC` /`E_DISPATCH_REENTRY` /`E_EMIT_STREAM_OPEN` (`persona-refresh` and other scenarios using the "handler holds an unclosed streaming emit" branch use this dedicated error code and no longer reuse `E_DISPATCH_REENTRY`).
- **Notes**: handler **MAY** call `scheduler.suspend` to yield; the kernel resumes it when conditions are satisfied.
- **Handler panic and `on_abort` cleanup** - When handler `dispatch` returns panic /error, the kernel **MUST** automatically trigger a close path equivalent to C3: if the handler registered `on_abort`, first call `on_abort(ctx,envelope_id)` so the program can clean up (release region locks, reclaim temporary kv keys, etc.), then emit audit `kind=abort` (details contain `reason="handler_panic"`); then return `E_HANDLER_PANIC`. If `on_abort` itself panics, the kernel **MUST** swallow that panic and attach `nested_panic=true` to the `kind=abort` details, so that internal stacks are not exposed; it does not call `on_abort` a second time. **`on_abort` deduplication**: `on_abort` for the same envelope is called **at most once**; if one trigger path has already called it, any later trigger path for the same envelope (such as concurrent close + panic) **MUST NOT** call it again.

Abort sequencing for SUSPENDED dispatch - If a dispatch has entered `SUSPENDED` through C1, but its associated envelope, unfinished stream, dispatch timeout, or external abort triggers abort while suspended, the kernel **MUST** finish in the following order:

1. Cancel the resume handle registered by that dispatch. Later `resume` for that handle **MUST** return `E_SUSPEND_INVALID` or `E_SUSPEND_EXPIRED`, with details marking `reason="aborted_while_suspended"`;
2. Stop and cancel the unfinished generator /async iterator held by that dispatch, using cancellation semantics equivalent to B3 `E_EMIT_STREAM_ABORTED`;
3. Call `on_abort` at most once according to the envelope_id deduplication rule;
4. Clean up dispatcher frames that have not yet been popped during that handler /turn;
5. Complete the original dispatch with the error corresponding to the trigger source: stream abort uses `E_EMIT_STREAM_ABORTED`, dispatch timeout uses `E_DISPATCH_TIMEOUT`, external abort uses `E_ABORT_NOT_OPEN` or a distribution-equivalent abort error with `aborted_while_suspended=true` in details;
6. Move session state to `IDLE`, unless the abort occurs inside a rollback truncation flow that can recover according to §10.1.1, in which case that recovery state prevails.

The kernel **MUST NOT** wait on the original resume condition to be naturally satisfied on this path; like ordinary C3, this exceptional exit path **MUST** write `abort` or corresponding `protocol_violation` audit.

B3 - `envelope_emit`

```
envelope_emit(
 kind: EnvKind, # { execute, output, edit } (whitelist)
 attrs: Map<string, string>,
 body: Bytes | Stream<Bytes> # uniformly bytes or a bytes stream
) → Result<()>
```

- **Preconditions**:
  - `kind ∈ { execute, output, edit }`; **`kind=rollback` is illegal**. Rollback envelopes can only be produced by the model path (§4.1.2a) and are mapped by the kernel to the internal A3-equivalent flow; when B3 receives `kind=rollback`, it **MUST** return `E_ENV_KIND_FORBIDDEN`;
  - The caller holds the `envelope.emit` cap (granted to all registered programs by default); body size ≤ `EMIT_BODY_MAX_BYTES`. **Judgment time for the Stream path** - in `body: Stream<Bytes>` mode, after consuming each chunk the kernel **MUST** incrementally compare the accumulated body bytes; once accumulated bytes exceed `EMIT_BODY_MAX_BYTES`, it immediately aborts the envelope (close + on_abort + audit path) and returns `E_EMIT_SIZE_LIMIT`; it **MUST NOT** wait until the generator is exhausted before reporting the error.
- **Postconditions**:
  - The kernel injects `open_token+attr_header_tokens+body_tokens+close_token`;
  - Reserved-token literal characters in the body **MUST** be escaped (`I-EMIT-ESCAPE`);
  - **Literal-level constraint on attrs values**: if any value in the `attrs` map contains a reserved-token literal sequence or its decoded UTF-8 byte length exceeds `ATTR_VALUE_MAX_BYTES`, the kernel **MUST** directly reject it and return `E_EMIT_ESCAPE_VIOLATION`; it **does not** perform visually equivalent rewriting (to preserve attribute-header cleanliness and align with `I-ATTR-CLEAN`).
  - If `kind ∈ {output, edit}` and the implementation declares `features.envelope_chunk_observation="self-output-edit"`, the kernel **MUST** generate final token chunks for both the `body:Bytes` and `body: Stream<Bytes>` paths and call the emitting handler's `on_envelope_chunk` (if registered); chunk size is capped by `CHUNK_MAX_TOKENS`;
  - The `tokens` seen by `on_envelope_chunk` **MUST** be the final token chunk that will be written to context after `I-EMIT-ESCAPE` escaping, tokenization, and L2 downgrade processing; raw unescaped bytes **MUST NOT** be exposed.

  - Emit audit.
- **Streaming over-limit residue handling** - When accumulated bytes in `body: Stream<Bytes>` exceed `EMIT_BODY_MAX_BYTES`, the kernel **MUST**: (a) immediately stop consuming the stream; (b) send a cancellation signal or throw an `E_EMIT_STREAM_ABORTED`-equivalent exception into the generator /async iterator; (c) inject a close token matching the already injected open; (d) include `partial_bytes_injected:u64` in audit details for `E_EMIT_STREAM_ABORTED` (or `E_EMIT_SIZE_LIMIT`) for downstream observation; (e) **not roll back** already injected content (preserving KV consistency; aligned with §10.1 truncation cost).
- **Errors**: `E_EMIT_ESCAPE_VIOLATION` /`E_EMIT_SIZE_LIMIT` /`E_EMIT_CAP_DENIED` /`E_EMIT_STREAM_ABORTED`/ `E_ENV_KIND_FORBIDDEN` /`E_EMIT_STREAM_BACKPRESSURE_TIMEOUT`.
- **Notes**: non-streaming (`Bytes`) and streaming (`Stream<Bytes>`) are carried by the same primitive and distinguished by body type.

Streaming Calling Convention

- The `body: Stream<Bytes>` passed by a program **MUST** be a host-language-native **lazy iterator /generator /async iterator**; the kernel consumes it chunk by chunk in a **pull-based** manner.
- Chunk size is determined by the kernel and capped by `CHUNK_MAX_TOKENS` (Appendix F).
- The `envelope.emit` syscall itself is synchronous and **does not** return until the stream is exhausted (or throws).
- The thread /coroutine where the handler runs is blocked until the Stream is exhausted.
- After `envelope.emit` returns, the handler **MUST NOT** call `next` on that generator again (it means the generator has been owned and exhausted by the kernel).
- Before the stream is exhausted, the kernel **MUST** keep the envelope open (open token injected, close token not yet injected).
- On stream exception (generator throws), the kernel **MUST** trigger a close path equivalent to `<|lmsc_abort|>`: stop pulling, send a cancellation signal or throw an `E_EMIT_STREAM_ABORTED`-equivalent exception into the generator /async iterator, inject the close token, clean up the frame, call `on_abort`, and emit audit `kind=abort` and `E_EMIT_STREAM_ABORTED`. Timeout, observer reject, turn abort, and external abort all use the same cancellation semantics to ensure sandbox /host resource release.
- From the program perspective, `envelope.emit` only returns `Ok(())` or an error and does not expose chunk granularity; programs that need chunk-level scheduling observation **SHOULD** register an `on_envelope_chunk` handler.

Stream Backpressure and Timeout

- `stream.next` blocks by default until downstream is ready or timeout occurs; timeout is controlled by `STREAM_WRITE_TIMEOUT` (Appendix F, default 30 s); timeout returns `E_EMIT_STREAM_BACKPRESSURE_TIMEOUT`.
- Timeout and generator exceptions follow the same "close token injection + on_abort + audit" path, ensuring the envelope does not remain in the open state indefinitely.
- When a turn is aborted, the stream immediately throws `E_EMIT_STREAM_ABORTED` (already defined).

5.4 C - Scheduling

C1 - suspend

```
suspend(resume_on: ResumeCondition) → SuspendHandle
ResumeCondition := Timer(Duration)
                 | Event(EventSpec)
                 | CapGrant(CapString)
                 | External
                 | Any(Vec<ResumeCondition>)
```

- **Precondition**: state ∈ { GENERATING, IN_ENVELOPE, DISPATCHING }; caller holds the `scheduler.suspend` cap; nesting ≤ `MAX_SUSPEND_NEST` (default 4).
- **Postcondition**: the underlying inference engine stops sampling, and the session state enters SUSPENDED; register the resume condition and create a `SuspendHandle`. SUSPENDED is not IDLE and is not a turn boundary. When the model path generates `<|lmsc_suspend|>` and no more specific resume condition is bound, the kernel **MUST** handle it as `suspend(External)` and record both `resume_on="External"` and `suspend_handle_id` in the `kind=suspend` audit details (the id may be redacted but **MUST** be mappable by an authorized host /runtime to the concrete `SuspendHandle`). An `External` resume event **MUST** first resolve to a concrete `SuspendHandle`, then call `resume(handle,payload)` according to C2; an external signal without a specified handle **MUST NOT** broadcast-wake any session or fork branch. If abort /timeout /stream abort occurs during suspension, handle it according to the SUSPENDED dispatch abort sequencing in §5.3 B2; that path cancels the resume handle rather than waiting for the resume condition to be satisfied.
- **Errors**: `E_SUSPEND_NESTED_LIMIT`.

C2 - resume

```
resume(handle: SuspendHandle, payload: ResumePayload) → Result<()>
```

- **Precondition**: the handle has not timed out or been canceled; the handle belongs to the current target session. An invalid handle across sessions /already forked branches **MUST** return `E_SUSPEND_INVALID`.
- **Postcondition**: optional `token_inject` payload; that payload is injected by C2 inside the atomic resume path, then the inference stack returns to GENERATING; trigger handler `on_event` (if registered). This payload does not give programs permission to call A4 directly while `SUSPENDED`. **Payload upper bound**: the total token count of `payload` **MUST** be `<= INJECT_MAX_TOKENS` (default 4096, sharing the A4 source); exceeding this **MUST** return `E_INJECT_BAD_TOKEN` (details preferably `reason="resume_payload_overflow"`), keep the SUSPENDED state, and not consume the handle. This rule prevents bypassing the A4 injection budget through `suspend` / `resume` loops. `payload=NULL` or an empty sequence **MUST** be treated as zero-token injection, but **MUST** still be registered under the §13.3 input-region creation rules (source identified by the distribution-declared external_input bridge).
- **Errors**: `E_SUSPEND_EXPIRED` /`E_SUSPEND_INVALID` /`E_INJECT_BAD_TOKEN`.

C3 - abort

```
abort(envelope_id: string, reason: string) → Result<()>
```

- **Preconditions**:
  - `envelope_id` is in the open state;
  - The caller holds **`scheduler.abort.own`** (**MAY** abort envelopes it initiated) **or `scheduler.abort.any`** (fixed-only, used by the `runtime` program and kernel internals).
- **Postcondition**: inject close token; clean up frame; trigger `on_abort`; write audit. If the target envelope belongs to an active dispatch in SUSPENDED state, the kernel **MUST** also cancel that dispatch's resume handle and complete the original dispatch according to the SUSPENDED dispatch abort sequencing in §5.3 B2.
- **Errors**: `E_ABORT_NOT_OPEN` /`E_ABORT_CAP_DENIED`.
- **Notes**: abort permissions explicitly distinguish `scheduler.abort.own` from `scheduler.abort.any`.

C4 - preempt

```
preempt(injection: EnvelopeSpec, reason: string) → Result<()>
```

- **Preconditions**:
  - The caller holds the `scheduler.preempt` cap;
  - **If `injection.kind=execute`, the caller additionally holds the `scheduler.preempt.execute` cap** (fixed-only; held by no one by default);
  - Time since the last preempt $\geq$ `PREEMPT_COOLDOWN` (default 30s);
  - The current envelope was not produced by preempt.
- **Postcondition**: close the current envelope; inject high-priority output; resume sampling; write audit.
- **Errors**: `E_PREEMPT_COOLDOWN` /`E_PREEMPT_CAP_DENIED` (details **MUST** contain `required_cap`) /`E_PREEMPT_NESTED`.

C5 - dispatcher_frame

```
frame.push(rules: FrameRules) → FrameId
frame.pop(frame_id: FrameId) → Result<()>
frame.supports(field: string) → bool #

FrameRules := {
 program_whitelist: Option<Vec<string>> # argv[0] whitelist (MUST support)
 mask_overlay: Option<Mask> # additional logit mask (MAY support)
 cap_extra: Option<Vec<CapString>> # additional requirements (SHOULD support)
}
```

- **Precondition**: `frame.push` /`frame.pop` require the `scheduler.frame` cap; `frame.supports` requires no cap (consistent with the §7.2 syscall table, where `scheduler.frame_supports` has cap "--"). Stack depth < `MAX_DISPATCHER_DEPTH` (default 8); `pop` can only pop a frame pushed by the caller.
- **Strict LIFO** - `frame.pop` **MAY** only pop the current top-of-stack frame. If `frame_id` matches a frame the caller pushed but that is not top-of-stack, pop **MUST** reject with `E_FRAME_NOT_OWNED`, details `reason="not_top"`; the original semantic path for "does not belong to current caller" uses details `reason="not_owner"`.
- **Postcondition**: kernel dispatcher stack push/pop; logit mask overlays or restores.
- **Errors**: `E_FRAME_OVERFLOW` /`E_FRAME_NOT_OWNED` /`E_FRAME_UNSUPPORTED_RULE`.
- **Field MRO**:
  - **MUST**: `program_whitelist` - all conforming implementations **MUST** support it;

  - **SHOULD**: `cap_extra` - strongly recommended; when unsupported, `frame.supports("cap_extra")` returns false;
  - **MAY**: `mask_overlay` - optional; when unsupported, `frame.supports("mask_overlay")` returns false.
  - If an unsupported field is passed and is not `None`, push **MUST** return `E_FRAME_UNSUPPORTED_RULE`; programs **SHOULD** first call `frame.supports` to probe.
- **`program_whitelist` combination semantics**: `None` means that frame adds no whitelist constraint; `Some(non_empty)` allows only the listed `argv[0]` values; `Some([])` explicitly denies all programs. The effective whitelist is the intersection of the base dispatch-reachable program set and every non-`None` `program_whitelist` on the frame stack. Dispatcher frames can only tighten the callable program set; they **MUST NOT** widen restrictions already imposed by manifests, capabilities, or outer frames.
- **Base dispatch-reachable program set (base set) definition** - The base set is the set of all `argv[0]` values that, **without considering** any `program_whitelist` constraint on the current dispatcher frame stack, can be dispatched in this session right now after applying all of the following filters:
  1. The program has been registered in the current session via §8 `program.register` and `on_load` has succeeded (programs with `status=loading` or those already `program.unregistered` are **excluded**);
  2. The caller's manifest and currently effective capabilities allow dispatching that `argv[0]` (including named grants such as `program.dispatch.<name>`);
  3. The program's own manifest visibility /call-source constraints (e.g. `caller=kernel` /`caller=program:*` /`dispatchable=false`) admit this call source;
  4. The required-program routes (`runtime` /`program` /`capability` /`kv`) defined in §12 are unconditionally reachable per spec and **MUST NOT** be removed from the base set by a distribution;
  5. The distribution's dispatch policy (sandbox /network isolation /egress filter, etc.) does not currently deny that `argv[0]` in this session.

  The base set **MUST NOT** be **widened** by dispatcher frames; it can only be further tightened by any non-`None` `program_whitelist` on the frame stack. The effective callable set = base set ∩ all non-`None` `program_whitelists` on the frame stack. The model-visible view of `program.list` **SHOULD** be a subset of the base set (with visibility filtering applied) and **MUST NOT** include programs outside the base set; when the model-visible view temporarily disagrees with the base set (for example during `on_load`), the **base set** is the dispatch-authorization source of truth, and `program.list` is only a hint. Whether dispatch succeeds is still decided by base set ∩ frame whitelists.
- **Notes**: recommended programs such as `focus` /`shell` implement their behavior through this primitive. With MRO and the probing API completed, they are portable across implementations.

5.5 D - Authorization

D1 - `capability_check`

```
capability_check(cap: CapString) → bool
capability_list() → Vec<CapString>
capability_list_requestable() → Vec<CapString>
```

Read-only query, O(log n) or implementation-equivalent complexity, no cap required, no audit write. `capability_list` and `capability_list_requestable` **MUST** be filtered by caller visibility; they are not authorization guards. Authorization failure at a syscall entry is emitted by that entry as `cap_denied` audit and returns `E_CAP_DENIED`; it **MUST NOT** be attributed to D1 pure-query failure.

D2 - `capability_grant`

```
capability_grant(cap, scope, ttl?, source) → Result<CapabilityId>
GrantSource := UserApproval | ExternalPolicy | BootConfig | ProgramDelegation
```

- **Precondition**: the caller holds the `capability.grant` cap (fixed-only, granted only to the `capability` required program); the target `cap` **MUST NOT** belong to the §11.4 fixed-only high-risk set, and **MUST NOT** belong to a distribution-declared exclusive set that can only be injected through `capabilities.fixed`. If the target cap is fixed-only, the kernel **MUST** reject and return `E_CAP_GRANT_DENIED`, details `reason="fixed_only_not_grantable"`.
- **Postcondition**: cap enters the effective set; register TTL revoke (if any); write audit.
- **Errors**: `E_CAP_GRANT_DENIED` /`E_CAP_INVALID_NAME`.

D3 - `capability_revoke`

```
capability_revoke(cap_id, reason) → Result<()>
```

- **Precondition**: the caller holds `capability.revoke` (fixed-only) or is the grantor of the cap.
- **Postcondition**: cap is removed; in-progress dispatch is not interrupted, and later `cap.check` returns false; write audit.

- **Errors**: `E_CAP_NOT_FOUND`.
- **Automatic revoke when grantor program unregisters** - When a grantor program `unregisters`, after `on_unload` the kernel **MUST** automatically revoke all **non-fixed** caps that it granted (fixed-only caps remain unaffected and are controlled by distribution boot config); each revoke **MUST** emit `kind=cap_revoke` audit, with details containing `reason="grantor_unregistered"`, the original grantor program name, and the revoked cap string.
- **Special case for fixed-only caps** - If the target cap belongs to `capabilities.fixed` (§11.4 fixed-only high-risk set), it **MUST NOT** be revoked through this path even if the caller is its grantor; the kernel **MUST** return `E_CAP_DENIED` (with details `reason="fixed_only_not_revocable_by_grantor"`). The only legal path is an explicit call by an actor holding `capability.revoke` (fixed-only). This constraint prevents a distribution from accidentally registering a program as grantor of a fixed cap in boot config and thereby creating a de facto bypass.

5.6 E - Program Table

E - `program_table`

```
program.register(manifest) → Result<ProgramId>
program.lookup(name) → Option<ProgramId>
program.info(id) → Option<ProgramInfo>
program.list() → Vec<ProgramInfo> # cap filtered
program.unregister(id) → Result<()>
```

- **Preconditions**:
  - `register`: caller holds `program.register` or `program.admin`;
  - `unregister`: caller holds `program.admin`; required programs **MUST NOT** be unregistered;
  - Others: read-only.
- **Postconditions**:
  - register: program enters the table; namespace is ready; `on_load` is called; write audit;
  - unregister: `on_unload` is called; kv /blob are handled by GC; ref resolver is unregistered; write audit.
- **`on_load` failure rollback** - If `on_load` returns `Err` /panic, the kernel **MUST** automatically `unregister` the program (clean up metadata and namespace already inserted into the table) and emit audit `kind=program_register_failed` (details contain error summary and `reason`); `register` returns an error to the caller. **The cleanup path for `on_load` failure does not call `on_unload`**: the program has not completed initialization, and the state that `on_unload` depends on **MAY** be inconsistent, making the call unsafe. The kernel only guarantees metadata rollback and does not guarantee transactional rollback of side effects such as `kv.put` /`blob.put` that occurred during `on_load`; programs **MUST** ensure idempotent cleanup themselves.
- **Errors**: `E_PROG_DUP_NAME` /`E_PROG_UNKNOWN_CAP` /`E_PROG_REF_KIND_TAKEN` /`E_PROG_MANIFEST_INVALID` /`E_PROG_PROTECTED` /`E_PROG_IN_USE`.
- **Notes**: program-table operations converge into "five operations under one program-table primitive", consistent with primitive families such as kv/blob.
- **Model-visible program-table updates**: after successful `program.register` /`program.unregister`, the kernel **SHOULD** inject the updated program-table summary into context before the next model dispatch (through a `runtime info` update or a `<lmsc_output>` system message), so the model can perceive the latest available program set. The exact injection time and format are distribution freedoms, but the implementation **MUST NOT** silently use a changed program table in the same dispatch cycle without notifying the model. If a distribution injects the summary through `<lmsc_output>`, the attribute header **SHOULD** contain at least `from="system"`, `schema="program_table_summary"`, and `visibility="all"`, and the body **SHOULD** include program names, visible action /capability summaries, and versions. If a distribution only updates `runtime info`, it **SHOULD** still ensure that a discoverable `runtime info` refresh point exists in model-visible context before the next model dispatch.
- **Visibility filtering**: `program.list` returns the set of programs visible to the caller; `program.lookup(name)` **MUST** return `None` for an invisible program, making it isomorphic with non-existence; `program.info(id)` for an invisible program **MUST** return `None` or only a redacted summary explicitly marked public by the distribution. A caller holding `program.admin` can obtain the full view. This policy remains consistent with §8.6 and Appendix D.

5.7 F - State

F1 - kv

```
kv.put(key, value, ttl?) → Result<()>
kv.get(key) → Option<Bytes>
kv.del(key) → Result<()>
kv.list(prefix) → Vec<string>
```

- Each single value $\leq$ `KV_VALUE_MAX_BYTES` (default 64 KB);

- Per-program namespace quotas are configured by the kernel;
- key is automatically prefixed with `program:<name>/`;
- Session-local; cross-session persistence is implemented by the recommended program `memory` (not in this specification).
- **Errors**: `E_KV_VALUE_TOO_LARGE` /`E_KV_QUOTA` /`E_KV_KEY_INVALID`.

F2 - blob

```
blob.put(data) → BlobId # opaque blob handle; deduplication policy below
blob.get(id) → Option<Bytes>
blob.incref(id) → Result<()>
blob.decref(id) → Result<()>
blob.stat(id) → Option<BlobInfo>
```

- `BlobId` is an opaque handle. The kernel **MAY** use content-addressed deduplication internally, but the `BlobId` returned to programs **MUST NOT** be normatively interpreted as a bare content hash, and programs **MUST NOT** rely on the same content producing the same ID across sessions or programs. When `blob.put(data)` succeeds, the calling session **MUST** obtain a session-level blob reference: if the content is newly created, initial refcount = 1; if the implementation chooses internal deduplication and hits an existing blob, refcount for that calling session increases by 1. The kernel **MUST** add the returned `BlobId` to the current session's `session -> Set<BlobId>` holding set. When refcount=0 and GC passes, delete it.
- The default security model is an **opaque bearer handle**: knowing a valid `BlobId` that is accessible to the current session is equivalent to being authorized to read that blob. blob does not inherit the program kv namespace isolation of §5.7 F1; its program isolation boundary is described in §13.10. The legal V1 enum of `runtimeinfo.features.blob_id_mode` is `{"opaque","content_hash"}` only. If a distribution exposes `BlobId` as a bare content hash, it **MUST** declare `runtimeinfo.features.blob_id_mode="content_hash"`, and **MUST NOT** use that mode for sensitive or low-entropy content. Per-session /per-program ACLs are **NOT** an enum value of `blob_id_mode` in V1; they are provided as a separate distribution extension (e.g. `features.blob_acl="per_session"`); ACL-bearing implementations **MUST** declare their semantics independently of `blob_id_mode`. When a distribution handles sensitive or low-entropy content, it **MUST** use unguessable opaque IDs, or enable a per-session /per-program ACL extension for sensitive blobs; it **MUST NOT** assume that a bare content hash is naturally confidential.

  > **Non-normative explanation**: blob GC timing is an implementation freedom; the kernel only guarantees that after refcount returns to zero, the blob's content **MUST NOT** be returned again (`blob.get` returns `E_BLOB_NOT_FOUND`), but actual reclamation **MAY** be delayed until batch GC. Programs **SHOULD NOT** assume memory is released immediately after calling `decref`. When a session ends or `drop_fork` releases a branch, the kernel performs session-level `decref` for the BlobIds in that session's holding set; program-explicit `blob.decref` can only release the reference held by the caller session.

- **Errors**: `E_BLOB_NOT_FOUND` /`E_BLOB_QUOTA`.

F3 - ref

```
ref.bind(kind, resolver) → Result<()> # once during on_load
ref.resolve(id, kind) → Result<ResolvedContent>
ref.kinds_registered() → Vec<string>
```

- `kind` is globally unique; unregister automatically unbinds it;
- kernel built-in `kind=output` resolver.
- **`ref.kinds_registered` ACL** - Returned results **MUST** be cap-filtered according to `program.capabilities_required` (same rule as `program.list`); unauthorized kinds **MUST NOT** be exposed.
- **Fork /ref cache CoW semantics** - Values already resolved before fork remain **valid** in both sessions (shared turn-local cache); resolves newly produced after fork are independent in their respective sessions and are not shared across sessions. `drop_fork` only cleans up new caches produced by the released side itself.
- **`resolve_ref` latency constraints (tightened; closed whitelist)** - `resolve_ref` is called **synchronously** on the token stream hook path (§6.3 /§9.3); therefore handler implementations **MUST** be **memory-level** operations.

Allowed set - The handler **MAY** perform only the following **5 classes** of calls; any syscall or path outside this list is **disabled**:

1. **Own program metadata /cap queries**: `cap.check`, internal state reads through already held handles;
2. **Current-session turn-local KV read-only**: `kv.get` /`kv.list` (for dynamic space under the program's own name);
3. **Program-owned blob reads**: `blob.get` /`blob.stat`;
4. **Public ref registry reverse resolution**: `ref.kinds_registered` /reverse resolution for already bound kinds;

5. **Clock read-only and local pure computation**: `clock.now` /`clock.monotonic` reads, and in-function in-memory pure computation.

Context snapshot queries are not a fast-path capability for `resolve_ref`; if a program needs region/context metadata, it **MUST** prefetch it into its own KV during a prior dispatch /suspend /resume phase.

Explicitly disabled set - Network /file /sandbox I/O (`net.*` /`fs.*` /`exec.sandbox`); scheduling and yielding classes (`scheduler.suspend` /`scheduler.resume` /`scheduler.preempt` /`scheduler.frame_push` /`scheduler.frame_pop`); classes that produce new envelopes (any `envelope.emit`, `tokens.inject`, `token_rollback`); cross-session access (KV /blob /region of other sessions /fork branches); direct reads of kernel-internal structures; direct `region.body` reads and `region.edit` writes; the previously mentioned "read-only query for `region.tag`" item, if region metadata is needed, **SHOULD** be prefetched into KV during a prior dispatch cycle; any operation that might wait on an external condition or hold a long lock (including distribution-defined equivalent syscalls). **Violating calls**: the kernel **MUST** return `E_CAP_DENIED` or `E_PROTOCOL_VIOLATION` and emit `kind=protocol_violation` audit (details contain `context="resolve_ref_forbidden_syscall"`), and **MUST NOT** merely log and allow the call.

Idempotence and caching - Within the same turn, `ref.resolve` for the same `(kind,id)` **SHOULD** be idempotent; the kernel **MAY** cache resolver return values at turn granularity; the cache is automatically invalidated at the turn boundary; `E_REF_EXPIRED` results **MUST NOT** be cached. **New resolves after fork are independent in each session** (consistent with the CoW semantics above); `restore/drop_fork` operations only clean up turn-local caches produced by the corresponding side itself. Idempotence is not required across turns. External data **MUST** be prefetched by the program in a prior dispatch /suspend /resume cycle and stored with `blob.put` /`kv.put`; `resolve_ref` only performs table lookup and return. Violation will block the inference stack (non-normative consequence) and **MAY** trigger implementation-defined inference stack timeout protection (this is an implementation freedom, not a kernel error code).

- **Errors**: `E_REF_KIND_TAKEN` /`E_REF_NOT_FOUND` /`E_REF_EXPIRED` /`E_REF_BODY_INVALID` /`E_PROTOCOL_VIOLATION` /`E_CAP_DENIED`.

F4 - `region`

```
region.tag(range: Range, attrs: Map<string, string>) → RegionId
region.edit(region_id: RegionId, replacement: Bytes, persist: bool = true) → Result<RegionEditResult>
RegionEditResult := { archived_blob_id?: BlobId }
```

`Range` is a half-open token-index interval `[start_token, end_token)` over the current context token sequence; indexes are based on the current context snapshot under the same kernel build and the same tokenizer. A Range is not guaranteed portable across tokenizers /builds; a persisted Range **MUST** be stored together with tokenizer/build metadata.

`tag` tags the interval; attrs contain `gen` /`visibility` /`attention` /`owner`; attr values **MUST** obey `ATTR_VALUE_MAX_BYTES` and the reserved-token literal prohibition, and violations return `E_EMIT_ESCAPE_VIOLATION`; `attention=pin` requires the `region.pin` cap (see §11.4); the `owner` attribute is only for audit and visualization consumers, and the kernel itself **does not** parse it.

- **`owner` is not forgeable** - During `region.tag`, the kernel automatically overwrites the input `owner` with `caller_program_name`; it ignores values filled in by the program.
- `edit`:
  - `replacement = []` and `persist` is the default true -> delete region; original content enters blob ("drop-soft") and returns `archived_blob_id`; that `RegionId` immediately becomes invalid, and subsequent access returns `E_REGION_NOT_FOUND`;
  - `replacement = []` and `persist=false` -> hard-delete region; additionally requires the `region.drop.hard` cap; that `RegionId` immediately becomes invalid;
  - `replacement != []` -> replace; original content enters blob and returns `archived_blob_id`; region range automatically shrinks or expands to cover the new token sequence after replacement;
  - A region with `attention=pin` **MUST NOT** be edited;
  - Requires the `region.compact` cap;
  - Write audit containing the original hash, new hash, and `archived_blob_id` (if produced). The `archived_blob_id` **MUST** be added to the calling session's `session -> Set<BlobId>` holding set and participate in fork refcount according to §9.4.2.
- **Errors**: `E_REGION_RANGE_INVALID` /`E_REGION_NOT_FOUND` /`E_REGION_LOCKED` /`E_REGION_DROP_HARD_DENIED` /`E_EMIT_ESCAPE_VIOLATION`.

- **Bytes injection and escaping** - `replacement` is a byte string, and the kernel's only processing path is: `Bytes -> UTF-8 validate/sanitize -> I-EMIT-ESCAPE -> tokenizer.encode -> tokens`. If the distribution chooses strict rejection of invalid UTF-8, it returns `E_EMIT_ESCAPE_VIOLATION`; if it chooses safe replacement, it **MUST** guarantee the output is valid UTF-8. When the bytes to inject contain reserved-token literal characters, the kernel **MUST** perform visually equivalent replacement according to `I-EMIT-ESCAPE` /§13.2 equivalent rules to prevent a second envelope from being accidentally generated inside the region body.
- **bytes->token determinism** - The kernel executes `tokenizer.encode` with its own tokenizer on the bytes after UTF-8 handling and escaping; programs **SHOULD NOT** assume token boundaries are stable across kernel builds, but under the **same kernel build** the result **MUST be deterministic** (the same tokenizer + build can reproduce the same token sequence). This constraint is consistent with the premise of §16.1 C-14.
- **Notes**: region capability converges into two primitives, `tag` /`edit`; hard delete uses a dedicated permission error code for distinction.

5.8 G - Audit

G1 - `audit_emit`

```
audit.emit(record) → () # does not return error; sink failure does not affect caller
```

- All programs **MAY** call it; the kernel automatically sets `source=program:<name>`; programs **MUST NOT** forge source;
- The kernel **MUST** automatically emit critical events (see §14.2), and programs **MUST NOT** suppress them;
- Append-only; does not enter context.

5.9 H - I/O

H1 - `fs`

```
fs.read~/{}fs.write~/{}fs.stat~/{}fs.list~/{}fs.mkdir~/{}fs.remove~/{}fs.move
```

- Each call independently checks `fs.<op>:<path>`;
- Syscall input `path` **MUST** be a relative path. After normalization it **MUST NOT** contain `..` and **MUST NOT** begin with `/`; capability scope **MAY** use a distribution-defined virtual absolute path (such as `/workspace/**`) as the matching namespace. During authorization, the kernel first maps the relative path to that virtual root, then matches `fs.<op>:<virtual-path>`; programs **MUST NOT** pass the virtual absolute path directly as the syscall input.
- Large files go through blob indirection.
- **Errors**: `E_FS_CAP_DENIED` /`E_FS_NOT_FOUND` /`E_FS_IO` /`E_FS_QUOTA`.

H2 - `net`

```
net.request(method, url, headers, body?, timeout) → Response
net.stream(url, ...) → Stream
```

- capability `net.<method>:<url-pattern>`;
- Response bodies **MUST** be escaped when rewritten to envelope bodies (`I-EMIT-ESCAPE`).
- **Errors**: `E_NET_CAP_DENIED` /`E_NET_TIMEOUT` /`E_NET_CONNECT` /`E_NET_STATUS`.

H3 - `exec_sandbox` (Level-Dependent Optional)

```
exec.sandbox(kind, code, stdin?, limits) → ExecResult
```

- A conforming L0 implementation **MUST** provide it; L1 implementations **MAY** provide it; L2 implementations **MAY** omit it;
- Supported `kind` values are determined by the kernel build;
- limits **MUST** be enforced (cpu_ms /wall_ms /memory_b /net disabled by default /fs_tmp writable under /tmp by default);
- sandbox processes **MUST NOT** access host fs /net /kernel memory.
- **Errors**: `E_EXEC_CAP_DENIED` /`E_EXEC_LIMIT` /`E_EXEC_INTERNAL` /`E_EXEC_UNSUPPORTED` (when L2 does not provide it).

5.10 I - Time

I1 - `clock`

```
clock.now() → Timestamp # MAY be sanitized
clock.monotonic() → Duration # since session start
clock.timer(duration, on_fire) → TimerId
clock.cancel(id) → Result<()>
```

- `now()` **MAY** be sanitized by policy; `monotonic()` does not jump; timer firing goes through `resume(ResumeCondition::Timer)`.
- **Sanitized-state observation** - `runtimeinfo.features` `clock_now_sanitized:bool` (**MUST** be exposed in boot output schema and runtime info; true means `clock.now()` returns a policy-sanitized timestamp, so programs can decide whether to fall back to `clock.monotonic()`).
- **Errors**: `E_CLOCK_BAD_DURATION`.

---

6. Inference Stack Integration Contract

6.1 Three Hook Points

Hook	Position	Semantics
Sampler Hook	Before sampling, where logits are mutable	Apply a logit mask
Token Stream Hook	After sampling, before append-to-context	Recognize events (envelope, control)
KV Cache Hook	rollback /fork /restore	Physically modify the KV cache

6.2 Sampler Hook Contract

```
mask = lmsc.sampler_hook(session_state)
logits = apply(logits, mask)
```

- Input: session state pointer;
- Output: `Mask` (nullable);
- Implementation recommendation: <= 100 us per step;
- Idempotence: multiple calls under the same state return equivalent masks.

> **Minimum `session_state` field set -** The minimum field set exposed by `session_state` for Sampler Hook reads includes: `{ kv_head_token_index, last_sampled_token_id, envelope_stack_depth, envelope_top_kind, attr_region_active, strict_protocol_mode, raw_text_outside_envelope }`; distributions **MAY** expose more fields, but the above is the subset that all implementations **MUST** expose. `strict_protocol_mode:bool` and `raw_text_outside_envelope` $\in$ `{"allowed","audit-only","forbidden"}` are read-only snapshots taken from the currently effective `features` values in boot output /runtime info (see Appendix E); they drive the L0 /L1 logit mask of §4.4 `I-STRICT-ENVELOPE-ONLY`. Implementations **MAY** precompile the current combination of feature flags into a static mask table, but **MUST** keep the mask and the `session_state` snapshot consistent across feature-flag transitions; an intermediate observable state where the mask disagrees with the current `features.*` value is **forbidden**.

6.3 Token Stream Hook Contract

```
for each newly sampled token t:
 event = lmsc.on_token(t, session_state)
 match event:
 Continue → append(t)
 EnvelopeOpen → append(t); update state
 EnvelopeClose(execute) → append(t); trigger B2 dispatch
 EnvelopeClose(output|edit) → append(t); emit audit
 EnvelopeClose(rollback) → trigger A3 equivalent
 (§4.1.2a: last_index_of + KV truncate;
 does not trigger B2 dispatch;
 after truncation, restore outer state per the §10.1.1 algorithm)
 RefOpen → append(t); start ref body buffer
 RefClose → append(t); parse ref body;
 trigger F3 resolve
 ControlAbort → trigger C3 equivalent
 ControlSuspend → trigger C1 equivalent
 Error → abort turn
```

> **Note -** This specification does not define the control single token `<|lmsc_rollback|>`, and implementations **MUST NOT** expose a `ControlRollback` event; rollback uniformly uses the `EnvelopeClose(rollback)` branch, and its semantics are not equivalent to an ordinary envelope close (it does not trigger dispatch).

- **MUST** complete synchronously;
- **MAY** trigger dispatch, during which the inference stack **MUST** pause sampling until the kernel notifies it to resume.
- **Semantics when `on_token` returns `Err` -** An `Err` returned by the token stream hook is uniformly mapped to the `protocol_violation` path: the kernel emits a `kind=protocol_violation` audit (the invariant is determined by the return-error context, and details include the error description returned by the hook) and aborts the current turn; like C3, it follows the same close + `on_abort` + audit path, unified with post-hoc detection of L2 invariants.

6.4 KV Cache Hook Contract

```
lmsc_kv_hook.truncate(pos) → Result # physical step for A3 rollback
lmsc_kv_hook.fork_snapshot() → KVHandle # physical step for A5 fork
lmsc_kv_hook.activate(handle) → Result # physical step for A5 restore
lmsc_kv_hook.drop(handle) → Result # physical step for A5 drop_fork
```

- truncate **SHOULD** be O(truncated_pages); fork **SHOULD** be O(1) (CoW);
- Correctly handles prefix sharing under paged attention.

6.5 Integration Levels (L0 /L1 /L2; Tier Aliases)

A conforming kernel **MUST** declare an L0 /L1 /L2 level; Tier-A /Tier-B /Tier-C are only aliases for these three levels. `runtime info` returns (§9.4 /Appendix E: `kernel.integration_level` /`kernel.integration_tier`, consistent with the boot output schema; all body text saying that "`runtime info` returns `integration_level` /`integration_tier`" refers to the corresponding fields of the `kernel` object in this snapshot):

> **Convention for the term "nested"** - In this specification, "nested" in invariant contexts such as §4.4 `I-CTRL-INSIDE-ENV` /`I-ENV-NO-SELF-NEST` /`I-ROLLBACK-NO-NEST` refers to literal nesting forms among reserved tokens /envelopes; in §8.5 Dispatcher Frame and §10.1 SUSPENDED it refers to the logical stack relation of the dispatcher frame stack or suspend handle stack (not literal nesting). Occurrences of "nested" in §8.5 /§10.1 uniformly refer to the latter. When these intersect with constraints such as `I-ROLLBACK-NO-NEST`, this note prevails, and the literal-nesting restriction is not repeated.

Level	Tier Alias	Support	Limitations
L0	**Tier-A** (production recommended)	All three hooks fully implemented; both A2 + H3 provided	No additional limitations
L1	**Tier-B**	Sampler + Token Stream; no full KV Hook; rollback truncate adapter required	A3 `scope=Envelope` **MAY** be implemented through a byte-precision downgrade, and **MUST NOT** be forcibly degraded to the turn start; **A5 unavailable** (`session.fork/restore/drop_fork` returns `E_ATOMIC_UNSUPPORTED`); A2 /H3 are level-dependent optional (this level may provide them)
L2	**Tier-C**	Token Stream only (post-processing recognition)	A1 degrades to stop-sequence; A3 `scope` ∈ {`Turn`, `Envelope`} is determined by post-hoc scanning; **A5 unavailable**; A2 and H3 **MAY** be omitted

> **Tier alias note** - Tier-A /Tier-B /Tier-C are respectively equivalent to L0 /L1 /L2; conformance is judged by L0 /L1 /L2.

L2 /Tier-C is the minimum conformance threshold; L0 /Tier-A is production recommended. This specification does not provide Word /Stmt scope, so rollback semantics at every level are "**most-recent match truncation for the pattern string in pattern mode**", with no level-dependent heuristic.

> **Note** - This specification uses only L0 /L1 /L2 and their Tier-A /B /C aliases; it does not introduce additional level aliases.

6.5.1 L2 Invariant Downgrade Semantics

An L2 implementation has no sampler hook. The following **nine protocol invariants** cannot be enforced through logit masks and are all post-hoc detected by the token stream hook; when `features.strict_protocol_mode=true` and `features.raw_text_outside_envelope="forbidden"`, the conditional invariant `I-STRICT-ENVELOPE-ONLY` is appended as the **10th item** in this list (see the end below):

1. `I-ENV-PAIR`;
2. `I-ENV-NO-SELF-NEST` (L2 detection point: check the current envelope stack top kind at the envelope open event);
3. `I-CTRL-INSIDE-ENV`;
4. `I-ROLLBACK-BOUND`;
5. `I-ROLLBACK-NO-NEST` (L2 detection point: rescan pattern bytes when the rollback envelope closes);
6. `I-ABORT-SCOPED`;
7. `I-ATTR-CLEAN` (L2 detection point: scan kernel-owned attribute headers for any reserved token literal sequence, and verify that the separator before the first attribute and the blank-line terminator are legal);

8. `I-ROLLBACK-NO-ATTR` - when observing a `<lmsc_rollback>` open, kernel-owned attribute headers or attribute metadata **MUST NOT** appear; any non-empty value is a violation and returns `E_ROLLBACK_PATTERN_INVALID`;
9. `I-REF-CHARSET` (L2 detection point: scan body bytes and the micro-grammar at `</lmsc_ref>` close).
10. `I-STRICT-ENVELOPE-ONLY` (**conditional**, included only when `features.strict_protocol_mode=true` and `features.raw_text_outside_envelope="forbidden"`; L2 detection point: at every token-on-stream check, if the envelope stack depth = 0 and the token is not one of `<lmsc_execute>` /`<lmsc_output>` /`<lmsc_edit>` /`<lmsc_rollback>` /`<|lmsc_suspend|>` /`<lms` open /EOS, it is a violation; returns `E_PROTOCOL_VIOLATION`). If that entry is a top-level `<lmsc_ref>`, a successful expansion must also follow the strict top-level ref materialization rule in §9.3; placing ordinary resolved bytes directly into context outside an envelope is the same invariant violation.

The first eight correspond to the complete §4.4 A1 group; the ninth corresponds to `I-REF-CHARSET` in the §4.4 "post-hoc recognition + abort" group; the 10th is the conditional invariant introduced in §4.4 /§10.1.2 -- when its activation condition is not met, the item does not exist and RC3 behavior is unaffected. `I-REF-ANY` (a ref element **MAY** appear in any envelope body) and `I-EMIT-ESCAPE` (enforced at syscall entry) are not in this list: the former has no violation form, and the latter is covered by syscall-entry checks.

> **Close-injection rule for self-nesting aborts** - When an L2 post-hoc abort is triggered, except for the invalid rollback special case in §6.5.1.1, the kernel **MUST** continuously inject a close sequence whose length is **equal** to the number of currently unpaired open tokens (paired in LIFO order) until the stack is empty; the already injected offending tokens are considered part of the context and **retained** (to preserve KV consistency; already injected content is not rolled back). All subsequent output in that turn is then considered aborted. `protocol_violation` audit details **MUST** include `close_tokens_injected:u32` and, on the streaming path, `partial_bytes_injected:u64`.

Explicitly:

- Under L2, the above invariants are **recognized post-hoc by the token stream hook** (nine by default; ten when the §10.1.2 condition is active); their semantics are downgraded from "enforced" to "best-effort detection + abort on detection".
- When the kernel detects a violation, it **MUST**:

1. Immediately execute a recovery path whose externally observable result is consistent with C3 (the previous phrase "equivalent to C3" is replaced with a behavioral description to avoid confusion with directly calling C3 from §5.2 A3);
2. Emit audit `kind=protocol_violation`, with details containing the `invariant` name, `token_position`, and `violation_detail`;
3. Return `E_PROTOCOL_VIOLATION` to the caller (if the abort is triggered through a program-side syscall path or the program explicitly observes the event; this is simplified uniformly with the §5.2 A3 L2 rollback path; the model path only emits audit and returns no error to any caller).

- L2 implementations **MUST NOT** silently ignore protocol violations.
- `runtime info` with `kernel.integration_level="L2"` **MUST** include `features.invariant_enforcement="post-hoc"`.
- **Invalid rollback is a special case of general post-hoc abort**: the general rule above that "already injected offending tokens are considered part of the context and **retained**" **does not apply** to invalid rollback (`I-ROLLBACK-NO-NEST` /`I-ROLLBACK-BOUND`); the postconditions for invalid rollback are in §6.5.1.1.

L0 /L1 are unaffected by this subsection: invariants remain enforced by A1.

6.5.1.1 Postconditions for Invalid L2 Rollback

When L2 detects invalid rollback (`I-ROLLBACK-NO-NEST` /`I-ROLLBACK-BOUND` post-hoc recognition), this subsection takes priority over the general post-hoc abort rules in §6.5.1; the kernel **MUST** satisfy four postconditions:

Side-effect isolation for the rollback body - Once the L2 token stream hook observes a `<lmsc_rollback>` open, before the corresponding close is confirmed and the `I-ROLLBACK-NO-NEST` /`I-ROLLBACK-BOUND` checks are completed, it **MUST** treat all tokens in the body only as pattern byte buffers; it **MUST NOT** trigger `RefOpen` /`RefClose` `ref.resolve` callbacks inside the rollback body, execute any program callback, or write program-visible KV/blob side effects. If the implementation cannot provide this isolation because of architectural limits, it **MUST** intercept the rollback body earlier at the stop-sequence /parser stage, or declare in boot output that L2 rollback is unsupported and handle it through the abort fallback in §16.1 C-15. Invalid rollback cleanup only guarantees that context, KV, and the kernel rollback parsing

cache return to the state before the rollback open; the specification does not promise to roll back any program side effects that have already executed in violation of this isolation requirement. Such an implementation is non-conforming.

(a) The invalid rollback envelope **MUST NOT** remain in final context (the already injected open and its body tokens **MUST** be cleaned up synchronously); (b) KV remains at the state **before** the `<lmsc_rollback>` open; (c) turn state is restored to **before the outer envelope** (consistent with model-path semantics; if there is no outer envelope, return to IDLE); (d) The primary audit event is `rollback_error` (consistent with the mutual-exclusion rule in §14.2.2; do not also emit `kind=rollback`).

If the inference stack adapter layer cannot physically roll back to before the rollback open, the kernel **MUST** abort the current turn, ensure that final stable context does not contain the invalid rollback envelope, and emit `rollback_error` (details contain `reason="rollback_cleanup_failed"` and `truncate_fallback="abort"`). Implementations **MUST NOT** retain an invalid rollback in context under the general L2 violation path.

6.5.1.2 L2 Rollback Result Matrix

The L2 rollback branch is determined by the following table; this table centralizes the priority among §5.2, §6.5.1.1, and §10.1.1:

Case	truncate precision	Context /KV postcondition	Audit	Outer state
Legal rollback and pattern hit	`byte`	Truncate exactly to the token before the first matched byte; the rollback envelope itself is not retained	`rollback(outcome=truncated, truncate_precision=byte)`	Restore per §10.1.1
Legal rollback and pattern hit	`token`	Discard the entire token containing the first matched byte, leaving the KV tail before that token; the rollback envelope itself is not retained	`rollback(outcome=truncated, truncate_precision=token)`	Restore per §10.1.1
Legal rollback and pattern miss or out of bounds	`byte` /`token`	KV unchanged; the rollback envelope is not retained as stable output	`rollback(outcome=pattern_not_found|pattern_out_of_bound)`	Return to the outer state before the trigger
Legal rollback but cannot truncate	`none`	Do not truncate; abort the current turn; final stable context does not contain the rollback envelope	`protocol_violation`, details contain `truncate_fallback="abort"`	IDLE
Invalid rollback (empty pattern /too long /contains reserved token /crosses hard boundary) and cleanup succeeds	`byte` /`token`	Clean up to before the rollback open; the rollback envelope **MUST NOT** be retained	`rollback_error`	IDLE if there is no outer envelope; otherwise restore to before the outer envelope
Invalid rollback and cleanup fails	Any	Abort the current turn; final stable context does not contain the invalid rollback envelope	`rollback_error`, details contain `reason="rollback_cleanup_failed"`	IDLE

Therefore, §10.1.1 applies only to paths where "legal rollback has completed physical or equivalent truncation"; `precision="none"`, invalid rollback cleanup failure, and general post-hoc protocol violations all take priority under abort rules.

6.5.1.3 L2 `I-ATTR-CLEAN` Byte-Level State Machine

The L2 token stream hook runs the following byte-level state machine over the **body portion of the kernel-owned attribute header**. Because an envelope open token is a complete reserved token, the scan target is not the internal bytes of `<lmsc_output>`, but the attribute header injected or associated by the kernel after the open token:

```
S_OPEN → (observe any byte) → S_ATTR
S_ATTR → (any reserved literal prefix appears in the accumulated byte sequence:
 `<lmsc_`~/{}`</lmsc_`~/{}`<|lmsc_`~/{}`<|key_`) → VIOLATION
S_ATTR → (the separator before the first attribute, attribute-line syntax, line_end, or blank-line terminator does not conform to
↪  §4.3) → VIOLATION_ATTR_FORMAT
S_ATTR → (attribute header length budget is exceeded before the terminating blank line appears) → VIOLATION_ATTR_FORMAT
S_ATTR → (two consecutive line_end values; attribute header blank line ends) → S_BODY
```

An AC trie or a literal-prefix set checked byte by byte is sufficient. `VIOLATION_ATTR_FORMAT` and reserved-literal `VIOLATION` are both violations of `I-ATTR-CLEAN`: the kernel **MUST** emit `kind=protocol_violation` (invariant=`I-ATTR-CLEAN`, with details containing `reason="attr_format_invalid"` or an equivalent reason) and abort the **current turn** (not merely abort the current envelope, unified with the handling of other invariant violations).

6.5.2 Streaming Downgrade for `envelope.emit` Under L2

L2 has no sampler hook, and the inference stack adapter layer also **MAY** lack support for true pull-based streaming token injection. A conforming L2 implementation **MAY** downgrade `envelope.emit(body: Stream<Bytes>)` as follows: first exhaust the stream completely into an internal buffer (still capped by `EMIT_BODY_MAX_BYTES`; exceeding it -> `E_EMIT_SIZE_LIMIT`), then inject the whole envelope once with the semantics of `body:Bytes`.

The conformance prerequisites for this downgrade are:

- The implementation **MUST** truthfully declare the current mode in `runtimeinfo.features` as `envelope_emit_stream` ∈ `{native, buffered}`: `native` means native pull-based consumption according to the streaming call convention in §5.3 B3; `buffered` means downgrade to injection after full buffering.
- **Timeout semantics in Buffered mode**: in `buffered` mode, the open token **MUST NOT** be injected into context before the stream is fully exhausted and buffering is complete; if `STREAM_WRITE_TIMEOUT` is triggered during buffering (a timeout on a single `next()`), the kernel **MUST** discard the buffered content, emit audit `kind=abort` (details contain `reason="stream_timeout"`), and return `E_EMIT_STREAM_BACKPRESSURE_TIMEOUT` -- it **MUST NOT** supplement with a close token (because no open token has been injected and no dangling envelope needs to be closed). An implementation **MUST NOT** simultaneously satisfy "inject open token first, then supplement close on timeout"; this is an illegal state in buffered mode.
- **`envelope_id` on the normal buffered path**: when `buffered` mode enables `on_envelope_chunk`, the kernel **MUST** preallocate the final `envelope_id` before the first chunk callback and reuse the same id in subsequent `on_envelope_chunk` callbacks, final envelope injection, and `envelope_open` /`envelope_emit` audits; the id observed by programs **MUST NOT** be rewritten from `pending` to a different final id. Only reject paths before open-token injection may use `pending`, as described below.
- **Buffered observer reject path**: in `buffered` mode, if `on_envelope_chunk` returns `AbortEnvelope` or `Err` before the open token is injected, the kernel **MUST** stop subsequent callbacks, cancel the generator /async iterator, discard the buffer, emit audit `kind=abort` (details contain `reason="handler_reject_chunk"`, `envelope_id="pending"`), and return `E_EMIT_STREAM_ABORTED`; it **MUST NOT** supplement with a close token, and **MUST NOT** count the pending envelope in final context. `on_abort` **MAY** be called, but its `envelope_id` **MUST** be marked as `pending`, and programs **MUST NOT** use it to access an opened envelope.
- **Mandatory error semantics for `envelope_id="pending"`**: `pending` is a one-shot diagnostic placeholder; it never corresponds to any real envelope already injected into context, and the kernel **MUST NOT** later remap it to some final envelope id. Any operation a program issues against the kernel using a `pending` id that **requires a real open envelope** - including but not limited to continuing `envelope.emit` against that id, `envelope.close`, `region.tag` /`region.edit` /`region.body` style queries or writes, `audit.emit(envelope_id=...)`, and `tokens.inject` with `AtEnvelopeClose` targeting that envelope - the kernel **MUST** reject with `E_ABORT_NOT_OPEN`, with details preferably containing `reason="pending_not_open"`, and **SHOULD** emit audit `kind=protocol_violation` (invariant=`I-CTRL-INSIDE-ENV` or an equivalent key, classified by syscall entry); the kernel **MUST NOT** log silently and let the call through. `on_abort(envelope_id="pending")` itself is not a violation, but inside that callback the handler **MUST NOT** use that id to reach envelope-state query /mutation syscalls. Inside `on_abort(envelope_id="pending")`, syscalls **MAY** be limited to diagnostic /bookkeeping calls that do not depend on a specific envelope state: `audit.emit` (handlers **MUST NOT** write a custom event tagged with `envelope_id="pending"` to forge correlation), `cap.check`, `clock.now` /`runtime info` (if the distribution exposes it), and KV /blob cleanup within the handler's own namespace; other syscalls **SHOULD** return `E_ABORT_NOT_OPEN` or an existing capability /context error.
- The downgrade **MUST NOT** affect the `on_envelope_chunk` callback semantics declared by `features.envelope_chunk_observation="self-output-edit"`: if a handler is registered and the implementation chooses `buffered` mode, the implementation **MUST** invoke chunk callbacks on the buffered content of `kind` ∈ `{output, edit}` at `CHUNK_MAX_TOKENS` granularity before injection, with `source_path="program_emit_buffered"`. If the implementation cannot provide those semantics, it **MUST** declare `features.envelope_chunk_observation="none"`, and **SHOULD** set the compatibility field `features.edit_stream_chunked` to `false`.

L0 /L1 implementations **MUST** be `native`; only L2 **MAY** declare `buffered`.

6.6 Tokenizer Contract

- Includes all reserved tokens listed in §4.1 as independent IDs;
- **MUST NOT** misrecognize the literal characters of reserved tokens (`<lmsc_execute>`, etc.) when tokenizing ordinary text;
- Exposes `id_of(name)` /`name_of(id)` for kernel calls.

- **Byte-lossless detokenize -** detokenize **MUST** be a byte-lossless inverse mapping: for any legal token sequence `T`, `detokenize(T)` returns a byte string that, when passed through `tokenize`, equals `T`; it **MUST NOT** insert extra whitespace, apply Unicode normalization, or perform any lossy transformation. This constraint is a necessary prerequisite for the determinism of §16.1 C-14.

---

7. Syscall Interface

7.1 Invocation Model

A handler receives `Context` (`ctx`) and accesses the kernel through the following subinterfaces:

```
ctx.tokens # A1–A5
ctx.envelope # B3 (B1/B2 are event/kernel-triggered, not syscalls)
ctx.scheduler # C1–C5
ctx.cap # D1–D3
ctx.program # E
ctx.kv # F1
ctx.blob # F2
ctx.ref # F3
ctx.region # F4
ctx.audit # G1
ctx.fs # H1
ctx.net # H2
ctx.exec # H3 (if provided)
ctx.clock # I1
```

7.2 Syscall Table

Syscall	Primitive	Capability
`tokens.logit_mask`	A1	`tokens.mask.direct`†
`tokens.is_special` /`name_of` /`id_of`	A2	--
`tokens.rollback`	A3	`tokens.rollback.explicit`† (unreachable from the V1 program side; retained only as a kernel-internal equivalent path and future extension entry point); the model rollback envelope path goes through kernel internals
`tokens.inject`	A4	`tokens.inject`* + `tokens.inject.special`† (when reserved tokens are included)
`session.current_handle` /`fork` /`restore` /`drop_fork`	A5	`session.fork`*
`envelope.emit`	B3	`envelope.emit`
`scheduler.suspend` /`resume`	C1 /C2	`scheduler.suspend`
`scheduler.abort`	C3	`scheduler.abort.own` or `scheduler.abort.any`†
`scheduler.preempt`	C4	`scheduler.preempt`*
`scheduler.frame_push` /`frame_pop`	C5	`scheduler.frame`
`scheduler.frame_supports`	C5	--
`cap.check` /`cap.list` /`cap.list_requestable`	D1	--
`cap.grant`	D2	`capability.grant`†
`cap.revoke`	D3	`capability.revoke`† or the original grantor
`program.register` /`unregister`	E	`program.register` (register) /`program.admin`† (unregister; low-level syscall; for user subcommand install/remove, see §12.1)
`program.lookup` /`info` /`list`	E	--
`kv.put` /`get` /`del` /`list`	F1	--
`blob.*`	F2	--
`ref.bind`	F3	`program.ref.bind`
`ref.resolve`	F3	--
`region.tag`	F4	-- (some attrs require caps)
`region.edit`	F4	`region.compact` (+ `region.drop.hard` if `persist=false` and `replacement=[]`)
`audit.emit`	G1	--
`fs.*`	H1	`fs.<op>:<path>`
`net.*`	H2	`net.<method>:<pattern>`
`exec.sandbox`	H3	`exec.sandbox:<kind>` (if provided)
`clock.*`	I1	--

* High privilege: by default granted only to required programs or requested on demand. † Privileged: fixed-only, **MUST NOT** be granted through D2.

7.3 Error Model

```
SyscallError := { code, message, hint?, retryable, details?: Map<string, any>, cause? }
```

> **Error details field** - `details` is an optional map used to carry finer-grained distinctions for the same error code. In particular, when `tokens.rollback` returns `E_ROLLBACK_PATTERN_NOT_FOUND`, `details.outcome` ∈ `{pattern_not_found, pattern_out_of_bound}` **MUST** be equivalent to the `outcome` field of the `rollback` audit from the same event; programs use this field to distinguish "no match at all" from "match outside the boundary". The remaining entries of `details` are defined independently by each error code (using the same criteria as the `origin` column in §15.2).

Handlers **MUST** report errors to the model (through `envelope.emit(kind=output, status=<code>)`); they **MUST NOT** swallow errors.

7.4 Defense in Depth Validation

At each syscall entry, the kernel **MUST** perform an independent capability check, even if it already performed an aggregate check at dispatch time (§13.1).

7.5 ABI

The specification **does not** define language bindings. A conforming implementation **MUST** at least support:

- **Native**: for required programs;
- **Sandboxed** (at least one): WASM /Lua.

A conforming distribution **MUST** publish a single machine-readable syscall schema, with canonical file name `lmsc-syscall-schema.yaml` (or an equivalent JSON representation). Language bindings **SHOULD** be generated automatically from that schema; Appendix D is a human-readable projection and **MUST NOT** be the only source of truth for machine processing.

The schema includes at least the following fields:

```yaml
schema: lmsc-syscall-schema
revision: "1.0"
syscalls:
  - name: tokens.rollback
    primitive: A3
    capability: tokens.rollback.explicit
    availability: internal-only-v1
    args:
      - { name: pattern, type: bytes, required: true }
      - { name: scope, type: Scope, required: true }
    errors: [E_CAP_DENIED, E_PROTOCOL_VIOLATION, E_ROLLBACK_PATTERN_NOT_FOUND]
```

`availability=internal-only-v1` means that the syscall name and argument shape are registered, but there is no legal authorization path from the V1 program side; implementations **MUST NOT** expose `tokens.rollback.explicit` to programs on that basis.

> **`Stream<Bytes>` ABI under sandbox** - The ABI for `Stream<Bytes>` on sandbox backends (WASM /Lua, etc.) is distribution-defined and is not a normative constraint; the recommended design is a pull callback + backpressure mechanism, with binding documentation that clearly maps `chunk_max_tokens` /backpressure windows and timeout strategy to `E_EMIT_STREAM_BACKPRESSURE_TIMEOUT`.

---

8. Program Model

8.1 Manifest

```yaml
name: string # required, globally unique
version: semver # required
author: string? # optional

actions: # required, subset of the §8.3 closed set
 - dispatch
 - emit_output
 - ...

capabilities_required: [...] # required
capabilities_optional: [...] # optional

ref_kinds: # optional
 - kind: string
 description: string

subcommands: # optional (for help)
 - name: string
 args: [string]
 description: string

handler:
 backends: # at least one
 - kind: native | wasm | lua | ...
 path: string

constraints: # optional
 rollback_safe: bool # default true
 max_dispatch_ms: u32 # wall-clock upper bound for a single dispatch (milliseconds); see semantics below
 reentrant: bool # default false
```

Semantics of `constraints.max_dispatch_ms` - This field declares the wall-clock execution upper bound (milliseconds) for a single `dispatch(ctx,args)` call. The kernel's enforcement semantics are explicitly declared by `runtime info.features.dispatch_timeout_enforcement` ∈ {"enforced", "advisory", "off"}:

- `enforced` (L0 recommended) - The kernel **MUST** take a path equivalent to C3 abort when dispatch execution exceeds this value: if the handler registered `on_abort`, first call `on_abort(ctx,envelope_id)` to clean up, then inject close sequences for any unclosed streaming `envelope.emit`, then emit audit `kind=abort`, with details containing `reason="dispatch_timeout"` and `elapsed_ms` (measured wall clock); dispatch ultimately returns **`E_DISPATCH_TIMEOUT`** (decoupled from `E_HANDLER_PANIC`; retryable=impl-defined, default true); if `on_abort` itself panics again, swallow it according to the §5.3 B2 rule and set `nested_panic=true` in details. When the field is not declared, Appendix E `limits.dispatch_timeout_default_ms` is used (if null, timeout is not enabled).

Native backend downgrade - A distribution **MAY** declare that the Native backend only supports cooperative cancellation (checking a cancel flag at coroutine /callback points) and run under `features.dispatch_timeout_enforcement="advisory"`; forced preemptive abort for Native backends is **not** a normative **MUST**. Sandbox backends still **MUST** support preemptive abort.

- `advisory` - When dispatch times out, the kernel only emits audit `kind=x-lmsc-dispatch-advisory` (using the `x-<vendor>-<name>` extension naming required by §14.2.1, to avoid using the unregistered bare identifier `hint`; the `x-lmsc-` prefix is reserved for observation-class extensions from this specification that are not RC gates), with details containing `reason="dispatch_timeout_advisory"`, `elapsed_ms`, and `budget_ms`; default `scope=system-only`, used only temporarily for observability. It **does not** interrupt dispatch and **does not** return an error; it is used for performance observation and capacity planning in production environments.
- `off` - The kernel ignores this field; the manifest **MAY** still declare it (as collaborator documentation), but the kernel neither audits nor enforces it.

Implementations that do not support enforcement semantics **MUST** declare `advisory` or `off`; they **MUST NOT** claim `enforced` while failing to interrupt timeouts in practice.

`constraints.max_dispatch_ms=0` is an illegal manifest value; the kernel **MUST** reject it during `program.install` /`program.register` and return `E_PROG_MANIFEST_INVALID`. If this field is unset, `limits.dispatch_timeout_default_ms` is used; if a distribution needs to express "timeout disabled", it **SHOULD** set the default to `null` or declare `features.dispatch_timeout_enforcement="off"`.

8.2 Handler Lifecycle

```
register(manifest)
 → on_load(ctx)
 → dispatch(ctx, args) # each execute
 → on_envelope_chunk(ctx, chunk) # if the emitting handler emits `kind ∈ {output, edit}` and the feature is enabled
 → on_event(ctx, event) # if subscribed
 → resolve_ref(ctx, id, kind) # if ref_kinds is non-empty
 → on_abort(ctx, env_id)
 → on_unload(ctx)
unregister(id)
```

Handler signatures:

```
StreamFrame := { chunk_index: u32, total_chunks_hint: Option<u32>, stream_closed: bool }
# StreamFrame field semantics:
# - chunk_index: zero-based ordinal of the current chunk; monotonically increases from 0.
# - total_chunks_hint:
# * On the `body: Bytes` path (including L2 `buffered` mode), this **SHOULD** be `Some(n)`,
# n is the accurate count after slicing by `CHUNK_MAX_TOKENS`;
# * On the native pull-based `body: Stream<Bytes>` path, this **SHOULD** be `None`
# until the generator is exhausted; conforming handlers **MUST NOT** use
# `total_chunks_hint.is_some()` as a control-flow condition for anything other than progress display.
# - stream_closed: `true` appears only in the frame of the final chunk
# (whether from normal exhaustion or a generator exception that follows the close path); all other frames are false.
# - The only reliable end signal is `stream_closed=true`; program correctness **MUST NOT** depend on `total_chunks_hint` (as
↪  above).

Handler := {
 dispatch: fn(Context, ExecuteArgs) → Result<()> # required
 on_envelope_chunk: fn(Context, EnvelopeChunk) → Result<ChunkDecision>?
 on_event: fn(Context, Event) → Result<()>?
 resolve_ref: fn(Context, id, kind) → Result<ResolvedContent>?
 on_load: fn(Context) → Result<()>?
 on_unload: fn(Context) → Result<()>?
 on_abort: fn(Context, envelope_id) → Result<()>?
}

EnvelopeChunk := {
 envelope_kind: "output" | "edit",
 envelope_id: string,
 envelope_from: string?,
 visibility: string?,
 source_path: "program_emit_bytes" | "program_emit_stream" | "program_emit_buffered",
 frame: StreamFrame,
 tokens: &[Token]
}

ChunkDecision := Continue | DetachObserver | AbortEnvelope
```

> **`on_envelope_chunk` trigger rule** - When `features.envelope_chunk_observation="self-output-edit"`, every emitting handler call to `envelope.emit` with `kind ∈ {output, edit}` **MUST** cause the kernel to trigger `on_envelope_chunk` for body chunks, regardless of whether the body is Bytes or Stream. On the Bytes path, the kernel slices by `CHUNK_MAX_TOKENS` and invokes normative callbacks with monotonically increasing `chunk_index`, `total_chunks_hint=Some(n)`, and `stream_closed=true` on the final slice. On the native Stream path, `total_chunks_hint` **MAY** be `None`, and the only reliable end signal is still `stream_closed=true`. The L2 buffered path follows §6.5.2. The `tokens` visible to the callback are the token chunks that will ultimately be written into context, not the original bytes. `kind=execute` and `kind=rollback` do not trigger this callback. Kernel-generated system error envelopes (for example the ref.resolve failure error in §9.3) also **do not** trigger the self-output-edit observer; if a distribution provides a global observer extension, it **MUST** separately define filtering, deduplication, and loop-prevention rules.

`ChunkDecision` semantics are as follows: `Continue` means continue consuming and injecting subsequent chunks; `DetachObserver` means stop subsequent chunk callbacks without aborting the envelope; for `AbortEnvelope` or a callback returning `Err`, the kernel **MUST** immediately follow a path equivalent to generator exception (stop pulling + cancel generator /async iterator + close + on_abort + audit `E_EMIT_STREAM_ABORTED` + details `reason="handler_reject_chunk"`). If the observer rejects before the open token is injected in L2 `buffered` mode, use the buffered reject special path in §6.5.2, without supplementing a close.

> **Handler Context lifecycle** - `Context` is valid **only** within the current callback frame; handlers **MUST NOT** hold it across callbacks. The `ctx` received by `dispatch` /`on_envelope_chunk` /`on_event` /`resolve_ref` /`on_load` /`on_unload` /`on_abort` becomes invalid after that callback returns; calls through an invalid `ctx` are undefined behavior (a conforming kernel **MAY** report `E_KERNEL_INTERNAL`).

Boundary between fork and handler-internal state - A5 `session.fork` snapshots only kernel-managed state (context, KV cache, kernel metadata, capabilities, audit cursor, dispatcher frames, suspend handles, blob refcounts, and related state; see §9.4). The kernel does **not** automatically copy process-global variables, heap objects, connection pools, or other external mutable state inside native /host handlers. A conforming handler that stores session-related mutable internal state **MUST** partition it by `session_id` /fork branch, or persist that state in kernel-managed KV /blob /ref /region state. If a distribution provides a native backend and cannot guarantee this isolation, it **MUST** state in backend documentation that A5 fork covers only kernel-managed state, and **MUST NOT** let programs assume native internal state is automatically CoW-forked.

`on_load` loading state and visibility (normative) - The semantic order of `program.register` is: (1) after manifest validation, the program is added to the registry; (2) namespaces (`program:<name>/` KV prefix, ref-kind registration, etc.) are set up; (3) the kernel calls `on_load(ctx)`. Between (1) and (3) the program is in **`status=loading`**; this paragraph defines the visibility and reachability constraints during that window:

1. **Self /admin visibility** - A `loading` program **SHOULD** be visible to itself (the executing `on_load` callback) and to callers holding `program.admin` in `program.list` /`program.lookup` /`program.info`, and **MUST** be reported with the field `status="loading"`.
2. **Default model-visible view** - By default, `loading` programs are **hidden** from the model-visible view of `program.list`, or are presented with `status="loading"` and a "not dispatchable" mark; distributions **MUST NOT** mix loading programs into the normal callable set without that status.
3. **External dispatch unreachable** - Before `on_load` returns successfully (`Result::Ok`), any external B2 dispatch, syscall routing, scaffold, or other path **MUST NOT** enter that program's `dispatch` /`on_envelope_chunk` /`on_event` /`resolve_ref` /`on_abort` handlers; an attempt to dispatch a `loading` program **MUST** return `E_PROG_NOT_FOUND` (equivalent to "not registered") or a distribution-declared equivalent error, with audit details preferably containing `reason="loading"`. The program **MUST NOT** enter the §5.4 base set until `on_load` succeeds.
4. **`on_load` failure** - If `on_load` returns `Err` or panics, the kernel **MUST** roll back the metadata of (1) and (2) (remove the program from the registry, release namespaces) and record the failure per existing audit rules. Side effects (content already written to KV /blob /region) follow the transactional rules of each primitive itself; this paragraph does **not** add additional transactional rollback requirements.
5. **Self-call during `on_load`** - Within `on_load`, when the program queries `runtime info` /`program.list`, it **SHOULD** see itself as `loading`; it **MUST NOT** issue a B2 dispatch to itself to form self-recursion (the "external dispatch unreachable" rule guarantees this).

8.3 Closed Action Set (7 Items)

Action	Semantics	Corresponding primitive
`dispatch`	Respond to `<lmsc_execute>`	B2
`emit_output`	Write `<lmsc_output>` (including streaming mode); the same action also covers `emit` to a `<lmsc_edit>` envelope (kind=edit) -- the action name remains `emit_output`, and its semantics cover both output /edit envelope kinds	B3
`push_dispatcher_frame`	Push a child dispatcher stack	C5
`pop_dispatcher_frame`	Pop a child dispatcher stack	C5
`suspend`	Call C1	C1
`preempt`	Call C4 (requires cap)	C4
`register_ref_resolver`	Call F3.bind	F3

Cross-mapping from actions to syscalls:

Action	Potential syscall family	Required capability	Manifest validation
`dispatch`	No direct syscall; declares that this program can be a B2 dispatch target	Overall `capabilities_required` **MUST** pass	Program **MUST** provide `handler.dispatch`
`emit_output`	`envelope.emit(kind=output|edit)`	`envelope.emit`	A program that writes output/edit envelopes **MUST** declare this action

Action	Potential syscall family	Required capability	Manifest validation
`push_dispatcher_frame`	`scheduler.frame_push` /`scheduler.frame_supports`	`scheduler.frame` (`frame_supports` has no cap)	A program that uses frame push **MUST** declare it
`pop_dispatcher_frame`	`scheduler.frame_pop` /`scheduler.frame_supports`	`scheduler.frame` (`frame_supports` has no cap)	A program that uses frame pop **MUST** declare it
`suspend`	`scheduler.suspend` /`scheduler.resume`	`scheduler.suspend`	A program that suspends or resumes its own dispatch **MUST** declare it
`preempt`	`scheduler.preempt`	`scheduler.preempt`; execute injection also requires `scheduler.preempt.execute`	A program that uses C4 **MUST** declare it
`register_ref_resolver`	`ref.bind`	`program.ref.bind`	Must be declared when manifest `ref_kinds` is non-empty

The action table constrains the categories of side effects declared in the manifest; syscall entries still perform independent capability validation according to §7.4. Syscalls not listed in the table are not automatically forbidden because an action is absent; they are constrained by capabilities, required-program identity, or fixed-only rules. `envelope.emit(kind=execute)` is not covered by the `emit_output` action; if a distribution allows ordinary programs to write execute envelopes, authorization is controlled entirely by the `envelope.emit` capability and distribution runtime policy, and the manifest **does not need** and **MUST NOT** declare an additional action. Unknown actions are still rejected under the rule below.

Action set boundary: the Action set is a **closed set** and is not extensible; edit output is covered by `emit_output`, and ack plus capability grant are both expressed by existing envelope /capability mechanisms.

Unknown Action handling: if a manifest contains an action name that is not one of the seven items above, the kernel **MUST** reject it during `program.install` /`program.register` and return `E_PROG_MANIFEST_INVALID` (details contain `field="actions"`, `unknown_action=<that value>`). It **MUST NOT** ignore or silently skip unknown actions.

> **Criterion for whether an action belongs in the closed set** - The action table describes the **types of side effects a program declares it will trigger** to the kernel (for manifest validation and observability), and is **not** a mirror of all callable syscalls. The trigger conditions for an action all hold simultaneously: (1) it corresponds to the **explicit behavior type** of one or more syscalls (for example, "write an output envelope into context") rather than a pure query; (2) the side effect cannot be covered by the semantics of an existing action; (3) the kernel's precondition validation /authorization path differs depending on whether the program declares that action. Privileged syscalls such as `session.fork` /`cap.grant` do not form new actions -- their authorization is fully carried by the capability mechanism, and the manifest needs no additional declaration field. This criterion is bound to the 7-item closed set in §16.1 C-5; any action **MUST** go through the specification major-version upgrade process.

8.4 Namespace Isolation

- **kv** is physically isolated to `program:<name>/`;
- **blob** marks its creator;
- **ref kind** is globally unique;
- Program `audit.emit` automatically carries `source=program:<name>` and **MUST NOT** forge it.

8.5 Dispatcher Frame

The kernel maintains a dispatcher stack. Initially it contains only the root frame. Each frame contains:

- A program lookup table (**MAY** override the parent frame);
- A logit mask overlay;
- Additional capability constraints (optionally stricter).

The stack depth limit is `MAX_DISPATCHER_DEPTH` (default 8). `frame_push` /`frame_pop` (C5) are called by programs that hold the `scheduler.frame` cap.

When a handler panics, dispatch times out, C3 aborts, dispatch ends normally, or a turn ends, the kernel **MUST** automatically pop dispatcher frames pushed during that handler /turn that have not yet been popped, and record `frames_unwound`

in `abort` /`dispatch` audit details or error details. Automatic cleanup **MUST NOT** bypass all C5 ownership-check semantics; it is kernel finalization for the current handler stack frame, not a user-space `frame.pop`.

8.6 Program Visibility

`program.list` returns a **model-visible view** and **MUST** filter by `cap.check(program.capabilities_required)`. Programs that cannot be called by the current holder **MUST NOT** appear. `program.lookup` returns `None` for invisible programs; `program.info` returns `None` or a redacted summary explicitly declared by the distribution for invisible programs. Only callers holding `program.admin` may obtain the complete manifest and handler metadata.

> **`status` field in `program.list` /`program.info` responses (normative) -** The above view and the `program.info` response **MUST** expose `status: "ok" | "loading" | "unloading"` for each program record: `ok` means `on_load` has succeeded and `on_unload` has not been entered; `loading` is defined in §8.2; `unloading` means `on_unload` is being scheduled (visible only to `program.admin` and not dispatchable). Distributions **MAY** add their own status values but **MUST NOT** omit this field or let its value contradict base-set reachability. The `programs[*].status` field in boot output /runtime info (Appendix E) **MUST** be drawn from the same closed enumeration.

---

9. State Model

9.1 Five Classes of State

Class	Primitive	Lifecycle	Enters context?
Context tokens	(all)	Session	Yes
Regions	F4	Session	Only the token itself; tags are metadata
kv	F1	Session (TTL)	No
blob	F2	Session (refcount)	No
Forks	A5	Until explicit drop	No

9.2 Generation Marker (gen Attribute)

gen is a free-string attribute of output envelopes and regions. The kernel **only passes it through** and does not interpret it. Any generation transition (g0 -> g1, summaries, etc.) is implemented by **programs** (usually the recommended program summarizer, which is outside this specification) through a combination of region.edit+blob.put+ref.bind.

> **Note** - gen only carries program-defined generation labels; enums and state machines are both outside the kernel specification scope (P-5).

Like other attribute values, gen is constrained by ATTR_VALUE_MAX_BYTES; when recommended programs need to share a generation vocabulary, they **SHOULD** keep gen within 64 bytes and place long descriptions in blob /ref /region metadata rather than in the attribute header.

9.3 Ref Resolution Chain

> **Ref expansion semantics** - The result of ref.resolve replaces the original <lmsc_ref>...</lmsc_ref> interval by **inline substitution in the token stream**; this path does not create a program-visible RegionId, does not use the cap /lock /persist rules of user-space region.edit, and does not emit region_edit audit. The expanded tokens enter context, and the original <lmsc_ref> open /close reserved tokens are **no longer retained** in context, to avoid triggering infinite-loop resolution. The content pending injection before expansion **MUST** pass through I-EMIT-ESCAPE.
>
> **Strict top-level ref materialization** - When features.strict_protocol_mode=true and features.raw_text_outside_envelope="forbidden", and the <lmsc_ref> open appears at envelope stack depth = 0 in GENERATING, ordinary inline bytes returned by a successful ref.resolve **MUST NOT** be written directly into context outside an envelope merely after I-EMIT-ESCAPE. The kernel **MUST** do one of the following: (1) materialize the resolved content as a complete kernel-generated <lmsc_output> system envelope (or a distribution-declared equivalent envelope-safe structure), with an attribute header containing at least from="system" and schema="ref_resolve_result", and with the body still processed by I-EMIT-ESCAPE; or (2) reject the expansion, emit audit kind=protocol_violation (invariant="I-STRICT-ENVELOPE-ONLY", context="ref_expand_strict_top_level"), and present a system error envelope to the model through the ref-resolution failure path below. This system envelope, like a ref failure error envelope, is directly injected by the kernel and does not trigger the self-output-edit observer. If a distribution wants to let a resolver return a typed protocol item rather than ordinary bytes, it **MUST** separately declare the deterministic parser, escaping, audit, and conformance behavior; the default ordinary inline-bytes path in this specification does not provide that capability.

The same ref **MAY** appear multiple times (sharing the blob). When resolution fails (E_REF_EXPIRED, etc.), the kernel **MUST** let the model see an explicit error and **MUST NOT** silently ignore it; that error **MUST** be presented through a <lmsc_output> system error envelope or a distribution-declared equivalent structure. The recommended attribute header contains at least from="system", status="error", and schema="ref_resolve_error"; the body contains at least error_code plus redacted kind /id summaries. The error envelope body or equivalent error description **MUST** execute I-EMIT-ESCAPE before being injected into context.



Audit attribution for ref-resolve failures (normative) - the kernel-injected ref-resolve error envelope (and the system envelope on the strict top-level ref-materialization path) **MUST** be expressed as a §14.2 `kind=envelope_open` audit, with details containing `envelope_kind="output"`, `envelope_from="system"`, `open_source="kernel:ref_resolve_error"` (use `open_source="kernel:ref_resolve_strict_top"` for strict top-level materialization), and `source` fixed to `"kernel"`. If the failure is triggered by an invariant breach such as `I-STRICT-ENVELOPE-ONLY`, the kernel **MUST** first emit `kind=protocol_violation` and then emit the `envelope_open` above; the order and timing of these two audits **MUST NOT** be reversed. This error envelope is injected directly by the kernel and **MUST NOT** trigger a self-output-edit observer, nor **MUST** it be expressed as `kind=envelope_emit` (which is reserved for B3 program-mode emits).

That system error envelope is directly injected by the kernel and is **not** part of an emitting handler's `envelope.emit(kind=output|edit)` path, so it **does not** trigger the §8.2 `features.envelope_chunk_observation="self-output-edit"` `on_envelope_chunk` callback. If a distribution separately provides a global observer, its extension specification must define filtering, deduplication, and loop-prevention rules.

External ID canonicalization (non-normative interoperability recommendation): the ref micro-grammar keeps the strict ASCII safe set, and the kernel does not relax `I-REF-CHARSET`. When mapping an external system ID to `ref.id`, prefer `base64url(no_padding(utf8_bytes))` for reversibility, or `sha256:<hex-prefix>` /`sha256:<full-hex>` for a short, stable, irreversible id. Resolver manifests, ref registry metadata, or distribution extension audits **SHOULD** record `external_id_scheme` and the collision policy (for example prefix length, second-stage extension on collision, or rejecting the bind); the kernel does not automatically compare canonical equivalence across schemes.

Rollback search uses the ref-expanded context: pattern matching for `token_rollback` (§13.3) operates on the **ref-expanded context**, namely the actual token sequence after `<lmsc_ref>` envelopes have been replaced by their resolved content; the search does not pass through the original ref envelope symbols, and only sees the bytes finally injected into context.

Recursive refs prohibited - Content returned by a resolver **MUST NOT** again contain a literal `<lmsc_ref>...</lmsc_ref>` (the kernel scans before expansion, and if found, returns `E_REF_BODY_INVALID` and aborts the current expansion without recursion); this is equivalent to setting `MAX_REF_RESOLVE_DEPTH=1`. Recursive refs are prohibited to avoid unbounded-depth calls on the synchronous token stream hook path and to simplify implementation verifiability.

9.4 Fork

A5 fork semantics apply only to implementations whose `runtimeinfo.kernel.atomics` includes A5. L1 /L2 implementations **MUST NOT** expose usable `session.current_handle` /`session.fork` /`session.restore` /`session.drop_fork` semantics; if a program calls these entries, the kernel **MUST** return `E_ATOMIC_UNSUPPORTED`. The following clauses in this section define the complete semantics that implementations supporting A5 **MUST** satisfy.

A5 fork applies to **the entire session state** (the following list is the normative complete snapshot set; fork **MUST** atomically save all of the following entries):

- context token sequence (including boot output);
- KV cache snapshot;
- program table references;
- kv /blob refcount (increase references; see §13.9);
- effective capability set;
- audit cursor;
- **dispatcher frame stack** - the whole stack is CoW-cloned into the new session; `frame.pop` in the new session only affects its own stack copy and **does not affect** the parent session's frame; the reverse also holds.
- **active suspend handles and timers**: independently copied with the session (each keeps its own timing); timer callbacks in parent and child sessions do not trigger each other. `ResumeCondition::External` also **MUST** target a specific `SuspendHandle`; parent and child session handles do not trigger each other, and the kernel **MUST NOT** broadcast an external resume signal without a specified handle to multiple fork branches.
- **`ROLLBACK_STORM_LIMIT` counter**: the child session **inherits the parent's current value** (rather than resetting), blocking the bypass of "avoid storm-limit through fork".
- **`persona-refresh` per-turn counter**: the child session **inherits the parent's current value**.
- **`preempt cooldown` timestamp**: the child session **inherits the parent's last preempt time** (after the child session obtains a new `session_id`, cooldown continues timing under the new key from the inherited value).
- **`SESSION_FORK_MAX_DEPTH` /`SESSION_FORK_MAX_CONCURRENT` quota**: depth is inherited along the parent chain; concurrency counts independently against the root session.
- **active Stream generator** (prohibited by the A5 precondition before fork): this restates consistency -- when a handler holds an unclosed streaming `envelope.emit`, it **MUST NOT** fork; there is no active Stream generator that needs to be copied with the session at fork time.
- **handler-internal mutable state**: the fork snapshot does not include process-global variables, heap objects, connection pools, or other external mutable state inside native /host handlers. If such state is session-related, the handler **MUST** isolate it by `session_id` /fork branch, or store it in kernel-managed state (KV /blob /ref /region) before it participates in fork semantics. The kernel **MUST NOT** imply that such external state is automatically CoW-forked by A5.

`current_handle()` returns the `SessionHandle` of the current session without creating a fork, allocating a CoW snapshot, or counting against fork quotas. `fork()` returns a new `SessionHandle`, and the original session remains alive. `restore(handle)` switches into the target session, and the original session remains alive until `drop_fork`. A program that needs to move back and forth between parent and child branches **MUST** save the parent handle with `current_handle()` before switching into the child; it can later use `restore(parent_handle)` to return to the parent branch. This supports tree-of-thought, OOM protection, and transactional dispatch.

> **Note** - A5 fork semantics are defined by §5.2 and §9.4: they apply to the entire session state and remain consistent throughout the document, without ambiguity.

9.4.1 Boot Output and Fork

- Boot output is **equivalent to a region with `attention=pin`**, marked by the kernel during INIT -> IDLE:
- It exposes the public reserved region id `region:boot`; programs **MAY** treat it as a legal `RegionId`, but any `region.edit` on that region or `region.tag` covering the boot output range **MUST** be rejected by the kernel with `E_REGION_LOCKED` (reusing the error-code convergence principle);
- **Boundary between kernel-owned and program-created pin** - kernel-owned pins (boot output, `<lmsc_output>` pin output injected by `runtimeadminpersona-refresh`) are **not subject to** the `region.pin` cap constraint; program-created pins (`region.tag(attention=pin,...)`) **MUST** hold `region.pin` (fixed-only). persona-refresh pin output is not exposed as an ordinary editable `RegionId`; it exists only as a rollback/pin boundary and system audit object.
- **MUST NOT** be touched by `region.edit` (`E_REGION_LOCKED`);
- **MUST NOT** be crossed by a `<lmsc_rollback>` envelope (`I-ROLLBACK-BOUND`).
- A child session from `session.fork` **inherits** the original boot output (it is part of context); the kernel **does not** re-emit boot output in the child session.
- `runtime info` is a current-state snapshot and **MAY** differ from boot output (the INIT-time snapshot); however, both **MUST use the same schema** (see Appendix E).

9.4.2 Fork and Blob Refcount

- During `fork`, the kernel increments the refcount by **+1** for **each** blob referenced by the original session (not only blobs hit by the fork);
- During `drop_fork`, it decrements the corresponding blob by **-1**;
- New blobs created by `blob.put` inside the new session belong to the new session; `drop_fork` in the original session does not affect blobs independently created by the new session;
- CoW KV cache **MUST NOT** be released before both sides drop it (consistent with §13.9).
- **Normative definition of the "referenced" set** - The kernel **MUST** maintain the normative model `session -> Set<BlobId>`. At fork, it performs session-level refcount +1 for each BlobId in that set; repeated appearances of the same BlobId in context count once, not +N times by number of appearances. This set includes:

1. blob references materialized into context by the kernel in a structured way (that is, blob ids actively tracked by the kernel through syscall paths such as explicit injection after `blob.get` returns a handle, `ref.resolve`, and region edit products); it **does not perform heuristic scans over ordinary free text** -- if the model freely generates a string similar to a blob id, the kernel does not include it in the reference set;
2. region edit products (blobs saved for drop-soft /replacement and exposed through `archived_blob_id`);
3. blobs returned by ref resolvers and already materialized (inline cache references held by the kernel).

If a kv value contains an entry holding a blob handle, the kernel **does not** scan kv content; programs that need to preserve that blob during fork **MUST** explicitly call `blob.incref` (consistent with the existing F2 refcount API, avoiding traversal of the full kv chain on the hot path). Except for the structured materialization paths listed above and explicit `blob.incref`, distribution extension syscalls, ordinary free text, or blob-like strings **MUST NOT** be implicitly included in `session -> Set<BlobId>`. After fork, `blob.decref` issued by either session against this refcount only affects the refcount held by the calling session (same criteria as §13.10).

- **Implementation note** - refcount updates **SHOULD** be implemented as per-blob O(1) layered operations; fork **MUST NOT** traverse the full session byte volume on the inference hot path to populate refcount. Recommended model: maintain a layered reference table for `session -> Set<BlobId>` (for example, a counting bloom or copy-on-write immutable set), share structure during fork, and decrement the difference set during drop_fork. This is a non-normative recommendation; the specification only requires consistency of observable semantics.

Minimum conformance test vectors:

1. When the same BlobId appears repeatedly in context through ref expansion and a region edit product, `fork` increments that BlobId's session-level refcount by +1 only once.
2. When a kv value stores a blob handle string but the program did not explicitly call `blob.incref`, `fork` does not scan kv content and therefore does not increase that blob refcount.
3. A new BlobId created by `blob.put` in the child session after fork independently belongs to the child session; `drop_fork` in the parent session **MUST NOT** decrement the refcount of that new BlobId.

9.4.3 Restore Across Builds

- An implementation **MAY** reject `restore` for a fork generated by a different kernel build id; when rejected, it returns `E_FORK_INVALID` and records the source build /current build in audit. This is a conformance-permitted behavior, not a requirement.

---

10. Scheduling and Session State Machine

10.1 State Machine



State transitions:

Current	Event	Next	Side effects
INIT	boot complete	IDLE	Inject boot output (performed directly by the kernel, equivalent to a region with `attention=pin`; see §9.4.1)
IDLE	token_inject(user msg)	GENERATING	--
GENERATING	envelope open	IN_ENVELOPE	Update stack
IN_ENVELOPE	close (execute)	DISPATCHING	Trigger B2
IN_ENVELOPE	close (output/edit)	GENERATING	audit
`IN_ENVELOPE(rollback)`	close (rollback)	Outer state restored per §10.1.1	Trigger A3 after legal rollback and completed truncation; does not enter DISPATCHING
`IN_ENVELOPE(rollback)`	`rollback_error` /`protocol_violation`	IDLE	Invalid rollback, unavailable truncation, or cleanup failed; abort fallback per §5.2 /§6.5.1.1
IN_ENVELOPE	`<|lmsc_abort|>`	GENERATING	C3
`GENERATING` /`IN_ENVELOPE` /`DISPATCHING`	`<|lmsc_suspend|>`	SUSPENDED	C1; model path defaults to `resume_on=External`
SUSPENDED	resume	Restore previous state	C2
DISPATCHING	handler returns	IDLE /GENERATING	--
DISPATCHING	handler suspend	SUSPENDED	--
DISPATCHING	preempt triggers	IN_ENVELOPE (new)	C4
DISPATCHING	Program-path A3 (`token_rollback`)	DISPATCHING	Truncate KV; does not change the state machine state itself; dispatcher frame stack is preserved; audit `rollback`
GENERATING	EOS	IDLE	End current turn
IN_ENVELOPE	EOS	IDLE	Protocol termination; abort current envelope, inject necessary close tokens or execute the cleanup path in §6.5.1.1, and write `abort` /`protocol_violation` audit
DISPATCHING	EOS observed	IDLE	The model **SHOULD** avoid producing EOS under DISPATCHING; if observed by the adapter layer, write `protocol_violation` and abort the current dispatch through the C3-equivalent path (see §5.3 B2 /§8.5)

Current	Event	Next	Side effects
*	abort (external)	IDLE	C3

The next-state decision for `DISPATCHING | handler returns` is as follows: if the handler did not inject any envelope/content that can continue sampling into context and there is no resume payload, return to IDLE; if the handler produced model-visible continuation context through `envelope.emit` or legal token injection, return to GENERATING; if the return path triggers suspend /preempt /abort, the corresponding path overrides this decision.

10.1.1 Outer-State Recovery Algorithm After Truncation

This algorithm applies only to the path where rollback is legal and the kernel has completed physical or equivalent KV truncation. Paths with `features.rollback_truncate_precision="none"`, invalid rollback cleanup failed, and any rollback_error /protocol_violation abort fallback do not enter this algorithm; those paths converge directly to IDLE or the corresponding abort postcondition according to §5.2 and §6.5.1.1.

On an applicable path, after `<lmsc_rollback>` /A3 triggers KV truncation, the kernel **MUST** deterministically reconstruct the outer turn state:

```
fn recover_outer_state(kv_after_truncate):
 stack := []
 # Traverse from the current turn's IDLE starting point to the tail after truncation
 for token t in kv[turn_start .. kv_tail]: # kv_tail is the tail token index **after truncation is complete**
 if t is envelope_open(kind): stack.push(kind)
 if t is envelope_close(kind): assert stack.top == kind; stack.pop()
 if stack.empty():
 return GENERATING
 else:
 return IN_ENVELOPE(stack.top)
```

- The scan starts at the point where the current turn left IDLE and ends at the KV tail after truncation. `kv_tail` means the tail token index **after KV truncation is complete**; the scan interval `[turn_start .. kv_tail]` represents the context after truncation and does not include the discarded rollback envelope itself.
- Protected by §9.4.1, boot output **MUST NOT** be crossed by rollback: the scan interval does not include boot output.
- Complexity is O(T), where T = number of remaining tokens after truncation. An implementation **MAY** store a stack snapshot at the rollback start point and reduce average complexity to O(1) (non-normative optimization).
- **Snapshot sampling timepoint and minimum fields** - If the implementation chooses the O(1) snapshot optimization, it **MUST** take the snapshot **before** the token stream hook **observes the `<lmsc_rollback>` open token** (or in the same logical step where the token has just been recognized but the state machine has not yet advanced); it **MUST NOT** take a late snapshot after entering the rollback body or close. The snapshot includes at least the envelope stack, current parser substate (attr/ref/rollback body active flags), turn start point, rollback storm count, KV tail pointer required for recovery, and current suspend-state reference. A conforming implementation **MUST** guarantee that, for the same pattern and the same KV snapshot, the O(1) snapshot path and the O(T) full-scan path produce **exactly the same** `(GENERATING | IN_ENVELOPE(kind))` result; the implementation **SHOULD** be able to validate the snapshot result with the O(T) scan path -- this is a direct consequence of §16.1 C-14.
- **Sampling behavior after truncation**: after truncation completes, the next sampling step continues directly from the restored outer state and **does not introduce implicit control tokens** (does not insert any special token for "retrigger" or "continue generation"); the restored outer state is the natural suffix point of the remaining context after truncation, and the model continues writing directly at that point.

10.1.2 Strict Protocol Mode and Auto Execute Scaffold

This section defines two **mutually independent**, default-off features: `strict_protocol_mode` (constraint on raw text outside envelopes) and `auto_execute_scaffold` (kernel pre-injection of execute open + attrs). Both are **disabled by default**; when disabled, the semantics of `GENERATING` are consistent with the rest of this specification and compatible with RC1 /RC2 /RC3 behavior. `strict_protocol_mode` **MUST NOT** be conflated with "the kernel always auto-injects `<lmsc_execute>`" -- the auto scaffold is an optional sub-mode under strict mode, not its default meaning.

When **strict protocol mode** (`features.strict_protocol_mode=true`) is enabled, the semantics of the `GENERATING` state are strengthened to "the model is sampling the next legal LMSC protocol item." When envelope stack depth = 0, the tokens allowed outside an envelope are determined by `features.raw_text_outside_envelope`:

raw_text_outside_envelope	Semantics	Enforcement
allowed	Same as default behavior: ordinary natural-language tokens **MAY** appear outside envelopes	Not enforced (default value)
audit-only	Allowed to pass, but each contiguous span of raw text outside an envelope emits one audit kind=raw_text_outside_envelope	Recorded as audit by the token stream hook; does not constitute a violation
forbidden	Outside envelopes, only the "legal LMSC protocol entry set" is allowed: the four envelope opens (<lmsc_execute> /<lmsc_output> /<lmsc_edit> /<lmsc_rollback>), '<	lmsc_suspend

<|lmsc_abort|> is excluded from the legal entry set outside envelopes due to I-ABORT-SCOPED; this means under strict + forbidden mode the model **CANNOT** "abort everything" mid-turn, and **MUST** rely on EOS or external abort instead. <lmsc_ref> open **MAY** appear in any envelope body and in ordinary chunks under §4.4 I-REF-ANY; under strict + forbidden mode <lmsc_ref> open at envelope stack depth = 0 **MUST** be treated as a legal entry (with the same standing as envelope opens) to avoid conflicting with I-REF-ANY -- i.e., the entry set under that mode is: the four envelope opens, <|lmsc_suspend|>, <lmsc_ref> open, and EOS. A successful expansion of that ref is still subject to the strict top-level ref materialization rule in §9.3; ordinary bytes returned by the resolver **MUST NOT** become raw text outside an envelope.

Boundary of "contiguous span" under audit-only - A span of raw text outside an envelope starts at the turn start or right after the previous reserved-token boundary, and ends at the first occurrence of any of: the next reserved token (any envelope open /control single token /<lmsc_ref> open), EOS, or IDLE. If the span byte length exceeds the byte budget corresponding to CHUNK_MAX_TOKENS, the kernel **MUST** emit kind=raw_text_outside_envelope audits (§14.2) sliced at CHUNK_MAX_TOKENS granularity; within the same turn, the same byte range **MUST NOT** be re-emitted.

Naming disambiguation between strict mode and §13.3 rollback_strict_mode - This section's features.strict_protocol_mode controls the constraint on raw text outside envelopes; §13.3's features.rollback_strict_mode controls the compression of rollback failure audits. Their scopes do not overlap; they are independently activated and **MUST NOT** be inferred from each other.

Auto execute scaffold (features.auto_execute_scaffold=true) allows the runtime, in scenarios where the next step is already determined to be program execution, to have the kernel **pre-inject** <lmsc_execute> open + a kernel-owned attribute header before sampling, with the model only generating the execute body afterward. This sub-mode is **orthogonal** to strict mode (each **MAY** be enabled separately), but the typical combination enables both together.

The attribute header injected by the scaffold **MUST** include at least:

Attribute	Value	Description
id	The unique envelope id allocated by the kernel	Generated at the moment of scaffold open
from	"model"	The body is generated by the model; the kernel only provides the scaffold

The scaffold injection **MUST NOT** pre-fill the program attribute. Reason: at the moment of injection, the model has not yet generated the body and the kernel does not know argv[0]; the dispatch target **MUST** still be parsed from the first word of the body after </lmsc_execute> close (consistent with the existing routing semantics in §8), avoiding a "dual source of truth" with the attrs. The implementation **MAY** append diagnostic fields to the attribute header (e.g., scaffold="execute") for audit /debugger use only, and **MUST NOT** treat them as dispatch input.

Relation between scaffold injection and A4 token_inject - Scaffold injection is a kernel-internal direct-injection path; it does **not** go through the program-side A4 token_inject syscall, and therefore **MUST NOT** be charged against the INJECT_MAX_TOKENS quota and **MUST NOT** trigger an inject audit kind. The kernel **MUST** emit a kind=envelope_open audit using the schema in §14.2; that schema is compatible with normal envelope-open audits when a distribution chooses to record them, while §14.2 still defines whether model-spontaneous opens are emitted. On the scaffold path, details contain open_source="kernel:scaffo

ld" and envelope_from="model", so that observers can distinguish it from envelopes opened spontaneously by the model. Once the scaffold-triggered envelope is open, its body and close are generated by the model and are **treated as a normal envelope**: governed by all existing constraints including I-CTRL-INSIDE-ENV, EMIT_BODY_MAX_BYTES, and the §6.5.1.1 EOS fallback.

The state transition triggered by the scaffold is added (in addition to the main transition table in §10.1; only effective when auto_execute_scaffold=true) as follows:

Current	Event	Next	Side effects
GENERATING	runtime triggers scaffold (envelope stack depth = 0)	IN_ENVELOPE(execute)	Kernel injects <lmsc_execute> open token + attribute header (containing id /from="model"); push execute onto the envelope stack; the model generates the subsequent body until the </lmsc_execute> close, or it converges per §6.5.1.1 /EOS fallback

The trigger condition for the scaffold is defined by the distribution outside runtime info (typically: the runtime has already determined that the next step must be a program call after the handler return). This specification **does not** specify a particular trigger predicate, but **MUST** guarantee that:

1. Scaffold injection occurs only in the GENERATING state with envelope stack depth = 0;
2. Each injection allocates a unique id;
3. After injection, the sampler enters the execute body mode (ordinary tokens allowed; legal close /control /ref paths reserved);
4. If the body byte count exceeds EMIT_BODY_MAX_BYTES or EOS is observed without seeing close, converge per §6.5.1.1 self-nested abort path and write a protocol_violation audit;
5. **Atomicity of scaffold open + attribute header injection** - The scaffold open token and the immediately following kernel-owned attribute header injection **MUST** complete atomically: from the start of the scaffold open injection until the blank-line terminator of the attribute header is written, the kernel **MUST NOT** interleave processing of any control event in C1 (suspend) /C3 (abort) /C4 (preempt); any C1 /C3 /C4 that arrives in the event queue during this window **MUST** be queued and processed only after the scaffold injection completes. If distribution policy chooses to abandon this scaffold (e.g., C3 has higher priority), it **MUST** cancel the decision **before** the scaffold open is injected and **MUST NOT** emit a kind=envelope_open audit; an intermediate observable state where "scaffold open is injected but the attribute header is incomplete" is **forbidden**.
6. **Determinism of the trigger predicate** - The trigger predicate **MUST** produce a consistent result under the same complete runtime snapshot (including session_state, event queue state, and the most recent handler return value), i.e., it is deterministic; the precise composition of the snapshot is defined by the distribution, but it **MUST** expose a minimal identifier as x-<vendor>-scaffold-policy-id: string in runtimeinfo.features so that training-data consumers can distinguish scaffold behaviors across distributions.

Boundary between debugger demo and protocol semantics - Auto-injection by debuggers /demonstration tools is for visualization only and **MUST NOT** be treated as protocol semantics; only when runtimeinfo.features.auto_execute_scaffold=true does the scaffold path defined in this section qualify as normative behavior.

10.2 Turn

Turn = the interval from leaving IDLE to the next time IDLE is reached. Per-turn limits (rollback count, accumulated preempt cooldown, etc.) are scoped to a turn. In §5.2 A3 /§10.1.1 /§13.3, "current turn" strictly means the starting point at which the system most recently entered IDLE and then left IDLE again; the rollback process itself does not form a new turn boundary. SUSPENDED is not a turn-end boundary; suspend/resume does not reset the turn count, rollback storm count, or rollback search window. After resume, rollback executes against the current restored post-edit context.

10.3 Concurrency

- Within a single session: serial.
- Across sessions: **MAY** be concurrent; state is isolated.
- Async events (timers, external resume) are queued to the event queue; the kernel handles them at IDLE or explicit resume points.

---

11. Capability Model

11.1 Capability Strings

```
capability := category "." verb [ "." qualifier ] [ ":" scope ]
```

Examples:

- `fs.read:/workspace/**`
- `net.get:https://api.example.com/*`
- `scheduler.preempt`
- `capability.grant` (fixed-only)
- `scheduler.abort.own`
- `scheduler.abort.any` (fixed-only)

> **Distribution extension namespace** - Distribution-defined capability strings (whether `category` or `qualifier`) and distribution-defined `ref kind` names **SHOULD** use the `x-<vendor>-<name>` prefix (consistent with the audit kind extension rule in §14.2.1), to avoid conflicts with future official names. Bare identifiers are reserved for future official versions; a conforming implementation **MAY** reject registration of unprefixed non-official names.

11.2 Three Pools

Each session has three sets:

Pool	Source	Lifecycle
`capabilities.fixed`	boot config (kernel image /distribution signature)	Session-level immutable
`capabilities.granted`	D2 runtime approval	Until TTL or explicit revoke
`capabilities.requestable`	list at boot	Can be requested through the capability program

Effective set = fixed ∪ granted.

11.3 Matching Rules

`cap.check("fs.read:/workspace/foo.txt")` checks the effective set by:

1. Exact equality;
2. Wildcard matching: `*` single segment, `**` multiple segments, `?` single character, `{a,b,c}` enumeration; "segment" is defined by owner lookup table (a typical matcher splits path-like scopes by `/`, URL scopes by the path after the protocol prefix using `/`, and counter-class scopes as a single segment), and is explicitly registered at registration time; unregistered capability categories always default to **single segment**, and implicit relaxation **MUST NOT** be allowed (consistent with P-2 mechanism rather than policy);
3. No match -> false.

Regular expressions are not supported.

11.4 Fixed-Only High-Risk Set

The following capabilities **MUST** be granted only through `capabilities.fixed`; they **MUST NOT** be granted, and **MUST NOT** appear in `capabilities.requestable`:

- `capability.grant`
- `capability.revoke`
- `program.admin`
- `scheduler.abort.any`
- `scheduler.preempt.execute`
- `tokens.mask.direct`
- `tokens.rollback.explicit`

- `tokens.inject.special`
- `region.pin` (explicitly granted by the distribution in `capabilities.fixed` to programs that need it, typically `runtime`; it **MUST NOT** be obtained through non-fixed-only paths)
- `region.drop.hard`
- `boot.refresh`

A conforming distribution **MUST** publish a machine-readable capability registry, with canonical file name `lmsc-capability-registry.yaml` (or an equivalent JSON representation). Appendix B is the human-readable projection of that registry; if the projection table in an implementation package conflicts with the registry, conformance checks use the registry and the fixed-only set in this section as the source of truth.

Minimum field set:

```yaml
schema: lmsc-capability-registry
revision: "1.0"
capabilities:
  - name: tokens.rollback.explicit
    fixed_only: true
    grantable: false
    requestable: false
    initial_holders: [kernel-internal]
    notes: V1 program path is unreachable.
```

Boot and `runtime info` validation **MUST** satisfy: fixed-only capabilities **MUST NOT** appear in `capabilities.granted` or `capabilities.requestable`; a D2 attempt to grant a fixed-only capability **MUST** return `E_CAP_GRANT_DENIED`, with details `reason="fixed_only_not_grantable"`; `tokens.rollback.explicit` **MUST** also satisfy the V1 program-side unreachable constraint in §16.1 C-16.

11.5 Request Flow

1. Program A needs `cap.X`;
2. A calls the `capability` program: `capabilityrequestcap.X-\/-reason...`;
3. The `capability` program:

- `cap.check(cap.X)` already holds -> ok;
- `cap.X` is in `capabilities.requestable` -> enter external decision; decision succeeds -> inject `cap.grant`;
- `cap.X` is not requestable -> `E_CAP_NOT_REQUESTABLE`;

4. The `capability` program calls `scheduler.suspend(ResumeCondition::CapGrant(cap.X))` (synchronous) or immediately returns pending (asynchronous);
5. Decision succeeds -> resume -> return ok.

> **External decider SHOULD**: the external decider **SHOULD** be declared by the distribution in the `capabilities.requestable` configuration, and the grant/resume **SHOULD** be completed through the `capability` program or an equivalent host interface; the distribution **SHOULD** document the decider identity and trigger conditions so program developers can anticipate request behavior.

---

12. Required Programs

A conforming kernel distribution **MUST** ship with, and **only** ship with, the following **4 programs** as the initial `/os/bin/` set. They **MUST NOT** be unregistered and **MUST NOT** be shadowed.

> **Note** - The required program set is fixed as `program` /`capability` /`runtime` /`kv`; boot output is emitted directly by the kernel, `slot` belongs to the recommended layer, and audit capability is merged into `runtime`.

12.1 `program`

Subcommands:

- `program list [--capability f] [--ref-kind k]`
- `program info <name>`
- `program install --from-blob <id>` /`--from-url <url>`
- `program remove <name>` (required programs **MUST NOT** be removed)
- `program register --manifest <blob_id>`
- `program unregister <name>`

Capability: `program.install` controls the user-visible install /remove subcommands; `program.register` and `program.admin` control the underlying E primitive calls. Read-only queries do not need a cap.

> **`program.install` cap semantics** - The `program.install` cap itself only manages install /delete write operations at the user subcommand layer (`program install` /`program remove` /`programregister-\/-manifest` /`program unregister`). These subcommands are delegated by the `program` required program to call the underlying E primitives; external programs **MUST NOT** use `program.install` to directly call the `program.register` syscall. Read-only queries (`program list` /`program info`) go through the `program.lookup` /`program.info` /`program.list` syscalls, which have no cap requirement, and **do not** involve this cap.
>
> **Delegated-call identity and audit** - When a user or external program calls install /delete class subcommands, the `program` required program first checks subcommand-layer authorization as the original caller (such as `program.install`, `net.get:<registry>`, distribution signature policy, manifest schema, and required-program protection rules). After the check passes, the underlying E primitive is delegated by the `program` required program using its own `program.register` /`program.admin` fixed caps; the external caller does not thereby receive the underlying syscall caps. The related audit details **MUST** record `actor=<original caller>`, `delegate="program"`, and the underlying `operation` at the same time, so audit consumers can distinguish "who requested" from "who delegated the call".

Default-held caps:

Capability	Source
`program.register`	`capabilities.fixed` (loaded by the distribution at startup)
`program.admin` (fixed-only)	`capabilities.fixed`
`program.install`	**MAY** be granted by an external decision; only manages user subcommand write paths (`program install` /`program remove` and so on); read-only queries (`program list` /`program info`) do not require this cap

12.2 `capability`

Subcommands:

- `capability list`
- `capabilitylist-requestable`
- `capability check <cap>`
- `capability request <cap> [--wait <dur>] [--async] [--reason ...]`
- `capability cancel <request_id>`
- `capability status <request_id>`

- `capability grant <cap> --ttl ... --scope ...` (decider only)
- `capability revoke <cap_id>`

Default-held caps:

Capability	Source
`capability.grant` (fixed-only)	`capabilities.fixed`
`capability.revoke` (fixed-only)	`capabilities.fixed`

Read-only subcommands (`list` /`check` /`list-requestable` /`status`) **do not** require a cap.

12.3 `runtime`

> **Structure** - `runtime` exposes its subcommands grouped by **3 namespaces**, with privilege level aligned to namespace. The short-path subcommand set is retained as V1 usability aliases; moving from `runtime <subcommand>` to `runtime <namespace> <subcommand>` is not a breaking change.

Namespaces and subcommands:

```
runtime info # Return the current state snapshot (same schema as boot output; values MAY differ because of snapshot timing, such
↪  as `capabilities.granted`~/{}`programs.recommended`~/{}`features.*` and the effective `limits` values; see §9.4~/{}Appendix E)
runtime stats # Token usage, kv entries, blob size, region count; protocol_overhead;
↪  rollback.current_turn_count~/{}rollback.remaining~/{}rollback.storm_locked

# query sub-namespace (readable by all programs by default)
runtime query errors [-n N] # Recent errors (projection of audit kind=*_denied|*_error)
runtime query regions # Region list
runtime query caps # = capability list alias

# audit sub-namespace (readable by all programs by default)
runtime audit tail [-n N] [--filter] # Audit projection (scope=model-visible only)
runtime audit search <query> # Query syntax is the minimal subset of "field prefix matching + glob"; see below
runtime audit export --to-blob # Requires audit.export cap

# admin sub-namespace (privileged)
runtime admin fork # Calls A5 session.fork, requires runtime.fork
runtime admin abort <envelope_id> # Calls C3, requires scheduler.abort.any (fixed-only)
 [--reason <text>]
runtime admin compact <region_id> # Calls F4 region.edit, requires region.compact
 --replacement <blob_id> [--persist]
runtime admin persona-refresh --diff <blob_id> # Optional runtime admin extension; requires boot.refresh, see §12.3.1
```

Note:

- Short-path aliases (`runtime fork` /`runtime compact` /`runtimepersona-refresh` /`runtime errors` /`runtime regions` /`runtime caps`) are V1-defined usability aliases that map to the namespace paths above; V1 conforming implementations **MUST** support them.
- `runtime audit` /`runtime query` are available to each program by default (requiring `runtime.read`); each `runtime admin` subcommand requires its dedicated cap (`runtime.fork` /`region.compact` /`boot.refresh`).
- The cap requirements above correspond one-to-one to subcommands, so the user can tell the privilege level from the subcommand path (and read-only queries are not mixed into the same namespace).

Capability: `runtime.read` (all programs by default), `runtime.fork`, `region.compact`, `audit.export`, `boot.refresh`.

The rollback observability fields in `runtime stats` are a snapshot of the current turn: `rollback.current_turn_count` is the number of successful + failed rollback attempts that have counted toward the storm limit in this turn, `rollback.remaining=max(0,limits.rollback_storm_limit-current_turn_count)`, and `rollback.storm_locked` indicates that the counter has reached the limit and is locked until IDLE. SUSPENDED does not end a turn, so these fields **MUST** preserve the same counting semantics across suspend/resume.

`runtime audit search` query micrograammar

```
query = field_glob , { "," , field_glob } ;
field_glob = ident , ":" , glob_pattern ;
glob_pattern = ? glob syntax consistent with the typical matcher in §11.3 ? ;
```

`field` is limited to direct field names of `AuditRecord` (`kind` /`source` /`program` /`envelope_id` /`capability` /`turn_id` /and so on); nested `details.*` queries are outside V1 scope (distributions **MAY** extend them). Multiple `field_glob` items are comma-separated and have bitwise AND semantics.

§12.3 alias mapping table - Short path -> namespace path:

Short path	Namespace path
`runtime fork`	`runtime admin fork`
`runtime compact`	`runtime admin compact`
`runtimepersona-refresh`	`runtimeadminpersona-refresh`
`runtime abort`	`runtime admin abort`
`runtime errors`	`runtime query errors`
`runtime regions`	`runtime query regions`
`runtime caps`	`runtime query caps`

Both forms **MUST** be accepted by the kernel in V1, with equivalent semantics.

Default-held caps:

Capability	Source	Supported subcommands
`runtime.read`	`capabilities.fixed`	`runtime info` /`stats` /`query *` /'audit tail
`scheduler.abort.any` (fixed-only)	`capabilities.fixed`	`runtime admin abort <envelope_id>` (operations use, authorization frame only)
`runtime.fork`	`capabilities.fixed`	`runtime admin fork` (subcommand authorization)
`session.fork`	`capabilities.fixed`	`runtime admin fork` (underlying A5 call)
`region.compact`	`capabilities.fixed`	`runtime admin compact`
`audit.export`	`capabilities.fixed`	`runtime audit export`
`boot.refresh` (fixed-only)	`capabilities.fixed` (the distribution **MAY** choose whether to load it)	`runtimeadminpersona-refresh`

Note - `runtime admin compact` itself is only a thin wrapper around F4 and **does not depend** on recommended programs such as `summarizer`.

12.3.1 `persona-refresh` Semantics

`runtimeadminpersona-refresh` is an optional runtime admin extension and does not increase the count of 4 required programs defined at the start of §12. The command in this subsection, the persona-refresh pin output in §9.4.1, the persona-refresh rollback boundary in §13.3, and the related conformance tests apply only when `runtimeinfo.features.persona_refresh=true`. If that feature is false, references to persona-refresh in other chapters are treated as conditional rules; a distribution **MUST NOT** use a subcommand with the same name to carry different semantics.

To remove the behavior vacuum around `persona-refresh`, this text specifies its minimal semantics:

Consistency with the §10.1 state machine - `persona-refresh` uses the kernel-internal B3-equivalent emit path, not the general A4 `tokens.inject` path. The kernel generates the complete `<lmsc_output>` open token, attribute header, body, and close token, and triggers the same `EnvelopeOpen` /`EnvelopeClose`, escaping, and audit events as ordinary envelope emit; this privileged path is not exposed as a program-callable reserved-token injection capability and does not require `tokens.inject.special`.

Relationship to C-6 - §16.1 C-6 constrains only the number (4) and names of required programs; the `runtimeadminpersona-refresh` subcommand is an optional runtime admin extension. The subcommand name is **namespace-reserved**, and a distribution **MUST NOT** use a subcommand with the same name to carry different semantics.

Invocation: `runtime admin persona-refresh --diff <blob_id>`

- **Preconditions**: the caller holds the `boot.refresh` cap (fixed-only); `blob_id` points to a persona diff document using a distribution-defined schema (format is non-normative).
- **Postconditions**:

1. the kernel injects the bytes of `blob_id` into the current context as a new `<lmsc_output>` envelope (it does not replace the original boot output); its kernel-owned attribute header contains at least `from="system" id="persona-refresh:<seq>" visibility="all" attention="pin"`;

2. no re-boot is triggered; session state is not cleared; kv /blob /region /fork /cap sets are retained;
3. emit audit `kind=persona_refresh` (dedicated kind, no longer mixed with `cap_grant`), with details containing at least `diff_blob_id`, `boot_refresh_reason` (distribution-defined), `persona_region_id`, `active_persona_pin_count`, and `active_persona_pin_tokens`; if this call supersedes older persona-refresh pins, it **MUST** also include `superseded_persona_region_ids`; default `scope=system-only`.

- **Pin lifecycle and quota**: a distribution enabling `features.persona_refresh=true` **MUST** declare finite `persona_refresh_pin_max_active` and `persona_refresh_pin_max_tokens` values in `runtimeinfo.limits`. Before injecting a new persona-refresh pin, the kernel **MUST** compute the active persona-refresh pin count and total token count after injection; if either limit would be exceeded, the kernel **MUST** either (a) return `E_BOOT_REFRESH_LIMIT` without injecting the new pin, or (b) supersede enough older persona-refresh pins according to a deterministic distribution-declared policy (for example newest-N). A superseded pin's envelope body remains as historical context, but it no longer acts as an active `attention=pin` pin and no longer forms a persona-refresh rollback hard boundary; the same `persona_refresh` audit **MUST** expose that metadata transition. A distribution **MUST NOT** allow persona-refresh pins to accumulate without bound.
- **Limits**:
- It **MUST NOT** be called while a handler **holds an unclosed streaming `envelope.emit`** (same precondition as §5.2 A5 `fork`); when this condition is satisfied, calling it inside a dispatch handler as a `runtime admin` subcommand is legal (`persona-refresh` itself is the dispatch path `<lmsc_execute>runtime admin persona-refresh ...</lmsc_execute>`). Violations return `E_EMIT_STREAM_OPEN`.
- At most 1 time per turn; exceeding this returns **`E_BOOT_REFRESH_LIMIT`**. This specification uniformly uses this dedicated error code and no longer reuses `E_PREEMPT_NESTED`.
- `persona-refresh` **does not reset** the `ROLLBACK_STORM_LIMIT` counter (design rationale). This policy is deliberate: persona-refresh is a privileged injection by the system role, not a ”restart” at the turn logic layer; allowing it to reset the counter would give malicious or faulty programs a side channel around the rollback storm quota.
- **Errors**: `E_CAP_DENIED` /`E_BLOB_NOT_FOUND` /`E_BOOT_REFRESH_LIMIT` /`E_EMIT_STREAM_OPEN`.

If a distribution does not need this capability, it **MAY** choose not to expose `runtimeadminpersona-refresh`. Enabled state **MUST** be exposed through `runtimeinfo.features.persona_refresh` or `program info runtime`; when it is not enabled, the command is absent or returns one distribution-registered choice from `E_UNKNOWN_PROGRAM` /`E_CAP_DENIED`, and **MUST NOT** silently execute a no-op.

12.4 kv

Subcommands:

- `kv put <key> <value> [--ttl <dur>]`
- `kv get <key>`
- `kv del <key>`
- `kv list [--prefix <p>]`

Namespace: the `kv` program's own kv namespace (`program:kv/`); keys accessed by the model through `kv` subcommands land here, without introducing a pseudo program name `model`.

Default-held caps: no additional caps; `kv.*` syscalls themselves require no cap, and `kv` program operations are limited to its own namespace.

12.5 Non-Replaceability

If a conforming implementation provides a custom replacement program, it **MUST**:

- Preserve all subcommand names and semantics;
- Preserve capability dependencies;
- **MUST NOT** relax authorization (for example, by making `program.install` public).

Optional runtime admin extensions (such as `runtimeadminpersona-refresh`) declare enabled state through `runtimeinfo.features`; disabled optional extensions do not count into the required subcommand set that this section says ”**MUST** be preserved”, but their reserved names **MUST NOT** be reused for other semantics.

Otherwise, it is non-conforming.

13. Security Invariants

13.1 Capability Three-Layer Verification

Every privileged operation **MUST** be checked three times:

1. Dispatch entry: against `program.capabilities_required` as a whole;
2. Syscall entry: independently for each `ctx.<op>`;
3. Resource-access internals: re-check after a handle has already been obtained and later operations are attempted.

Failure at any layer immediately produces `E_CAP_DENIED` + audit.

13.2 Protocol Boundary Escaping (Corresponds to `I-EMIT-ESCAPE`)

The following four byte-injection paths **MUST** uniformly apply the escaping rules in this section (explicit enumeration):

1. The bytes body of `envelope.emit` (including both `body:Bytes` and `body: Stream<Bytes>` subpaths);
2. Rewriting a `net.*` response body into an envelope body;
3. Injecting `replacement` bytes from `region.edit`;
4. Injecting an error description or error envelope body into context when `ref.resolve` fails.

For any path above, the kernel **MUST**:

1. Scan for reserved token literals: `<lmsc_execute>`, `</lmsc_execute>`, `<lmsc_output>`, `</lmsc_output>`, `<lmsc_edit>`, `</lmsc_edit>`, `<lmsc_rollback>`, `</lmsc_rollback>`, `<lmsc_ref>`, `</lmsc_ref>`, `<|lmsc_abort|>`, `<|lmsc_suspend|>`, and any `<|key_*|>`. The shared prefix set is: `<lmsc_`, `</lmsc_`, `<|lmsc_`, `<|key_`;
2. Replace them with standard visually equivalent character sequences that the tokenizer **does not recognize**.
3. **Output MUST be valid UTF-8**: the byte sequence produced after escaping replacement **MUST** be legal UTF-8; if the input byte string contains an illegal UTF-8 sequence, the kernel **MUST** safely replace illegal bytes before tokenization (for example with the U+FFFD replacement character) or return `E_EMIT_ESCAPE_VIOLATION`; it **MUST NOT** write illegal UTF-8 bytes directly into context.

Standard escaping mapping - This specification defines the default `escape_mapping_id="lmsc-angle-u2039-v1"`. For any fully matched reserved token literal, the kernel **MUST** replace the first-byte character `<` (U+003C) in that literal with ‹ (U+2039 SINGLE LEFT-POINTING ANGLE QUOTATION MARK), while keeping the remaining characters unchanged; for example, `<lmsc_output>` → `‹lmsc_output>`, `</lmsc_output>` → `‹/lmsc_output>`, `<|lmsc_abort|>` → `‹|lmsc_abort|>`, and `<|key_0|>` → `‹|key_0|>`. The mapping output **MUST** be legal UTF-8 and **MUST NOT** be recognized by the current tokenizer as any reserved token prefix. If a distribution provides another mapping, it **MUST** declare `features.escape_mapping_id` in the boot/runtime schema and ensure that interoperability tests compare escaped context bytes only under the same mapping id.

Escaping interoperability test vectors: conforming implementations **SHOULD** at least cover the following tokenizer tests; test results are judged by the bytes that actually enter context after escaping:

Input	Chunking	Expected
`<lmsc_output>`	Single chunk	Output `‹lmsc_output>`, and the tokenizer does not recognize it as a reserved token
`</lmsc_rollback>`	`</lmsc_` + `rollback>` across chunks	Output `‹/lmsc_rollback>` after tail-window delay
‘<	key_0	>‘
Body containing illegal UTF-8 bytes	Any	Safely replace with legal UTF-8 or return `E_EMIT_ESCAPE_VIOLATION`; **MUST NOT** write illegal UTF-8

`escape_mapping_id` is a feature registry field; distribution-defined mapping ids **MUST** have machine-readable registrations that describe the replacement rule, applicable tokenizer set, and test-vector version.

`envelope.emit` `attrs` values are not part of the four body-bytes injection paths in this section; if an attrs value contains a reserved-token literal or exceeds `ATTR_VALUE_MAX_BYTES`, it is directly rejected under §5.3 B3 with `E_EMIT_ESCAPE_VIOLATION`, and the visually equivalent mapping above **MUST NOT** be applied and silent truncation **MUST NOT** occur.

> **Cross-chunk scanning on streaming paths** - On the `body: Stream<Bytes>` path, the kernel **MUST** run the scan above over a **cross-chunk** byte sliding window; sliding-window size **MUST be** $\geq$ **`len(max_literal)-1`** (that is, the length of the longest reserved literal minus 1, to prevent a suffix and prefix of a reserved literal from being left across two adjacent chunks and escaping detection); this window is also used for real-time rewriting on the `net.stream` path (the unified escaping rule applies at any kernel boundary where bytes enter an envelope body). Tail-window state machine: tail-window bytes that match any reserved-literal prefix **MUST** be delayed until the next chunk confirms they cannot form a complete reserved literal; only after they are confirmed safe **MAY** they be flushed.
>
> **Replacement is a lossy operation** - Visually equivalent replacement is performed by the kernel by default. Bytes embedded in the model-visible projection might no longer round-trip to the original bytes (if reconstruction of the original text is required, the program side needs to save it externally); the kernel provides no reverse mapping. A distribution **MAY** provide a strict mode that turns escaping into a direct `E_EMIT_ESCAPE_VIOLATION` error to avoid lossy rewriting.

`envelope.emit` does not support a token-id stream form for the body; token-id-level injection belongs only to A4 `tokens.inject` and is constrained by the reserved-token injection boundary in §13.4. If a distribution extends token-id bodies, it **MUST** separately register signature, size, escaping, chunk observation, backpressure, and error codes; the body of this specification does not define that path.

> **Escaped context bytes**: rollback pattern matching operates on the **bytes actually injected into context** (that is, content after escaping), **not** the original bytes before injection. This means that if a segment is visually-equivalent replaced during injection, the pattern **MUST** match the replacement character. Example: if a program writes raw text `<lmsc_output>` through `envelope.emit`, the default mapping injects `‹lmsc_output>` into context; a later rollback targeting that segment must use the pattern `‹lmsc_output>`, not `<lmsc_output>`. This applies to both the model path and the program path (A3).

13.3 Rollback Boundaries

The pattern-matching search window for A3 and the model path `<lmsc_rollback>` **MUST NOT** cross:

> **Rollback operates on post-edit context**: rollback pattern search and truncation both operate on the **post-edit context**; that is, after any modifications made by `region.edit` have already been reflected in context, rollback is performed against that context. If rollback and `region.edit` happen sequentially in the same dispatch cycle, rollback sees the context after the edit is complete.

- Closed envelopes (excluding the unclosed body of the current open envelope);
- **The open token of the current unclosed envelope** - that is, if `<lmsc_rollback>` itself is opened inside some envelope body, matching search **MUST NOT** cross that envelope's open token; escaping into the outer context is out of bounds. If there is currently no unclosed envelope (`GENERATING`), this item does not impose an envelope-open boundary, and other boundaries such as the current turn's IDLE start apply instead;
- Boot output (equivalent to an `attention=pin` region);
- **The boundary of any active `attention=pin` region** - including pins created by programs through `region.tag(attention=pin,...)`, and the `<lmsc_output>` pin output injected by `runtimeadminpersona-refresh` until it is superseded; all active pin regions are hard boundaries for rollback. Search from outside stops when it reaches the start of an active pin region and **MUST NOT** enter the pin region for matching; bytes inside a pin do not participate in external rollback pattern matching. Persona-refresh pins superseded by the §12.3.1 lifecycle policy remain as historical context, but no longer act as active pins or rollback hard boundaries.
- **The current turn's user /external input injection interval** - the kernel **MUST** treat these intervals as kernel-owned input regions; rollback **MUST NOT** cross them and **MUST NOT** search into them from outside for matching. **Visibility rule**: input regions are hidden boundaries by default, do not expose ordinary editable `RegionIds`, and are not affected by `region.edit` /`region.compact`. If a distribution chooses to expose metadata through runtime query, it **MUST** only return a restricted view that is locked, kernel-owned, and non-editable (such as range and turn_id), and **MUST NOT** allow programs to bypass input boundaries through that view.
- Persisted side effects (`rollback_safe:false` dispatch boundaries); **implementation requirement**: the kernel uses the `<lmsc_execute>` open token as the barrier start; at dispatch entry, according to manifest `rollback_safe:false`, it marks `rollback_barrier=true` in that envelope's metadata; pattern search stops when it reaches the execute envelope open token with that mark.
- The current turn's IDLE start (cross-turn rollback is always outside the rollback search scope regardless of `scope`);
- The parent session's context (the `session.fork` fork point is an implicit boundary for the child session).

Input region creation rules (normative) - The kernel **MUST** create an input region interval for the current turn only via the following paths, and **MUST** include such intervals in the rollback hard boundaries and input-region visibility rules above:

1. The host injecting a user message into the current turn on the user's behalf (including the first message at turn start and additional user messages within the same turn);
2. The C2 `resume` external-event payload entering the token sequence of the current turn (this is the C2 atomic restoration path, **not** treated as program-state A4 injection);
3. ”External input bridge” paths **explicitly declared** by the distribution in boot output or runtime info (such as IDE host, tool host, external sensors, upstream agent transcription); each such path **MUST** be distinguished in audit by `source=”external_input:<bridge>”`.

The following paths **MUST NOT** create input regions (they are not part of the input-region set): any envelope and body bytes written by a program through `envelope.emit`; all A4 `token_inject` cases (including `BeforeNextSample` /`AtEnvelopeClose`); pin output injected by `runtimeadminpersona-refresh` (which belongs to the persona pin region kind, distinct from input regions); inline replacement bytes from a successful `ref.resolve` expansion; auto execute scaffold injection (§10.1.2); the kernel's own boot output (which belongs to the boot region). Any injection path not in the allowed set above **MUST NOT** be registered as an input region by an implementation; if a distribution wants to include additional paths in the input region set, it **MUST** explicitly declare them in boot output or runtime info under item 3 (”external input bridge”); otherwise the distribution is considered to deviate from this specification.

If multiple permitted input injections occur within the same turn, the kernel **MUST** create a region per segment and record them as an **ordered set of intervals** in occurrence order; each remains an independent rollback hard boundary, and they **MUST NOT** be merged into a single contiguous interval or crossed by later injections. Each input region's audit /runtime-query view **SHOULD** carry at least the fields `kind=”input”`, `turn_id`, `range`, and `source` (a user message or `external_input:<bridge>`).

Out-of-bound handling (distinguishing control flow from audit outcome) - If any byte of the matched interval `[i, i+len(P))` falls outside a boundary, the kernel **MUST**:

- **Control flow**: behave as if there were no hit - KV remains unchanged; if triggered by the program path A3, the syscall returns `E_ROLLBACK_PATTERN_NOT_FOUND`; if triggered by the model path, no error is returned to any caller (audit only).
- **Audit `outcome` field**: **MUST** write `pattern_out_of_bound` (not `pattern_not_found`), so downstream training /analysis can clearly distinguish it from `pattern_not_found`, where there is truly no match in the whole context (same wording as §5.2 A3 /§4.1.2a).

Redacted field set for `runtime query regions`: if a distribution exposes input /boot /persona pin region metadata, each returned item **MAY** contain at most `{ region_id, kind, range, turn_id, owner=”kernel”, locked=true, editable=false, reason }`. Here `kind` ∈ `{boot, input, persona_refresh_pin, program_region}`; for items where `kind` ∈ `{boot, input, persona_refresh_pin}`, `region_id` **MUST** be used only for query and display, and **MUST NOT** be accepted by `region.edit`, `region.tag`, or any program-state mutation syscall. A distribution **MUST NOT** return fields from which the original user input content can be inferred.

Region registry cleanup after successful rollback: after a legal rollback completes physical or equivalent truncation, the kernel **MUST** synchronously clean up the region registry. Regions whose ranges remain completely before the new KV tail are preserved. If the range of any ordinary `program_region` intersects the discarded suffix (partially or fully), that region **MUST** become invalid as a whole; subsequent access returns `E_REGION_NOT_FOUND`, and the same rollback audit details record the number of invalidated regions (for example `regions_invalidated`) or emit an equivalent region cleanup audit. The kernel **MUST NOT** keep dangling `RegionIds` that point to tokens that no longer exist. Kernel-owned regions such as boot /input /persona pins normally cannot be truncated by external rollback because they are hard boundaries; if an internal implementation path finds such a region intersecting the discarded suffix, it **MUST** use a closed failure path such as abort /rollback_error, and **MUST NOT** silently clip it.

Search window upper bound: actual search window = structural boundary crop (the boundary items above) ∩ independent search upper bound `ROLLBACK_SEARCH_MAX_BYTES`. If `ROLLBACK_SEARCH_MAX_BYTES` is non-null, when the kernel searches backward from the rollback point, the search range **MUST NOT** exceed that many bytes (prefer the smaller of the structural boundary and this upper bound). If the nearest match exists but falls outside that independent lookback window, audit `outcome` **MUST** be `pattern_out_of_bound`, with `effective_bound=”search_max_bytes”`; it **MUST NOT** be classified as a true miss `pattern_not_found`. This field is declared in Appendix E boot output as `limits.rollback_search_max_bytes`.

Constraints when `ROLLBACK_SEARCH_MAX_BYTES=null`: when a distribution chooses not to set an independent lookback byte limit, the kernel **MUST** satisfy all three of the following clauses to compensate for the missing independent resource bound:

1. **Structural boundaries still apply** - `null` only removes the independent lookback upper bound; it does not relax the structural boundaries above (closed envelopes, open tokens, boot /pin /input regions, `rollback_safe=false` barriers, the IDLE start of the turn, parent-session boundaries).
2. **Algorithmic-complexity commitment** - the actual search of rollback pattern matching **MUST** be linear in the relative window byte count, i.e. `O(window_bytes+len(pattern))` (typical implementations: a single backward sweep + KMP /Aho-Corasick style linear matching, or byte-level reverse-suffix search). Worst-case `O(window_bytes·len(pattern))` or higher-complexity implementations are **forbidden**.
3. **Runtime observability** - when `ROLLBACK_SEARCH_MAX_BYTES=null`, the audit details of each rollback computation **MUST** additionally expose `effective_search_window_bytes` (the upper bound of bytes actually traversed for that match); `runtimeinfo.stats` (if provided) **SHOULD** expose `rollback_search_max_bytes_effective` (the largest window-byte count observed since startup). When `ROLLBACK_SEARCH_MAX_BYTES` is non-null, `effective_search_window_bytes` is a **SHOULD** field. The intent is to let observers monitor whether a distribution lets the search window grow unbounded under long turns /large contexts.

A distribution **MAY** set `ROLLBACK_SEARCH_MAX_BYTES` to a finite value (covering at least ~256 KiB is recommended) or **MAY** leave it `null`; when `null` is chosen, all three clauses above **MUST** hold. Neither setting is permitted to silently best-effort truncate large windows (i.e. give up the search and emit `pattern_not_found` upon encountering a large window).

Model-path default scope inference (**reference** to the §4.1.2a source of truth; this section **MUST NOT** conflict with it):

- If, before the `<lmsc_rollback>` open, the envelope stack contains at least one **non-rollback** envelope frame: `scope=Envelope`;
- Otherwise (the stack contains no non-rollback envelope): `scope=Turn`.

The rollback envelope itself **MUST NOT** participate in this inference, even if it is still on top of the stack at the moment `</lmsc_rollback>` close is processed. The inferred result is written into the `search_scope` field in §14.2 rollback audit details; top-level `AuditRecord.scope` continues to represent audit visibility.

Scope requirements for non-model injection paths: rollback initiated by a program (A3 /`token_rollback`) or another non-model path **MUST** pass `scope` explicitly in call arguments; the kernel **MUST NOT** infer a default scope for non-model paths. If the caller does not provide the `scope` argument, the kernel **MUST** reject the call and return `E_PROTOCOL_VIOLATION` or an equivalent binding-layer error, and **MUST NOT** implicitly substitute `scope=Envelope`.

Actual upper bound for Scope=Turn - The farthest actual rollback point for `scope=Turn` is the nearer of the following two rules: if an unclosed envelope exists, the point immediately after the **outermost** unclosed envelope's open token; otherwise the current turn IDLE start.

Search start for Scope=Envelope - The search start for `scope=Envelope` is the point after the open token of the current innermost non-rollback envelope at rollback trigger time (excluding that open token and its attribute header). If rollback is triggered in an ordinary chunk and there is currently no non-rollback envelope, it degrades to the current turn IDLE start; if rollback has just completed truncation and the outer state has been restored by §10.1.1, it uses the nearest envelope /turn start recovered by that algorithm.

Pattern content constraints - The pattern body itself **MUST NOT** contain the literal byte sequence of any reserved token (`I-ROLLBACK-NO-NEST`); length $\leq$ `ROLLBACK_PATTERN_MAX_BYTES` (default 512, Appendix F).

Frequency - Within a single turn, the total number of successful + failed rollback attempts is $\leq$ `ROLLBACK_STORM_LIMIT` (default 16); `persona-refresh` **does not** reset this counter.

> **Storm-limit refusal branch and counter lock** - When the counter has already reached `ROLLBACK_STORM_LIMIT` within a single turn, subsequent `<lmsc_rollback>` /A3 calls:
>
> - Branches rejected with `E_ROLLBACK_STORM` **do not** count toward the counter (it remains equal to the limit, without being unlocked by refusal or triggering a second overflow trigger);
> - The counter is **locked** while `>= ROLLBACK_STORM_LIMIT` until the current turn ends (`IDLE`); `persona-refresh` still does not reset it;
> - In locked state, `rollback_error` audit details **MUST** contain `storm_locked=true`, so downstream consumers can observe that the session has entered locked state.

`runtime stats` **MUST** expose the current-turn rollback storm snapshot: `rollback.current_turn_count`, `rollback.remaining`, and `rollback.storm_locked`. These fields reflect only the current turn's runtime state and do not enter the boot output schema; SUSPENDED does not reset the counter, so `remaining` and `storm_locked` keep continuous semantics across suspend/resume.

> **Strict mode against rollback failure flooding**: a distribution **MAY** declare strict mode in boot output (`features.rollback_strict_mode=true`). In this mode, when the count of rollback failure audit events within a single turn (`rollback_error`, plus `rollback` with `outcome` ∈ {`pattern_not_found`, `pattern_out_of_bound`}, plus `E_ROLLBACK_STORM` refusal paths) exceeds the distribution-configured threshold (`limits.rollback_failure_audit_limit`, **SHOULD** be provided), the kernel **MUST NOT** silently drop critical audit; subsequent failures of the same class **MUST** be merged into compressed `rollback_failure_summary` audit. The summary records at least `suppressed_count`, `first_seq`, `last_seq`, `outcomes`, and `error_codes` sets, and is flushed at turn end or when the failure type changes. Non-strict mode does not perform this compression.

13.4 Inject Boundaries

A4 **MUST NOT**:

- Inject an envelope close token outside an envelope;
- Inject an envelope open token outside an envelope (same prohibition as close tokens, to prevent programs from constructing dangling opens outside an envelope);
- Inject a reserved token without holding `tokens.inject.special` (fixed-only);
- Exceed `INJECT_MAX_TOKENS` (default 4096).

13.5 Preempt Constraints

- Frequency: ≥ `PREEMPT_COOLDOWN` (default 30s); cooldown key = `(session_id,program)`, and kernel-internal preempt uses a separate independent key;
- Depth: preempt **MUST NOT** occur again **inside** an envelope produced by preempt;
- Audit: contains `reason` and `preempted_envelope_id` (details for the `preempt` audit **MUST** contain the interrupted envelope id).

13.6 Region Operations

- **Region overlap rule**: a region range is represented as a half-open token index interval `[start_token, end_token)` over the current context token sequence. The `range` of `region.tag` **MUST NOT** have a non-empty intersection with the range of any existing region, and **MUST NOT** form a containment relationship; adjacent boundaries (such as `end==other.start`) are legal. Violations return `E_REGION_RANGE_INVALID`. This non-overlap rule reduces implementation complexity and avoids ambiguity in pin/locked rules over overlapping ranges.
- `region.compact` is by default granted only to the specific program responsible for compaction (recommended: `summarizer`);
- `region.edit` with `persist=false` requires the additional `region.drop.hard` cap (fixed-only);
- Regions with `attention=pin` **MUST NOT** be edited;
- Every edit **MUST** write audit containing the original hash, new hash, and caller program name.

13.7 Audit Cannot Be Bypassed

- Programs **MUST NOT** suppress key events automatically emitted by the kernel;
- When a program calls `audit.emit`, the kernel automatically stamps `source=program:<name>`, and this **MUST NOT** be forged;
- Audit sink write failure **MUST NOT** affect the original operation's return value (unless strict mode is configured).

13.8 Sandbox Hard Constraints (If H3 Is Provided)

`exec.sandbox` **MUST** enforce:

- CPU /wall /memory limits;
- Network disabled by default;
- fs disabled by default (except `/tmp`);
- stdout /stderr returned through syscall, and **MUST NOT** be written to disk.

13.9 Fork Safety

- After `session.fork`, refcounts for blobs are correctly incremented for the original session and the new session (rules are in §9.4.2);
- CoW KV cache **MUST NOT** be released before both sides drop it;
- `restore` **MUST NOT** switch an in-progress dispatch to a different session (`E_FORK_INVALID`);
- The fork point is written to audit (`kind=fork`);
- The **dispatcher frame stack** is cloned with context CoW, and a pop in the child session only affects its own stack copy;
- Process-global variables, heap objects, connection pools, and other external mutable state inside native /host handlers are not part of the fork snapshot; if such state affects session-observable behavior, the handler must isolate it by `session_id` /fork branch or move it into kernel-managed state;
- Boot output retains pin semantics in the child session and is not emitted again.

13.10 Program Isolation

- kv namespaces of different programs are physically isolated; blobs do not belong to the program kv namespace isolation semantics. `blob.get` /`incref` /`decref` all **do not require caps**, but the `BlobId` security model is defined by §5.7 F2: by default it is an opaque bearer handle, and disclosure is authorization. If a distribution declares `features.blob_id_mode="content_hash"`, that mode **MUST NOT** be used for sensitive or low-entropy content unless per-session /per-program ACLs are also enabled. Secrecy for sensitive or low-entropy blobs **MUST** be provided by unguessable opaque IDs or ACLs; actual operations still apply only to the refcount held by the calling session;

  > **Privacy warning for `content_hash` mode and ref inlining (normative)** - when `features.blob_id_mode="content_hash"`, any path that exposes a `BlobId` to model-visible context - including post `ref.resolve` inline expansion that lets the model see the original blob reference, writing `BlobId` into envelope body, the `archived_blob_id` after persist edit, etc. - **MAY** allow the model to confirm low-entropy content (sensitive fields, short tokens, enumerable identifiers, boolean facts) via the hash value. The distribution **MUST** switch to `blob_id_mode="opaque"` or enable per-session ACLs in any of the following scenarios: (a) the referenced content originates from an external untrusted source; (b) the referenced content is low-entropy or enumerable; (c) `BlobId` literals MAY appear in model-visible context. This rule introduces no new cap, but the distribution **MUST** reflect it in its security self-assessment document.

- The kernel maintains per-session refcounts; `blob.decref` **MUST** affect only the refcount owned by the caller's session (§9.4.2 set), and has no side effects on refcounts in other sessions; this prevents `decref` from being abused to break references held by other sessions;
- `ref_kind` is globally unique;
- Programs **MUST NOT** read another program's audit;
- Programs **MUST NOT** modify another program's manifest.

13.11 Stack Depth

- Envelope nesting stack $\leq$ `MAX_ENVELOPE_NEST` (default 4; note: the open->close of a rollback envelope temporarily occupies the stack and counts toward current depth; after `</lmsc_rollback>` is observed, the whole pair is removed and leaves no nesting residue);
- Dispatcher frame stack $\leq$ `MAX_DISPATCHER_DEPTH` (default 8);
- Suspend nesting $\leq$ `MAX_SUSPEND_NEST` (default 4).

Over limit **MUST** be rejected; if the subsystem has defined a dedicated error code, return the dedicated error code, otherwise return `E_STACK_OVERFLOW`.

Rollback temporary stack occupancy and envelope depth limit - (1) When depth has already reached the limit, `<lmsc_rollback>` open **MUST** be blocked by logit mask (L0 /L1) or post-hoc abort (L2); (2) if truncation actually reduces the envelope stack, the depth quota is released accordingly.

---

14. Audit Log

14.1 Record Structure

```
AuditRecord := {
 seq: u64 # Monotonically increasing (per-session)
 ts: Timestamp
 session_id: string
 turn_id: u64
 kind: string
 source: string # "kernel" | "program:<name>"
 scope: string # "model-visible" | "system-only"
 program: Option<string>
 envelope_id: Option<string>
 capability: Option<string>
 details: Map<string, any>
 hash_prev: bytes? # tamper-evident, optional; algorithm see below when enabled
 signature: bytes? # tamper-evident, optional; algorithm see below when enabled
}
```

Audit hash-chain algorithm (normative) - when a distribution enables the tamper-evident chain, `hash_prev` **MUST** be derived from the canonical-serialized bytes of the previous record after hashing; the default hash algorithm is **SHA-256**; the chaining formula is `record.hash = SHA-256( record.hash_prev || canonical_bytes(record_without_hash_signature) )`, where `||` denotes byte concatenation and `canonical_bytes` follows the canonical YAML /JSON serialization of the §14.3 export schema (field names sorted ASCII ascending, UTF-8 NFC, decimal integers, lowercase booleans). For every record, `hash_prev` **MUST** equal the previous record's `record.hash` produced by this formula; the first record's `hash_prev` **SHOULD** be either an all-zero byte sequence or the SHA-256 32-byte digest of `session_id` (the distribution declares its choice in `runtimeinfo.audit_hash_init`). The default `signature` algorithm is **Ed25519**; if a distribution chooses another algorithm (e.g. ECDSA-P256-SHA256), it **MUST** declare so in §14.3 export and `runtimeinfo.features.audit_signature_alg`. Any distribution that declares tamper-evident enabled **MUST** expose `hash_algorithm` and `signature_algorithm` fields in the export schema (Appendix H) so cross-implementation verification is possible.

`seq` and `turn_id` semantics - `seq` is **per-session independently monotonically increasing**, with `session_id` as the ownership field; a forked child session continues from the fork point seq (it does not restart from 0). `turn_id` is **per-session independently monotonically increasing**: it increments by 1 each time the session leaves IDLE; fork inherits the parent's current value; restore does not change turn_id.

`source` field attribution rule (normative) - `source` is constrained to a **closed enumeration**: only `"kernel"` and `"program:<name>"` are allowed; distributions **MUST NOT** introduce extra values such as `"model"` /`"user"` /`"host"`. Audit records the kernel automatically emits while processing model-generated content (including rollback computation, abort injection, scaffold injection, `protocol_violation` detection, `I-EMIT-ESCAPE` triggers, ref-resolve-failure envelope injection, etc.) **MUST** use `source="kernel"`. Finer-grained attribution related to model behaviour (e.g. whether a rollback was issued by the model itself or by a program) **MUST** be expressed via dedicated fields in `details` (typically `rollback_origin ∈ {"model","program:<name>","kernel"}`, `envelope_from`, `open_source`, etc.) and **MUST NOT** be carried by mutating the `source` field. `source="program:<name>"` is only used when the event is triggered directly by that program through a user-mode syscall (including `audit.emit`). Events triggered by the host /runtime are attributed to `source="kernel"`.

14.2 Events Automatically Emitted by the Kernel

kind	Trigger	details
`boot`	Session start	protocol.revision, features
`dispatch`	B2	program, argv, status, **`envelope_from`**
`cap_grant`	D2	cap, source, ttl
`cap_revoke`	D3	cap_id, reason
`program_register`	E	name, version
`program_unregister`	E	name
`program_register_failed`	E /`on_load` returned error	name, error_code, reason (error summary)

kind	Trigger	details
preempt	C4	program, reason ∈ {"user_interrupt","priority_alert","resource_limit","watchdog","x- **envelope_from**, cooldown_ms?; after a successful preempt, when the kernel injects an envelope it **MUST** additionally emit one envelope_open (open_source="kernel:preempt"); the order is preempt first then envelope_open
rollback	A3 /</lmsc_rollback> close	outcome∈{truncated,pattern_not_found,pattern_out_of_bound}, search_scope, pattern_bytes_len, truncated_tokens (when outcome=truncated), regions_invalidated (when successful truncation triggers region cleanup), effective_bound ∈ {turn_start, nearest_open_envelope, boot_output, rollback_safe_false, fork_point, pin_region, user_input_region, search_max_bytes}, rollback_origin∈{"model","program:<name>"}; **MUST NOT** use envelope_from
rollback_error	A3 syscall returned error (program path); or the model path recognizes a violation at </lmsc_rollback> close (pattern is empty /too long /contains a reserved token) - the model path **does not** return an error to any caller and only emits this audit	error_code, search_scope, pattern_bytes_len (the original pattern text **does not enter audit**, to avoid writing sensitive strings to disk), storm_locked?
rollback_failure_summary	Strict-mode compressed rollback failure audit	suppressed_count, first_seq, last_seq, outcomes, error_codes
abort	C3	envelope_id, reason, **envelope_from**
region_edit	F4	region_id, hash_before, hash_after, persist, archived_blob_id?
suspend	C1	resume_on, suspend_handle_id
resume	C2	handle
fork	A5	new_session_id
cap_denied	Authorization failure at syscall entry or resource access	cap, program, context
protocol_violation	Token stream hook detected a protocol violation (L2 is the primary source)	invariant, token_position, violation_detail
raw_text_outside_envelope	Strict protocol mode with features.raw_text_outside_envelope="audit-only" (§10.1.2): a contiguous span of raw text observed at envelope stack depth = 0 (not a violation; audit only)	bytes_observed:u64, token_count:u32, turn_id, span_start_token_index, span_end_token_index; **MUST NOT** include body plaintext. Default scope=system-only; distributions **MAY** explicitly downgrade to model-visible
persona_refresh	runtimeadminpersona-refresh (§12.3.1)	diff_blob_id, boot_refresh_reason, persona_region_id, active_persona_pin_count, active_persona_pin_tokens, superseded_persona_region_ids?
envelope_emit	B3 envelope.emit returned successfully	kind, attrs_keys, body_bytes_len, stream (bool), chunk_observed?
envelope_open	Envelope open event (only the scaffold injection path **MUST** emit; a model-spontaneous open **MAY** omit this audit, at distribution discretion)	envelope_kind∈{execute,output,edit,rollback}, envelope_id:string, envelope_from∈{"model","program:<name>"}, open_source∈{"model","kernel:scaffold"}; if top-level AuditRecord.envelope_id is present, details.envelope_id **MUST** equal it; on the scaffold path open_source="kernel:scaffold" and envelope_from="model" **MUST** be present (§10.1.2 /§16.1 C-N4); on a non-scaffold path open_source **MAY** be omitted or set to "model". Default scope=system-only

14.2.1 Distribution Extensions and Model-Visible Projection

- A distribution **MAY** extend with custom audit kinds; to avoid conflicts with future official kinds, custom kinds **MUST** use the x-<vendor>-<name> prefix; bare identifiers are reserved for future official versions.
- The **model-visible projection** of runtime audit * is limited to the kinds enumerated in the table above; custom kinds default to scope=system-only unless the distribution explicitly marks them otherwise.
- **LoRA training pipeline and raw audit** - LoRA /RLHF training pipelines **MUST** read the raw audit stream (including scope=system-only), and **MUST NOT** rely only on the model-visible projection of runtime audit tail; the

model-visible projection is a redacted view for the inference path and does not satisfy training-time consistency needs.

- `kind=persona_refresh` and `kind=cap_grant` are **independent schemas**; their `details` fields are independently defined and are not required to be isomorphic.
- **Default scope for `envelope_emit`** - In the table above, `envelope_emit` audit defaults to `scope=system-only`, to avoid creating self-loop noise in the model-visible projection every time a program calls `envelope.emit`; a distribution **MAY** explicitly downgrade it to `model-visible` as an observability feature. Its `details` **MUST NOT** contain body plaintext, only `body_bytes_len` and whether it is streaming (`stream:bool`); `attrs_keys` is a deduplicated list of attribute keys. If an implementation has triggered `on_envelope_chunk`, details **MAY** set `chunk_observed=true`; this field **MUST NOT** contain chunk contents and **MUST NOT** implicitly expose observer lists. If cross-program observers later enter the specification, the scope and redaction rules for `observed_by` **MUST** be defined separately.

14.2.2 Mutual-Exclusion Semantics of `rollback` and `rollback_error`

For the same rollback event (one model-path `</lmsc_rollback>` close or one program-path A3 call), the kernel **MUST** emit only **one** audit record representing that event, choosing one of three:

- `rollback`: pattern successfully matches (`outcome=truncated`) or legally misses (`outcome ∈ {pattern_not_found, pattern_out_of_bound}`) - that is, it semantically completed the normal adjudication flow of §4.1.2a /§5.2 A3;
- `rollback_error`: a protocol-level invariant violation occurred - specifically: (1) `pattern` is empty, (2) `pattern` byte length exceeds `ROLLBACK_PATTERN_MAX_BYTES`, (3) the `pattern` byte sequence contains a reserved-token literal (`I-ROLLBACK-NO-NEST` triggered), or (4) the single-turn rollback counter has reached the `ROLLBACK_STORM_LIMIT` upper bound; the kernel **MUST** include `error_code` in details and **MUST NOT** emit `rollback` at the same time. Note: an out-of-bound hidden match (a match exists but its first byte falls outside `I-ROLLBACK-BOUND`) **does not** trigger `rollback_error`; it uses normal `rollback` audit with `outcome=pattern_out_of_bound`.
- `rollback_failure_summary`: used only after strict-mode compression in §13.3 takes effect, representing multiple rollback failure events in one continuous failure range. Events covered by the summary **MUST NOT** each emit their own `rollback` /`rollback_error`, but they also **MUST NOT** be silently lost; the summary **MUST** provide counts and ranges so audit consumers can reconstruct the failure count.

Implementations **MUST NOT** concurrently emit two records for the same event; if an internal decision chain identifies an invariant violation first, `rollback_error` takes effect and short-circuits `rollback`; and vice versa. This mutual exclusion is the basis for `ROLLBACK_STORM_LIMIT` (§13.3) counting "successful + failed total attempts" - each event contributes exactly one count.

The search-range field in `rollback` /`rollback_error` details **MUST** be named `search_scope`. Top-level `AuditRecord.scope` only represents visibility (such as `system-only` /`model-visible`) and **MUST NOT** be used as the rollback search range; the legacy draft field `details.scope` may be accepted only as an input-compatibility alias, and conforming implementations **MUST NOT** continue emitting it in new audit records.

14.3 Persistence

Append-only; not inserted into context; sink configured by the kernel (memory /disk /remote); `runtime audit export` requires `audit.export`.

The raw export of `runtimeauditexport-\/-to-blob` **MUST** use the `AuditExport` schema; canonical file name is `lmsc-audit-export-schema.yaml` (or equivalent JSON representation). Minimum shape:

```yaml
schema: lmsc-audit-export
revision: "1.0"
session_id: string
export_id: string
generated_at: Timestamp
range:
  seq_start: u64
  seq_end: u64
page:
  cursor: string?
  has_more: bool
projection: raw # raw | model-visible
redaction_policy: string
records: [] # AuditRecord[]; raw export MAY contain scope=system-only
hash_chain:
  first_hash_prev: bytes?
  last_hash: bytes?
signature: bytes?
```

Differences between raw export and model-visible projection **MUST** be explicitly registered: raw export **MAY** contain `scope=system-only` and full details; model-visible projection **MUST** contain only the redacted fields allowed by §14.4. Training pipelines reading raw export **MUST NOT** substitute model-visible projection.

Rollback audit mutual-exclusion test matrix:

Case	Unique audit kind	Counter effect
Hit and truncation succeeds	`rollback(outcome=truncated)`	+1
Legal pattern miss	`rollback(outcome=pattern_not_found)`	+1
Match exists but is out of bounds	`rollback(outcome=pattern_out_of_bound)`	+1
Pattern is empty	`rollback_error(error_code=E_ROLLBACK_PATTERN_EMPTY)`	+1
Pattern too long	`rollback_error(error_code=E_ROLLBACK_PATTERN_TOO_LONG)`	+1
Pattern contains reserved token	`rollback_error(error_code=E_ROLLBACK_PATTERN_INVALID)`	+1
Storm limit already locked	`rollback_error(error_code=E_ROLLBACK_STORM)` or strict-mode summary	Does not increase further; remains locked

14.4 Projection to the Model

`runtime audit tail` /`search` return a **projection** - the kernel **MUST** return only `scope=model-visible` and redact host privacy.

---

15. Error Code Registry

15.1 Naming Rules

`E_<CATEGORY>_<REASON>`.

Prefix	Category
`E_TOKEN_` /`E_MASK_` /`E_ROLLBACK_` /`E_INJECT_` /`E_FORK_`	A
`E_ENVELOPE_` /`E_ENV_` /`E_DISPATCH_` /`E_UNKNOWN_` /`E_HANDLER_` /`E_EMIT_`	B (`E_ENV_`, `E_UNKNOWN_`, and `E_HANDLER_` are legal variant prefixes of class B for `E_ENV_KIND_FORBIDDEN`, `E_UNKNOWN_PROGRAM`, and `E_HANDLER_PANIC`, respectively; class B error codes **SHOULD** prefer `E_ENVELOPE_` /`E_DISPATCH_` /`E_EMIT_`)
`E_SUSPEND_` /`E_ABORT_` /`E_PREEMPT_` /`E_FRAME_`	C
`E_CAP_`	D
`E_PROG_`	E
`E_KV_` /`E_BLOB_` /`E_REF_` /`E_REGION_`	F
`E_AUDIT_`	G
`E_FS_` /`E_NET_` /`E_EXEC_`	H
`E_CLOCK_`	I
`E_STACK_` /`E_KERNEL_`	Cross-class /internal
`E_ATOMIC_`	An exempted atomic operation was called (A5 under L1/L2 and so on, §16.1 C-1). Currently only `E_ATOMIC_UNSUPPORTED`; ownership is **cross-class**
`E_BOOT_`	boot /runtime admin persona-refresh limits
`E_PROTOCOL_`	Protocol invariant violations triggered by the model /program

15.2 Error Codes That MUST Be Defined (Minimum Enumeration)

This section lists the **minimum error-code enumeration** that conforming implementations **MUST** support. A distribution **MUST** also publish a machine-readable error-code property registry together with the syscall schema, with canonical file name `lmsc-error-code-registry.yaml` (or equivalent JSON representation). This registry **MUST** cover every code listed in this section and contain at least the following columns: `code`, `category`, `origin` ∈ {`model`, `program`, `kernel`, `context-dependent`}, `retryable`, and `notes`. If an implementation extends with new error codes, it **MUST** complete these columns in the same registry; missing any minimum code or property column is non-conforming.

Minimum shape:

```yaml
schema: lmsc-error-code-registry
revision: "1.0"
errors:
  - code: E_ROLLBACK_PATTERN_NOT_FOUND
    category: A
    origin: model
    retryable: false
    notes: details.outcome distinguishes pattern_not_found from pattern_out_of_bound.
```

Rollback boundary error expression - Model-path out-of-bounds is expressed by `outcome=pattern_out_of_bound`; the program path has no legal trigger source. A conforming implementation **MUST NOT** produce `E_ROLLBACK_BOUNDARY` on any code path; substitutes are `E_ROLLBACK_PATTERN_NOT_FOUND` or `outcome=pattern_out_of_bound`. See the negative example entry in §16.4.

```
# A
E_TOKEN_BAD_ID
E_MASK_INVALID
E_ROLLBACK_STORM
E_ROLLBACK_PATTERN_EMPTY
E_ROLLBACK_PATTERN_NOT_FOUND # Distinguish not_found vs out_of_bound by outcome
E_ROLLBACK_PATTERN_TOO_LONG
E_ROLLBACK_PATTERN_INVALID
E_INJECT_BAD_TOKEN
E_INJECT_BAD_POSITION
E_INJECT_CAP_DENIED
E_INJECT_TOO_LARGE
E_FORK_INVALID
E_FORK_OOM # CoW KV snapshot allocation~/{}memory baseline failure;
 # Distinguished from `E_FORK_MEM_EXCEEDED` (Appendix F.3 memory limit);
 # Retryable: implementation-defined - retry can succeed after physical memory recovers;
```

```
 # Recommendation: `drop_fork` old branches first, then retry.
E_ATOMIC_UNSUPPORTED

# B
E_DISPATCH_REENTRY
E_DISPATCH_TIMEOUT # dispatch timeout; retryable=impl-defined, default true
E_EMIT_STREAM_OPEN # Triggered when a handler holds an unclosed streaming emit during dispatch~/{}persona-refresh~/{}session.fork;
↪  retryable=false; details contain at least reason="streaming_emit_in_progress" and open_stream_count: u32; include unclosed
↪  envelope_id list when safe to expose
E_UNKNOWN_PROGRAM
E_HANDLER_PANIC
E_EMIT_ESCAPE_VIOLATION # Body or attribute header value contains reserved-token literal; retryable=false (content problem, retry
↪  is ineffective)
E_EMIT_SIZE_LIMIT
E_EMIT_CAP_DENIED
E_EMIT_STREAM_ABORTED
E_EMIT_STREAM_BACKPRESSURE_TIMEOUT
E_ENV_KIND_FORBIDDEN

# C
E_SUSPEND_NESTED_LIMIT
E_SUSPEND_EXPIRED
E_SUSPEND_INVALID
E_ABORT_NOT_OPEN
E_ABORT_CAP_DENIED
E_PREEMPT_COOLDOWN
E_PREEMPT_CAP_DENIED
E_PREEMPT_NESTED
E_FRAME_OVERFLOW
E_FRAME_NOT_OWNED
E_FRAME_UNSUPPORTED_RULE

# D
E_CAP_DENIED
E_CAP_GRANT_DENIED
E_CAP_INVALID_NAME
E_CAP_NOT_FOUND
E_CAP_NOT_REQUESTABLE
E_CAP_WAIT_TIMEOUT # `capability request --wait` timeout

# E
E_PROG_DUP_NAME
E_PROG_UNKNOWN_CAP
E_PROG_REF_KIND_TAKEN
E_PROG_MANIFEST_INVALID
E_PROG_PROTECTED
E_PROG_IN_USE

# F
E_KV_VALUE_TOO_LARGE
E_KV_QUOTA # retryable; SHOULD include current_usage~/{}quota_limit in details
E_KV_KEY_INVALID
E_BLOB_NOT_FOUND
E_BLOB_QUOTA # retryable; SHOULD include current_usage~/{}quota_limit in details
E_REF_KIND_TAKEN
E_REF_NOT_FOUND
E_REF_EXPIRED
E_REF_BODY_INVALID
E_REGION_RANGE_INVALID
E_REGION_NOT_FOUND
E_REGION_LOCKED
E_REGION_DROP_HARD_DENIED

# H
E_FS_CAP_DENIED
E_FS_NOT_FOUND
E_FS_IO
E_FS_QUOTA
E_NET_CAP_DENIED
E_NET_TIMEOUT
E_NET_CONNECT
E_NET_STATUS
E_EXEC_CAP_DENIED
E_EXEC_LIMIT
E_EXEC_INTERNAL
E_EXEC_UNSUPPORTED

# I
E_CLOCK_BAD_DURATION

# Boot
E_BOOT_REFRESH_LIMIT # `runtime admin persona-refresh` exceeds the per-turn limit of ≤ 1

# Cross
E_STACK_OVERFLOW
E_KERNEL_INTERNAL
E_PROTOCOL_VIOLATION
```

```
E_FORK_DEPTH_EXCEEDED # Reused for both depth limit (reason="depth_limit") and concurrency limit (reason="concurrent_limit");
↪  distinguished by audit details.reason
E_FORK_MEM_EXCEEDED
```

15.2.1 Error-Code Attribution (`origin`)

To help RL /observability distinguish fault source, every error code **SHOULD** be labeled with the "initiator" property `origin` ∈ `{model, program, kernel}`:

- `origin=model`: direct result of a model semantic error. Typical: `E_ROLLBACK_PATTERN_*`.
- `origin=program`: program code or calling-style error. Typical: `E_DISPATCH_REENTRY`, `E_ENV_KIND_FORBIDDEN`, `E_FRAME_UNSUPPORTED_RULE`.
- `origin=kernel`: kernel /resource /environment failure. Typical: `E_KERNEL_INTERNAL`, `E_FORK_OOM`, `E_NET_TIMEOUT`.
- `origin=context-dependent`: depends on initiating context and **SHOULD** be further distinguished by audit `source`. Typical: `E_CAP_DENIED` (can be triggered by either program or model path).

This column is a **MUST**; the error-code property registry issued by a conforming kernel distribution **MUST** include the `origin` column for training pipelines to consume.

15.3 Retryable Flag

Every error code **MUST** define whether it is retryable in the distribution error-code property registry. The following are default recommendations for the minimum enumeration; if a distribution overrides them, it **MUST** explain the reason in `notes`:

- retryable: `E_NET_TIMEOUT`, `E_SUSPEND_EXPIRED`, `E_KV_QUOTA`, `E_CAP_WAIT_TIMEOUT`;
- **not** retryable: `E_CAP_DENIED`, `E_UNKNOWN_PROGRAM`, `E_INJECT_BAD_TOKEN`, `E_EXEC_UNSUPPORTED`;
- **not** retryable: `E_ROLLBACK_PATTERN_EMPTY` /`E_ROLLBACK_PATTERN_NOT_FOUND` /`E_ROLLBACK_PATTERN_TOO_LONG` /`E_ROLLBACK_PATTERN_INVALID` - all are model problems, and retry is ineffective;
- **not** retryable: `E_ENV_KIND_FORBIDDEN`, `E_FORK_DEPTH_EXCEEDED` /`E_FORK_MEM_EXCEEDED` (the caller needs to first reduce depth /release forks before requesting again);
- **not** retryable: `E_REF_KIND_TAKEN` /`E_REF_NOT_FOUND` /`E_REF_EXPIRED` /`E_REF_BODY_INVALID` - ref resolution errors are all orchestration or format problems (kind not registered, ref already expired, body microgrammar violation), and retry is meaningless.
- **not** retryable: `E_BOOT_REFRESH_LIMIT` - the quota has already been reached within the current turn, so another trigger needs to wait until the next turn.
- **implementation-defined** (impl-defined): `E_HANDLER_PANIC`. By default it **SHOULD** be treated as not retryable (an isolated panic usually indicates a deterministic bug); an implementation **MAY** mark it retryable in the error-code registry and observe it in `runtimeinfo.features` - under the `max_dispatch_msenforced` path (pure timeout interruption rather than program bug), the retryable attribution of that path and the normal panic path **MUST** be explicitly declared by the implementation in the error-code registry; if necessary, it **MAY** split them into two entries (such as `E_HANDLER_PANIC` + `E_HANDLER_PANIC:dispatch_timeout` variant, distinguished by audit `details.reason`; otherwise the two share the same retryable conclusion).

---

16. Conformance

16.1 MUST

Implementations claiming ”LMSC conforming” **MUST**:

- **C-1** - Implement the §5 atomic primitive subset according to the declared level. Exemption matrix:

Level	**MUST** provide	**MAY** exempt
L0 /Tier-A	24 core + A2 + H3	None
L1 /Tier-B	24 core except **A5**	A5 (`session.fork/restore/drop_fork`, calls return `E_ATOMIC_UNSUPPORTED`); A2 /H3 are level-dependent optional (this level may provide them)
L2 /Tier-C	24 core except **A5**	A5; A1 degraded to stop-sequence; `I-*` invariants are recognized post-hoc (see §6.5.1); A2 /H3 **MAY** be omitted

The `atomics` list for this level **MUST** be accurately reflected in Appendix E boot output. Calling an exempted primitive **MUST return** `E_ATOMIC_UNSUPPORTED`. **`runtimeinfo.kernel.atomics`**: `runtime info` **MUST** additionally expose the `kernel.atomics` field, listing the set of **supported atomic primitives** at the current implementation level (same wording as Appendix E), so programs can check availability at runtime rather than only at boot; conforming programs **SHOULD** query this field before calling optional primitives such as A5.

- **C-2** - Implement the protocol surface according to §4; the tokenizer reserved token set is consistent with §4.1, with total count = **12** + **K** (4 envelope pairs, 2 controls, 2 refs, and K keys).
- **C-3** - Integrate the inference stack according to §6 and declare L level (L0 /L1 /L2, L2 minimum). `runtime info` **MUST** also return `kernel.integration_tier` (A/B/C) as an alias.
- **C-4** - Expose syscalls according to §7 and support at least one restricted backend (WASM or Lua).
- **C-5** - Load manifest-format programs according to §8; the action closed set is exactly **7 entries**.
- **C-6** - Ship with **exactly 4** required programs according to §12.
- **C-7** - Enforce all security invariants in §13.
- **C-8** - Write audit logs according to §14.
- **C-9** - Use the error-code namespace according to §15.
- **C-10** - The kernel **directly** emits boot output when INIT -> IDLE, without depending on any program; boot output is automatically marked as an `attention=pin` region.
- **C-11** - L2-level implementations **MUST** implement all **nine** invariants in §6.5.1 as post-hoc detection (the first 8 are the full §4.4 A1 group, plus `I-REF-CHARSET`), and when detecting a violation **MUST** `abort` the current turn and emit audit `kind=protocol_violation`.
- **C-12** - The kernel **MAY** reject `restore` for forks across build ids; if it rejects, it **MUST** return `E_FORK_INVALID` and write audit. **Consistency constraint**: L1 /L2 **SHOULD** reject, L0 **MAY** reject; this item is consistent with the cross-build restore rule in §9.4.3.
- **C-13** - `envelope.emit` receiving `kind=rollback` **MUST** return `E_ENV_KIND_FORBIDDEN`; rollback envelopes **MUST** be produced only by the model path (§4.1.2a) or A3 `token_rollback`.
- **C-14** - After rollback truncation, outer state **MUST** be restored by the deterministic algorithm in §10.1.1; **precondition**: given the same pattern, same KV snapshot, **same tokenizer, and same kernel build**, recovery state **MUST** be consistent across different conforming implementations. This clause makes no commitment about implementation consistency across tokenizers or kernel builds.
- **C-15** - If an L2 implementation's adapter layer provides neither byte-precise nor token-level truncate APIs, it **MUST** follow the §5.2 A3 ”fallback path when L2 KV truncation is completely unsupported”: declare `features.rollback_truncate_precision="none"`, and when observing rollback close execute C3 abort + `kind=protocol_violation` audit (invariant=`I-ROLLBACK-BOUND`, details `truncate_fallback="abort"`). It **MUST NOT** silently ignore it.
- **C-16** - **Program-side `token_rollback` is unreachable in V1**: the `tokens.rollback.explicit` cap is listed as fixed-only in the current specification version and is **not granted to any program** (§5.2 A3 note); the conforming syscall table **MUST** mark that this cap has no legal grant path in V1, to prevent implementations from accidentally allowing it to programs. Any program that claims to hold `tokens.rollback.explicit` through `capabilities.granted` or `capabilities.requestable` **MUST** be rejected by the kernel at cap-check time.
- **C-17** - The sampler /token-stream implementation of `I-CTRL-INSIDE-ENV` **MUST** stay consistent with `I-REF-ANY`: inside a non-rollback envelope body, a complete `<lmsc_ref>...</lmsc_ref>` ref element is legal and does not enter

the envelope stack; inside a rollback envelope body, <lmsc_ref> open /close remains a reserved token and **MUST** be rejected through the I-ROLLBACK-NO-NEST violation path.

- **C-18** - A4 tokens.inject **MUST** reject ordinary syscall calls while SUSPENDED and return E_INJECT_BAD_POSITION; C2 resume payload injection exists only as C2's atomic restoration path. Any injection that would make the envelope stack exceed MAX_ENVELOPE_NEST **MUST** return E_STACK_OVERFLOW.
- **C-19** - When L2 declares features.envelope_emit_stream="buffered" and enables on_envelope_chunk, the normal buffered path **MUST** preallocate the final envelope_id before the first chunk callback and reuse it for final injection and audit; only the reject-before-open path may use envelope_id="pending".
- **C-20** - When features.persona_refresh=true, runtimeinfo.limits **MUST** expose finite persona_refresh_pin_max_active and persona_refresh_pin_max_tokens values; runtimeadminpersona-refresh **MUST** enforce that quota policy and record active pin count, token total, and superseded pins (if any) in audit.
- **C-21** - rollback /rollback_error audit details **MUST** use search_scope for the rollback search range and **MUST NOT** emit details.scope in new audit records; top-level AuditRecord.scope represents audit visibility only. The storm-limit locked path for rollback_error details **MUST** include storm_locked=true.
- **C-22** - Kernel-owned attribute headers, envelope.emit attrs, and region attrs that will be materialized as attribute headers **MUST** enforce the ATTR_VALUE_MAX_BYTES cap; if any attribute value exceeds the cap or contains a reserved-token literal, the relevant syscall /injection path **MUST** return E_EMIT_ESCAPE_VIOLATION or an equivalent binding-layer error and **MUST NOT** silently truncate. gen remains a per-program free string, and the kernel **MUST NOT** compare it across programs.
- **C-23** - features.envelope_chunk_observation="self-output-edit" covers only output/edit chunks produced by the emitting handler itself through envelope.emit(kind=output|edit); kernel-generated system error envelopes (including ref.resolve failure errors) **MUST NOT** trigger that observer.
- **C-24** - An implementation that declares A5 support **MUST** provide session.current_handle(), and it uses the same session.fork cap as session.fork(). current_handle() **MUST NOT** create a fork, allocate a CoW snapshot, change context /KV /audit cursor /dispatcher frame, or count against fork depth /concurrency /memory quotas; the returned handle **MUST** be usable by a later session.restore(handle) to return to the current branch. L1 /L2 implementations **MUST** return E_ATOMIC_UNSUPPORTED for this entry.
- **C-N1** - When features.strict_protocol_mode=true and features.raw_text_outside_envelope="forbidden" (§10.1.2), L0 /L1 implementations **MUST** enforce §4.4 I-STRICT-ENVELOPE-ONLY via logit mask in the sampler hook: at GENERATING with envelope stack depth = 0, all tokens other than <lmsc_execute> /<lmsc_output> /<lmsc_edit> /<lmsc_rollback> /<|lmsc_suspend|> /<lmsc_ref> open /EOS **MUST** be masked out (<lmsc_ref> open is included to stay consistent with I-REF-ANY -- a ref **MAY** appear in any envelope body and in ordinary chunks); L2 implementations follow item 10 of §6.5.1 to detect post-hoc and emit kind=protocol_violation (invariant=I-STRICT-ENVELOPE-ONLY). A successful expansion of a top-level ref must also satisfy the §9.3 strict top-level ref materialization rule. Both levels **MUST NOT** downgrade this constraint to "post-hoc discard" or "single-token truncation".
- **C-N2** - When features.raw_text_outside_envelope="audit-only" (§10.1.2), each contiguous span of raw text observed at envelope stack depth = 0 **MUST** cause the kernel to emit a kind=raw_text_outside_envelope audit (§14.2; schema therein), and the kernel **MUST NOT** return E_PROTOCOL_VIOLATION and **MUST NOT** trigger abort. audit-only and forbidden are mutually exclusive; within the same turn the same span **MUST NOT** simultaneously emit protocol_violation and raw_text_outside_envelope.
- **C-N3** - When features.auto_execute_scaffold=true (§10.1.2), the kernel-owned attribute header that immediately follows the kernel-injected <lmsc_execute> open **MUST** contain id and from="model", and **MUST NOT** contain a program field; the dispatch target **MUST** still be parsed from the first word of the body after </lmsc_execute> close. Any implementation that pre-fills program into the scaffold attribute header and skips body-first-word routing on that basis is **non-conforming**.
- **C-N4** - Scaffold injection **MUST** occur only at GENERATING with envelope stack depth = 0; in any other state (IN_ENVELOPE, DISPATCHING, SUSPENDED, INIT, or IDLE before it has been left) the scaffold **MUST NOT** be triggered. The scaffold injection path **MUST** emit a kind=envelope_open audit with details.open_source="kernel:scaffold" and details.envelope_from="model"; this path **MUST NOT** be charged against INJECT_MAX_TOKENS, and sharing the same counter with the program-side A4 token_inject is **non-conforming**.
- **C-N5** - Under strict + raw_text_outside_envelope="forbidden", a successful expansion of <lmsc_ref> at envelope stack depth 0 **MUST NOT** write ordinary inline bytes returned by the resolver directly into context outside an envelope. The kernel **MUST** materialize the content as a complete system envelope /equivalent envelope-safe structure per §9.3, or reject the expansion and emit protocol_violation (invariant="I-STRICT-ENVELOPE-ONLY", context="ref_expand_strict_top_level").
- **C-N6** - For any non-rollback envelope, the open token and the kernel-owned attribute header that immediately follows **MUST** be written as an indivisible unit (the §4.2 attribute-header injection atomicity general rule): this covers all

paths - model-spontaneous open + default attribute header, `envelope.emit`, boot output, persona-refresh, auto execute scaffold, and canonicalization of open-tag-form input. Any C1 /C3 /C4 control event arriving during the write **MUST** be queued and handled only after the attribute header completes. The kernel **MUST NOT** allow an observable intermediate state where "the open is written but the attribute header is incomplete". If the write is abandoned, cancellation **MUST** happen **before** the open token is written and the kernel **MUST NOT** emit a `kind=envelope_open` audit.

- **C-N7** - When a rollback envelope reaches `ROLLBACK_PATTERN_MAX_BYTES` under L0 /L1, the kernel **MUST** prefer to force-emit `</lmsc_rollback>` (forced close); only when the forced close would simultaneously violate other invariants such as `I-ROLLBACK-NO-NEST` /`I-ROLLBACK-NO-ATTR` may it downgrade to `<|lmsc_abort|>` (§4.1.2a). On the forced-close path, the `kind=rollback` audit details **MUST** contain `forced_close=true` and `effective_bound="pattern_max_bytes"`, and the resulting rollback envelope body **MUST NOT** exceed the upper bound. On the abort-fallback path, both `kind=rollback` (with `forced_close=true`, `forced_close_outcome="abort_fallback"`) and `kind=protocol_violation` (`invariant=I-ROLLBACK-BOUND`) **MUST** be emitted. Implementations **MUST NOT** handle the upper bound by silent truncation or by arbitrarily switching between the two paths.
- **C-N8** - When A4 `token_inject` injects into a **non-rollback** envelope body, the kernel **MUST** validate at the syscall entry that the injected token sequence satisfies `I-CTRL-INSIDE-ENV` (§4.4): only `<|lmsc_abort|>`/`<|lmsc_suspend|>`/a complete ref element /a nested `<lmsc_rollback>` open are permitted; open /close tokens of any other envelope **MUST NOT** be injected, even if the caller holds the `tokens.inject.special` cap. Violation **MUST** return `E_INJECT_BAD_TOKEN` (details `reason="ctrl_inside_env_violation"`) and emit `kind=protocol_violation` (`invariant=I-CTRL-INSIDE-ENV`).
- **C-N9** - The dispatcher-frame base set (§5.4) **MUST** be computed by the following filters: (1) `program.register` complete and `on_load` succeeded; (2) caller manifest /capabilities allow it; (3) the program's own manifest visibility allows the call source; (4) the §12 required-program routes are unconditionally reachable and **MUST NOT** be removed; (5) the distribution's dispatch policy does not deny it. `program_whitelist` on the frame stack can only **tighten** the set, not **widen** the base set; when the model-visible view of `program.list` temporarily disagrees with the base set (e.g. during `on_load`), dispatch authorization is decided by the base set.
- **C-N10** - Input regions for the current turn **MUST** be created only via the paths listed in §13.3 (host-injected user message, the C2 `resume` external-event payload, and "external input bridge" paths explicitly declared by the distribution); the audit `source` field **MUST** match `external_input:<bridge>` or otherwise indicate the user-message origin. Paths such as `envelope.emit`, A4 `token_inject`, persona-refresh pin, `ref.resolve` expansion, scaffold injection, and boot output **MUST NOT** be registered as input regions by an implementation. Multiple input injections in the same turn **MUST** be recorded as an ordered set of intervals and **MUST NOT** be merged into a single contiguous interval.
- **C-N11** - Between `program.register` and the successful return of `on_load`, the program is in `status=loading` (§8.2). The kernel **MUST** return `E_PROG_NOT_FOUND` (preferably with `details.reason="loading"`) for any external B2 dispatch /syscall routing /scaffold path; the model-visible view of `program.list` **MUST** by default hide loading programs or mark them with `status="loading"`, while only `program.admin` callers and the program itself can observe its loading state during `on_load`. If `on_load` fails, the kernel **MUST** roll back the program-registry entry and namespace metadata and record the failure under existing audit rules.
- **C-N12** - Any program call that uses `envelope_id="pending"` to reach an envelope-state syscall (continued `envelope.emit`, `envelope.close`, `region.*` queries /writes, `audit.emit`, `tokens.inject` with `AtEnvelopeClose`, etc.) - whether on the `on_envelope_chunk` reject path or inside `on_abort` - **MUST** be rejected by the kernel with `E_ABORT_NOT_OPEN` (preferably `details.reason="pending_not_open"`) and **SHOULD** emit `kind=protocol_violation` (§6.5.2). The kernel **MUST NOT** later remap a `pending` id to a final envelope id.
- **C-N13** - When `ROLLBACK_SEARCH_MAX_BYTES` is set to a non-null value, the nearest match outside the independent lookback window **MUST** be audited as `outcome=pattern_out_of_bound`, `effective_bound="search_max_bytes"`, and **MUST NOT** be downgraded to `pattern_not_found`. When set to `null`: (a) structural boundaries still apply; (b) the pattern-matching implementation **MUST** run in `O(window_bytes+len(pattern))` linear time, with worst-case quadratic or higher complexity **forbidden**; (c) audit details **MUST** additionally expose `effective_search_window_bytes`, and `runtimeinfo.stats` (if provided) **SHOULD** expose `rollback_search_max_bytes_effective` (§13.3). Under either setting, silent best-effort truncation followed by classification as `pattern_not_found` is **forbidden**.

16.1.1 Minimum Conformance Test Matrix

Test item	L0 /Tier-A	L1 /Tier-B	L2 /Tier-C
`runtimeinfo.kernel.atomics`	Lists A1-A5, B2-B3, C1-C5, D1-D3, E, F1-F4, G1, H1-H3, I1	**MUST NOT** list A5; A2 /H3 are level-dependent optional (may be listed)	**MUST NOT** list A5; A2 /H3 **MAY** be omitted

Test item	L0 /Tier-A	L1 /Tier-B	L2 /Tier-C
A5 call	Succeeds or returns `E_FORK_*` according to quota	`E_ATOMIC_UNSUPPORTED`	`E_ATOMIC_UNSUPPORTED`
`tokens.rollback` program path	`E_CAP_DENIED`; **MUST NOT** grant/request	Same as L0	Same as L0
`<lmsc_ref>...</lmsc_ref>` inside a non-rollback envelope body	Legal; ref body checked by `I-REF-CHARSET`	Same as L0	Same as L0, detected post-hoc
`<lmsc_ref>` inside a rollback envelope body	`I-ROLLBACK-NO-NEST` violation	Same as L0	Abort after post-hoc detection
`features.rollback_truncate_precision`	`byte`	`byte` or `token`	`byte` /`token` /`none`
L2 `precision=none` rollback close	Not applicable	Not applicable	abort current turn, emit `protocol_violation`, **MUST NOT** silently ignore
`features.invariant_enforcement`	`enforced`	`enforced`	`post-hoc`
`kernel.integration_tier`	`A`	`B`	`C`
`tokens.inject` during `SUSPENDED`	`E_INJECT_BAD_POSITION` for ordinary A4 calls; C2 payload remains allowed	Same as L0	Same as L0
L2 buffered `on_envelope_chunk.envelope_id`	Not applicable	Not applicable	final id preallocated and stable on normal path; `pending` only on reject-before-open path
`persona_refresh` pin quota (when enabled)	finite active-count and token limits enforced/audited	Same as L0	Same as L0
rollback audit search-range field	details use `search_scope`; do not emit `details.scope`	Same as L0	Same as L0
attribute value over cap	`E_EMIT_ESCAPE_VIOLATION`; no truncation	Same as L0	Same as L0
ref.resolve failure error envelope	does not trigger self-output-edit observer	Same as L0	Same as L0

Required programs and optional extension test: `programs.required` **MUST** be exactly the four entries `program`, `capability`, `runtime`, and `kv`. `runtimeadminpersona-refresh` does not increase the required programs count; it only controls subcommand existence and whether the conditional rules in §12.3.1 are enabled through `features.persona_refresh`.

16.2 SHOULD

- **S-1** - Kernel core code $\leq$ 3000 LOC (excluding binding-generated code and required programs).
- **S-2** - Provide both WASM and Lua backends.
- **S-3** - L0-level integration.
- **S-4** - Provide A2 and H3 (for non-L2 implementations).
- **S-5** - `runtime stats` **SHOULD** expose the per-turn protocol overhead ratio (`envelope_bytes/total_bytes`, `control_tokens/total_tokens`, `ref_tokens/total_tokens`) so deployers can evaluate the cost of lightweight interaction. `ref_tokens` counts the reserved tokens `<lmsc_ref>` open and `</lmsc_ref>` close; the ordinary-token ratio of the ref body is additionally recorded as `ref_body_tokens/total_tokens` (implementation extension field optional).
- **S-6** - LoRA training sets **SHOULD** construct `<lmsc_rollback>PATTERN</lmsc_rollback>` with the **pattern as an actual substring** (slicing prefixes/suffixes from real corpora), avoiding generative misalignment; pattern length **SHOULD** cover most points in `[1, ROLLBACK_PATTERN_MAX_BYTES]`.
- **S-7** - Distribution documentation **SHOULD** provide a ref external-ID canonicalization convention (such as `base64 url(no_padding(utf8_bytes))` or `sha256:<hex-prefix>`) and a collision policy, and register `external_id_scheme` in resolver manifests /metadata.

16.3 MAY

- Key token sets, supported `exec.sandbox` kinds, other extension attributes, and audit sink types are distribution-defined.

16.4 Non-Conforming Examples

- Making `capability.grant` a requestable cap;
- Allowing `program.admin` to be granted;
- Failing to perform literal escaping in envelope bodies;
- Tokenizer treating `<lmsc_ref>` or `</lmsc_ref>` as ordinary tokens;
- Required programs being shadowed;
- Audit records being suppressible by programs;
- Kernel depending on recommended programs such as `summarizer` to provide any capability from C-1 through C-10;
- The action closed set having more or fewer than 7 entries;
- The required program count is not 4.
- Producing unregistered `E_ROLLBACK_BOUNDARY`, instead of expressing out-of-bounds with `rollback(outcome=pattern_out_of_bound)` or the program path's `E_ROLLBACK_PATTERN_NOT_FOUND` + `details.outcome=pattern_out_of_bound`.

---

17. Appendices

Appendix A - Special Token Registry

#	Token	Type	Primitive	Notes
1	`<lmsc_execute>`	envelope open	B1	Model-initiated command
2	`</lmsc_execute>`	envelope close	B1	--
3	`<lmsc_output>`	envelope open	B1	Structured output
4	`</lmsc_output>`	envelope close	B1	--
5	`<lmsc_edit>`	envelope open	B1	Streaming edit
6	`</lmsc_edit>`	envelope close	B1	--
7	`<lmsc_rollback>`	envelope open	A3	Pattern-string rollback; body is pattern
8	`</lmsc_rollback>`	envelope close	A3	Triggers matching and truncation
9	`<|lmsc_abort|>`	control	C3	Meaningful only inside an envelope
10	`<|lmsc_suspend|>`	control	C1	Model actively suspends; default `suspend(External)`
11	`<lmsc_ref>`	ref open	F3	Body uses `kind:"summary"; id:"x";` microgrammar
12	`</lmsc_ref>`	ref close	F3	Triggers ref resolution
13+	`<|key_*|>`	key	A4	Distribution-defined

Subtotal: envelope 4 pairs = 8 tokens + control 2 + ref 2 + key K = **12 + K**, consistent with §4.1.5.

Appendix B - Capability Name Registry (Core)

This table is the human-readable projection of `lmsc-capability-registry.yaml`; fixed-only and grantable status **MUST** be validated by the machine-readable registry in the implementation package, and **MUST** remain consistent with §11.4.

Capability	Grantable	Initial holder
`envelope.emit`	yes	Every registered program by default
`tokens.mask.direct`	**no, fixed only**	kernel internals /inference stack adapter layer
`tokens.rollback.explicit`	**no, fixed only**	kernel internals
`tokens.inject`	yes	kernel internals; ordinary programs only after explicit authorization
`tokens.inject.special`	**no, fixed only**	kernel internals; **MUST NOT** be exposed as a general A4 capability for persona-refresh
`session.fork`	yes	`runtime`
`scheduler.suspend`	yes	As needed
`scheduler.abort.own`	yes	Every registered program by default
`scheduler.abort.any`	**no, fixed only**	`runtime`
`scheduler.preempt`	yes	Notification /alert class programs
`scheduler.preempt.execute`	**no, fixed only**	No default holder
`scheduler.frame`	yes	As needed (`focus` /`shell` recommended programs)
`capability.grant`	**no, fixed only**	`capability` required program
`capability.revoke`	**no, fixed only**	`capability` required program
`program.register`	**no, fixed only**	`program` required program
`program.admin`	**no, fixed only**	`program` required program
`program.install`	yes	External decision approval
`program.ref.bind`	yes	Programs that declare ref_kinds
`region.pin`	**no, fixed only**	Fixed configuration by distribution
`region.compact`	yes	Compaction class programs (recommended `summarizer`; `runtime admin compact` actually checks this cap)
`region.drop.hard`	**no, fixed only**	No default holder
`boot.refresh`	**no, fixed only**	External
`audit.export`	yes	Operations
`runtime.read`	yes	All programs by default
`runtime.fork`	yes	As needed
`fs.read:<pattern>`	yes	As needed
`fs.write:<pattern>`	yes	As needed
`net.<method>:<pattern>`	yes	As needed

Capability	Grantable	Initial holder
`exec.sandbox:<kind>`	yes	As needed (if H3 is provided)

Appendix C - Action Registry

7 entries (listed in §8.3). **Closed set**, **MUST NOT** be extended.

Appendix D - Complete Syscall Method List

This appendix expands every primitive in the §7.2 syscall table into method-level signatures. It does not change the specification content; it only gives implementers and program authors a lookup table.

Method	Primitive	Capability	Notes
`tokens.logit_mask(mask)`	A1	`tokens.mask.direct`†	kernel internal by default
`tokens.is_special(id)`	A2	--	L0 **MUST** provide; L1 optional; L2 **MAY** omit
`tokens.name_of(id)`	A2	--	Same as above
`tokens.id_of(name)`	A2	--	Same as above
`tokens.rollback(pattern,scope)`	A3	`tokens.rollback.explicit`†	V1 program side unreachable; model path uses kernel internals
`tokens.inject(tokens,position)`	A4	`tokens.inject*` (+`tokens.inject.special`† if reserved tokens are included)	ordinary calls while SUSPENDED return `E_INJECT_BAD_POSITION`; stack overflow returns `E_STACK_OVERFLOW`
`session.current_handle()`	A5	`session.fork*`	Unavailable under L1; does not create a fork
`session.fork()`	A5	`session.fork*`	Unavailable under L1
`session.restore(handle)`	A5	`session.fork*`	
`session.drop_fork(handle)`	A5	`session.fork*`	
`envelope.emit(kind,attrs,body)`	B3	`envelope.emit`	body supports Bytes or Stream
`scheduler.suspend(resume_on)`	C1	`scheduler.suspend`	
`scheduler.resume(handle,payload)`	C2	`scheduler.suspend`	
`scheduler.abort(envelope_id,reason)`	C3	`scheduler.abort.own` or `.any`†	
`scheduler.preempt(spec,reason)`	C4	`scheduler.preempt*`	cooldown enforced
`scheduler.frame_push(rules)`	C5	`scheduler.frame`	`rules` structure in §5.4 C5
`scheduler.frame_pop(frame_id)`	C5	`scheduler.frame`	Can only pop frames it pushed itself
`scheduler.frame_supports(field)`	C5	--	queries FrameRules field MRO
`cap.check(cap)`	D1	--	Pure function
`cap.list()`	D1	--	
`cap.list_requestable()`	D1	--	
`cap.grant(cap,scope,ttl?,source)`	D2	`capability.grant`†	
`cap.revoke(cap_id,reason)`	D3	`capability.revoke`† or the grantor	
`program.register(manifest)`	E	`program.register`	
`program.lookup(name)`	E	--	
`program.info(id)`	E	--	cap-filtered
`program.list()`	E	--	cap-filtered
`program.unregister(id)`	E	`program.admin`†	Required programs **MUST NOT** be unregistered; user subcommands `programremove/unregister` require `program.install` and are delegated by the `program` required program
`kv.put(key,value,ttl?)`	F1	--	Program namespace
`kv.get(key)`	F1	--	
`kv.del(key)`	F1	--	
`kv.list(prefix)`	F1	--	
`blob.put(data)`	F2	--	Returns BlobId
`blob.get(id)`	F2	--	
`blob.incref(id)` /`decref(id)`	F2	--	
`blob.stat(id)`	F2	--	
`ref.bind(kind,resolver)`	F3	`program.ref.bind`	One-time in `on_load`
`ref.resolve(id,kind)`	F3	--	
`ref.kinds_registered()`	F3	--	

Method	Primitive	Capability	Notes
`region.tag(range,attrs)`	F4	Some attrs require caps (such as `region.pin`)	
`region.edit(region_id,replacement, persist?)`	F4	`region.compact` (+ `region.drop.hard` for hard delete)	Returns `RegionEditResult`; drop-soft /replacement includes `archived_blob_id`
`audit.emit(record)`	G1	--	Kernel automatically adds source
`fs.read/write/stat/list/mkdir/remove/move`	H1	`fs.<op>:<path>`	
`net.request/stream`	H2	`net.<method>:<pattern>`	
`exec.sandbox(kind,code,stdin?,limits)`	H3	`exec.sandbox:<kind>`	L0 **MUST** provide; L1 optional; L2 **MAY** omit
`clock.now()`	I1	--	**MAY** be sanitized
`clock.monotonic()`	I1	--	
`clock.timer(dur,cb)`	I1	--	
`clock.cancel(id)`	I1	--	

* High privilege; † fixed-only.

The machine-processing authoritative source is `lmsc-syscall-schema.yaml` as specified by §7.5. This human table is for reading and indexing and **MUST NOT** be the only authoritative source; any method count, combined-row expansion rule, and language-binding generation **MUST** be validated or generated from the schema.

Appendix E - Boot Output Schema

When INIT -> IDLE, the kernel **directly** injects one `<lmsc_output>`, immediately followed by a kernel-owned attribute header (containing at least `from="system"id="boot"visibility="all"`); body YAML (or an implementation-defined structured format) **MUST** contain:

> **`atomics` filtering criterion** - This field only includes primitives that can semantically be called explicitly by programs through syscalls in this implementation; event primitives (such as B1 `envelope_event`) are **not included** because they have no syscall entry. A5 is exempted by level according to §16.1 C-1; `atomics` **MUST NOT** include A5 under L1 /L2.



Estimate:

- token_stream + kv_cache_adapter: ~600
- envelope /scheduler: ~600 (including C5 frame)
- state: ~600
- capability /program_table /audit: ~400
- io: ~300-400 (H3 level-dependent optional)
- clock /glue: ~200
- required programs (4 x ~250): ~1000

Total ~3700 LOC (including required programs); pure kernel excluding required programs is about **2700 LOC**.

Appendix H - Machine-Readable Artifact List

A V1 conforming distribution package **MUST** publish at least the following machine-readable artifacts; human-readable tables in the body **MUST NOT** replace these artifacts:

File	Authoritative content	Corresponding section
`lmsc-syscall-schema.yaml`	syscall names, parameters, capability, availability, error set	§7.5 /Appendix D

File	Authoritative content	Corresponding section
`lmsc-capability-registry.yaml`	capability grantability, fixed-only, requestable, initial holders	§11.4 /Appendix B
`lmsc-error-code-registry.yaml`	error-code category, origin, retryable, notes	§15.2
`lmsc-boot-runtime-schema.yaml`	shared schema for boot output and `runtime info`	Appendix E
`lmsc-audit-export-schema.yaml`	raw audit export pagination, hash, signature, projection fields	§14.3
`lmsc-feature-registry.yaml`	`features.*` fields, value domains, custom extension naming	§13.2 /Appendix E

If a distribution also provides JSON representation, JSON and YAML **MUST** be generated from the same schema, with equivalent field sets and semantics.

Bibliography

Bibliography

[1] ISO/IEC Directives, Part 2, *Principles and rules for the structure and drafting of ISO and IEC documents*, ninth edition, 2021. Available at https://www.iso.org/sites/directives/current/part2/index.xhtml.

[2] IETF RFC 2119, *Key words for use in RFCs to Indicate Requirement Levels*, 1997.

[3] IETF RFC 8174, *Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words*, 2017.