

A Survey of Evaluation in Music Genre Recognition

Bob L. Sturm^(✉)

Audio Analysis Lab, AD:MT, Aalborg University Copenhagen,
A.C. Meyers Vænge 15, 2450 Copenhagen SV, Denmark
`bst@create.aau.dk`

Abstract. Much work is focused upon music genre recognition (MGR) from audio recordings, symbolic data, and other modalities. While reviews have been written of some of this work before, no survey has been made of the approaches to evaluating approaches to MGR. This paper compiles a bibliography of work in MGR, and analyzes three aspects of evaluation: experimental designs, datasets, and figures of merit.

1 Introduction

Despite much work [1–467], music genre recognition (MGR) remains a compelling problem to solve by a machine. In addition to many background chapters of master’s theses [39, 79, 113, 132, 153, 154, 188, 193, 239, 361, 367, 371, 418] and doctoral dissertations [9, 141, 146, 280, 284, 290, 320, 341, 342, 381, 427, 447] at least five reviews are devoted specifically to MGR [23, 85, 123, 241, 373], and 19 other reviews discuss related aspects [24, 25, 51, 71, 84, 100, 101, 152, 181, 198, 224, 233, 270, 282, 315, 398, 423, 441, 442]. Many of these reviews compile the variety of feature extraction methods and classification algorithms that have been applied to MGR, and some compare system performance using specific figures of merit (FoM) on particular benchmark datasets. There have also been no fewer than 10 campaigns to formally evaluate and compare state-of-the-art algorithms for MGR [170, 171, 293–299, 316]. However, the variety of approaches used for evaluating performance in MGR has yet to be surveyed. *How does one measure the capacity of a system — living or not — to recognize and discriminate between abstract characteristics of the human phenomenon of music?*

There currently exists at least eleven works [77, 78, 116, 117, 246, 320, 404, 409, 410, 433, 449] that address the difficult but clearly relevant question of how to evaluate the performance of MGR systems, not to mention how to properly create a dataset from which a machine is to learn an abstract and high-level concept such as genre [468, 469]. A few works critically address evaluation in MGR. For instance, [77, 78, 409, 410] argue for more realistic approaches than having a system apply a single label to music, and comparing against a “ground truth” — which itself can be quite wrong [404, 408]. Furthermore, [77, 78, 246, 449] argue for measuring performance in ways that take into account the natural ambiguity arising from genre.

In this paper, we take a different direction to answer the question we pose above. We review a significant portion of published research touching upon aspects of evaluation in MGR. We consider all work that is based upon recorded music, and/or symbolic representations of the music, e.g., MIDI, and/or other modalities, e.g., lyrics, album covers, user tags, movie scenes, etc. We do not, however, consider work addressing the more general problem of “tagging,” e.g., [470]. While we consider both “genre” and “style,” and make no attempt to differentiate them, we do not include “mood” or “emotion,” e.g., [471]. We are herein interested only in the ways systems for MGR are evaluated, be they algorithms, humans [79, 169, 201, 258, 261, 262, 278, 290, 366, 367, 370, 381, 383, 460], pigeons [347], sparrows [439, 440], koi [58], primates [278] or rats [317]. To facilitate this survey, we created a spreadsheet summarizing every relevant paper we found in terms of its experimental design, details of the datasets it uses, and the figures of merit it reports. This resource provides a simple means to delimit sets of references sharing particular aspects of evaluation. The bibliography file we assembled for this work is available here: <http://imi.aau.dk/~bst/research/MGRbibliography.bib>; and the spreadsheet we created identifying the characteristics of the references is available here: <http://imi.aau.dk/~bst/research/MGRspreadsheet.xlsx>.

Figure 1 shows how the number of the works we reference is distributed since the 1995 work of Matityaho and Furst [271] — before which we have only found the 1984 work of Porter and Neuringer [347]. Many papers allude to the 2002 article of Tzanetakis and Cook [426] as the beginning of research in automatic MGR. We find their manuscript (received Nov. 2001 and growing from [425]) is preceded by seventeen works [44, 53, 83, 89, 91, 132, 148, 204, 270, 271, 346, 348, 350, 401, 443, 472, 473], and is contemporary with nine works [22, 79, 176, 193, 202, 218, 351, 385, 448]. The dataset created by Tzanetakis and Cook for [426], however, is the first “benchmark” MGR dataset to have been made publicly available, and as a result continues to be the most used public dataset for MGR.

In our analysis, we do not include [474–479] as they are written in Turkish, and [472] as it is written in German, and we can read neither. We could not




Fig. 1. Annual numbers of publications in this survey.




Fig. 2. Annual numbers of publications in this survey having an experimental component (top number), and which use any form of statistical testing for making comparisons (bottom number).

obtain [473, 480, 481], and so do not include them in the analysis. Finally, we neither analyze nor cite seven published works because of plagiarism.

2 Evaluation Approaches in Music Genre Recognition

We now catalogue approaches to evaluation in MGR along three dimensions — experimental design, datasets, and figures of merit (FoM) — and present summary statistics of each. Experimental design is the method employed to answer a specific hypothesis, e.g., in the case of MGR, “System A recognizes ‘Blues.’” The dataset is simply the collection of data used in the experiment. A FoM quantifies the performance of a system in the experiment, e.g., accuracy. Figure 2 shows how the number of works having an experimental component is distributed over the years. Compared to Fig. 1, the remaining works are reviews, or primarily concerning evaluation.

2.1 Experimental Design

Table 1 describes the ten different experimental designs we find, along with their appearance in the literature. We see that the most common experimental design to test MGR systems is *Classify*. More than 91 % (397)¹ of the referenced work having an experimental component (435) uses such a design [1–9, 11–21, 26–43, 45, 47–50, 52–56, 58–60, 62–65, 68–70, 72–76, 79–83, 86–90, 92–99, 102–106, 108–122, 124–135, 137–148, 150, 151, 153–165, 167–172, 174–180, 182–197, 199–202, 204–217, 219–223, 225–232, 234, 235, 238–240, 242–261, 263–269, 271–281, 283–287, 289–301, 303, 305–307, 309–313, 317, 319–333, 335–349, 352–359, 361–364, 366–372, 375–383, 385–393, 395–397, 399, 401–403, 405–407, 409–412, 414, 416, 418–422, 424–433, 435–440, 443–445, 447, 448, 450–465, 467]. For instance, Matityaho and Furst [271] test

¹ Numbers in parentheses are the number of works in the references.

Table 1. Ten experimental designs of MGR, and the percentage of references having an experimental component (435) in which they appear

Design	Description	%
<i>Classify</i>	To answer the question, “How well does the system identify the genres used by music?” The system applies genre labels to music, which researcher then compares to a “ground truth”	91.3
<i>Features</i>	To answer the question, “At what is the system looking to identify the genres used by music?” The system ranks and/or selects features, which researcher then inspects	32.6
<i>Generalize</i>	To answer the question, “How well does the system identify genre in varied datasets?” <i>Classify</i> with two or more datasets having different genres, and/or various amounts of training data	15.9
<i>Robust</i>	To answer the question, “To what extent is the system invariant to aspects inconsequential for identifying genre?” The system classifies music that researcher modifies or transforms in ways that do not harm its genre identification by a human	6.9
<i>Eyeball</i>	To answer the question, “How well do the parameters make sense with respect to identifying genre?” The system derives parameters from music; researcher visually compares	6.7
<i>Cluster</i>	To answer the question, “How well does the system group together music using the same genres?” The system creates clusters of dataset, which researcher then inspect	6.7
<i>Scale</i>	To answer the question, “How well does the system identify music genre with varying numbers of genres?” <i>Classify</i> with varying numbers of genres	6.7
<i>Retrieve</i>	To answer the question, “How well does the system identify music using the same genres used by the query?” The system retrieves music similar to query, which researcher then inspects	4.4
<i>Rules</i>	To answer the question, “What are the decisions the system is making to identify genres?” The researcher inspects rules used by a system to identify genres	3.7
<i>Compose</i>	To answer the question, “What are the internal genre models of the system?” The system creates music in specific genres, which the researcher then inspects	0.7

a neural network trained to discriminate between classical and pop music. They extract features from the audio, input them to the neural network, and compare the output labels against those they assigned to the excerpts of their dataset. Almost all of the experimental work that applies *Classify* employ a single-label approach, but at least ten employ a multi-labeling approach [31, 255, 258, 280, 367–369, 373, 415, 437]. For instance, McKay [280] looks at how genres at both root and leaf nodes are applied by his hierarchical approach to classification.

One extension of the *Classify* experimental design is *Generalize* [1, 2, 9, 13, 15, 16, 19, 30, 31, 38, 45, 55, 58, 62, 66, 75, 82, 94, 97, 128, 137, 146, 153, 161–164, 199, 200, 209, 214, 218, 222, 223, 225, 226, 231, 238, 240, 249, 262, 268, 269, 285, 287, 289, 290, 302, 303, 307, 312, 313, 319, 320, 327, 335, 341, 347, 349, 361, 364, 374, 378, 426, 427, 435, 439, 440, 461]. For instance, Porter and Neuringer [347] test whether pigeons trained to discriminate between music by J. S. Bach and Stravinsky are able to discriminate between music by composers contemporary with J. S. Bach (Buxtehude and Scarlatti) and Stravinsky (Carter and Piston). Another extension of *Classify* is *Scale* [9, 13, 14, 19, 45, 48, 49, 53, 62, 68, 83, 94, 132, 144, 199, 225, 226, 238, 261, 275, 280, 303, 320, 336, 337, 339–341, 390]. For instance, Chai and Vercoe [53] test their system on various class pairs from their dataset of three folk music genres, as well as on all three classes together.

The second most-used experimental design is *Features* [1, 7, 9, 16, 17, 26, 27, 33–35, 37, 43, 48, 49, 53, 68, 69, 72, 93, 95, 102, 103, 105, 109, 115, 122, 126, 127, 139, 141, 143, 144, 146, 153, 157–160, 179, 182–184, 187–189, 192, 196, 197, 199, 200, 211–213, 219–221, 226–230, 232, 236–238, 240, 242, 244, 245, 247, 249–252, 272–277, 280, 281, 283–287, 289–291, 300–303, 307, 309, 320, 327, 333, 337, 340, 341, 345, 361, 362, 364, 370, 371, 376, 377, 379, 385, 387, 390, 393, 396, 397, 401, 403, 406, 417, 420, 421, 425–427, 430, 432, 434, 436, 438, 443, 447, 451, 454–456, 460, 462, 464, 465, 467]. We do not include in this experimental design work that performs feature selection without an interpretation of the results. For instance, Tzanetakis et al. [425] use *Classify* in comparing rhythmic features (statistics of an autocorrelation of wavelet decomposition) and timbral features (spectral centroid, rolloff, etc.). On the other hand, Yoon et al. [459] explore two different feature selection approaches using *Classify*, but do not discuss or list the selected features. Akin to *Features* is a fifth design, *Rules*, which appears in at least sixteen works [3, 5, 13, 14, 26, 42, 43, 70, 94, 98, 139, 303, 308, 340, 341, 434]. For instance, Bickerstaffe and Makalic [43] look at a decision stump that discriminates “rock” and “classical” music. As another example, Abeßer et al. [5] provide the details of a decision tree algorithmically built for discriminating between 13 genres.

Another experimental design is *Cluster* [22, 33, 66, 67, 72, 107, 126, 136, 189, 196, 218, 236, 237, 242, 253, 261, 301, 302, 304, 318, 320, 334, 350, 351, 365, 415, 417, 430, 438]. For instance, Rauber and Frühwirth [350] employ the self-organizing map method with features extracted from 230 music excerpts, and analyze the contents of the resulting groupings. We find that both *Classify* and *Cluster* are used in about 2.6 % (12) of the experimental work [33, 72, 126, 189, 196, 242, 253, 261, 301, 320, 430, 438]. A seventh experimental design is *Retrieve*, which appears in at least 19 works [10, 46, 57, 61, 86, 118, 119, 121, 203, 222, 232, 262, 320, 348, 384, 388, 446, 447, 466]. For instance, Kuo and Shan [203] incorporate style recognition into their music retrieval system.

An eighth experimental design is *Eyeball*, which appears in at least 29 works [26, 29, 44, 83, 91, 105, 146, 149, 155, 166, 173, 189, 218, 242, 259, 261, 288, 300, 302, 304, 310, 314, 320, 358, 360, 402, 403, 413, 463]. For instance, Dannenberg et al. [83] visually inspect class separability for a few pairs of features to explore the reason for a discrepancy in performance in identifying style between an expert approach

and machine learning approach. Bigerelle and Iost [44] visually compare means of fractal dimensions computed from several musical excerpts of various genres.

A ninth experimental design is *Robust* [3, 10, 21, 27, 38, 48, 49, 52, 55, 58, 75, 79, 131, 142, 200, 235, 247, 267, 268, 290, 313, 320, 333, 347, 387, 388, 401, 409, 428, 439]. For instance, Porter and Neuringer [347] test whether pigeons that have been taught to discriminate between music by J. S. Bach and Hindemith demonstrate their ability regardless of excerpt content and loudness. Soltau et al. [401] investigate the variability of their system using *Classify* by using features computed from excerpts of several durations. Burred and Lerch [48] consider the effect of noise and filtering in feature extraction using *Classify*.

The final experimental design we consider is *Compose*, which appears in only three works [80, 82, 409]. For instance, Cruz-Alcáza and Vidal-Ruiz [80, 82] invert their music style identification system to compose music in the styles it has learned, which the authors then qualitatively evaluate. While Cruz-Alcáza and Vidal-Ruiz do not directly use this as a means to assess the extent to which their system has learned a style, [409] shows by a formal listening test that excerpts composed to be genre-representative by two high-accuracy MGR systems embody little in common with what is commonly held to be characteristic of those genres.

The bias that results from training and testing MGR systems using music data from the same artist and/or excerpted from the same album are well-documented, e.g., [117–119, 319]. Among the 435 works that include experimental work, we find that only 8.3 % (36) explicitly mention the use of an artist or album filter [30, 57, 74–76, 117–119, 153, 174, 187, 194, 209, 222, 225, 239, 254, 262, 266, 319, 320, 349, 353, 355, 367–369, 376, 378, 381, 383, 384, 401, 418, 447, 461], or attempt to apply one to datasets without known artists [382]. The earliest article applying an artist filter is from 1998 by Soltau et al. [401].

We find that at least twelve works use human evaluation in the analysis of the experiment [22, 46, 80, 82, 83, 260, 320, 347, 409, 410, 434, 447]. For instance, Dannenberg et al. [83] discuss the performance of their system in a live-performance context. Cruz-Alcáza and Vidal-Ruiz [80] rate the quality of the melodies composed by their style recognition system. And Pampalk [320] uses a formal listening test to show genre labels are strongly correlated with perceptual similarity.

Figure 1 shows the number of experimental works employing formal statistics over each year. Only 16.5 % (72) of the experimental work we survey contains formal statistical testing [9, 15, 25, 27, 37, 44, 46, 58, 68, 75, 79, 114–117, 121, 122, 124, 131, 132, 145, 146, 169, 174, 201, 221, 252, 258, 272, 273, 275, 277, 278, 283–285, 289–291, 295–299, 304, 308–310, 314, 317, 320, 333, 337, 341, 349, 357, 377, 384, 395, 397, 409–412, 422, 434, 439, 440, 444, 447, 457, 466]. For instance, Flexer [116] provides excellent argumentation for the need for statistical testing in music information research, and provides a demonstration of its use in comparing the performance between two MGR systems. We find half of the work using living subjects (11 of 22) employ formal statistical tests [58, 79, 131, 169, 201, 258, 278, 290, 317, 439, 440]. For instance, Chase [58] uses a one-tailed paired t-test of percentages of non-responses of koi fish to test the null hypothesis that the koi are unable to discriminate between music that uses Blues or Classical genres.

Nearly half (213) of the experimental work we survey employs only one experimental design from Table 1. For instance, in several formal MGR challenges [170, 171, 293–299], performance is evaluated only by *Classify*. We find about 32 % (142) of the work we survey employ two experimental designs. For instance, Golub [132] uses *Classify* to test his MGR system for a three-genre problem, and then uses *Scale* to observe how its behavior changes when he augments the dataset with four other genres. More than 18 % (80) employ more than two experimental designs. For instance, the only two experimental designs not used by Pampalk [320] are *Rules* and *Compose*.

2.2 Datasets

We find that of the works we survey having experimental components (435) over 58 % (253) use private data [1–5, 7–11, 13–16, 18, 19, 22, 26, 28–31, 34, 40, 43–49, 53, 56–58, 62–70, 72, 73, 79–83, 87–89, 91–99, 104, 105, 109–111, 118–120, 125–128, 130–138, 142–146, 148–151, 154, 156–160, 163, 164, 166, 169, 172, 173, 175, 176, 178–180, 184–188, 190, 191, 193, 196, 197, 199–205, 207, 209–211, 217–221, 225, 226, 228, 229, 231, 232, 242, 243, 245–253, 255, 257–261, 266, 271–275, 277, 281, 287–292, 300–305, 308, 312, 313, 317–320, 327–331, 334–342, 344, 346–348, 350, 358, 360, 361, 363–365, 372, 374, 385–387, 389, 390, 401, 413, 416, 418, 425–435, 437–440, 443–448, 452, 453, 455, 458, 459, 462–465, 467]. Of those works that use private data, we find over 75 % (191) exclusively use private data. Some work provides a detailed description of the composition of the data such that one can recreate it. For instance, Tsatsishvili [418] lists the 210 names of the albums, artists, and songs in his dataset. Schedl et al. [374] provide a URL for obtaining the list of the artists in their dataset, but the resource no longer exists. Mace et al. [258] also provide a list, but since they only list the song and artist name uncertainty arises, e.g., which recording of “The Unanswered Question” by Ives do they use? It is impossible to recreate the dataset used in [48, 49] since they only state that they assemble 850 audio examples in 17 different genres. We find that about 51 % (224) of the works we survey having experimental components use datasets that are publicly available. Of these, over 79 % (177) only use public data.

Table 2 lists 18 publicly available datasets used in the work we survey. *GTZAN* appears in 23 % (100) of the work having an experimental component [6, 12, 15, 17, 19, 27, 33, 35–39, 41, 46, 55, 59–61, 94, 103, 121, 122, 124, 129, 146, 147, 153, 155, 161, 162, 182, 183, 195, 200, 206, 214, 222, 223, 226, 227, 230–232, 234, 235, 238–240, 243, 244, 249, 263–265, 269, 276, 303, 306, 321–326, 352, 356, 357, 361, 362, 364, 371, 377, 379–382, 384, 387, 388, 405–407, 409–412, 416, 419–422, 426, 427, 450, 451, 454, 456, 457, 461, 466]. This dataset has only recently been analyzed and shown to have faults [408]. The second most-used publicly available dataset is that created for the 2004 Audio Description Contest of ISMIR [170], which appears in 76 works [15, 32, 45, 50, 75, 94, 114, 116, 117, 161, 162, 167, 170, 174, 189, 208, 209, 212–216, 222, 223, 225, 238–240, 242, 243, 256, 264–268, 276, 290, 303, 311, 319–327, 332, 342, 343, 345, 357, 359, 366, 367, 370, 377, 379, 381, 382, 384, 395–397, 402, 403, 412, 417, 424, 436, 450, 457, 460, 461]. Datasets derived from Magnatune, e.g., Magnatagatune [485] but excepting *ISMIR2004* [170], appear in

Table 2. Datasets used in MGR, the type of data they contain, the references in which they are used, and the percentage of experimental work (435) that use them. All datasets listed after *Private* are public.

Dataset	Description	%
<i>Private</i>	Constructed for research but not made available; used in: <i>see text</i>	58.2
<i>GTZAN</i>	Audio; http://marsyas.info/download/data_sets ; used in: <i>see text</i>	23.0
<i>ISMIR2004</i>	Audio; http://ismir2004.ismir.net/genre_contest ; used in: <i>see text</i>	17.4
<i>Latin</i> [394]	Features; http://www.ppgia.pucpr.br/~silla/lmd/ ; used in [74–76, 97, 102, 242, 254, 267, 268, 295–299, 377, 391–397]	5.1
<i>Ballroom</i>	Audio; http://mtg.upf.edu/ismir2004/contest/tempoContest/ ; used in [115, 139–141, 163, 164, 333, 345, 378, 381, 382, 384, 419–421]	3.4
<i>Homburg</i> [165]	Audio; http://www-ai.cs.uni-dortmund.de/audio.html ; used in [20, 21, 46, 108, 165, 302, 303, 307, 345, 353, 355, 378, 381, 382, 384]	3.4
<i>Bodhidharma</i>	Symbolic; http://jmir.sourceforge.net/Codaich.html ; used in [52, 86, 128, 192, 279–281, 284, 285, 293, 399]	2.5
<i>USPOP2002</i> [482]	Audio; http://labrosa.ee.columbia.edu/projects/musicsim/uspop2002.html ; used in [38, 42, 239, 262, 290, 293, 349, 354]	1.8
<i>1517-artists</i>	Audio; http://www.seyerlehner.info ; used in [378, 381–384]	1.1
<i>RWC</i> [483]	Audio; http://staff.aist.go.jp/m.goto/RWC-MDB/ ; used in [106, 107, 153, 353]	0.9
<i>SOMeJB</i>	Features; http://www.ifs.tuwien.ac.at/~andi/somejb/ ; used in [177, 236, 237, 351]	0.9
<i>SLAC</i>	Audio & symbols; http://jmir.sourceforge.net/Codaich.html ; used in [283–286]	0.9
<i>SALAMI</i> [400]	Features; http://ddmal.music.mcgill.ca/research/salami ; used in [309, 310, 400]	0.7
<i>Unique</i>	Features; http://www.seyerlehner.info ; used in [381, 382, 384]	0.7
<i>Million Song</i> [484]	Features; http://labrosa.ee.columbia.edu/millionsong/ ; used in [90, 168, 376]	0.7
<i>ISMIS2011</i>	Features; http://tunedit.org/challenge/music-retrieval ; used in [171, 194, 375]	0.4

at least 5.7 % (25) of the references having an experimental component [16,28–31, 38,112,113,146,225,269,290,293,319,320,342,349,353,355,367–369,414,446,447].

Over 79 % (344) of the experimental work we survey approaches MGR using audio data or features of audio [1–3, 6–10, 12, 13, 15–22, 27–32, 35–39, 42, 44–50, 52, 55–58, 60–64, 68, 73–76, 79, 88–93, 96, 97, 99, 102–119, 121, 122, 124, 127, 129–141, 143–151, 153–155, 161–165, 167–179, 182, 183, 186–191, 193–195, 200, 201, 204–217, 222, 223, 225–228, 230–232, 234–240, 244, 246–250, 252, 254–256, 258, 260–269, 271, 273–277, 283, 285–307, 309–313, 317–320, 327–334, 341–345, 347–353, 355–362, 364–372, 375, 376, 378–384, 386–397, 401–403, 405–407, 409–412, 414, 416–422, 424–433, 436–440, 443–448, 450–457, 459–467]. The use of symbolic data, e.g., MIDI and humdrum, appears in over 18 % (81) of these references [1–5, 11, 13–15, 26, 34, 43, 52, 53, 65–67, 69, 70, 72, 80–83, 86, 87, 94, 95, 120, 128, 156–160, 166, 180, 184, 185, 192, 196, 197, 199, 202, 203, 218–221, 229, 240, 243, 245, 251, 253, 257, 259, 261, 279–281, 283–286, 293, 335–341, 346, 363, 385, 399, 413, 428, 434, 435]. We find about 6 % (27) of the work having an experimental component approaches MGR using other kinds of data, e.g., lyrics, co-occurrences on the WWW, album covers, and so on [25, 40, 62, 98, 125, 142, 272–277, 283–286, 308, 309, 354, 374, 381, 415, 438, 448, 458, 464, 465].

Figure 3 shows the number of experiments in the evaluative work we survey using datasets with specific numbers of labels. We can clearly see the influence of the *GTZAN* (10 genre labels) and *ISMIR2004* (6 genre labels) datasets. We find 16 works using datasets having 25 or more labels [25,30,31,40,106,107,153, 199,228,232,280,309,353,376,434,437], and only two using datasets having more than 100 labels [40, 437]. Over 72 % (316) of the papers with an experimental component uses only a single dataset, at least 20 % (90) use two datasets, and 6.2 % (27) use more than two datasets. Three references provide no details about the dataset used [54,145,331].




Fig. 3. The number of experiments in this survey employing datasets with specific numbers of labels.

We find a majority of the works with experimental components involves datasets that consist primarily of Western music. For instance, the label “classical”

is part of *GTZAN*, *ISMIR2004*, and *RWC*, and exists in the private datasets used in [22, 125, 144, 146, 173, 209, 225, 246, 266, 313, 341, 342, 344, 360, 363, 387]. The label “blues” is in *GTZAN*, *ISMIR2004*, and *Homburg*, and exists in the private datasets used by [4, 5, 19, 22, 125, 313, 342, 344, 358, 387]. And the label “jazz” is in *GTZAN*, *ISMIR2004*, *Homburg*, and *RWC*, and exists in the private datasets used by [19, 22, 57, 125, 144, 146, 173, 209, 225, 229, 266, 303, 313, 341, 342, 344, 358, 360, 387, 389]. However, we find that only about 10 % (48) of the private datasets used include music from around the world, such as Asia, Africa, and South America [3–5, 11, 19, 22, 57, 96–98, 125, 133–135, 137, 163, 164, 173, 179, 187, 202, 205, 209, 225, 229, 242, 243, 247–250, 255, 257, 266, 303, 308, 312, 313, 342, 344, 358, 360, 363, 385, 389, 430, 462, 463]. Finally, we find only 5 % (22) of the work with experimental components perform human validation of the “ground truth” labels in the public and/or private datasets used [8, 9, 34, 45, 79, 246, 247, 287, 289–291, 301, 346, 366, 367, 370, 383, 387, 394, 401, 408, 434]. For instance, Soltau et al. [401] validate the labels in their private four-class dataset with a human listening experiment.

2.3 Figures of Merit (FoMs)

Table 3 defines several FoMs we find in the work we surveyed. The FoMs most often reported in the work we survey here are those that accompany the *Classify* experimental design: *Mean accuracy*, *Recall*, *Precision*, *F-measure*, *Receiver Operating Characteristic (ROC)*, and the *Contingency table*. We find *Mean accuracy* in over 82 % (385) of the references. For instance, Fu et al. [123] compare the reported mean accuracies of 16 MGR algorithms using *Classify* in *GTZAN*. This computation can also involve taking into consideration “partial credit” for labelings in the correct hierarchical branch, e.g., [293, 294, 296]. When it appears, *Mean accuracy* is accompanied by a standard deviation (SD), or standard error of the mean (SEM), about 25 % (96) of the time. For instance, [116] uses these statistics to test the null hypothesis that the *Mean accuracy* of two MGR systems are not significantly different.

We find *Recall* in over 25 % (119) of the references. For instance, this FoM appears in the MIREX evaluations of MGR algorithms [295, 297–299]. When it appears, *Recall* is accompanied by the standard deviation or standard error of the mean in about 10 % (12) of the references. *Precision* appears in over 10 % (47) of the references. Together, *Mean accuracy*, *Recall* and *Precision* appear in over 6 % (31) of the work we survey. The *F-measure* can be computed in “Micro form” and “Macro form” [437], but we make no distinction here. This FoM appears in at least 17 works. For instance, Burred and Peeters [50] cite the *F-measure* of their MGR system, as well as its *Mean accuracy*, *Recall*, and *Precision*. We find the *ROC* in only 7 references [105, 121, 245, 349, 432, 440, 466]. For instance, Watanabe and Sato [440] plot the ROC of their sparrows trained to discriminate Baroque and Modern music.

We find a *Contingency table* reported in over 32 % (150) of the work we survey. For instance, Soltau et al. [401] show their MGR system often confuses the music in their private dataset having the labels “rock” or “pop,” and rarely confuses

Table 3. Figures of merit (FoMs) of MGR, their description, and the percentage of work (467) that cite them

FoM	Description	%
<i>Mean accuracy</i>	Proportion of the number of correct trials to the total number of trials of the system	82
<i>Contingency table</i>	Counts of labeling outcomes of the system for each labeled input	32
<i>Recall</i>	Proportion of the number of correct trials of the system to the total number of a specific input label	25
<i>Confusions</i>	Discussion of confusions of the system in general or with specifics	24
<i>Precision</i>	Proportion of the number of correct trials of the system to the total number of a specific output label	10
<i>F-measure</i>	Twice the product of <i>Recall</i> and <i>Precision</i> divided by their sum	4
<i>Composition</i>	Observations of the composition of clusters created by the system, and distances within and between	4
<i>Precision@ k</i>	Proportion of the number of correct items of a specific label in the k items retrieved by the system	3
<i>ROC</i>	<i>Precision</i> vs. <i>Recall</i> for several systems, parameters, etc.	1

music labeled “classic” with music labeled “techno” or “rock.” Of those works that present contingency tables, only 52 % (78) of them are accompanied by some musical reflection of the results. For instance, in the analysis of their *Contingency table*, Dixon et al. [93] reason that the high number of confusions produced between three of eight classes come from the fact that they are indistinguishable using meter- and tempo-sensitive features employed in their system. When they expand their feature set, the new *Contingency table* confirms this hypothesis.

General discussions about observed confusions without reference to a *Contingency table* are reported in over 8 % (39) of the references. For instance, Matityaho and Furst [271] note that their MGR system trained to discriminate between music labeled “classic” and “pop” classifies as “classic” a signal of complete silence and a “complex tone,” and as “pop” a signal of white noise. Using *Eyeball*, Bigerelle and Iost [44] argue that “Music classification becomes very logical [by comparing the fractal dimension]. ... Progressive music has the same fractal dimension as the electronic one: we could explain this fact by the abundance of synthesizers used in progressive music.” Only 15 works mention confusions in detail, e.g., a specific piece of misclassified music [3,68,98,210,228,301,342,366,367,370,407–410,412]. For instance, [410] notices that one MGR system persistently misclassifies as Hip hop “Kung Fu Fighting” by Carl Douglas, and as Classical “Why?” by Bronski Beat.

We find over 44 % (175) of the 397 works employing *Classify* report only one FoM and over 53 % (214) report more than one FoM. Only 21 present four or

more FoM [6,34,50,56,93,156,188,200,208,238–240,333,353,355,367,368,410,412,418,433]. For instance, Lidy [239] reports *mean accuracies, recalls, precisions, F-measures*, and *contingency tables* of the systems he tests.

The FoM most often reported in the case of the *Retrieve* experimental design is *Precision@k*. This FoM is reported in 12 of the 19 works using *Retrieve* [10,57,61,86,203,222,262,320,384,446,447,466]; and [388] reports “normalized precision” and “normalized recall,” which takes into account the ranking of retrieved elements. Of the references using *Retrieve*, the *ROC* is reported in [121,466]. For instance, Fu et al. [121] plot the ROC of four systems to show their retrieval approach provides statistically significant improvement.

The FoMs most often reported in the case of *Cluster* experimental design are based on observations of the cluster compositions. The contents of clusters are analyzed in over 62 % (18) of the *Clustering* experiments [33,107,136,196,236,237,253,301,302,304,318,320,334,350,351,365,415,430]. For instance, Rauber and Frühwirth [350] show that one cluster created by the self-organizing map method consists mainly of music labeled “classical.” Comparisons of cluster distances, e.g., that within classes to that between classes, are reported in five works [22,72,302,318,334]. For instance, Aucouturier and Pachet [22] compare average distances between neighbors of the same class to those between neighbors of different classes. Visualizations of the clusters, e.g., using self-organizing maps, are presented in seven works [189,218,241,242,350,351,473]. Both [233,417] report the “purity” of a collection of clusters, which measures the mean class homogeneity of the clusters.

Human-weighted ratings of classification and/or clustering results are reported in at least six works [22,154,203,246,366,370]. Other FoMs include, “staying time” [278,439] (measuring the time during which the subject stayed in the presence of musical stimuli for particular classes), “stability measure” [161,162] (essentially inter-intra class distance), “Hamming loss” [367–369] (describing instance-label pair misclassifications in a multilabel scenario), and “persistent misclassifications” [65,342,409,410] (noting instances that a system always mislabels).

3 Conclusion

While genre is an inevitable condition of human communication in general [469], a way to automatically identify it in music remains elusive. In this paper, we have attempted to present an exhaustive survey of evaluation in MGR, and to organize it along three dimensions: experimental design, datasets, and figures of merit. By the sheer size of this task, it is certain that we have missed some relevant work, misunderstood aspects of evaluation in some of the works we cite, and committed errors in the bibliography. We will thus continue to maintain this bibliography, and expand it when new work is published. The bibliography file we assembled for this work is available here: <http://imi.aau.dk/~bst/research/MGRbibliography.bib>; and the spreadsheet we created identifying the characteristics of the references is available here: <http://imi.aau.dk/~bst/research/MGRspreadsheet.xlsx>.

Acknowledgments. For Pepi [58]. Thank you to Carla Sturm for her bibliographic entry prowess. This work is supported in part by: Independent Postdoc Grant 11-105218 from Det Frie Forskningsråd; and the Danish Council for Strategic Research of the Danish Agency for Science Technology and Innovation in project CoSound, case no. 11-115328.

References

1. Abeßer, J., Dittmar, C., Großmann, H.: Automatic genre and artist classification by analyzing improvised solo parts from musical recordings. In: Proceedings of the Audio Mostly Conference, Piteå, Sweden, pp. 127–131 (2008)
2. Abeßer, J., Lukashevich, H.M., Dittmar, C., Schuller, G.: Genre classification using bass-related high-level features and playing styles. In: Proceedings of the ISMIR, pp. 453–458 (2009)
3. Abeßer, J., Lukashevich, H., Dittmar, C., Bräuer, P., Karuse, F.: Rule-based classification of musical genres from a global cultural background. In: Proceedings of the CMMR, pp. 317–336 (2010)
4. Abeßer, J., Bräuer, P., Lukashevich, H.M., Schuller, G.: Bass playing style detection based on high-level features and pattern similarity. In: Proceedings of the ISMIR, pp. 93–98 (2010)
5. Abeßer, J., Lukashevich, H., Bräuer, P.: Classification of music genres based on repetitive basslines. *J. New Music Res.* **41**(3), 239–257 (2012)
6. Ahonen, T.E.: Compressing lists for audio classification. In: Proceedings of the International Workshop on Machine Learning and Music. MML ’10, pp. 45–48. ACM, New York (2010)
7. Ahrendt, P., Meng, A., Larsen, J.: Decision time horizon for music genre classification using short-time features. In: Proceedings of the EUSIPCO (2004)
8. Ahrendt, P., Larsen, J., Goutte, C.: Co-occurrence models in music genre classification. In: Proceedings of the IEEE Workshop Machine Learning Signal Process, Sept 2005
9. Ahrendt, P.: Music genre classification systems - a computational approach. Ph.D. thesis, Technical University of Denmark (2006)
10. Almoosa, N., Bae, S.H., Juang, B.H.: Feature extraction by incremental parsing for music indexing. In: Proceedings of the ICASSP, pp. 2410–2413, Mar 2010
11. Anan, Y., Hatano, K., Bannai, H., Takeda, M.: Music genre classification using similarity functions. In: Proceedings of the ISMIR, pp. 693–698 (2011)
12. Andén, J., Mallat, S.: Multiscale scattering for audio classification. In: Proceedings of the ISMIR, pp. 657–662 (2011)
13. Anglade, A., Ramirez, R., Dixon, S.: Genre classification using harmony rules induced from automatic chord transcriptions. In: Proceedings of the ISMIR (2009)
14. Anglade, A., Ramirez, R., Dixon, S.: First-order logic classification models of musical genres based on harmony. In: Proceedings of the SMC (2009)
15. Anglade, A., Benetos, E., Mauch, M., Dixon, S.: Improving music genre classification using automatically induced harmony rules. *J. New Music Res.* **39**(4), 349–361 (2010)
16. Annesi, P., Basili, R., Gitto, R., Moschitti, A., Petitti, R.: Audio feature engineering for automatic music genre classification. In: Proceedings of the Recherche d’Information Assistée par Ordinateur, Pittsburgh, Pennsylvania, pp. 702–711 (2007)

17. Arabi, A.F., Lu, G.: Enhanced polyphonic music genre classification using high level features. In: IEEE International Conference on Signal and Image Processing Applications (2009)
18. Arenas, J., Larsen, J., Hansen, L., Meng, A.: Optimal filtering of dynamics in short-time features for music organization. In: Proceedings of the ISMIR (2006)
19. Ariyaratne, H., Zhang, D.: A novel automatic hierarchical approach to music genre classification. In: Proceedings of the ICME, pp. 564–569, July 2012
20. Aryafar, K., Shokoufandeh, A.: Music genre classification using explicit semantic analysis. In: Proceedings of the ACM MIRUM Workshop, Scottsdale, AZ, USA, pp. 33–38, Nov 2011
21. Aryafar, K., Jafarpour, S., Shokoufandeh, A.: Music genre classification using sparsity-eager support vector machines. Technical report, Drexel University (2012)
22. Aucouturier, J.J., Pachet, F.: Music similarity measures: what's the use? In: Proceedings of the ISMIR, Paris, France, Oct 2002
23. Aucouturier, J.J., Pachet, F.: Representing music genre: a state of the art. *J. New Music Res.* **32**(1), 83–93 (2003)
24. Aucouturier, J.J., Pampalk, E.: Introduction - from genres to tags: a little epistemology of music information retrieval research. *J. New Music Res.* **37**(2), 87–92 (2008)
25. Aucouturier, J.J.: Sounds like teen spirit: computational insights into the grounding of everyday musical terms. In: Minett, J., Wang, W. (eds.) *Language, Evolution and the Brain. Frontiers in Linguistic Series.* Academia Sinica Press, Taipei (2009)
26. Backer, E., van Kranenburg, P.: On musical stylometry - a pattern recognition approach. *Pattern Recogn. Lett.* **26**, 299–309 (2005)
27. Bağcı, U., Erzin, E.: Automatic classification of musical genres using inter-genre similarity. *IEEE Signal Proc. Lett.* **14**(8), 521–524 (2007)
28. Balkema, W.: Variable-size gaussian mixture models for music similarity measures. In: Proceedings of the ISMIR, pp. 491–494 (2007)
29. Balkema, W., van der Heijden, F.: Music playlist generation by assimilating GMMs into SOMs. *Pattern Recogn. Lett.* **31**(1), 1396–1402 (2010)
30. Barbedo, J.G.A., Lopes, A.: Automatic genre classification of musical signals. *EURASIP J. Adv. Signal Process.* **2007**, 1–12 (2007)
31. Barbedo, J.G.A., Lopes, A.: Automatic musical genre classification using a flexible approach. *J. Audio Eng. Soc.* **56**(7/8), 560–568 (2008)
32. Barbieri, G., Esposti, M.D., Pachet, F., Roy, P.: Is there a relation between the syntax and the fitness of an audio feature? In: Proceedings of the ISMIR (2010)
33. Barreira, L., Cavaco, S., da Silva, J.: Unsupervised music genre classification with a model-based approach. In: Proceedings of the Portuguese Conference on Progress in Artificial Intelligence, pp. 268–281 (2011)
34. Basili, R., Serafini, A., Stellato, A.: Classification of musical genre: a machine learning approach. In: Proceedings of the ISMIR (2004)
35. Behun, K.: Image features in music style recognition. In: Proceedings of the Central European Seminar on Computer Graphics (2012)
36. Benetos, E., Kotropoulos, C.: A tensor-based approach for automatic music genre classification. In: Proceedings of the EUSIPCO, Lausanne, Switzerland (2008)
37. Benetos, E., Kotropoulos, C.: Non-negative tensor factorization applied to music genre classification. *IEEE Trans. Audio Speech Lang. Process.* **18**(8), 1955–1967 (2010)

38. Bergstra, J., Casagrande, N., Erhan, D., Eck, D., Kégl, B.: Aggregate features and Adaboost for music classification. *Mach. Learn.* **65**(2–3), 473–484 (2006)
39. Bergstra, J.: Algorithms for classifying recorded music by genre. Master's thesis, Université de Montréal, Montréal, Canada, Aug 2006
40. Bergstra, J., Lacoste, A., Eck, D.: Predicting genre labels for artist using FreeDB. In: *Proceedings of the ISMIR*, pp. 85–88 (2006)
41. Bergstra, J., Mandel, M., Eck, D.: Scalable genre and tag prediction with spectral covariance. In: *Proceedings of the ISMIR* (2010)
42. Bertin-Mahieux, T., Weiss, R.J., Ellis, D.P.W.: Clustering beat-chroma patterns in a large music database. In: *Proceedings of the ISMIR*, Utrecht, Netherlands, Aug 2010
43. Bickerstaffe, A.C., Makalic, E.: MML classification of music genres. In: Gedeon, T.T.D., Fung, L.C.C. (eds.) *AI 2003. LNCS (LNAI)*, vol. 2903, pp. 1063–1071. Springer, Heidelberg (2003)
44. Bigerelle, M., Iost, A.: Fractal dimension and classification of music. *Chaos Soliton. Fract.* **11**(14), 2179–2192 (2000)
45. Blume, H., Haller, M., Botteck, M., Theimer, W.: Perceptual feature based music classification - a DSP perspective for a new type of application. In: *International Conference on Embedded Computer Systems* (2008)
46. Bogdanov, D., Serra, J., Wack, N., Herrera, P., Serra, X.: Unifying low-level and high-level music similarity measures. *IEEE Trans. Multimed.* **13**(4), 687–701 (2011)
47. Brecheisen, S., Kriegel, H.P., Kunath, P., Pryakhin, A.: Hierarchical genre classification for large music collections. In: *Proceedings of the ICME*, pp. 1385–1388, July 2006
48. Burred, J., Lerch, A.: A hierarchical approach to automatic musical genre classification. In: *Proceedings of the DAFx*, London, UK, Sept 2003
49. Burred, J.J., Lerch, A.: Hierarchical automatic audio signal classification. *J. Audio Eng. Soc.* **52**(7), 724–739 (2004)
50. Burred, J.J., Peeters, G.: An adaptive system for music classification and tagging. In: *International Workshop on Learning Semantics of Audio Signals* (2009)
51. Casey, M., Veltkamp, R., Goto, M., Leman, M., Rhodes, C., Slaney, M.: Content-based music information retrieval: current directions and future challenges. *Proc. IEEE* **96**(4), 668–696 (2008)
52. Cataltepe, Z., Yaslan, Y., Sonmez, A.: Music genre classification using MIDI and audio features. *EURASIP J. Adv. Signal Process.* **2007**, 1–8 (2007)
53. Chai, W., Vercoe, B.: Folk music classification using hidden Markov models. In: *International Conference on Artificial Intelligence* (2001)
54. Chang, L., Yu, X., Wan, W., Yao, J.: Research on fast music classification based on SVM in compressed domain. In: *Proceedings of the ICALIP*, pp. 638–642, July 2008
55. Chang, K., Jang, J.S.R., Iliopoulos, C.S.: Music genre classification via compressive sampling. In: *Proceedings of the ISMIR*, Amsterdam, The Netherlands, pp. 387–392, Aug 2010
56. Charami, M., Halloush, R., Tsekeridou, S.: Performance evaluation of TreeQ and LVQ classifiers for music information retrieval. In: Boukis, C., Pnevmatikakis, L., Polymenakos, L., et al. (eds.) *Artificial Intelligence and Innovations 2007: From Theory to Applications*. IFIP, vol. 247, pp. 331–338. Springer, Boston (2007)
57. Charbuillet, C., Tardieu, D., Peeters, G.: GMM supervector for content based music similarity. In: *Proceedings of the DAFx*, Paris, France, Sept 2011

58. Chase, A.: Music discriminations by carp “*Cyprinus carpio*”. *Learn. Behav.* **29**, 336–353 (2001)
59. Chathuranga, D., Jayaratne, L.: Musical genre classification using ensemble of classifiers. In: *Proceedings of the International Conference on Computational Intelligence, Modelling and Simulation*, pp. 237–242, Sept 2012
60. Chen, K., Gao, S., Zhu, Y., Sun, Q.: Music genres classification using text categorization method. In: *Proceedings of the IEEE Workshop on Multimedia Signal Processing*, pp. 221–224, Oct 2006
61. Chen, G., Wang, T., Herrera, P.: Relevance feedback in an adaptive space with one-class SVM for content-based music retrieval. In: *Proceedings of the ICALIP*, pp. 1153–1158, July 2008
62. Chen, L., Wright, P., Nejdl, W.: Improving music genre classification using collaborative tagging data. In: *International Conference on Web Search and Data Mining*, Barcelona, Spain, Feb 2009
63. Chen, S.H., Chen, S.H.: Content-based music genre classification using timbral feature vectors and support vector machine. In: *Proceedings of the International Conference on Interaction Sciences*, pp. 1095–1101, Nov 2009
64. Chen, S.H., Chen, S.H., Guido, R.C.: Music genre classification algorithm based on dynamic frame analysis and support vector machine. In: *IEEE International Symposium on Multimedia* (2010)
65. Chew, E., Volk, A., Lee, C.Y.: Dance music classification using inner metric analysis. In: Golden, B., Raghavan, S., Wasil, E. (eds.) *The Next Wave in Computing, Optimization, and Decision Technologies. Proceedings of the INFORMS Computing Society Conference*, pp. 355–370. Kluwer, Dordrecht (2005)
66. Cilibrasi, R., Vitányi, P., de Wolf, R.: Algorithmic clustering of music based on string compression. *Comput. Music J.* **28**(4), 49–67 (2004)
67. Cilibrasi, R., Vitanyi, P.: Clustering by compression. *IEEE Trans. Inf. Theory* **51**(4), 1523–1545 (2005)
68. Collins, N.: Influence in early electronic dance music: an audio content analysis investigation. In: *Proceedings of the ISMIR* (2012)
69. Conklin, D.: Melodic analysis with segment classes. *Mach. Learn.* **65**, 349–360 (2006)
70. Conklin, D.: Melody classification using patterns. In: *Proceedings of the International Workshop on Machine Learning and Music*, pp. 37–41 (2009)
71. Cornelis, O., Lesaffre, M., Moelants, D., Leman, M.: Access to ethnic music: advances and perspectives in content-based music information retrieval. *Signal Process.* **90**(4), 1008–1031 (2010)
72. Correa, D.C., Saito, J.H., da Costa, L.F.: Musical genres: beating to the rhythms of different drums. *New. J. Phys.* **12**(5), 053030 (2010)
73. Costa, C.H.L., Valle Jr., J.D., Koerich, A.L.: Automatic classification of audio data. In: *Proceedings of the IEEE International Conference on Systems, Man and Cybernetics*, pp. 562–567 (2004)
74. Costa, Y.M.G., Oliveira, L.S., Koerich, A.L., Gouyon, F.: Music genre recognition using spectrograms. In: *Proceedings of the International Conference on Systems, Signals and Image Processing* (2011)
75. Costa, Y., Oliveira, L., Koerich, A., Gouyon, F., Martins, J.: Music genre classification using LBP textural features. *Signal Process.* **92**(11), 2723–2737 (2012)
76. Costa, Y.M.G., Oliveira, L.S., Koerich, A.L., Gouyon, F.: Comparing textural features for music genre classification. In: *Proceedings of the IEEE World Congress on Computational Intelligence*, June 2012

77. Craft, A., Wiggins, G.A., Crawford, T.: How many beans make five? The consensus problem in music-genre classification and a new evaluation method for single-genre categorisation systems. In: *Proceedings of the ISMIR* (2007)
78. Craft, A.: The role of culture in the music genre classification task: human behaviour and its effect on methodology and evaluation. Technical report, Queen Mary University of London, Nov 2007
79. Crump, M.: A principal components approach to the perception of musical style. Master's thesis, University of Lethbridge (2002)
80. Cruz-Alcáza, P.P., Vidal-Ruiz, E.: Modeling musical style using grammatical inference techniques: a tool for classifying and generating melodies. In: *Proceedings of the WEDELMUSIC*, pp. 77–84, Sept 2003
81. Cruz-Alcázar, P.P., Vidal-Ruiz, E., Pérez-Cortés, J.C.: Musical style identification using grammatical inference: the encoding problem. In: Sanfeliu, A., Ruiz-Shulcloper, J. (eds.) *CIARP 2003. LNCS*, vol. 2905, pp. 375–382. Springer, Heidelberg (2003)
82. Cruz-Alcáza, P.P., Vidal-Ruiz, E.: Two grammatical inference applications in music processing. *Appl. Artif. Intell.* **22**(1/2), 53–76 (2008)
83. Dannenberg, R.B., Thom, B., Watson, D.: A machine learning approach to musical style recognition. In: *Proceedings of the ICMC*, pp. 344–347 (1997)
84. Dannenberg, R., Foote, J., Tzanetakis, G., Weare, C.: Panel: new directions in music information retrieval. In: *Proceedings of the ICMC* (2001)
85. Dannenberg, R.B.: Style in music. In: Argamon, S., Burns, K., Dubnov, S. (eds.) *The Structure of Style*, pp. 45–57. Springer, Heidelberg (2010)
86. DeCoro, C., Barutcuoglu, S., Fiebrink, R.: Bayesian aggregation for hierarchical genre classification. In: *Proceedings of the ISMIR* (2007)
87. Dehghani, M., Lovett, A.M.: Efficient genre classification using qualitative representations. In: *Proceedings of the ISMIR*, pp. 353–354 (2006)
88. Dellandrea, E., Harb, H., Chen, L.: Zipf, neural networks and SVM for musical genre classification. In: *Proceedings of the IEEE International Symposium on Signal Processing and Information Technology*, pp. 57–62, Dec 2005
89. Deshpande, H., Singh, R., Nam, U.: Classification of music signals in the visual domain. In: *Proceedings of the DAFx*, Limerick, Ireland, Dec 2001
90. Dieleman, S., Brakel, P., Schrauwen, B.: Audio-based music classification with a pretrained convolutional network. In: *Proceedings of the ISMIR* (2011)
91. Diodati, P., Piazza, S.: Different amplitude and time distribution of the sound of light and classical music. *Eur. Phys. J. B - Condens. Matter Complex Syst.* **17**, 143–145 (2000)
92. Dixon, S., Pampalk, E., Widmer, G.: Classification of dance music by periodicity patterns. In: *Proceedings of the ISMIR* (2003)
93. Dixon, S., Gouyon, F., Widmer, G.: Towards characterisation of music via rhythmic patterns. In: *Proceedings of the ISMIR*, Barcelona, Spain, pp. 509–517 (2004)
94. Dixon, S., Mauch, M., Anglade, A.: Probabilistic and logic-based modelling of harmony. In: Ystad, S., Aramaki, M., Kronland-Martinet, R., Jensen, K. (eds.) *MMR 2010. LNCS*, vol. 6684, pp. 1–19. Springer, Heidelberg (2011)
95. Dor, O., Reich, Y.: An evaluation of musical score characteristics for automatic classification of composers. *Comput. Music J.* **35**(3), 86–97 (2011)
96. Doraisamy, S., Golzari, S., Norowi, N.M., Sulaiman, M.N.B., Udzir, N.I.: A study on feature selection and classification techniques for automatic genre classification of traditional Malay music. In: *Proceedings of the ISMIR*, Philadelphia, PA (2008)

97. Doraisamy, S., Golzari, S.: Automatic musical genre classification and artificial immune recognition system. In: Raś, Z.W., Wiczorkowska, A.A. (eds.) *Advances in Music Information Retrieval. SCI*, vol. 274, pp. 390–402. Springer, Heidelberg (2010)
98. Doudpota, S.M., Guha, S.: Mining movies for song sequences with video based music genre identification system. *Int. J. Info. Process. Manag.* **49**(2), 529–544 (2013)
99. Downie, J., Ehmann, A., Tcheng, D.: Real-time genre classification for music digital libraries. In: *Proceedings of the Joint ACM/IEEE Conference on Digital Libraries*, p. 377, June 2005
100. Downie, J.S.: The music information retrieval evaluation exchange (2005–2007): a window into music information retrieval research. *Acoust. Sci. Technol.* **29**(4), 247–255 (2008)
101. Downie, J.S., Ehmann, A.F., Bay, M., Jones, M.C.: The music information retrieval evaluation exchange: some observations and insights. In: Raś, Z.W., Wiczorkowska, A.A. (eds.) *Advances in Music Information Retrieval. SCI*, vol. 274, pp. 93–115. Springer, Heidelberg (2010)
102. Draman, N.A., Wilson, C., Ling, S.: Modified AIS-based classifier for music genre classification. In: *Proceedings of the ISMIR*, pp. 369–374 (2010)
103. Draman, N.A., Ahmad, S., Muda, A.K.: Recognizing patterns of music signals to songs classification using modified AIS-based classifier. In: Zain, J.M., Wan Mohd, W.M., El-Qawasmeh, E. (eds.) *ICSECS 2011, Part II. CCIS*, vol. 180, pp. 724–737. Springer, Heidelberg (2011)
104. Dunker, P., Dittmar, C., Begau, A., Nowak, S., Gruhne, M.: Semantic high-level features for automated cross-modal slideshow generation. In: *Proceedings of the Content-Based Multimedia Indexing*, pp. 144–149 (2009)
105. Esmaili, S., Krishnan, S., Raahemifar, K.: Content based audio classification and retrieval using joint time-frequency analysis. In: *Proceedings of the ICASSP*, vol. 5, pp. 665–668 (2004)
106. Ezzaïdi, H., Rouat, J.: Comparison of the statistical and information theory measures: Application to automatic musical genre classification. In: *Proceedings of the IEEE Workshop on Machine Learning for Signal Processing*, pp. 241–246, Aug 2007
107. Ezzaïdi, H., Bahoura, M., Rouat, J.: Taxonomy of musical genres. In: *International Conference on Signal Image Technology and Internet Based Systems* (2009)
108. Fadeev, A., Missaoui, O., Frigui, H.: Dominant audio descriptors for audio classification and retrieval. In: *Proceedings of the ICMLA*, Louisville, KY, USA, pp. 75–78, Dec 2009
109. Feng, Y., Dou, H., Qian, Y.: A study of audio classification on using different feature schemes with three classifiers. In: *Proceedings of the International Conference on Information, Networking, Automation*, pp. 298–302 (2010)
110. Fernández, F., Chávez, F., Alcalá, R., Herrera, F.: Musical genre classification by means of fuzzy rule-based systems: a preliminary approach. In: *IEEE Congress on Evolutionary Computation* (2011)
111. Fernández, F., Chávez, F.: Fuzzy rule based system ensemble for music genre classification. In: Machado, P., Romero, J., Carballal, A. (eds.) *EvoMUSART 2012. LNCS*, vol. 7247, pp. 84–95. Springer, Heidelberg (2012)
112. Fiebrink, R., Fujinaga, I.: Feature selection pitfalls and music classification. In: *Proceedings of the ISMIR*, Victoria, BC, Canada, pp. 340–341 (2006)
113. Fiebrink, R.: An exploration of feature selection as a tool for optimizing musical genre classification. Master's thesis, McGill University, June 2006

114. Flexer, A., Pampalk, E., Widmer, G.: Hidden Markov models for spectral similarity of songs. In: *Proceedings of the DAFx*, Madrid, Spain, Sept 2005
115. Flexer, A., Gouyon, F., Dixon, S., Widmer, G.: Probabilistic combination of features for music classification. In: *Proceedings of the ISMIR*, Victoria, BC, Canada, pp. 111–114, Oct 2006
116. Flexer, A.: Statistical evaluation of music information retrieval experiments. *J. New Music Res.* **35**(2), 113–120 (2006)
117. Flexer, A.: A closer look on artist filters for musical genre classification. In: *Proceedings of the ISMIR*, Vienna, Austria, Sept 2007
118. Flexer, A., Schnitzer, D.: Album and artist effects for audio similarity at the scale of the web. In: *Proceedings of the SMC*, Porto, Portugal, pp. 59–64, July 2009
119. Flexer, A., Schnitzer, D.: Effects of album and artist filters in audio similarity computed for very large music databases. *Comput. Music J.* **34**(3), 20–28 (2010)
120. Frederico, G.: Classification into musical genres using a rhythmic kernel. In: *Proceedings of the SMC* (2004)
121. Fu, Z., Lu, G., Ting, K.M., Zhang, D.: Learning naive Bayes classifiers for music classification and retrieval. In: *Proceedings of the ICPR*, pp. 4589–4592 (2010)
122. Fu, Z., Lu, G., Ting, K.M., Zhang, D.: On feature combination for music classification. In: *Proceedings of the International Workshop on Structural and Syntactic Pattern Recognition*, pp. 453–462 (2010)
123. Fu, Z., Lu, G., Ting, K.M., Zhang, D.: A survey of audio-based music classification and annotation. *IEEE Trans. Multimed.* **13**(2), 303–319 (2011)
124. Fu, Z., Lu, G., Ting, K.M., Zhang, D.: Music classification via the bag-of-features approach. *Pattern Recogn. Lett.* **32**(14), 1768–1777 (2011)
125. García, J., Hernández, E., Meng, A., Hansen, L.K., Larsen, J.: Discovering music structure via similarity fusion. In: *Proceedings of the Music, Brain and Cognition Workshop* (2007)
126. García-García, D., Arenas-García, J., Parrado-Hernandez, E., de Maria, F.D.: Music genre classification using the temporal structure of songs. In: *IEEE International Workshop on Machine Learning for Signal Processing*, Kittilä, Finland, Aug–Sept 2010
127. García, A., Arenas, J., García, D., Parrado, E.: Music genre classification based on dynamical models. In: *International Conference on Pattern Recognition Applications and Methods*, pp. 250–256 (2012)
128. Gedik, A.C., Alpkoçak, A.: Instrument independent musical genre classification using random 3000 ms segment. In: Savacı, F.A. (ed.) *TAINN 2005. LNCS (LNAI)*, vol. 3949, pp. 149–157. Springer, Heidelberg (2006)
129. Genussov, M., Cohen, I.: Musical genre classification of audio signals using geometric methods. In: *Proceedings of the EUSIPCO*, Aalborg, Denmark, pp. 497–501, Aug 2010
130. Ghosal, A., Chakraborty, R., Dhara, B., Saha, S.: Instrumental/song classification of music signal using RANSAC. In: *Proceedings of the International Conference on Electronics Computer Technology*, pp. 269–272, Apr 2011
131. Gjerdengen, R.O., Perrott, D.: Scanning the dial: the rapid recognition of music genres. *J. New Music Res.* **37**(2), 93–100 (2008)
132. Golub, S.: Classifying recorded music. Master's thesis, University of Edinburgh, Edinburgh, Scotland, UK (2000)
133. Golzari, S., Doraisamy, S., Sulaiman, N., Udzir, N.I.: A hybrid approach to traditional Malay music genre classification: combining feature selection and artificial immune recognition system. In: *Proceedings of the International Symposium on Information Technology*, Aug 2008

134. Golzari, S., Doraisamy, S., Sulaiman, M.N.B., Udzir, N.I., Norowi, N.M.: Artificial immune recognition system with nonlinear resource allocation method and application to traditional Malay music genre classification. In: Bentley, P.J., Lee, D., Jung, S. (eds.) ICARIS 2008. LNCS, vol. 5132, pp. 132–141. Springer, Heidelberg (2008)
135. Golzari, S., Doraisamy, S., Norowi, N.M., Sulaiman, M.N., Udzir, N.I.: A comprehensive study in benchmarking feature selection and classification approaches for traditional Malay music genre classification. In: *Proceedings of Data Mining*, pp. 71–77, July 2008
136. González, A., Granados, A., Camacho, D., de Borja Rodríguez, F.: Influence of music representation on compression-based clustering. In: *Proceedings of the IEEE Congress on Evolutionary Computation* (2010)
137. Goulart, A.J.H., Maciel, C.D., Guido, R.C., Paulo, K.C.S., da Silva, I.N.: Music genre classification based on entropy and fractal lacunarity. In: *IEEE International Symposium on Multimedia* (2011)
138. Goulart, A., Guido, R., Maciel, C.: Exploring different approaches for music genre classification. *Egypt. Inf. J.* **13**(2), 59–63 (2012)
139. Gouyon, F., Dixon, S., Pampalk, E., Widmer, G.: Evaluating rhythmic descriptors for musical genre classification. In: *Proceedings of the International Audio Engineering Society Conference*, pp. 196–204 (2004)
140. Gouyon, F., Dixon, S.: Dance music classification: a tempo-based approach. In: *Proceedings of the ISMIR*, pp. 501–504 (2004)
141. Gouyon, F.: A computational approach to rhythm description – audio features for the computation of rhythm periodicity functions and their use in tempo induction and music content processing. Ph.D. thesis, Universitat Pompeu Fabra (2005)
142. Govaerts, S., Corthaut, N., Duval, E.: Using search engine for classification: does it still work? In: *Proceedings of the IEEE International Symposium on Multimedia*, pp. 483–488, Dec 2009
143. Grimaldi, M., Cunningham, P., Kokaram, A.: A wavelet packet representation of audio signals for music genre classification using different ensemble and feature selection techniques. In: *Proceedings of the ACM Multimedia*, pp. 102–108 (2003)
144. Grimaldi, M., Cunningham, P., Kokaram, A.: Discrete wavelet packet transform and ensembles of lazy and eager learners for music genre classification. *Multimed. Syst.* **11**, 422–437 (2006)
145. Grosse, R., Raina, R., Kwong, H., Ng, A.Y.: Shift-invariant sparse coding for audio classification. In: *Proceedings of the Twenty-third Conference on Uncertainty in Artificial Intelligence* (2007)
146. Guaus, E.: Audio content processing for automatic music genre classification: descriptors, databases, and classifiers. Ph.D. thesis, Universitat Pompeu Fabra, Barcelona, Spain (2009)
147. Hamel, P., Eck, D.: Learning features from music audio with deep belief networks. In: *Proceedings of the ISMIR* (2010)
148. Han, K.P., Park, Y.S., Jeon, S.G., Lee, G.C., Ha, Y.H.: Genre classification system of TV sound signals based on a spectrogram analysis. *IEEE Trans. Consumer Elect.* **44**(1), 33–42 (1998)
149. Hansen, L.K., Ahrendt, P., Larsen, J.: Towards cognitive component analysis. In: *Proceedings of the International and Interdisciplinary Conference on Adaptive Knowledge Representation and Reasoning*, Espoo, Finland, pp. 148–153, June 2005

150. Harb, H., Chen, L., Auloge, J.Y.: Mixture of experts for audio classification: an application to male female classification and musical genre recognition. In: Proceedings of the ICME (2004)
151. Harb, H., Chen, L.: A general audio classifier based on human perception motivated model. *Multimed. Tools Appl.* **34**, 375–395 (2007)
152. Hartmann, K., Büchner, D., Berndt, A., Nürnberger, A., Lange, C.: Interactive data mining and machine learning techniques for musicology. In: Proceedings of the Conference on Interdisciplinary Musicology, pp. 1–8 (2007)
153. Hartmann, M.A.: Testing a spectral-based feature set for audio genre classification. Master's thesis, University of Jyväskylä, June 2011
154. Heittola, T.: Automatic classification of music signals. Master's thesis, Tampere University of Technology, Feb 2003
155. Henaff, M., Jarrett, K., Kavukcuoglu, K., LeCun, Y.: Unsupervised learning of sparse features for scalable audio classification. In: Proceedings of the ISMIR, Miami, FL, Oct 2011
156. de la Higuera, C., Piat, F., Tantini, F.: Learning stochastic finite automata for musical style recognition. In: Farré, J., Litovsky, I., Schmitz, S. (eds.) CIAA 2005. LNCS, vol. 3845, pp. 345–346. Springer, Heidelberg (2006)
157. Hillewaere, R., Manderick, B., Conklin, D.: Global feature versus event models for folk song classification. In: Proceedings of the ISMIR, pp. 729–733 (2009)
158. Hillewaere, R., Manderick, B., Conklin, D.: Melodic models for polyphonic music classification. In: Proceedings of the International Workshop on Machine Learning and Music (2009)
159. Hillewaere, R., Manderick, B., Conklin, D.: String quartet classification with monophonic models. In: Proceedings of the ISMIR, pp. 537–542 (2010)
160. Hillewaere, R., Manderick, B., Conklin, D.: String methods for folk tune genre classification. In: Proceedings of the ISMIR (2012)
161. Holzapfel, A., Stylianou, Y.: A statistical approach to musical genre classification using non-negative matrix factorization. In: Proceedings of the ICASSP, pp. 693–696, Apr 2007
162. Holzapfel, A., Stylianou, Y.: Musical genre classification using nonnegative matrix factorization-based features. *IEEE Trans. Audio Speech Lang. Process.* **16**(2), 424–434 (2008)
163. Holzapfel, A., Stylianou, Y.: Rhythmic similarity of music based on dynamic periodicity warping. In: Proceedings of the ICASSP, pp. 2217–2220 (2008)
164. Holzapfel, A., Stylianou, Y.: A scale based method for rhythmic similarity of music. In: Proceedings of the ICASSP, Taipei, Taiwan, pp. 317–320, Apr 2009
165. Homburg, H., Mierswa, I., Möller, B., Morik, K., Wurst, M.: A benchmark dataset for audio classification and clustering. In: Proceedings of the ISMIR, London, UK (2005)
166. Honingh, A., Bod, R.: Clustering and classification of music by interval categories. In: Agon, C., Andreatta, M., Assayag, G., Amiot, E., Bresson, J., Mandereau, J. (eds.) MCM 2011. LNCS, vol. 6726, pp. 346–349. Springer, Heidelberg (2011)
167. Hsieh, C.T., Han, C.C., Lee, C.H., Fan, K.C.: Pattern classification using eigenspace projection. In: Proceedings of the International Conference on Intelligent Information Hiding and Multimedia Signal Processing, pp. 154–157, July 2012
168. Hu, Y., Ogihara, M.: Genre classification for million song dataset using confidence-based classifiers combination. In: Proceedings of the ACM SIGIR, pp. 1083–1084. ACM, New York (2012)

169. Iñesta, J.M., Ponce de León, P.J., Heredia, J.L.: A ground-truth experiment on melody genre recognition in absence of timbre. In: Proceedings of the International Conference on Music Perception and Cognition, pp. 758–761 (2009)
170. ISMIR: Genre results (2004). http://ismir2004.ismir.net/genre_contest/index.htm
171. ISMIS: Genre results, Mar 2011. <http://tunedit.org/challenge/music-retrieval>
172. Jang, D., Jin, M., Yoo, C.D.: Music genre classification using novel features and a weighted voting method. In: Proceedings of the ICME, pp. 1377–1380 (2008)
173. Jennings, H., Ivanov, P., Martins, A., da Silva, P., Viswanathan, G.: Variance fluctuations in nonstationary time series: a comparative study of music genres. *Phys. A: Stat. Theor. Phys.* **336**(3–4), 585–594 (2004)
174. Jensen, J., Christensen, M., Murthi, M., Jensen, S.: Evaluation of MFCC estimation techniques for music similarity. In: Proceedings of the EUSIPCO (2006)
175. Jensen, K.: Music genre classification using an auditory memory model. In: Ystad, S., Aramaki, M., Kronland-Martinet, R., Jensen, K., Mohanty, S. (eds.) CMMR and FRSM 2011. LNCS, vol. 7172, pp. 79–88. Springer, Heidelberg (2012)
176. Jiang, D.N., L.-Lu, Zhang, H.J., Tao, J.H., Cai, L.H.: Music type classification by spectral contrast features. In: Proceedings of the ICME (2002)
177. Jin, X., Bie, R.: Random forest and PCA for self-organizing maps based automatic music genre discrimination. In: Proceedings of the Data Mining, pp. 414–417 (2006)
178. Lu, J., Wan, W., Yu, X., Li, C.: Music style classification using support vector machine. In: Proceedings of the International Conference on Wireless Communication and Mobile Computing, pp. 452–455, Dec 2009
179. Jothilakshmi, S., Kathiresan, N.: Automatic music genre classification for Indian music. In: Proceedings of the International Conference on Software and Computer Applications (2012)
180. Ju, H., Xu, J.X., VanDongen, A.M.J.: Classification of musical styles using liquid state machines. In: Proceedings of the International Joint Conference on Neural Networks, pp. 1–7 (2010)
181. Kaminskas, M., Ricci, F.: Contextual music information retrieval and recommendation: state of the art and challenges. *Comput. Sci. Rev.* **6**(2–3), 89–119 (2012)
182. Karkavitsas, G.V., Tsihrintzis, G.A.: Automatic music genre classification using hybrid genetic algorithms. In: Tsihrintzis, G.A., Virvou, M., Jain, L.C., Howlett, R.J. (eds.) IIMSS 2011. SIST, vol. 11, pp. 323–335. Springer, Heidelberg (2011)
183. Karkavitsas, G.V., Tsihrintzis, G.A.: Optimization of an automatic music genre classification system via hyper-entities. In: Proceedings of the International Conference on Intelligent Information Hiding and Multimedia Signal Processing, pp. 449–452 (2012)
184. Karydis, I.: Symbolic music genre classification based on note pitch and duration. In: Manolopoulos, Y., Pokorný, J., Sellis, T.K. (eds.) ADBIS 2006. LNCS, vol. 4152, pp. 329–338. Springer, Heidelberg (2006)
185. Karydis, I., Nanopoulos, A., Manolopoulos, Y.: Symbolic musical genre classification based on repeating patterns. In: Proceedings of the ACM Workshop on Audio and Music Computing Multimedia, pp. 53–58 (2006)
186. Kim, H.G., Cho, J.M.: Car audio equalizer system using music classification and loudness compensation. In: Proceedings of the International Conference on ICT Convergence (2011)
187. Kini, S., Gulati, S., Rao, P.: Automatic genre classification of North Indian devotional music. In: National Conference on Communications (2011)

188. Kirss, P.: Audio based genre classification of electronic music. Master's thesis, University of Jyväskylä, June 2007
189. Kitahara, T., Tsuchihashi, Y., Katayose, H.: Music genre classification and similarity calculation using bass-line features. In: Proceedings of the IEEE International Symposium on Multimedia, pp. 574–579, Dec 2008
190. Kobayakawa, M., Hoshi, M.: Musical genre classification of MPEG-4 Twin VQ audio data. In: Proceedings of the ICME (2011)
191. Koerich, A., Poitevin, C.: Combination of homogeneous classifiers for musical genre classification. In: IEEE International Conference on Systems, Man and Cybernetics, Oct 2005
192. Kofod, C., Ortiz-Arroyo, D.: Exploring the design space of symbolic music genre classification using data mining techniques. In: Proceedings of the International Conference on Computational Intelligence for Modelling, Control and Automation, pp. 432–448, Dec 2008
193. Kosina, K.: Music genre recognition. Master's thesis, Hagenberg Technical University, Hagenberg, Germany, June 2002
194. Kostek, B., Kupryjanow, A., Zwan, P., Jiang, W., Raś, Z.W., Wojnarski, M., Swietlicka, J.: Report of the ISMIS 2011 contest: music information retrieval. In: Kryszkiewicz, M., Rybinski, H., Skowron, A., Raś, Z.W. (eds.) ISMIS 2011. LNCS, vol. 6804, pp. 715–724. Springer, Heidelberg (2011)
195. Kotropoulos, C., Arce, G.R., Panagakis, Y.: Ensemble discriminant sparse projections applied to music genre classification. In: Proceedings of the ICPR, pp. 823–825, Aug 2010
196. van Kranenburg, P., Baker, W.: Musical style recognition - a quantitative approach. In: Proceedings of the Conference on Interdisciplinary Musicology (2004)
197. van Kranenburg, P.: On measuring musical style - the case of some disputed organ fugues in the J.S. Bach (BWV) catalogue. *Computing In Musicology* (2007-8)
198. van Kranenburg, P., Garbers, J., Volk, A., Wiering, F., Grijp, L., Velkamp, R.: Collaboration perspectives for folk song research and music information retrieval: the indispensable role of computational musicology. *J. Interdiscipl. Music Stud.* **4**(1), 17–43 (2010)
199. van Kranenburg, P., Volk, A., Wiering, F.: A comparison between global and local features for computational classification of folk song melodies. *J. New Music Res.* **42**, 1–18 (2012)
200. Krasser, J., Abeßer, J., Großmann, H., Dittmar, C., Cano, E.: Improved music similarity computation based on tone objects. In: Proceedings of the Audio Mostly Conference, pp. 47–54 (2012)
201. Krumhansl, C.L.: Plink: “thin slices” of music. *Music Percept.: Interdiscipl. J.* **27**(5), 337–354 (2010)
202. Kuo, F.F., Shan, M.K.: A personalized music filtering system based on melody style classification. In: Proceedings of the IEEE International Conference on Data Mining, pp. 649–652 (2002)
203. Kuo, F.F., Shan, M.K.: Looking for new, not known music only: music retrieval by melody style. In: Proceedings of the Joint ACM/IEEE Conference on Digital Libraries, pp. 243–251, June 2004
204. Lambrou, T., Kudumakis, P., Speller, R., Sandler, M., Linney, A.: Classification of audio signals using statistical features on time and wavelet transform domains. In: Proceedings of the ICASSP, pp. 3621–3624, May 1998
205. Lampropoulos, A.S., Lampropoulou, P.S., Tsihrintzis, G.A.: Musical genre classification enhanced by improved source separation techniques. In: Proceedings of the ISMIR (2005)

206. Lampropoulos, A.S., Lampropoulou, P.S., Tsihrintzis, G.A.: Music genre classification based on ensemble of signals produced by source separation methods. *Intell. Dec. Technol.* **4**(3), 229–237 (2010)
207. Lampropoulos, A., Lampropoulou, P., Tsihrintzis, G.: A cascade-hybrid music recommender system for mobile services based on musical genre classification and personality diagnosis. *Multimed. Tools Appl.* **59**, 241–258 (2012)
208. Langlois, T., Marques, G.: A music classification method based on timbral features. In: *Proceedings of the ISMIR* (2009)
209. Langlois, T., Marques, G.: Automatic music genre classification using a hierarchical clustering and a language model approach. In: *Proceedings of the International Conference on Advances in Multimedia* (2009)
210. Lee, J.-W., Park, S.-B., Kim, S.-K.: Music genre classification using a time-delay neural network. In: Wang, J., Yi, Z., Žurada, J.M., Lu, B.-L., Yin, H. (eds.) *ISNN 2006. LNCS*, vol. 3972, pp. 178–187. Springer, Heidelberg (2006)
211. Lee, C.H., Shih, J.L., Yu, K.M., Su, J.M.: Automatic music genre classification using modulation spectral contrast feature. In: *Proceedings of the ICME* (2007)
212. Lee, C.H., Shih, J.L., Yu, K.M., Lin, H.S., Wei, M.H.: Fusion of static and transitional information of cepstral and spectral features for music genre classification. In: *IEEE Asia-Pacific Service Computing Conference* (2008)
213. Lee, C.H., Lin, H.S., Chou, C.H., Shih, J.L.: Modulation spectral analysis of static and transitional information of cepstral and spectral features for music genre classification. In: *Proceedings of the International Conference on Intelligent Information Hiding and Multimedia Signal Processing* (2009)
214. Lee, C., Shih, J., Yu, K., Lin, H.: Automatic music genre classification based on modulation spectral analysis of spectral and cepstral features. *IEEE Trans. Multimed.* **11**(4), 670–682 (2009)
215. Lee, H., Largman, Y., Pham, P., Ng, A.Y.: Unsupervised feature learning for audio classification using convolutional deep belief networks. In: *Proceedings of the Neural Information Processing Systems*, Vancouver, BC, Canada, Dec 2009
216. Lee, C.H., Chou, C.H., Lien, C.C., Fang, J.C.: Music genre classification using modulation spectral features and multiple prototype vectors representation. In: *International Congress on Image and Signal Processing* (2011)
217. Lehn-Schioler, T., Arenas-García, J., Petersen, K.B., Hansen, L.: A genre classification plug-in for data collection. In: *Proceedings of the ISMIR* (2006)
218. de León, P., Iñesta, J.: Musical style identification using self-organising maps. In: *Proceedings of the WEDELMUSIC*, pp. 82–89 (2002)
219. de León, P., Iñesta, J.: Feature-driven recognition of music styles. In: Perales, F.J., Campilho, A.C., Pérez, N., Sanfeliu, A. (eds.) *IbPRIA 2003. LNCS*, vol. 2652, pp. 773–781. Springer, Heidelberg (2003)
220. de León, P.J.P., Iñesta, J.M.: Musical style classification from symbolic data: a two-styles case study. In: Wiil, U.K. (ed.) *CMMR 2003. LNCS*, vol. 2771, pp. 167–178. Springer, Heidelberg (2004)
221. de León, P.P., Iñesta, J.: Pattern recognition approach for music style identification using shallow statistical descriptors. *IEEE Trans. Syst. Man Cybern.: Part C: Appl. Rev.* **37**(2), 248–257 (2007).
222. de León, F., Martínez, K.: Enhancing timbre model using MFCC and its time derivatives for music similarity estimation. In: *Proceedings of the EUSIPCO*, Bucharest, Romania, pp. 2005–2009, Aug 2012
223. de León, F., Martínez, K.: Towards efficient music genre classification using FastMap. In: *Proceedings of the DAFx* (2012)

- 224. Lerch, A.: An Introduction to Audio Content Analysis: Applications in Signal Processing and Music Informatics. Wiley/IEEE Press, Hoboken (2012)
- 225. Levy, M., Sandler, M.: Lightweight measures for timbral similarity of musical audio. In: Proceedings of the ACM Workshop on Audio and Music Computing Multimedia, pp. 27–36 (2006)
- 226. Li, T., Ogihara, M., Li, Q.: A comparative study on content-based music genre classification. In: Proceedings of the International ACM SIGIR Conference on Research and Development in Information Retrieval (2003)
- 227. Li, T., Tzanetakis, G.: Factors in automatic musical genre classification of audio signals. In: Proceedings of the IEEE Workshop on Applications of the Signal Processing to Audio and Acoustics (2003)
- 228. Li, T., Ogihara, M.: Music artist style identification by semi-supervised learning from both lyrics and contents. In: Proceedings of the ACM Multimedia (2004)
- 229. Li, M., Sleep, R.: Melody classification using a similarity metric based on Kolmogorov complexity. In: Proceedings of the SMC (2004)
- 230. Li, M., Sleep, R.: Genre classification via an LZ78-based string kernel. In: Proceedings of the ISMIR (2005)
- 231. Li, T., Ogihara, M.: Music genre classification with taxonomy. In: Proceedings of the ICASSP, Philadelphia, PA, pp. 197–200, Mar 2005
- 232. Li, T., Ogihara, M.: Toward intelligent music information retrieval. *IEEE Trans. Multimed.* **8**(3), 564–574 (2006)
- 233. Li, T., Ogihara, M., Shao, B., Wang, D.: Machine learning approaches for music information retrieval. In: Theory and Novel Applications of Machine Learning. I-Tech, Austria (2009)
- 234. Li, T.L., Chan, A.B., Chun, A.H.: Automatic musical pattern feature extraction using convolutional neural network. In: Proceedings of the International Conference on Data Mining and Applications (2010)
- 235. Li, T., Chan, A.: Genre classification and the invariance of MFCC features to key and tempo. In: Proceedings of the International Conference on Multimedia Modeling, Taipei, China, Jan 2011
- 236. Lidy, T., Rauber, A.: Genre-oriented organization of music collections using the SOMeJB system: an analysis of rhythm patterns and other features. In: Proceedings of the DELOS Workshop Multimedia Contents in Digital Libraries (2003)
- 237. Lidy, T.: Marsyas and rhythm patterns: evaluation of two music genre classification systems. In: Proceedings of the Workshop Data Analysis, June 2003
- 238. Lidy, T., Rauber, A.: Evaluation of feature extractors and psycho-acoustic transformations for music genre classification. In: Proceedings of the ISMIR (2005)
- 239. Lidy, T.: Evaluation of new audio features and their utilization in novel music retrieval applications. Master's thesis, Vienna University of Technology, Dec 2006
- 240. Lidy, T., Rauber, A., Pertusa, A., Iñesta, J.M.: Improving genre classification by combination of audio and symbolic descriptors using a transcription system. In: Proceedings of the ISMIR, Vienna, Austria, pp. 61–66, Sept 2007
- 241. Lidy, T., Rauber, A.: Classification and clustering of music for novel music access applications. In: Cord, M., Cunningham, P. (eds.) *Machine Learning Techniques for Multimedia*, pp. 249–285. Springer, Heidelberg (2008)
- 242. Lidy, T., Silla, C., Cornelis, O., Gouyon, F., Rauber, A., Kaestner, C.A., Koerich, A.L.: On the suitability of state-of-the-art music information retrieval methods for analyzing, categorizing and accessing non-western and ethnic music collections. *Signal Process.* **90**(4), 1032–1048 (2010)

243. Lidy, T., Mayer, R., Rauber, A., de León, P.P., Pertusa, A., Quereda, J.: A cartesian ensemble of feature subspace classifiers for music categorization. In: *Proceedings of the ISMIR*, pp. 279–284 (2010)
244. Lim, S.C., Jang, S.J., Lee, S.P., Kim, M.Y.: Music genre/mood classification using a feature-based modulation spectrum. In: *Proceedings of the International Conference on Modelling, Identification and Control* (2011)
245. Lin, C.-R., Liu, N.-H., Wu, Y.-H., Chen, A.L.P.: Music classification using significant repeating patterns. In: Lee, Y.J., Li, J., Whang, K.-Y., Lee, D. (eds.) *DASFAA 2004. LNCS*, vol. 2973, pp. 506–518. Springer, Heidelberg (2004)
246. Lippens, S., Martens, J., De Mulder, T.: A comparison of human and automatic musical genre classification. In: *Proceedings of the ICASSP*, pp. 233–236, May 2004
247. Liu, Y., Xu, J., Wei, L., Tian, Y.: The study of the classification of Chinese folk songs by regional style. In: *Proceedings of the International Conference on Semantic Computing*, pp. 657–662, Sept 2007
248. Liu, X., Yang, D., Chen, X.: New approach to classification of Chinese folk music based on extension of hmm. In: *Proceedings of the ICALIP*, pp. 1172–1179, July 2008
249. Liu, Y., Wei, L., Wang, P.: Regional style automatic identification for Chinese folk songs. In: *World Congress on Computer Science and Information Engineering* (2009)
250. Liu, Y., Xiang, Q., Wang, Y., Cai, L.: Cultural style based music classification of audio signals. In: *Proceedings of the ICASSP*, Taipei, Taiwan, Apr 2009
251. Lo, Y.L., Lin, Y.C.: Content-based music classification. In: *Proceedings of the International Conference on Computer Science Information Technology*, pp. 112–116 (2010)
252. Loh, Q.J.B., Emmanuel, S.: ELM for the classification of music genres. In: *Proceedings of the International Conference on Control, Automation, Robotics and Vision*, pp. 1–6 (2006)
253. Londei, A., Loreto, V., Belardinelli, M.O.: Musical style and authorship categorization by informative compressors. In: *Proceedings of the ESCOM Conference on Hanover, Germany*, pp. 200–203, Sept 2003
254. Lopes, M., Gouyon, F., Koerich, A., Oliveira, L.E.S.: Selection of training instances for music genre classification. In: *Proceedings of the ICPR*, Istanbul, Turkey (2010)
255. Lukashevich, H., Abeßer, J., Dittmar, C., Großmann, H.: From multi-labeling to multi-domain-labeling: a novel two-dimensional approach to music genre classification. In: *Proceedings of the ISMIR* (2009)
256. Lukashevich, H.: Applying multiple kernel learning to automatic genre classification. In: Gaul, W.A., Geyer-Schulz, A., Schmidt-Thieme, L., Kunze, J. (eds.) *Challenges at the Interface of Data Analysis, Computer Science, and Optimization*, pp. 393–400. Springer, Berlin (2012)
257. Christanti, M.V., Kurniawan, F., Tony: Automatic music classification for Dangdut and Campursari using Naïve Bayes. In: *International Conference on Electrical Engineering and Informatics* (2011)
258. Mace, S.T., Wagoner, C.L., Teachout, D.J., Hodges, D.A.: Genre identification of very brief musical excerpts. *Psychol. Music* **40**(1), 112–128 (2011)
259. Manaris, B., Romero, J., Machado, P., Krehbiel, D., Hirzel, T., Pharr, W., Davis, R.B.: Zipf’s law, music classification, and aesthetics. *Comput. Music J.* **29**(1), 55–69 (2005)

- 260. Manaris, B., Krehbiel, D., Roos, P., Zalonis, T.: Armonique: experiments in content-based similarity retrieval using power-law melodic and timbre metrics. In: *Proceedings of the ISMIR*, pp. 343–348 (2008)
- 261. Manaris, B., Roos, P., Krehbiel, D., Zalonis, T., Armstrong, J.: Zipf's law, power laws and music aesthetics. In: Li, T., Ogihara, M., Tzanetakis, G. (eds.) *Music Data Mining*, pp. 169–216. CRC Press, Boca Raton (2011)
- 262. Mandel, M.I., Poliner, G.E., Ellis, D.P.W.: Support vector machine active learning for music retrieval. *Multimed. Syst.* **12**, 3–13 (2006)
- 263. Manzagol, P.A., Bertin-Mahieux, T., Eck, D.: On the use of sparse time-relative auditory codes for music. In: *Proceedings of the ISMIR*, Philadelphia, PA, pp. 603–608, Sept 2008
- 264. Markov, K., Matsui, T.: Music genre classification using self-taught learning via sparse coding. In: *Proceedings of the ICASSP*, pp. 1929–1932, Mar 2012
- 265. Markov, K., Matsui, T.: Nonnegative matrix factorization based self-taught learning with application to music genre classification. In: *Proceedings of the IEEE International Workshop on Machine Learning for Signal Processing*, pp. 1–5, Sept 2012
- 266. Marques, G., Langlois, T.: A language modeling approach for the classification of music pieces. In: *Proceedings of the Data Mining*, pp. 193–198 (2009)
- 267. Marques, G., Lopes, M., Sordo, M., Langlois, T., Gouyon, F.: Additional evidence that common low-level features of individual audio frames are not representative of music genres. In: *Proceedings of the SMC*, Barcelona, Spain, July 2010
- 268. Marques, G., Langlois, T., Gouyon, F., Lopes, M., Sordo, M.: Short-term feature space and music genre classification. *J. New Music Res.* **40**(2), 127–137 (2011)
- 269. Marques, C., Guiherme, I.R., Nakamura, R.Y.M., Papa, J.P.: New trends in musical genre classification using optimum-path forest. In: *Proceedings of the ISMIR* (2011)
- 270. Martin, K.D., Scheirer, E.D., Vercoe, B.L.: Music content analysis through models of audition. In: *Proceedings of the ACM Multimedia Workshop on Content Processing of Music for Multimedia Applications*, Sept 1998
- 271. Matityaho, B., Furst, M.: Neural network based model for classification of music type. In: *Proceedings of the Convention of Electrical and Electronics Engineers in Israel*, pp. 1–5, Mar 1995
- 272. Mayer, R., Neumayer, R., Rauber, A.: Rhyme and style features for musical genre classification by song lyrics. In: *Proceedings of the ISMIR* (2008)
- 273. Mayer, R., Neumayer, R., Rauber, A.: Combination of audio and lyrics features for genre classification in digital audio collections. In: *Proceedings of the ACM Multimedia*, pp. 159–168, Oct 2008
- 274. Mayer, R., Rauber, A.: Building ensembles of audio and lyrics features to improve musical genre classification. In: *International Conference on Distributed Frameworks for Multimedia Applications* (2010)
- 275. Mayer, R., Rauber, A.: Multimodal aspects of music retrieval: audio, song lyrics - and beyond? *Stud. Comput. Intell.* **274**, 333–363 (2010)
- 276. Mayer, R., Rauber, A., Ponce de León, P.J., Pérez-Sancho, C., Iñesta, J.M.: Feature selection in a cartesian ensemble of feature subspace classifiers for music categorisation. In: *Proceedings of the ACM International Workshop on Machine Learning and Music*, pp. 53–56 (2010)
- 277. Mayer, R., Rauber, A.: Music genre classification by ensembles of audio and lyrics features. In: *Proceedings of the ISMIR*, pp. 675–680 (2011)
- 278. McDermott, J., Hauser, M.D.: Nonhuman primates prefer slow tempos but dislike music overall. *Cognition* **104**(3), 654–668 (2007)

279. McKay, C., Fujinaga, I.: Automatic genre classification using large high-level musical feature sets. In: *Proceedings of the ISMIR* (2004)
280. McKay, C.: Automatic genre classification of MIDI recordings. Ph.D. thesis, McGill University, Montréal, Canada, June 2004
281. McKay, C., Fujinaga, I.: Automatic music classification and the importance of instrument identification. In: *Proceedings of the Conference on Interdisciplinary Musicology* (2005)
282. McKay, C., Fujinaga, I.: Music genre classification: is it worth pursuing and how can it be improved? In: *Proceedings of the ISMIR*, Victoria, Canada, Oct 2006
283. McKay, C., Fujinaga, I.: Combining features extracted from audio, symbolic and cultural sources. In: *Proceedings of the ISMIR*, pp. 597–602 (2008)
284. McKay, C.: Automatic music classification with jMIR. Ph.D. thesis, McGill University, Montréal, Canada, Jan 2010
285. McKay, C., Fujinaga, I.: Improving automatic music classification performance by extracting features from different types of data. In: *Multimedia Information Retrieval*, pp. 257–266 (2010)
286. McKay, C., Burgoyne, J.A., Hockman, J., Smith, J.B.L., Vigliensoni, G., Fujinaga, I.: Evaluating the genre classification performance of lyrical features relative to audio, symbolic and cultural features. In: *Proceedings of the ISMIR*, pp. 213–218 (2010)
287. McKinney, M.F., Breebaart, J.: Features for audio and music classification. In: *Proceedings of the ISMIR*, Baltimore, MD, Oct 2003
288. Mendes, R.S., Ribeiro, H.V., Freire, F.C.M., Tateishi, A.A., Lenzi, E.K.: Universal patterns in sound amplitudes of songs and music genres. *Phys. Rev. E* **83**, 017101 (2011)
289. Meng, A., Ahrendt, P., Larsen, J.: Improving music genre classification by short-time feature integration. In: *Proceedings of the ICASSP*, Philadelphia, PA, pp. 497–500, Mar 2005
290. Meng, A.: Temporal feature integration for music organization. Ph.D. thesis, Technical University of Denmark (2006)
291. Meng, A., Shawe-Taylor, J.: An investigation of feature models for music genre classification using the support vector classifier. In: *Proceedings of the ISMIR* (2008)
292. Mierswa, I., Morik, K.: Automatic feature extraction for classifying audio data. *Mach. Learn.* **58**(2–3), 127–149 (2005)
293. MIREX: Genre results (2005). <http://www.music-ir.org/mirex/wiki/2005:MIREX2005.Results>
294. MIREX: Genre results (2007). <http://www.music-ir.org/mirex/wiki/2007:MIREX2007.Results>
295. MIREX: Genre results (2008). <http://www.music-ir.org/mirex/wiki/2008:MIREX2008.Results>
296. MIREX: Genre results (2009). <http://www.music-ir.org/mirex/wiki/2009:MIREX2009.Results>
297. MIREX: Genre results (2010). <http://www.music-ir.org/mirex/wiki/2010:MIREX2010.Results>
298. MIREX: Genre results (2011). <http://www.music-ir.org/mirex/wiki/2011:MIREX2011.Results>
299. MIREX: Genre results (2012). <http://www.music-ir.org/mirex/wiki/2012:MIREX2012.Results>
300. Mitra, V., Wang, C.J.: Content based audio classification: a neural network approach. *Soft Comput. - A Fusion Found. Methodol. Appl.* **12**, 639–646 (2008)

301. Mitri, G., Uitdenbogerd, A.L., Ciesielski, V.: Automatic music classification problems. In: *Proceedings of the Australasian Computer Science Conference* (2004)
302. Moerchen, F., Ultsch, A., Nöcker, M., Stamm, C.: Databionic visualization of music collections according to perceptual distance. In: *Proceedings of the ISMIR*, London, UK, pp. 396–403, Sept 2005
303. Moerchen, F., Mierswa, I., Ultsch, A.: Understandable models of music collections based on exhaustive feature generation with temporal statistics. In: *International Conference on Knowledge Discover and Data Mining* (2006)
304. Mostafa, M.M., Billor, N.: Recognition of western style musical genres using machine learning techniques. *Expert Syst. Appl.* **36**(8), 11378–11389 (2009)
305. Nagathil, A., Gerkmann, T., Martin, R.: Musical genre classification based on highly-resolved cepstral modulation spectrum. In: *Proceedings of the EUSIPCO*, Aalborg, Denmark, pp. 462–466, Aug 2010
306. Nagathil, A., Göttel, P., Martin, R.: Hierarchical audio classification using cepstral modulation ratio regressions based on Legendre polynomials. In: *Proceedings of the ICASSP*, pp. 2216–2219, July 2011
307. Nayak, S., Bhutani, A.: Music genre classification using GA-induced minimal feature-set. In: *Proceedings of the National Conference on Computer Vision, Pattern Recognition, Image Processing and Graphics* (2011)
308. Neubarth, K., Goienetxea, I., Johnson, C., Conklin, D.: Association mining of folk music genres and toponyms. In: *Proceedings of the ISMIR* (2012)
309. Neumayer, R., Rauber, A.: Integration of text and audio features for genre classification in music information retrieval. In: Amati, G., Carpineto, C., Romano, G. (eds.) *ECiR 2007. LNCS*, vol. 4425, pp. 724–727. Springer, Heidelberg (2007)
310. Ni, Y., McVicar, M., Santos, R., Bie, T.D.: Using hyper-genre training to explore genre information for automatic chord estimation. In: *Proceedings of the ISMIR* (2012)
311. Nie, F., Xiang, S., Song, Y., Zhang, C.: Extracting the optimal dimensionality for local tensor discriminant analysis. *Pattern Recogn.* **42**(1), 105–114 (2009)
312. Nopthaisong, C., Hasan, M.M.: Automatic music classification and retrieval: experiments with Thai music collection. In: *Proceedings of the International Conference on Information and Communication Technology*, pp. 76–81, Mar 2007
313. Norowi, N.M., Doraisamy, S., Wirza, R.: Factors affecting automatic genre classification: an investigation incorporating non-western musical forms. In: *Proceedings of the ISMIR* (2005)
314. Novello, A., McKinney, M.F., Kohlrausch, A.: Perceptual evaluation of music similarity. In: *Proceedings of the ISMIR*, pp. 246–249 (2006)
315. Orio, N.: Music retrieval: a tutorial and review. *Found. Trends Inf. Retr.* **1**(1), 1–90 (2006)
316. Orio, N., Rizo, D., Miotto, R., Schedl, M., Montecchio, N., Lartillot, O.: MusiClef: a benchmark activity in multimodal music information retrieval. In: *Proceedings of the ISMIR*, pp. 603–608 (2011)
317. Otsuka, Y., Yanagi, J., Watanabe, S.: Discriminative and reinforcing stimulus properties of music for rats. *Behav. Process.* **80**(2), 121–127 (2009)
318. Pampalk, E., Dixon, S., Widmer, G.: On the evaluation of perceptual similarity measures for music. In: *Proceedings of the DAFx*, London, UK, pp. 7–12, Sept 2003
319. Pampalk, E., Flexer, A., Widmer, G.: Improvements of audio-based music similarity and genre classification. In: *Proceedings of the ISMIR*, London, UK, pp. 628–233, Sept 2005

320. Pampalk, E.: Computational models of music similarity and their application in music information retrieval. Ph.D. thesis, Vienna University of Technology, Vienna, Austria, Mar 2006
321. Panagakis, Y., Benetos, E., Kotropoulos, C.: Music genre classification: a multi-linear approach. In: Proceedings of the ISMIR, Philadelphia, PA, pp. 583–588, Sept 2008
322. Panagakis, Y., Kotropoulos, C., Arce, G.R.: Music genre classification via sparse representations of auditory temporal modulations. In: Proceedings of the EUSIPCO, Glasgow, Scotland, Aug 2009
323. Panagakis, Y., Kotropoulos, C., Arce, G.R.: Music genre classification using locality preserving non-negative tensor factorization and sparse representations. In: Proceedings of the ISMIR, Kobe, Japan, pp. 249–254, Oct 2009
324. Panagakis, Y., Kotropoulos, C., Arce, G.R.: Non-negative multilinear principal component analysis of auditory temporal modulations for music genre classification. *IEEE Trans. Acoust. Speech Lang. Process.* **18**(3), 576–588 (2010)
325. Panagakis, Y., Kotropoulos, C., Arce, G.R.: Sparse multi-label linear embedding nonnegative tensor factorization for automatic music tagging. In: Proceedings of the EUSIPCO, pp. 492–496, Aug 2010
326. Panagakis, Y., Kotropoulos, C.: Music genre classification via topology preserving non-negative tensor factorization and sparse representations. In: Proceedings of the ICASSP, pp. 249–252, Mar 2010
327. Paradzinets, A., Harb, H., Chen, L.: Multiexpert system for automatic music genre classification. Technical report, Ecole Centrale de Lyon, Lyon, France, June 2009
328. Park, D.C.: Classification of audio signals using fuzzy c-means with divergence-based kernel. *Pattern Recon. Lett.* **30**(9), 794–798 (2009)
329. Park, D.C.: Partitioned feature-based classifier model. In: Proceedings of the IEEE International Symposium on Signal Processing and Information Technology, pp. 412–417 (2009)
330. Park, D.C.: Partitioned feature-based classifier model with expertise table. In: Proceedings of the IEEE International Conference on Bio-inspired Computing (2010)
331. Park, S., Park, J., Sim, K.: Optimization system of musical expression for the music genre classification. In: Proceedings of the International Conference on Control, Automation, and Systems, pp. 1644–1648, Oct 2011
332. Peeters, G.: A generic system for audio indexing: application to speech/music segmentation and music genre recognition. In: Proceedings of the DAFx, Bordeaux, France, Sept 2007
333. Peeters, G.: Spectral and temporal periodicity representations of rhythm for the automatic classification of music audio signal. *IEEE Trans. Audio Speech Lang. Process.* **19**(5), 1242–1252 (2011)
334. Peng, W., Li, T., Ogiwara, M.: Music clustering with constraints. In: Proceedings of the ISMIR, pp. 27–32 (2007)
335. Pérez-Sancho, C., Iñesta, J.M., Calera-Rubio, J.: A text categorization approach for music style recognition. In: Marques, J.S., Pérez de la Blanca, N., Pina, P. (eds.) *IbPRIA 2005. LNCS*, vol. 3523, pp. 649–657. Springer, Heidelberg (2005)
336. Iñesta, T.P.J.M., Rizo, D.: metamidi: a tool for automatic metadata extraction from MIDI files. In: Proceedings of the Workshop on Exploring Musical Information Spaces, pp. 36–40, Oct 2009

- 337. Pérez-García, T., Pérez-Sancho, C., Iñesta, J.: Harmonic and instrumental information fusion for musical genre classification. In: Proceedings of the ACM International Workshop on Machine Learning and Music, pp. 49–52 (2010)
- 338. Pérez-Sancho, C., Iñesta, J.M., Calera-Rubio, J.: Style recognition through statistical event models. *J. New Music Res.* **34**(4), 331–340 (2005)
- 339. Pérez-Sancho, C., Rizo, D., Iñesta, J.: Stochastic text models for music categorization. In: da Vitoria Lobo, N., et al. (eds.) *SSPR & SPR 2008*. LNCS, vol. 5342, pp. 55–64. Springer, Heidelberg (2008)
- 340. Pérez-Sancho, C., Rizo, D., Iñesta, J.M.: Genre classification using chords and stochastic language models. *Connect. Sci.* **21**, 145–159 (2009)
- 341. Pérez-Sancho, C.: Stochastic language models for music information retrieval. Ph.D. thesis, Universidad de Alicante, Spain, June 2009
- 342. Pohle, T.: Extraction of audio descriptors and their evaluation in music classification tasks. Ph.D. thesis, Technischen Universität Kaiserslautern, Jan 2005
- 343. Pohle, T., Knees, P., Schedl, M., Widmer, G.: Independent component analysis for music similarity computation. In: Proceedings of ISMIR, pp. 228–233 (2006)
- 344. Pohle, T., Pampalk, E., Widmer, G.: Evaluation of frequently used audio features for classification of music into perceptual categories. In: International Workshop on Content-Based Multimedia Indexing (2008)
- 345. Pohle, T., Schnitzer, D., Schedl, M., Knees, P., Widmer, G.: On rhythm and general music similarity. In: Proceedings of the ISMIR (2009)
- 346. Pollastri, E., Simoncelli, G.: Classification of melodies by composer with hidden Markov models. In: Proceedings of the WEDELMUSIC, pp. 88–95, Nov 2001
- 347. Porter, D., Neuringer, A.: Music discriminations by pigeons. *Exp. Psychol.: Animal Behav. Process.* **10**(2), 138–148 (1984)
- 348. Pye, D.: Content-based methods for the management of digital music. In: Proceedings of the ICASSP (2000)
- 349. Rafailidis, D., Nanopoulos, A., Manolopoulos, Y.: Nonlinear dimensionality reduction for efficient and effective audio similarity searching. *Multimed. Tools Appl.* **42**, 273–293 (2009)
- 350. Rauber, A., Frühwirth, M.: Automatically analyzing and organizing music archives. In: Constantopoulos, P., Sølvberg, I.T. (eds.) *ECDL 2001*. LNCS, vol. 2163, p. 402. Springer, Heidelberg (2001)
- 351. Rauber, A., Pampalk, E., Merkl, D.: Using psycho-acoustic models and self-organizing maps to create a hierarchical structuring of music by musical styles. In: Proceedings of the ISMIR, pp. 71–80, Oct 2002
- 352. Ravelli, E., Richard, G., Daudet, L.: Audio signal representations for indexing in the transform domain. *IEEE Trans. Audio Speech Lang. Process.* **18**(3), 434–446 (2010)
- 353. Reed, J., Lee, C.H.: A study on music genre classification based on universal acoustic models. In: Proceedings of the ISMIR (2006)
- 354. Reed, J., Lee, C.H.: A study on attribute-based taxonomy for music information retrieval. In: Proceedings of the ISMIR, pp. 485–490 (2007)
- 355. Rin, J.M., Chen, Z.S., Jang, J.S.R.: On the use of sequential patterns mining as temporal features for music genre classification. In: Proceedings of the ICASSP (2010)
- 356. Ren, J.M., Jang, J.S.R.: Time-constrained sequential pattern discovery for music genre classification. In: Proceedings of the ICASSP, pp. 173–176 (2011)
- 357. Ren, J.M., Jang, J.S.R.: Discovering time-constrained sequential patterns for music genre classification. *IEEE Trans. Audio Speech Lang. Process.* **20**(4), 1134–1144 (2012)

358. Ribeiro, H., Zunino, L., Mendes, R., Lenzi, E.: Complexity-entropy causality plane: a useful approach for distinguishing songs. *Phys. A: Stat. Mech. Its Appl.* **391**(7), 2421–2428 (2012)
359. Rizzi, A., Buccino, N.M., Panella, M., Uncini, A.: Genre classification of compressed audio data. In: *Proceedings of the International Workshop on Multimedia Signal Processing* (2008)
360. Ro, W., Kwon, Y.: 1/f noise analysis of songs in various genre of music. *Chaos Soliton. Fract.* **42**(4), 2305–2311 (2009)
361. Rocha, B.: Genre classification based on predominant melodic pitch contours. Master's thesis, Universitat Pompeu Fabra, Barcelona, Spain, Sept 2011
362. Rump, H., Miyabe, S., Tsunoo, E., Ono, N., Sagayama, S.: Autoregressive MFCC models for genre classification improved by harmonic-percussion separation. In: *Proceedings of the ISMIR*, pp. 87–92 (2010)
363. Ruppín, A., Yeshurun, H.: Midi music genre classification by invariant features. In: *Proceedings of the ISMIR*, pp. 397–399 (2006)
364. Salamon, J., Rocha, B., Gomez, E.: Musical genre classification using melody features extracted from polyphonic music signals. In: *Proceedings of the ICASSP*, Kyoto, Japan, Mar 2012
365. Sanden, C., Befus, C., Zhang, J.Z.: Clustering-based genre prediction on music data. In: *Proceedings of the International C* Conference on Computer Science and Software Engineering*, pp. 117–119 (2008)
366. Sanden, C., Befus, C.R., Zhang, J.: Perception based multi-label genre classification on music data. In: *Proceedings of the ICMC*, pp. 9–15 (2010)
367. Sanden, C.: An empirical evaluation of computational and perceptual multi-label genre classification on music. Master's thesis, University of Lethbridge (2010)
368. Sanden, C., Zhang, J.Z.: Enhancing multi-label music genre classification through ensemble techniques. In: *Proceedings of the International ACM SIGIR Conference on Research and Development in Information Retrieval*, pp. 705–714 (2011)
369. Sanden, C., Zhang, J.Z.: Algorithmic multi-genre classification of music: an empirical study. In: *Proceedings of the ICMC* (2011)
370. Sanden, C., Befus, C.R., Zhang, J.Z.: A perceptual study on music segmentation and genre classification. *J. New Music Res.* **41**(3), 277–293 (2012)
371. de los Santos, C.A.: Nonlinear audio recurrence analysis with application to music genre classification. Master's thesis, Universitat Pompeu Fabra, Barcelona, Spain (2010)
372. Scaringella, N., Zoia, G.: On the modeling of time information for automatic genre recognition systems in audio signals. In: *Proceedings of the ISMIR*, pp. 666–671 (2005)
373. Scaringella, N., Zoia, G., Mlynek, D.: Automatic genre classification of music content: a survey. *IEEE Signal Process. Mag.* **23**(2), 133–141 (2006)
374. Schedl, M., Pohle, T., Knees, P., Widmer, G.: Assigning and visualizing music genres by web-based co-occurrence analysis. In: *Proceedings of the ISMIR* (2006)
375. Schierz, A., Budka, M.: High-performance music information retrieval system for song genre classification. In: Kryszkiewicz, M., Rybinski, H., Skowron, A., Raś, Z.W. (eds.) *ISMIS 2011. LNCS (LNAI)*, vol. 6804, pp. 725–733. Springer, Heidelberg (2011)
376. Schindler, A., Mayer, R., Rauber, A.: Facilitating comprehensive benchmarking experiments on the million song dataset. In: *Proceedings of the ISMIR*, Oct 2012
377. Schindler, A., Rauber, A.: Capturing the temporal domain in echonest features for improved classification effectiveness. In: *Proceedings of the Adaptive Multimedia Retrieval*, Oct 2012

378. Schlüter, J., Osendorfer, C.: Music similarity estimation with the mean-covariance restricted Boltzmann machine. In: Proceedings of the ICMLA (2011)
379. Seo, J., Lee, S.: Higher-order moments for musical genre classification. *Signal Process.* **91**(8), 2154–2157 (2011)
380. Serra, J., de los Santos, C.A., Andrzejak, R.G.: Nonlinear audio recurrence analysis with application to genre classification. In: Proceedings of the ICASSP (2011)
381. Seyerlehner, K.: Content-based music recommender systems: beyond simple frame-level audio similarity. Ph.D. thesis, Johannes Kepler University, Linz, Austria, Dec 2010
382. Seyerlehner, K., Widmer, G., Pohle, T.: Fusing block-level features for music similarity estimation. In: Proceedings of the DAFx (2010)
383. Seyerlehner, K., Widmer, G., Knees, P.: A comparison of human, automatic and collaborative music genre classification and user centric evaluation of genre classification systems. In: Detyniecki, M., Knees, P., Nürnberger, A., Schedl, M., Stober, S. (eds.) *AMR 2010. LNCS*, vol. 6817, pp. 118–131. Springer, Heidelberg (2012)
384. Seyerlehner, K., Schedl, M., Sonnleitner, R., Hauger, D., Ionescu, B.: From improved auto-taggers to improved music similarity measures. In: Proceedings of the Adaptive Multimedia Retrieval, Copenhagen, Denmark, Oct 2012
385. Shan, M.K., Kuo, F.F., Chen, M.F.: Music style mining and classification by melody. In: Proceedings of the ICME, vol. 1, pp. 97–100 (2002)
386. Shao, X., Xu, C., Kankanhalli, M.S.: Unsupervised classification of music genre using hidden Markov model. In: Proceedings of the ICME, pp. 2023–2026 (2004)
387. Shen, J., Shepherd, J.A., Ngu, A.H.H.: On efficient music genre classification. In: Zhou, L., Ooi, B.-C., Meng, X. (eds.) *DASFAA 2005. LNCS*, vol. 3453, pp. 253–264. Springer, Heidelberg (2005)
388. Shen, J., Shepherd, J., Ngu, A.H.H.: Towards effective content-based music retrieval with multiple acoustic feature combination. *IEEE Trans. Multimed.* **8**(6), 1179–1189 (2006)
389. Shen, Y., Li, X., Ma, N.W., Krishnan, S.: Parametric time-frequency analysis and its applications in music classification. *EURASIP J. Adv. Signal Process.* **2010**, 1–9 (2010)
390. Shih, J.L., Lee, C.H., Lin, S.W.: Automatic classification of musical audio signals. *J. Inf. Technol. Appl.* **1**(2), 95–105 (2006)
391. Silla Jr., C.N., Kaestner, C.A.A., Koerich, A.L.: Time-space ensemble strategies for automatic music genre classification. In: Sichman, J.S., Coelho, H., Rezende, S.O. (eds.) *IBERAMIA 2006 and SBIA 2006. LNCS (LNAI)*, vol. 4140, pp. 339–348. Springer, Heidelberg (2006)
392. Silla, C.N., Koerich, A., Kaestner, C.: Automatic music genre classification using ensembles of classifiers. In: Proceedings of the IEEE International Conference on Systems, Man, Cybernetics, pp. 1687–1692 (2007)
393. Silla, C.N., Koerich, A.L., Kaestner, C.A.A.: Feature selection in automatic music genre classification. In: Proceedings of the IEEE International Symposium on Multimedia, pp. 39–44 (2008)
394. Silla, C.N., Koerich, A.L., Kaestner, C.A.A.: The Latin music database. In: Proceedings of the ISMIR (2008)
395. Silla, C., Freitas, A.: Novel top-down approaches for hierarchical classification and their application to automatic music genre classification. In: IEEE International Conference on Systems, Man, and Cybernetics, San Antonio, USA, Oct 2009

396. Silla, C.N., Koerich, A.L., Kaestner, C.A.A.: A feature selection approach for automatic music genre classification. *Int. J. Semantic Comput.* **3**(2), 183–208 (2009)
397. Silla, C., Koerich, A., Kaestner, C.: Improving automatic music genre classification with hybrid content-based feature vectors. In: *Proceedings of the Symposium on Applied Computer*, Sierre, Switzerland, Mar 2010
398. Silla, C.N., Freitas, A.A.: A survey of hierarchical classification across different application domains. *Data Mining Knowl. Disc.* **22**, 31–72 (2011)
399. Simsekli, U.: Automatic music genre classification using bass lines. In: *Proceedings of the ICPR* (2010)
400. Smith, J.B.L., Burgoyne, J.A., Fujinaga, I., Roure, D.D., Downie, J.S.: Design and creation of a large-scale database of structural annotations. In: *Proceedings of the ISMIR* (2011)
401. Soltau, H., Schultz, T., Westphal, M., Waibel, A.: Recognition of music types. In: *Proceedings of the ICASSP* (1998)
402. Song, Y., Zhang, C., Xiang, S.: Semi-supervised music genre classification. In: *Proceedings of the ICASSP*, pp. 729–732 (2007)
403. Song, Y., Zhang, C.: Content-based information fusion for semi-supervised music genre classification. *IEEE Trans. Multimed.* **10**(1), 145–152 (2008)
404. Sordo, M., Celma, O., Blech, M., Guaus, E.: The quest for musical genres: do the experts and the wisdom of crowds agree? In: *Proceedings of the ISMIR* (2008)
405. Sotiropoulos, D., Lampropoulos, A., Tsihrintzis, G.: Artificial immune system-based music genre classification. In: Tsihrintzis, G., Virvou, M., Howlett, R., Jain, L. (eds.) *New Directions in Intelligent Interactive Multimedia*. SCI, vol. 142, pp. 191–200. Springer, Heidelberg (2008)
406. Srinivasan, H., Kankanhalli, M.: Harmonicity and dynamics-based features for audio. In: *Proceedings of the ICASSP*, vol. 4, pp. 321–324 (2004)
407. Sturm, B.L., Noorzad, P.: On automatic music genre recognition by sparse representation classification using auditory temporal modulations. In: *Proceedings of the CMMR*, London, UK, June 2012
408. Sturm, B.L.: An analysis of the GTZAN music genre dataset. In: *Proceedings of the ACM MIRUM Workshop*, Nara, Japan, Nov 2012
409. Sturm, B.L.: Two systems for automatic music genre recognition: what are they really recognizing? In: *Proceedings of the ACM MIRUM Workshop*, Nara, Japan, Nov 2012
410. Sturm, B.L.: Classification accuracy is not enough: on the analysis of music genre recognition systems. *J. Intell. Inf. Syst.* **41**, 371–406 (2013)
411. Sturm, B.L.: On music genre classification via compressive sampling. In: *Proceedings of the ICME*, July 2013, pp. 1–6 (2013)
412. Sturm, B.L.: Music genre recognition with risk and rejection. In: *Proceedings of the ICME*, July 2013, pp. 1–6 (2013)
413. Su, Z.Y., Wu, T.: Multifractal analyses of music sequences. *Phys. D: Nonlin. Phen.* **221**(2), 188–194 (2006)
414. Sundaram, S., Narayanan, S.: Experiments in automatic genre classification of full-length music tracks using audio activity rate. In: *Proceedings of the IEEE Workshop Multimedia Signal Processing* (2007)
415. Tacchini, E., Damiani, E.: What is a “musical world”? An affinity propagation approach. In: *Proceedings of the ACM MIRUM Workshop*, Scottsdale, AZ, USA, pp. 57–62, Nov 2011

416. Happi Tietche, B., Romain, O., Denby, B., Benaroya, L., Viateur, S.: FPGA-based radio-on-demand broadcast receiver with musical genre identification. In: Proceedings of the IEEE International Symposium on Industrial Electronics, pp. 1381–1385, May 2012
417. Tsai, W.H., Bao, D.F.: Clustering music recordings based on genres. In: Proceedings of the International Conference on Information Science and Applications (2010)
418. Tsatsishvili, V.: Automatic subgenre classification of heavy metal music. Master's thesis, University of Jyväskylä, Nov 2011
419. Tsunoo, E., Tzanetakis, G., Ono, N., Sagayama, S.: Audio genre classification by clustering percussive patterns. In: Proceedings of the Acoustical Society of Japan (2009)
420. Tsunoo, E., Tzanetakis, G., Ono, N., Sagayama, S.: Audio genre classification using percussive pattern clustering combined with timbral features. In: Proceedings of the ICME (2009)
421. Tsunoo, E., Tzanetakis, G., Ono, N., Sagayama, S.: Beyond timbral statistics: improving music classification using percussive patterns and bass lines. *IEEE Trans. Audio Speech Lang. Process.* **19**(4), 1003–1014 (2011)
422. Turnbull, D., Elkan, C.: Fast recognition of musical genres using RBF networks. *IEEE Trans. Knowl. Data Eng.* **17**(4), 580–584 (2005)
423. Typke, R., Wiering, F., Veltkamp, R.C.: A survey of music information retrieval systems. In: Proceedings of the ISMIR, London, UK, Sept 2005
424. Tzagkarakis, C., Mouchtaris, A., Tsakalides, P.: Musical genre classification via generalized Gaussian and alpha-stable modeling. In: Proceedings of the ICASSP, May 2006
425. Tzanetakis, G., Essl, G., Cook, P.: Automatic music genre classification of audio signals. In: Proceedings of the ISMIR (2001)
426. Tzanetakis, G., Cook, P.: Musical genre classification of audio signals. *IEEE Trans. Speech Audio Process.* **10**(5), 293–302 (2002)
427. Tzanetakis, G.: Manipulation, analysis and retrieval systems for audio signals. Ph.D. thesis, Princeton University, June 2002
428. Tzanetakis, G., Ermolinskyi, A., Cook, P.: Pitch histograms in audio and symbolic music information retrieval. *J. New Music Res.* **32**(2), 143–152 (2003)
429. Umapathy, K., Krishnan, S., Jimaa, S.: Multigroup classification of audio signals using time-frequency parameters. *IEEE Trans. Multimed.* **7**(2), 308–315 (2005)
430. Valdez, N., Guevara, R.: Feature set for philippine gong music classification by indigenous group. In: Proceedings of the IEEE Region 10 Conference, pp. 339–343, Nov 2011
431. Vatulkin, I., Theimer, W.M., Botteck, M.: Partition based feature processing for improved music classification. In: Proceedings of the Annual Conference of the German Classification Society, pp. 411–419 (2010)
432. Vatulkin, I., Preuß, M., Rudolph, G.: Multi-objective feature selection in music genre and style recognition tasks. In: Genetic and Evolutionary Computation Conference (2011)
433. Vatulkin, I.: Multi-objective evaluation of music classification. In: Gaul, W.A., Geyer-Schulz, A., Schmidt-Thieme, L., Kunze, J. (eds.) *Challenges at the Interface of Data Analysis, Computer Science, and Optimization*, pp. 401–410. Springer, Berlin (2012)
434. Volk, A., van Kranenburg, P.: Melodic similarity among folk songs: an annotation study on similarity-based categorization in music. *Musicae Scientiae* **16**(3), 317–339 (2012)

435. Völkel, T., Abeßer, J., Dittmar, C., Großmann, H.: Automatic genre classification of Latin music using characteristic rhythmic patterns. In: Proceedings of the Audio Mostly Conference, Piteå, Sweden (2010)
436. Wang, L., Huang, S., Wang, S., Liang, J., Xu, B.: Music genre classification based on multiple classifier fusion. In: Proceedings of the International Conference on Natural Computation (2008)
437. Wang, F., Wang, X., Shao, B., Li, T., Ogihara, M.: Tag integrated multi-label music style classification with hypergraph. In: Proceedings of the ISMIR (2009)
438. Wang, D., Li, T., Ogihara, M.: Are tags better than audio? The effect of joint use of tags and audio content features for artistic style clustering. In: Proceedings of the ISMIR, pp. 57–62 (2010)
439. Watanabe, S., Nemoto, M.: Reinforcing property of music in Java sparrows (*Padda oryzivora*). *Behav. Process.* **43**(2), 211–218 (1998)
440. Watanabe, S., Sato, K.: Discriminative stimulus properties of music in Java sparrows. *Behav. Process.* **47**(1), 53–57 (1999)
441. Watanabe, S.: How animals perceive music? Comparative study of discriminative and reinforcing properties of music for infrahuman animals. *CARLS Series of Advanced Study of Logic and Sensibility* vol. 2, pp. 5–16 (2008)
442. Weihs, C., Ligges, U., Morchen, F., Mullensiefen, D.: Classification in music research. *Adv. Data Anal. Classif.* **1**(3), 255–291 (2007)
443. Welsh, M., Borisov, N., Hill, J., von Behren, R., Woo, A.: Querying large collections of music for similarity. Technical report, University of California, Berkeley (1999)
444. West, K., Cox, S.: Features and classifiers for the automatic classification of musical audio signals. In: Proceedings of the ISMIR (2004)
445. West, K., Cox, S.: Finding an optimal segmentation for audio genre classification. In: Proceedings of the ISMIR, pp. 680–685 (2005)
446. West, K., Lamere, P.: A model-based approach to constructing music similarity functions. *EURASIP J. Appl. Signal Process.* **1**(1), 149 (2007)
447. West, K.: Novel techniques for audio music classification and search. Ph.D. thesis, University of East Anglia (2008)
448. Whitman, B., Smaragdis, P.: Combining musical and cultural features for intelligent style detection. In: Proceedings of the ISMIR, Paris, France, Oct 2002
449. Wiggins, G.A.: Semantic gap?? Schemantic schmap!! Methodological considerations in the scientific study of music. In: Proceedings of the IEEE International Symposium on Multimedia, pp. 477–482, Dec 2009
450. Wu, M.J., Chen, Z.S., Jang, J.S.R., Ren, J.M.: Combining visual and acoustic features for music genre classification. In: International Conference on Machine Learning and Applications (2011)
451. Wülfing, J., Riedmiller, M.: Unsupervised learning of local features for music classification. In: Proceedings of the ISMIR, Porto, Portugal, Oct 2012
452. Xu, C., Maddage, M., Shao, X., Cao, F., Tian, Q.: Musical genre classification using support vector machines. In: Proceedings of the ICASSP (2003)
453. Yang, W., Yu, X., Deng, J., Pan, X., Wang, Y.: Audio classification based on fuzzy-rough nearest neighbour clustering. In: Proceedings of the International Conference on Wireless Communications and Mobile Computation, pp. 320–324 (2011)
454. Yang, X., Chen, Q., Zhou, S., Wang, X.: Deep belief networks for automatic music genre classification. In: Proceedings of the INTERSPEECH, pp. 2433–2436 (2011)

- 455. Yao, Q., Li, H., Sun, J., Ma, L.: Visualized feature fusion and style evaluation for musical genre analysis. In: International Conference on Pervasive Computing, Signal Processing and Applications (2010)
- 456. Yaslan, Y., Cataltepe, Z.: Audio music genre classification using different classifiers and feature selection methods. In: Proceedings of the ICPR, pp. 573–576 (2006)
- 457. Yeh, C.C.M., Yang, Y.H.: Supervised dictionary learning for music genre classification. In: Proceedings of the ACM International Conference on Multimedia Retrieval, Hong Kong, China, June 2012
- 458. Ying, T.C., Doraisamy, S., Abdullah, L.N.: Genre and mood classification using lyric features. In: International Conference on Information Retrieval and Knowledge Management (2012)
- 459. Yoon, W.-J., Lee, K.-K., Park, K.-S., Yoo, H.-Y.: Automatic classification of western music in digital library. In: Fox, E.A., Neuhold, E.J., Premismit, P., Wuwongse, V. (eds.) ICADL 2005. LNCS, vol. 3815, pp. 293–300. Springer, Heidelberg (2005)
- 460. Zaroni, M., Ciminieri, D., Sarti, A., Tubaro, S.: Searching for dominant high-level features for music information retrieval. In: Proceedings of the EUSIPCO, Bucharest, Romania, pp. 2025–2029, Aug 2012
- 461. Zeng, Z., Zhang, S., Li, H., Liang, W., Zheng, H.: A novel approach to musical genre classification using probabilistic latent semantic analysis model. In: Proceedings of the ICME, pp. 486–489 (2009)
- 462. Zhang, Y., Zhou, J.: A study on content-based music classification. In: Proceedings of the International Symposium on Signal Processing and Its Applications, pp. 113–116, July 2003
- 463. Zhang, Y.B., Zhou, J., Wang, X.: A study on Chinese traditional opera. In: Proceedings of the International Conference on Machine Learning and Cybernetics, pp. 2476–2480, July 2008
- 464. Zhen, C., Xu, J.: Solely tag-based music genre classification. In: Proceedings of the International Conference on Web Information Systems and Mining (2010)
- 465. Zhen, C., Xu, J.: Multi-modal music genre classification approach. In: Proceedings of the IEEE International Conference on Computer Science and Information Technology (2010)
- 466. Zhou, G.T., Ting, K.M., Liu, F.T., Yin, Y.: Relevance feature mapping for content-based multimedia information retrieval. *Pattern Recogn.* **45**, 1707–1720 (2012)
- 467. Zhu, J., Xue, X., Lu, H.: Musical genre classification by instrumental features. In: Proceedings of the ICMC (2004)
- 468. Fabbri, F.: A theory of musical genres: two applications. In: Proceedings of the International Conference on Popular Music Studies, Amsterdam, The Netherlands (1980)
- 469. Frow, J.: *Genre*. Routledge, New York (2005)
- 470. Bertin-Mahieux, T., Eck, D., Mandel, M.: Automatic tagging of audio: the state-of-the-art. In: Wang, W. (ed.) *Machine Audition: Principles, Algorithms and Systems*. IGI Publishing, Hershey (2010)
- 471. Kim, Y., Schmidt, E., Migneco, R., Morton, B., Richardson, P., Scott, J., Speck, J., Turnbull, D.: Music emotion recognition: a state of the art review. In: Proceedings of the ISMIR, pp. 255–266 (2010)
- 472. Soltau, H.: *Erkennung von Musikstilen*. Ph.D. thesis, Universität Karlsruhe, Karlsruhe, Germany, May 1997
- 473. Kiernan, F.J.: Score-based style recognition using artificial neural networks. In: Proceedings of the ISMIR (2000)

474. Avcu, N., Kuntalp, D., Alpkocak, V.A.: Musical genre classification using higher-order statistics. In: Proceedings of the IEEE Signal Processing and Communication Applications Conference, pp. 1–4, June 2007
475. Bagci, U., Erzin, E.: Inter genre similarity modeling for automatic music genre classification. In: Proceedings of the IEEE Signal Processing and Communications Applications, pp. 1–4, Apr 2006
476. Herkiloglu, K., Gursoy, O., Gunsul, B.: Music genre determination using audio fingerprinting. In: Proceedings of the IEEE Signal Processing and Communications Applications, pp. 1–4, Apr 2006
477. Sonmez, A.: Music genre and composer identification by using Kolmogorov distance. Master's thesis, Istanbul Technical University, Istanbul, Turkey (2005)
478. Yaslan, Y., Cataltepe, Z.: Music genre classification using audio features, different classifiers and feature selection methods. In: Proceedings of the IEEE Signal Processing and Communications Applications, pp. 1–4, Apr 2006
479. Yaslan, Y., Cataltepe, Z.: Audio genre classification with co-MRMR. In: Proceedings of the IEEE Signal Processing and Communications Applications, pp. 408–411, Apr 2009
480. Allamanche, E., Kastner, T., Wistorf, R., Lefebvre, N., Herre, J.: Music genre estimation from low level audio features. In: Proceedings of the International Audio Engineering Society Conference (2004)
481. Seo, J.S.: An informative feature selection method for music genre classification. *Trans. Japanese Eng. Tech. Org.* **94–D**(6), 1362–1365 (2011)
482. Berenzweig, A., Logan, B., Ellis, D.P.W., Whitman, B.: A large-scale evaluation of acoustic and subjective music-similarity measures. *Comput. Music J.* **28**(2), 63–76 (2004)
483. Goto, M., Hashiguchi, H., Nishimura, T., Oka, R.: RWC music database: music genre database and musical instrument sound database. In: Proceedings of the ISMIR (2003)
484. Bertin-Mahieux, T., Ellis, D.P., Whitman, B., Lamere, P.: The million song dataset. In: Proceedings of the ISMIR (2011)
485. Law, E.: Human computation for music classification. In: Li, T., Ogihara, M., Tzanetakis, G. (eds.) *Music Data Mining*, pp. 281–301. CRC Press, Boca Raton (2011)

Adaptive Multimedia Retrieval: Semantics, Context, and
Adaptation

10th International Workshop, AMR 2012, Copenhagen,
Denmark, October 24-25, 2012, Revised Selected
Papers

Nurnberger, A.; Stober, S.; Larsen, B.; Detyniecki, M.
(Eds.)

2014, X, 291 p. 98 illus., Softcover

ISBN: 978-3-319-12092-8