

Introduction to Node.js

Frank Walsh

Diarmuid O'Connor




Agenda

- What is node.js
- The Dev Env for the Labs
- Event-based processes
- Callbacks in node
- Introduction to Express


What's Node: Basics

- A Javascript runtime. “Server side JS”
- The “.js” doesn’t mean that it’s written completely in JavaScript.
 - approx. 40% JS and 60% C++
- Ecosystem of packages (**NPM**)
- Official site: “Node's goal is to provide an easy way to build scalable network programs”.
- Single Threaded, Event based
 - Supports concurrency using events and callbacks...



NPM – the Package Manager

- Node has a small core API
- Most applications depend on third party modules
- Curated in online registry called the Node Package Manager system (NPM)
- NPM downloads and installs modules, placing them into a **node_modules** folder in your current folder.




This Photo by Unknown Author is licensed under CC BY-SA-NC

NPM init

- You can use NPM to manage your node projects
- Run the following in the root folder of your app/project:
npm init
- This will ask you a bunch of questions, and then create a **package.json** for you.
- It attempts to make reasonable guesses about what you want things to be set to, and then writes a package.json file with the options you've selected.

NPM Common Commands

- **npm init**
initialize a package.json file
- **npm install <package name> -g**
install a package, if -g option is given package will be installed globally,
- **--save and --save-dev**
add package to your dependencies
- **npm install**
install packages listed in package.json
- **npm ls -g**
list local packages (without -g) or global packages (with -g)
- **npm update <package name>** *update a package*



NPX - the package runner

- Makes it easy to run a Node.js based executable that you would normally install via npm.
- Can use it at command line to execute packages, even if they are not previously installed.
- Very good for one-off commands/tests (like in-class demos!)
- Comes with the latest versions of NPM
- The following example will execute the babel-node package to transpile and run index.js.

`npx babel-node index.js`

Node Development Environment





Development Environment Setup for Labs

Node.js:

We just talked about it

Babel:

Allow us to use up-to-date Javascript features, according to ECMAScript Standardisation

Nodemon:

monitor for any changes in your source and automatically restart your node app.

ESLint:

Find, report and fix problems in your javascript


Testing:

Manual: Postman

Automated: Mocha, Should, Sinon (maybe...)



Babel

The image is a screenshot of the Babel website's homepage. The background is dark with a faint, stylized illustration of a person's head and shoulders. At the top, there is a navigation bar with links for 'Docs', 'Setup', 'Try it out', 'Videos', 'Blog', a search bar labeled 'Search', and links for 'Donate', 'Team', and 'GitHub'. The Babel logo is in the top left corner. The main heading is 'Babel is a JavaScript compiler.' in a large, bold, yellow font. Below it, the text 'Use next generation JavaScript, today.' is in a smaller, white font. A yellow banner in the center contains the text 'Babel 7.13 is released! Please read our [blog post](#) for highlights and [changelog](#) for more details!'. At the bottom, there is a code editor interface with two panels. The left panel is titled 'Put in next-gen JavaScript' and contains the code:

```
const styles = {  
  ...defaults,  
  color: '#f
```

. The right panel is titled 'Get browser-compatible JavaScript out' and is currently empty.

Node.js and Babel

We're using ES6+ syntax for front end development

E.g. imports, spread operator, arrow functions, export default

Node.js, as yet, does not support all of the latest and greatest ES6+ features


We can use Babel to “*Transpile*” code from ES6+ to ES5 before we run it

We will install as **Development Dependency** for our project


```
npm install --save-dev babel-cli
```

```
npm install --save-dev babel-preset-env
```


Nodemon



ESLint



Testing(Maybe...)



POSTMAN

Product ▾ Use Cases ▾ Pricing Enterprise Explore Learning Center

The Collaboration Platform for API Development

Simplify each step of building an API and streamline collaboration so you can create better APIs—faster.

[Launch Postman](#) [Learn More](#)



simple, flexible, fun

Mocha is a feature-rich JavaScript test framework running on [Node.js](#) and in the browser,

Input/Output




[This Photo](#) by Unknown Author
is licensed under [CC BY-NC](#)

- Input/Output (io) is slow.
 - Reading/writing to data store, network access.
 - Read 4K randomly from SSD* 150,000 ns
~1GB/sec SSD
 - Round trip over network within same datacenter
500,000 ns
 - Send packet US->Netherlands->US
150,000,000 ns
- CPU operations are fast.
 - L1 cache reference 0.5 ns
 - L2 cache reference 7 ns
- I/O operations detrimental to highly concurrent apps (e.g. web applications)
- Solutions to deal with this are:
 - **Blocking code** combined with multiple threads of execution (e.g. Apache, IIS)
 - **Non-blocking, event-based code** in single thread (e.g. NGINX, Node.js)

Blocking/Non-blocking Example


Blocking

1. Read from db and set equal to contents
2. Print Contents
3. Do other stuff...



Non-blocking

- 1) Read from db
Whenever read is complete, print contents
- 2) Do other stuff...



Blocking/Non-blocking example: Javascript

Blocking

```
import fs from 'fs';  
  
const contents = fs.readFileSync('./text.txt', 'utf8');  
console.log(contents);  
console.log('Doing something else');
```

Console output

Hello World.....
Doing something else

Non-blocking


```
import fs from 'fs';  
fs.readFile('./text.txt', 'utf8', (err, contents) => {  
  console.log(contents);  
});  
console.log('Doing something else');
```

Console output

Doing something else
Hello World

The Node Event Loop and Callbacks

- A **Callback** is a function called at the completion of a given task. This prevents any blocking, and allows other code to be run in the meantime
- The Event Loop checks for known events, registers Callbacks and triggers callback on completion of operation
- More info here:
<https://developer.ibm.com/tutorials/learn-nodejs-the-event-loop/>





Node.js - Simple HTTP Server

```
import http from 'http';

const port = 8080;


const server = http.createServer((req, res) => {
  res.writeHead(200);
  res.end("Hello World!");
});

server.listen(port);
console.log(`Server running at ${port}`);
```



Emitting Event in Node

Many objects can emit events in node.



Example – Hello/Goodbye Callback


```
import http from 'http';
const server = http.createServer((request, response)=>{
  response.writeHead(200);
  response.write("Hello!");
  setTimeout(()=>{
    response.write("Good Bye!");
    response.end();
  }, 5000);
});
server.listen(8080);
```

“Request” Callback

“Timeout” Callback

Callback Timeline, Non Blocking

Timing example: 2 requests to web application (indicated by red and blue in diagram)




Avoid Blocking Calls in Node.js apps

- setTimeout in previous slide is an example of an asynchronous, non-blocking call.
- Avoid potential blocking/synchronous calls
- **Activity likely to be blocking should be called asynchronously.**


Examples:

- Calls to 3rd party Web Services
- Database queries
- Computationally expensive operations (image file processing)

What if setTimeout() blocked...



Node Modules



Node Modules

- To install NPM modules, navigate to the application folder and run “npm install”. For example :
- **npm install express --save**
- This installs into a “**node_module**” folder in the current folder.
- The **--save** bit updates your **package.json** with the dependency
- To use the module in your code, use:
- **import express from 'express';**
- This loads express from local **node_modules** folder.

Creating your own Node Modules

- We want to create the following module called **custom_hello.js**:

```
const hello = function() {  
  console.log("hello!");  
}  
export default hello;
```

Export defines what
import returns

- To access in our application, **index.js**:

```
import hello from './custom_hello';  
hello();
```

Creating your own Node Modules

- Exporting Multiple Properties



Config.js


```
const env = process.env;

export const nodeEnv = env.NODE_ENV || 'development';

export const logStars = function(message) {
  console.info('*****');
  console.info(message);
  console.info('*****');
};

export default {
  port: env.PORT || 8080,
  host: env.HOST || '0.0.0.0',
  get serverUrl() {
    return `http://${this.host}:${this.port}`;
  }
};
```

- Accessing in other scripts



```
import config from './config';
import { logStars, nodeEnv } from './config';

logStars(`Port is ${config.port}, host is ${config.host}, environment is ${nodeEnv}`);
console.info(`Contact api available at ${config.serverUrl}/api/contests`);
```

express

4.16.4 • Public • Published 5 months ago

Readme

30 Dependencies

31,220 Dependents

261 Versions

express

Fast, unopinionated, minimalist web framework for node.

npm

v4.16.4

downloads

31M/m

linux

passing

windows

passing

coverage

100%

```
var express = require('express')
var app = express()

app.get('/', function (req, res) {
  res.send('Hello World')
})


app.listen(3000)
```

install

```
> npm i express
```

weekly downloads

7,597,647



version	license
4.16.4	MIT
open issues	pull requests
115	59
homepage	repository
expressjs.com	github
last publish	
4 months ago	

What Express Gives Us...

- Parses arguments and headers
- Easy Routing
 - Route a URL to a callback function
- Sessions
- File Uploads
- Middleware...

Simple Express App (index.js)

```
import express from 'express';
```

Loads Express module

```
const app = express();
```

Instantiates Express
server

```
app.use(express.static('public'));
```

Define static content for
HTTP GET

```
app.listen(8080, () => {  
  console.info('Express listening on port', 8080);  
});
```

Routing Examples

Syntax follows the pattern:

App.[verb](path, (req,res)=>{});

```
import express from 'express';

const app = express();

app.use(express.static('public'));

app.get('/contacts', (req,res)=>{res.end('I should really be a collection of contacts');});

app.listen(8080, () => {
  console.info('Express listening on port', 8080);
});
```

// Other Route examples

app.post('/contacts', createContact);

app.get('/contacts/:id', contactsRouter);

//Catch-all

app.all('/private(/*)?', requiresLogin);

HTTP POST request

Parametised URL. Accepts :app route argument

Catch-all – works for all HTTP verbs