

ReactJS.


Fundamentals

Agenda

- **Background.**
- **The V in MVC**
- **JSX (JavaScript Extension Syntax).**
- **Developer tools..**
- **React Component basics.**
- **Material Design.**

ReactJS.

- A Javascript framework for building dynamic Web User Interfaces.
 - A Single Page Apps technology.
 - Open-sourced in 2012.



- Client-side framework.
 - More a library than a framework.

Before ReactJS.

- MVC pattern – **The convention for app design. Promoted by market leaders**, e.g. **AngularJS (1.x), EmberJS, BackboneJS**.
- **React is not MVC, just V.**
 - **It challenged established best practice (MVC).**
- Templating – **widespread use in the V layer.**
 - **React based on components.**

	Templates	(React) Components
Separation of concerns	Technology (JS, HTML)	Responsibility
Semantic	New concepts and micro-languages	HTML and Javascript
Expressiveness	Underpowered	Full power of Javascript

Components

- **Philosophy:** *Build components, not templates.*
- **All about the User Interface (UI).**
 - **Not about business logic or the data model (Mvc)**
- **Component - A unit comprised of:**
 - UI description (HTML) + UI behavior (JS)*
 - **Two aspects are tightly coupled and co-located.**
 - **Pre-React frameworks decoupled them.**
 - **Benefits:**
 - 1. Improved Composition.**
 - 2. Greater Reusability.**

Creating the UI description

- React.createElement() – **create a HTML element.**
- ReactDOM.createRoot() – **which DOM node to attach an element.**
- React.createElement() **arguments:**
 1. **type (h1, div, button etc).**
 2. **properties (style, event handler etc).**
 3. **children (0 -> M).**
 - **We never use createElement() directly – too cumbersome.**
- ReactDOM.createRoot () **arguments:**
 1. **DOM node on which to mount the element.**

Code Demos

A screenshot of a web browser window displaying a file directory listing. The address bar shows the URL `127.0.0.1:5500`. The directory structure is as follows:

```
~ /  
  js  
  02-UIDescription.html  
  05-simpleComponent.html  
  README  
  node_modules  
  03-JSX-error.html  
  package-lock.json  
  style.css  
  01-UIDescription.html  
  04-JSX.html  
  package.json
```

Below the file listing, a blue callout box contains the text:

See Archive accompanying these slides.
Run code using VS Code Live Server extension

UI description implementation

(the imperative way)

- **See the demos:**
 - **Ref.** 01-UIDescription.html.
 - **Nesting createElement() calls - Ref.** 02-UIDescription.html
-

Imperative programming is a programming paradigm that uses statements that change a program's state


Declarative programming is a programming paradigm ... that expresses the logic of a computation without describing its control flow.

UI description implementation

(the declarative way)

- **JSX – JavaScript extension syntax.**
- **Declarative syntax for coding UI descriptions.**
- **Retains the full power of Javascript.**
- **Allows tight coupling between UI behavior and UI description.**
- **Must be transpiled before being sent to browser.**
 - The Babel tool
- **Reference** 03-JSX-error.html and 04-JSX.html

REPL (Read-Evaluate-Print-Loop) transpiler.



JSX.

- **HTML-like markup.**
 - It's actually XML code.
- Some minor HTML tag attributes differences, e.g. `className` (`class`), `htmlFor` (`for`).
- Allows UI description to be coded in a declarative style and be inlined in JavaScript.
- Combines the ease-of-use of templates with the power of JS.

Transpiling JSX.

- **What?**
 - The **Babel** platform.
- **How?**
 - 1. Manually, via REPL or command line.**
 - When experimenting only.
 - 2. Using specially instrumented web server during development mode - the Webpack library..**
 - 3. Using bundler tools as part the build process before deployment – Webpack again.**

React Components.

- **We develop COMPONENTS.**
 - A JS function **that returns a UI description**, i.e. JSX.
- **Can reference a component like a HTML tag.**
 - e.g.

```
const rootElement =  
  ReactDOM.createRoot(document.getElementById("mount-point"));  
rootElement.render(<DynamicLanguages/>);
```

- **Reference 05-simpleComponent.html**

React Developer tools.

- **create-react-app (CRA) - Features:**
 - **Scaffolding/Generator.**
 - **Development web server: auto-transpilation on file change + live reloading.**
 - **Builder: build production standard version of app, i.e. minification, bundling.**
- **Storybook - Features:**
 - **A development environment for React components.**
 - **Allows components be developed in isolation.**
 - **Promotes more reusable, testable components.**
 - **Quicker development – ignore app-specific dependencies.**



- **Installation:**

```
$ npm install @storybook/react
```

- **Tool has two aspects:**

1. **A web server.**

```
$ ./node_modules/.bin/start-storybook -p 6006 -c ./storybook
```

- **Performs live re-transpilation and re-loading.**

2. **Web browser user interface.**



- Storybook User interface.

A screenshot of a web browser window displaying the Storybook user interface. The title bar shows multiple tabs: "Storybook", "Middleware · R", "Semicolons in j", and "Travel anyw". The address bar shows the URL: "localhost:9001/?selectedKind=DynamicLanguages&selectedStory=nor".

The main content area has a header "STORYBOOK" and a "Filter" input field. On the left, there is a "Component catalogue" sidebar with a list of components: "DynamicLanguages", "OtherComponentX", and "OtherComponentY". A red arrow points from the "DynamicLanguages" item in the catalogue to the "Dynamic Languages" section in the main content area.

The main content area displays the "Dynamic Languages" component. It features a large title "Dynamic Languages" and a list of supported languages: "Python" and "Javascript". A blue callout bubble labeled "Component Rendering." points towards the list of languages.

```
> DynamicLanguages
> OtherComponentX
> OtherComponentY
```

Component catalogue

Dynamic Languages

- Python
- Javascript

Component Rendering.



- **What is a Story?**
- **A component may have several STATES → State effects how it renders.**
 - **Each state case termed a STORY.**
 - **Stories are a design consideration.**
- **EX.: DynamicLanguages component.**
 - **States might be:**
 - Default – **5 or less languages → Render full list**
 - Boundary – **empty list → Render ‘No languages’ message**
 - Exceptional – **More than 5 languages → Render first 5 and a ‘See More...’ link to display next 5.**

STORYBOOK

- List a component's states/stories under its name:

The screenshot shows a web browser window with the URL `localhost:9001/?selectedKind=DynamicLanguages&selectedStory=exceptional`. The page title is "STORYBOOK". On the left, there is a sidebar with a "Filter" input field and a list of components: "DynamicLanguages", "OtherComponentX", and "OtherComponentY". The "DynamicLanguages" item is expanded, showing three story types: "default", "boundary", and "exceptional". A blue speech bubble labeled "Set of Stories" points to the "exceptional" story. An orange arrow points from the "exceptional" story in the sidebar to the list of languages on the right. The main content area has a large heading "Dynamic Languages" and a bulleted list of languages: Python, Javascript, Ruby, PHP, and Groovy. There is also a "See more ..." link.

Set of Stories

Dynamic Languages

- Python
- Javascript
- Ruby
- PHP
- Groovy

[See more ...](#)



- Define component groups when component library is large.
 - helps others team members with searching.

The screenshot shows a web browser window titled "Storybook" with multiple tabs open. The main content area displays a component tree on the left and a detailed view of a selected component on the right.

Component Tree (Left):

- Group A
 - OtherComponentX
 - DynamicLanguages
 - default
 - boundary
 - exceptional** (highlighted in grey)
- Group B
 - OtherComponentY

Selected Component View (Right):

Dynamic Languages

- Python
- Javascript
- Ruby
- PHP
- Groovy

[See more ...](#)

Aside – JS Modularity.

- Split application code into multiple files, termed **modules**.
- Reusability - make modules available to other modules..
- Pre-ES6 provided module system via separate library;
- ES6 modules built into language.
 - Two main options: Default exports; Named exports.

- Also Mixed exports.

```
29 // lib.js
30 export default function() {
31   ...
32 }
33 // -----
34 // bar.js
35 import myFunc from './lib';
36 myFunc();
37
```

```
// lib.js (Named exports)
export let myStr = 'important string';
export const pi = 3.14159526;
export function myFunc() {
  ...
}
export class myClass {
  ...
}
// -----
// bar.js
import {myFunc, myStr} from './lib';
myFunc();
console.log(myStr)
```

Writing stories

- **.stories.js file extension (convention)**
- **1 Stories file per component**

```
import React from "react";
import DynamicLanguages from "../components/dynamicLanguages";

export default {
  title: "Dynamic Languages",
  component: DynamicLanguages,
};

export const Default = () => {
  const list = ["Javascript", "Python", "Java", "C#"];
  return <DynamicLanguages languages={list} />;
};

export const Exceptional = () => {
  .....
};

export const Error = () => {
  .....
};
```

default export; Metadata; How Storybook lists components.

- Story implemented as a function.
- Named exports.
- UpperCamelCase
- 3 stories for this component

Grouping stories.

- **Use directory pathname symbol (/) to indicate component grouping (i.e. group/subgroup/....).**


```
export default {  
  title: "Group A/ Component 1",  
  component: Component1,  
};  
  
... stories ...
```

```
export default {  
  title: "Group A/ Component 2",  
  component: Component2,  
};  
  
... stories ...
```

```
export default {  
  title: "Group B/ Component X",  
  component: Component1,  
};  
  
... stories ...
```

... back to components . . .

Demo Samples




The screenshot shows a file explorer window with a dark theme. The root directory is "BASICREACTLAB". Inside it are ".storybook", "node_modules", and a "src" folder. The "src" folder contains "components", "samples", and "stories". The "samples" folder is expanded, showing files: "01_staticComponent.js", "02_embeddedVar.js", "03_props.js", "04_iteration.js", "05_hierarchy.js", and "06_state.js". The "stories" folder contains "exercises" and "samples". The "samples" folder under "stories" is highlighted with a blue background. A ".gitignore" file and package lock files ("package-lock.json" and "package.json") are also present at the root level.

Annotations:

- A blue callout points to the ".storybook" file with the text "Configuration – boilerplate".
- A yellow callout points to the "01_staticComponent.js" file with the text "Lab exercise".
- A blue callout points to the "samples" folder under "stories" with the text "Sample Components".
- A blue callout points to the "samples" folder under "stories" with the text "Stories".

JSX - embedded variables.

- Dereference variable embedded in JSX using {} braces.
 - Braces can contain any valid JS expression.
- Reference samples/02_embeddedVariables.js



```
JS 02_embeddedVar.js ×
components > samples > JS 02_embeddedVar.js > ...
1 import React from "react";
2
3 const Demo = () => {
4   const languages = ["Go", "Julia", "Kotlin"];
5   const header = "Modern";
6   return (
7     <div>
8       <h1>{` ${header} Languages`} </h1>
9       <ul>
10         <li>{languages[0]}</li>
11         <li>{languages[1]} </li>
12         <li>{languages[2]} </li>
13       </ul>
14     </div>
15   );
16 };
17
18 export default Demo
```

Reusability.

- **We achieve reusability through** parameterization.
- **props – Component properties / attribute / parameters.**
 1. **Passing props to a component:**
`<CompName prop1Name={value} prop2Name={value} . . . />`
 2. **Access inside component via props object:**
`const ComponentName = (props) => {
 const p1 = props.prop1Name

}`
 3. **Props are Immutable.**
 4. **Part of a component's design.**
- **Reference** samples/03_props.js (and related story).

Aside.

- We can assign a single JSX element to a variable.

```
9
0  const demo = <div>
1      <h1>Something</h1>
2      <h2>Something else</h2>
3  </div> ;
```

- Why?

```
const demo = React.createElement(
  "div",
  null,
  React.createElement("h1", null, "Something"),
  React.createElement("p", null, "Some text ...")
);
```

Component collection - Iteration

- **Use case:** We want to generate an array of (similar) component from a data array.
- **Reference** samples/04_iteration.js

```
▼<div id="root">
  <h2>Most Popular client-side frameworks</h2> == $0
  ▼<ul>
    ▼<li>
      <a href="https://facebook.github.io/react/">React</a>
    </li>
    ▼<li>
      ▶<a href="https://vuejs.org/">...</a>
    </li>
    ▼<li>
      ▶<a href="https://angularjs.org/">...</a>
    </li>
  </ul>
</div>
```

Required HTML produced by component.
(From Chrome Dev Tools)

Component return value.

- **Examples:**
 1. return <MyComponent prop1={.....} prop2={.....} /> ;
 2. return (

```
<div>
  <h1>{this.props.type}</h1>
  <MyComponent prop1={.....} prop2={.....} />
  <p>
    . . .
  </p>
</div>
```

) ;
- **Must enclose in () when multiline.**

Component return value.

- **Must return only ONE element.**
- **Error Examples:**
 - ```
return (
 <h1>{this.props.type}</h1>
 <MyComponent prop1={.....} prop2={.....} />
 <p>

 </p>
) ;
```
  - **Error** – ‘Adjacent JSX elements must be wrapped in an enclosing tag’
  - **Solution: Wrap elements in a <div> tag.**

# Component return value.

- **Old solution:**

```
return (
 <div>
 <h1></h1>
 <MyComponent />
 <p> </p>
 </div>
) ;
```
- **Adds unnecessary depth to DOM → effects performance.**
- **Alternative solution:**

```
return (
 <>
 <h1></h1>
 <MyComponent />
 <p> </p>
</>
) ;
```
- **<> </> – special React element, termed Fragment.**
  - No DOM presence.

# Component *Hierarchy*.

All React application are designed as a hierarchy of components.

- Components have children – nesting.
- Ref. 05\_hierarchy.js.

The screenshot shows the Storybook interface with the sidebar navigation expanded. The 'Samples' section is selected, and the '05 - component hierarchy' item is highlighted in blue. The main content area displays two sections: 'Ranked client-side frameworks' and 'Ranked Server-side Languages'. The 'Ranked client-side frameworks' section lists React, Vue, and Angular, with a note that data is sourced from npm-stat.com. The 'Ranked Server-side Languages' section lists Javascript, Python, and Java, with a note that data is sourced from StackOverflow. Red circles numbered 1, 2, and 3 are overlaid on the right side of the content blocks, likely indicating a nesting or parent-child relationship.

**Ranked client-side frameworks**

- React
- Vue
- Angular

Data sourced from [npm-stat.com](#)

**Ranked Server-side Languages**

- Javascript
- Python
- Java

Data sourced from [StackOverflow](#)

# React version 18

- Released March 2022.
- One significant breaking change.

```
You, 1 second ago | 1 author (You)
1 import React from 'react'
2 import ReactDOM from 'react-dom'
3 import App from './App'
4 You, 5 months ago • Completed app but using Bootstrap
5 ReactDOM.render(<App />, document.getElementById('root'));
```

```
You, 1 second ago | 1 author (You)
1 import React from 'react' React 18
2 import { createRoot } from 'react-dom/client'
3 import App from './App'
4 You, 3 weeks ago • Initialize project using Create React App
5 const rootElement = createRoot(document.getElementById('root'))
6 rootElement.render(<App />);
```



# Material UI.

A 3<sup>rd</sup> party component library to build  
high quality digital UIs

# Material Design.

- Material (Design) **is a** design system **created by Google to help teams build** high-quality digital experiences **for Android, iOS, and web.**
- A visual language **that synthesizes classic principles of good design with the innovation and possibility of technology and science.**
- **Inspired by:**
  - **the physical world and its textures, including how they reflect light and cast shadows.**
  - **the study of paper and ink.**
- **Material is a metaphor.**
  - **Material surfaces reimagine the mediums of paper and ink.**

# Material Components.

- Material Components are **interactive building blocks** for creating a **digital user interface**.
- They cover a range of interface needs, including:
  1. **Display:** Placing and organizing content using components like cards, lists, and grids.
  2. **Navigation:** Allowing users to move through an application using components like navigation drawers and tabs.
  3. **Actions:** Allowing users to perform tasks using components such as the floating action button.
  4. **Input:** Enter information or make selections using components like text fields and selection controls.
  5. **Communication:** Alerting users to key information and messages using snackbars, banners and dialogues.

# Theming.

- Material Design does not mean copy Google design.
- Material Theming makes it easy to customize Material Design to match the look and feel of your brand, with built-in support and guidance for customizing colors, typography styles, and corner shape.
- Color - Material's color system is an organized approach to applying color to a UI. Global color styles have semantic names and defined usage in components – primary, secondary.
- Typography - The Material type system provides 13 typography styles for everything from headlines to body text and captions.
  - Each style has a clear meaning and intended application within an interface.

# Material UI.

- MUI is a React component library based on the Material Design system.
- Its React components include: <Card />, <Box />, <Grid />, <Menu />, <Button />, <Icon />, <Snackbar />, <Typography />  
.....
- Build your own design system, or start with Material Design.
- The CSS-in-JS model.

# CSS-in-JS

- **Plain CSS**

```
.my-header {
 background-color: lightblue;
 padding: 10px;
}

```

```
import 'app.css'
```

```
<header
 className="my-header">

```

```
</header>
```

- **CSS-in-JS**

```
const myHeader = {
 backgroundColor: "lightblue",
 padding: "10px"
};

```

```
<header style={myHeader}>
----- </header>
```

Must be  
CamelCase

# Summary.

- **JSX.**
  - UI description and behaviour **tightly coupled**.
  - **Can embed variables/expressions with braces.**
- **All about components.**
  - A function that takes a **props argument** and returns a single **JSX element** .
  - **Components can be nested.**
- **Storybook tool.**
  - **Develop components in isolation.**
  - **Story – the state (data values) of a component can effect its rendering (and behaviour).**
- **Material Design – The Material UI React library.**

