

TEXTILE

GLAZED PORCELAIN STONEWARE

18" x 18"

12" x 12"


RAGNO  USA



R8M4 Textile SA Rectified
24" x 24"

R8M9 Textile SA Rectified
12" x 24"

R8L9 Textile SA Rectified
12" x 48"*



AJ2H Textile SA
Mosaic 1" x 3"
12" x 12"



R9C0 Damasko SA Rectified
Deco
12" x 24"



R8L4 Textile Ramage MA
Rectified
24" x 24"*



TRIMS


R8R2 Textile SA SBN
R8R3 Textile GR SBN
R8Q9 Textile MA SBN
R8R0 Textile AN SBN
4" x 24"



R8M5 Textile GR Rectified
24" x 24"

R8N0 Textile GR Rectified
12" x 24"

R8M0 Textile GR Rectified
12" x 48"*



AJ2F Textile GR
Mosaic 1" x 3"
12" x 12"



R9A9 Damasko GR Rectified
Deco
12" x 24"




R8L5 Textile Ramage AN
Rectified
24" x 24"*



R8M1 Textile MA Rectified
24" x 24"

R8M6 Textile MA Rectified
12" x 24"

R8L6 Textile MA Rectified
12" x 48"*



AJ2E Textile MA
Mosaic 1" x 3"
12" x 12"



R9A7 Lamè MA Rectified
Deco
12" x 24"

R9A5 Lamè MA Rectified
Listelli
1 1/8" x 24"



R8Z9 Rattan MA Rectified
Deco
12" x 24"


R9C5 Rattan MA Rectified
Listelli
1 1/2" x 24"



R8M2 Textile AN Rectified
24" x 24"

R8M7 Textile AN Rectified
12" x 24"

R8L7 Textile AN Rectified
12" x 48"*



AJ2G Textile AN
Mosaic 1" x 3"
12" x 12"



R9A6 Lamè NE Rectified
Deco
12" x 24"

R9A4 Lamè NE Rectified
Listelli
1 1/8" x 24"



R8Z8 Rattan NE Rectified
Deco
12" x 24"

R9C4 Rattan NE Rectified
Listelli
1 1/2" x 24"



Field Tile



Wall Tile



Modular Tile



3d Printing
Technique



Rectified Tile



Decorative Tile



Trim Available



Suitable for
Outdoors



Uniform Variation



Frost Resistant



Meets ADA
Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)
44% Minimum
Pre-Consumer
Recycled Content



Certified No VOC



Contributes to
LEED Credits

***SPECIAL ORDER**

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength 12" x 24"	≥ 250 lbf.	≥ 928 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.25 % or +/- 0.8 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.40 % or +/- 1.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class V	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.80 ≤ COF < 0.90	C1028
Chemical Resistance	Class A - Class E	Class B	C650
Stain Resistance	Class A - Class E	Class B	C1378

* Whichever is less

