

PETRA

GLAZED PORCELAIN STONEWARE

20"x20"

13"x13"

6 1/2"x6 1/2"

RAGNO  USA



GAKF Eburneus IV
20"x20"
GAKP Eburneus IV
13"x13"
GAKV Eburneus IV
6 1/2"x6 1/2"



GAM0 Eburneus IV
Mosaic-Square 2"x2"
13"x13"



GAM4 Eburneus IV
Mosaic-Brick 2"x3"
13"x13"



GALC Eburneus IV
Insert
6 1/2"x6 1/2"



GAM8 Marble
Insert
2"x2"

TRIMS



GAKZ Eburneus IV Bullnose
GAL0 Auratus BG Bullnose
GAL1 Columnus NO Bullnose
GAL2 Luteus MT Bullnose
3"x13"



GAKG Auratus BG
20"x20"
GAKQ Auratus BG
13"x13"
GAKW Auratus BG
6 1/2"x6 1/2"



GAM1 Auratus BG
Mosaic-Square 2"x2"
13"x13"



GAM5 Auratus BG
Mosaic-Brick 2"x3"
13"x13"



GALD Auratus BG
Insert
6 1/2"x6 1/2"



AG3J Palace
Border
1 1/4"x13"



GALL Eburneus IV V-Cap Corner
GALM Auratus BG V-Cap Corner
GALN Columnus NO V-Cap Corner
GALP Luteus MT V-Cap Corner
1 3/4"x2 1/4"



GAKH Columnus NO
20"x20"
GAKR Columnus NO
13"x13"
GAKX Columnus NO
6 1/2"x6 1/2"



GAM2 Columnus NO
Mosaic-Square 2"x2"
13"x13"



GAM6 Columnus NO
Mosaic-Brick 2"x3"
13"x13"



GALE Columnus NO
Insert
6 1/2"x6 1/2"



AG3L Palace
Corner
1 1/4"x1 1/4"



GALG Eburneus IV V-Cap Corner
GALH Auratus BG V-Cap Corner
GALJ Columnus NO V-Cap Corner
GALK Luteus MT V-Cap Corner
2 1/4"x6 1/2"



GAKJ Luteus MT
20"x20"
GAKT Luteus MT
13"x13"
GAKY Luteus MT
6 1/2"x6 1/2"



GAM3 Luteus MT
Mosaic-Square 2"x2"
13"x13"



GAM7 Luteus MT
Mosaic-Brick 2"x3"
13"x13"



GALT Luteus MT
Insert
6 1/2"x6 1/2"



AG3K Palace
Insert
1 1/4"x1 1/4"



GALW Eburneus IV Beak
GALX Auratus BG Beak
GALY Columnus NO Beak
GALZ Luteus MT Beak
1"x1"



Field Tile



Wall Tile



Modular Tile



Decorative Tile



Trim Available



Suitable for
Outdoors



Extreme Variation



Frost Resistant



Meets ADA
Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum
Pre-Consumer
Recycled Content



Certified No VOC



Contributes to
LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 471 lbf.
	13"x13"	≥ 250 lbf.	≥ 515 lbf.
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

