

MARAJÁ

GLAZED PORCELAIN STONEWARE

20"x20"

13"x13"

6 1/2"x6 1/2"

RAGNO  USA



RE97 Marajá BG

20"x20"

RF01 Marajá BG

13"x13"

RF05 Marajá BG

6 1/2"x6 1/2"



RE98 Marajá MT

20"x20"

RF02 Marajá MT

13"x13"

RF06 Marajá MT

6 1/2"x6 1/2"



RE99 Marajá VE

20"x20"

RF03 Marajá VE

13"x13"

RF07 Marajá VE

6 1/2"x6 1/2"



RF00 Marajá NE

20"x20"

RF04 Marajá NE

13"x13"

RF08 Marajá NE

6 1/2"x6 1/2"



RJ67 Marajá BG

Mosaic-Square 2"x2"

13"x13"



RJ68 Marajá MT

Mosaic-Square 2"x2"

13"x13"



RJ69 Marajá VE

Mosaic-Square 2"x2"

13"x13"



RJ70 Marajá NE

Mosaic-Square 2"x2"

13"x13"



RJ71 Marajá Listelli BG

13"x13"



RJ72 Marajá Listelli MT

13"x13"



RJ73 Marajá Listelli VE

13"x13"




RJ74 Marajá Listelli NE

13"x13"




RK94 Kali BG

2"x13"



RK93 Kali MT

2"x13"



RK92 Kali VE

2"x13"



RK91 Kali NE

2"x13"

TRIMS



RJ75 Marajá FR. BG/MT

2"x13"



AH5H Marajá BG Cove Base

6"x8"



AH5M Marajá BG Cove Base In Angle

1"x6"



AH5R Marajá BG Cove Base Out Angle

1"x6"




RJ76 Marajá FR. VE/MT

2"x13"



A387 Marajá BG V-Cap Corner

2 1/4"x2 1/4"




A375 Marajá BG V-Cap

1 3/4"x2 1/4"



A383 Marajá BG Beak

1 3/4"x2 1/4"



A381 Marajá VE Bead

2 1/4"x6 1/2"




RJ77 Marajá FR. NE/MT

2"x13"



A388 Marajá MT V-Cap Corner

2 1/4"x2 1/4"




A377 Marajá VE V-Cap

1 3/4"x2 1/4"



A385 Marajá VE Beak

1 3/4"x2 1/4"



A382 Marajá NE Bead

2 1/4"x6 1/2"



Field Tile



Wall Tile



Modular Tile



Decorative Tile



Trim Available



Suitable for Outdoors



Substantial Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum Pre-Consumer Recycled Content



Certified No VOC



Contributes to LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	76	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 635 lbf.
	13"x13"	≥ 250 lbf.	≥ 495 lbf.
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

