

# STATUS

GLAZED PORCELAIN STONEWARE

18" x 18"

12" x 12"

**RAGNO**  **USA**



**AF2D** Status BG  
18"x18"



**AF2A** Status BG  
12"x12"



**AF2E** Status MT  
18"x18"



**AF2B** Status MT  
12"x12"



**AF2F** Status NO  
18"x18"



**AF2C** Status NO  
12"x12"



Field Tile



Wall Tile



Trim Available



Suitable for  
Outdoors



Moderate Variation



Frost Resistant



Meets ADA  
Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



7% Minimum  
Pre-Consumer  
Recycled Content



Certified No VOC



Contributes to  
LEED Credits

## TRIMS



**AF4L** Status BG SBN

**AF4M** Status MT SBN

**AF4N** Status NO SBN

3"x12"

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	18"x18" ≥ 250 lbf.	≥ 467 lbf.	C648
	12"x12" ≥ 250 lbf.	≥ 364 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.60 ≤ COF < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

\* Whichever is less

