

BOARDWALK

COLOR BODY PORCELAIN STONEWARE | RECTIFIED

20"x 20"

13"x 13"

RAGNO  **USA**



Field Tile



Wall Tile



Decorative Tile



Trim Available



Suitable for Outdoors



Substantial Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)




Certified No VOC



21% Minimum Pre-Consumer Recycled Content



AJ4B Boardwalk BG
20"x20"




AJ38 Boardwalk BG
13"x13"



AJ4Y Boardwalk BG
3 1/4"x6 1/2"




AJ4C Boardwalk GR
20"x20"



AJ39 Boardwalk GR
13"x13"



AJ4Z Boardwalk GR
3 1/4"x6 1/2"



AJ4D Boardwalk MC
20"x20"



AJ4A Boardwalk MC
13"x13"



AJ52 Boardwalk MC
3 1/4"x6 1/2"



AJ53 Boardwalk BG
Mosaic - Square 2"x2"
13"x13"



AJ56 Boardwalk BG
Mosaic - Brick 1"x4 1/4"
13"x13"



AJ54 Boardwalk GR
Mosaic - Square 2"x2"
13"x13"



AJ57 Boardwalk GR
Mosaic - Brick 1"x4 1/4"
13"x13"



AJ55 Boardwalk MC
Mosaic - Square 2"x2"
13"x13"



AJ58 Boardwalk MC
Mosaic - Brick 1"x4 1/4"
13"x13"

TRIMS

BULLNOSE



AJ4L Boardwalk BG
AJ4M Boardwalk GR
AJ4N Boardwalk MC
3"x13"

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 598 lbf.
	13"x13"	≥ 250 lbf.	≥ 414 lbf.
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.25 % or +/- 0.8 mm*	Within Standard	C502
Warp (Flatness)	+/- 0.40 % or +/- 1.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less



Contributes to
LEED Credits