## CRYSTAL STONE MESH MOUNTED GLASS/STONE MOSAICS

12"x 12"



Field Tile

Wall Tile Decorative Tile

Average Variation

Abrasion Resistance

Frost Resistant

**0.4** C.O.F. (Wet)

**0.6** C.O.F. (Dry)


Ш



**LG4A** Ivory 12"x12"



LG4D Marine 12"x12"



LG4G Purple 12"x12"



LG4B Caramel 12"x12"



LG4E Coffee 12"x12"



LG4H Honey 12"x12"



LG4C Breeze 12"x12"




LG4F Walnut 12"x12"



LG4J Gold 12"x12"





TECHNICAL SPECIFICATIONS			
DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	2% - 5%	2% - 5%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	≥ 250 lbf.	N/A	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class III	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.40 ≤ COF < 0.50	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

<sup>\*</sup> Whichever is less