

# ECLIPSE

GLAZED PORCELAIN STONEWARE

20"x 20"

13"x 13"

6 1/2"x6 1/2"

RAGNO  USA



**R674** Moon Light BI  
20"x20"

**R687** Moon Light BI  
13"x13"

**R692** Moon Light BI  
6 1/2"x6 1/2"



**R676** Desert Shade BG  
20"x20"

**R689** Desert Shade BG  
13"x13"

**R694** Desert Shade BG  
6 1/2"x6 1/2"



**R686** Solar Coat GI  
20"x20"

**R691** Solar Coat GI  
13"x13"

**R696** Solar Coat GI  
6 1/2"x6 1/2"



**AF2H** Moon Light BI  
Mosaic - Square 2"x2"  
13"x13"



**AF2K** Desert Shade BG  
Mosaic - Square 2"x2"  
13"x13"



**AF2M** Solar Coat GI  
Mosaic - Square 2"x2"  
13"x13"



**AF2L** Forest Light NO  
Mosaic - Square 2"x2"  
13"x13"



**R677** Forest Light NO  
20"x20"

**R690** Forest Light NO  
13"x13"

**R695** Forest Light NO  
6 1/2"x6 1/2"



**R675** Flaming Sun RS  
20"x20"

**R688** Flaming Sun RS  
13"x13"

**R693** Flaming Sun RS  
6 1/2"x6 1/2"



**RE01** Garden Shade VE  
20"x20"

**RD99** Garden Shade VE  
13"x13"

**RE00** Garden Shade VE  
6 1/2"x6 1/2"



**AF2J** Flaming Sun RS  
Mosaic - Square 2"x2"  
13"x13"



**AF2N** Garden Shade VE  
Mosaic - Square 2"x2"  
13"x13"

## TRIMS



**AE29** Space BI V-Cap  
**AE2A** Space RS V-Cap  
**AE2B** Space BG V-Cap  
**AE2D** Space GI V-Cap  
**AE2E** Space VE V-Cap  
2 1/4"x6 1/2"



**AE2M** Space BI Bead  
**AE2N** Space RS Bead  
**AE2P** Space BG Bead  
**AE2Q** Space NO Bead  
**AE2R** Space GI Bead  
**AE2S** Space VE Bead  
1"x6 1/2"



**AE2T** Space BI Beak  
**AE2V** Space BG Beak  
**AE2W** Space NO Beak  
**AE2X** Space GI Beak  
**AE2Y** Space VE Beak  
1"x1"



**R811** Flash BI SBN  
**R812** Flash RS Bullnose  
**R813** Flash BG Bullnose  
**R814** Flash NO Bullnose  
**R815** Flash GI Bullnose  
3"x13"  
SINGLE FIRED



**R658** Flash BI Bullnose  
**R659** Flash RS Bullnose  
**R660** Flash BG Bullnose  
**R661** Flash NO Bullnose  
**R662** Flash GI Bullnose  
**A364** Flash VE Bullnose  
3"x13"  
GLAZED PORCELAIN



Field Tile



Wall Tile



Modular Tile



Decorative Tile



Trim Available



Suitable for  
Outdoors



Substantial Variation



Frost Resistant



Meets ADA  
Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum  
Pre-Consumer  
Recycled Content



Certified No VOC



Contributes to  
LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength 20"x20"	≥ 250 lbf.	≥ 600 lbf.	C648
13"x13"	≥ 250 lbf.	≥ 450 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.60 ≤ COF < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

\* Whichever is less

