OMETSTONE

20"x 20" 13"x 13" 61/2"x61/2"





R591 Snow Ball BI 20"x20" R596 Snow Ball BI 13"x13" R653 Snow Ball BI 61/2"x61/2"







R595 Solar Swish GI 20"x20" R600 Solar Swish GI 13"x13" R657 Solar Swish GI 61/2"x61/2



AF2H Snow Ball BI Mosaic - Square 2"x2" 13"x13"

AF2M Solar Swish GI

Mosaic - Square 2"x2" 13"x13"

AF2J Sun Flash RS

Mosaic - Square 2"x2" 13"x13"



AF2K Gold Wing BG Mosaic - Square 2"x2" 13"x13"





Mosaic - Square 2"x2" 13"x13"





AF2N Green Valley VE Mosaic - Square 2"x2" 13"x13"



Frost Resistant Meets ADA



Recommendations Abrasion Resistance

Substantial Variation



C.O.F. (Wet)

Field Tile

Wall Tile

Decorative Tile

Trim Available

Suitable for

Outdoors



C.O.F. (Dry) 21% Minimum Pre-Consumer Recycled Content



Certified No VOC





R594 Cliff Tail NO 20"x20" R599 Cliff Tail NO 13"x13" R656 Cliff Tail NO 61/2"x61/2"

AH2Z Snow Ball BI

AH22 Sun Flash RS

AH24 Cliff Tail NO

AH23 Gold Wing BG

AH25 Solar Swish GI

AH26 Green Valley VE Cove Base

TRIMS

6"x8"



R592 Sun Flash RS 20"x20" R597 Sun Flash RS 13"x13" R654 Sun Flash RS 61/2"x61/2"

AH27 Snow Ball BI

AH28 Sun Flash RS


AH3A Cliff Tail NO

AH3B Solar Swish GI

AH29 Gold Wing BG



13"x13" RD98 Green Valley VE 61/2"x61/2"



Cove Base Out Angle AH3E Sun Flash RS Cove Base Out Angle Cove Base Out Angle AH3F Gold Wing BG Cove Base Out Angle AH3G Cliff Tail NO AH3H Solar Swish GI Cove Base Out Angle AH3J Green Valley VE Cove Base Out Angle

SINGLE FIRED

GLAZED PORCELAIN

Cove Base

Cove Base

Cove Base

Cove Base

Cove Base

3"x13



R812 Flash RS Bullnose R814 Flash NO Bullnose R815 Flash GI Bullnose 3"x13"

R658 Flash BI Bullnose R659 Flash RS Bullnose R660 Flash BG **Bullnose** R661 Flash NO Bullnose R662 Flash GI Bullnose A364 Flash VE Bullnose

1"x6'

AE29 Space BI V-Cap AE2A Space RS V-Cap AE2B Space BG V-Cap AE2D Space GI V-Cap AE2E Space VE V-Cap 21/4"x61/2"

AE2M Space BI Bead AE2N Space RS Bead Space BG Bead AE2P AE2Q Space NO Bead AE2R Space GI Bead AE2S Space VE Bead 1"x61/2"

AE2T Space BI Beak AE2V Space BG Beak AE2W Space NO Beak AE2X Space GI Beak AE2Y Space VE Beak

TECHNICAL SPECIFICATIONS				
DESCRIPTION		ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption		≤ 0.50%	≤ 0.50%	C373
Frost Resistance		As Reported	Resistant	C1026
Scratch Resistance		MOHS 1-10	6	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 598 lbf.	C648
	13"x13"	≥ 250 lbf.	≥ 517 lbf.	C648
Facial Dimension		-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness		≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)		+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)		+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance		Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)		As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)		As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance		Class A - Class E	Class A	C650
Stain Resistance		Class A - Class E	Class A	C1378



^{*} Whichever is less