

BURGUNDY

GLAZED PORCELAIN STONEWARE | RECTIFIED

18" x 18"

12" x 12"

RAGNO  USA



AF3N Burgundy GR

20" x 20"

AF3J Burgundy GR

13" x 13"

AF56 Burgundy GR

6 1/2" x 6 1/2"



AG58 Burgundy GR

Mosaic - Square 2" x 2"

13" x 13"



AF3P Burgundy GO

20" x 20"

AF3K Burgundy GO

13" x 13"

AF57 Burgundy GO

6 1/2" x 6 1/2"



AG59 Burgundy GO

Mosaic - Square

2" x 2"

13" x 13"



AF62 Burgundy GR Listelli

1" x 13"



AF63 Burgundy GO Listelli

1" x 13"



AF3Q Burgundy NO

20" x 20"

AF3L Burgundy NO

13" x 13"

AF58 Burgundy NO

6 1/2" x 6 1/2"



AG6A Burgundy NO

Mosaic - Square 2" x 2"

13" x 13"



AF3R Burgundy TC


20" x 20"

AF3M Burgundy TC

13" x 13"

AF59 Burgundy TC

6 1/2" x 6 1/2"



AG6B Burgundy TC

Mosaic - Square 2" x 2"

13" x 13"



AF64 Burgundy NO Listelli

1" x 13"



AF65 Burgundy TC Listelli

1" x 13"

TRIMS



AF3S Burgundy GR Bullnose

AF3T Burgundy GO Bullnose

AF3U Burgundy NO Bullnose

AF3V Burgundy TC Bullnose

3" x 13"



AF5E Burgundy GR Bead

AF5F Burgundy GO Bead

AF5G Burgundy NO Bead

AF5H Burgundy TC Bead

1" x 6 1/2"



AF5J Burgundy GR Beak

AF5K Burgundy GO Beak

AF5L Burgundy NO Beak

AF5M Burgundy TC Beak

1" x 1"



AF5N Burgundy GR V-Cap

AF5P Burgundy GO V-Cap

AF5Q Burgundy NO V-Cap

AF5R Burgundy TC V-Cap

2" x 6 1/2"



AF5S Burgundy GR V-Cap Corner

AF5T Burgundy GO V-Cap Corner

AF5U Burgundy NO V-Cap Corner

AF5V Burgundy TC V-Cap Corner

7/8" x 2"



Field Tile



Wall Tile



Modular Tile



Decorative Tile



Trim Available



Suitable for
Outdoors



Moderate Variation



Frost Resistant



Meets ADA
Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



Certified No VOC



21% Minimum
Pre-Consumer
Recycled Content



Contributes to
LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	18" x 18" ≥ 250 lbf.	≥ 530 lbf.	C648
	12" x 12" ≥ 250 lbf.	≥ 400 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

