## LASTRICATO

GLAZED PORCELAIN STONEWARE

12"x18" 12"x12" 5<sup>7/8</sup>"x12"

5<sup>7/8</sup>"x5<sup>7/8</sup>" 3<sup>7/8</sup>"x3<sup>7/8</sup>"



3Y79 Surbo BI 12"x18" 3Y82 Surbo BI 12"x12" 3Y85 Surbo BI 5<sup>7/8</sup>"x12" 3Y88 Surbo BI 5<sup>7/8</sup>"x5<sup>7/8</sup>" 3Y91 Surbo BI 3<sup>7/8</sup>"x3<sup>7/8</sup>"



2X54 Porfido GR 12"x18" **2X51** Porfido GR 12"x12" 2X57 Porfido GR 5<sup>7/8</sup>"x12" 2X60 Porfido GR 2X80 Porfido GR 3<sup>7/8</sup>"x3<sup>7/8</sup>"




3Y77 Trani BG 12"x18" 3Y80 Trani BG 12"x12" 3Y83 Trani BG 5<sup>7/8</sup>"x12" 3Y86 Trani BG 5<sup>7/8</sup>"x5<sup>7/8</sup>" 3Y89 Trani BG 3<sup>7/8</sup>"x3<sup>7/8</sup>"



2X52 Porfido RS 12"x18" **2X49** Porfido RS 12"x12" 2X55 Porfido RS 57/8"x12" 2X58 Porfido RS 2X78 Porfido RS 3<sup>7/8</sup>"x3<sup>7/8</sup>"



3Y78 Borriol BR 12"x18" 3Y81 Borriol BR 12"x12" **3Y84** Borriol BR 5<sup>7/8</sup>"x12" 3Y87 Borriol BR 5<sup>7/8</sup>"x5<sup>7/8</sup>" 3Y90 Borriol BR 3<sup>7/8</sup>"x3<sup>7/8</sup>"



2X53 Basalto NE 12"x18" **2X50** Basalto NE 12"x12" 2X56 Basalto NE 57/8"x12" **2X59** Basalto NE 5<sup>7/8</sup>"x5<sup>7/8</sup>" 2X79 Basalto NE 37/8"x37/8"



**RAGNO** USA



Wall Tile



Trim Available



Suitable for Outdoors



Slight Variation



Frost Resistant



Meets ADA Recommendations





Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



TECHNICAL SPECIFICATIONS				
DESCRIPTION		ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption		≤ 0.50%	≤ 0.50%	C373
Frost Resistance		As Reported	Resistant	C1026
Scratch Resistance		MOHS 1-10	8	MOHS SCALE
Breaking Strength	12"x18"	≥ 250 lbf.	≥ 500 lbf.	C648
	12"x12"	≥ 250 lbf.	≥ 655 lbf.	C648
Facial Dimension		-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness		≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)		+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)		+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance		Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)		As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)		As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance		Class A - Class E	Class A	C650
Stain Resistance		Class A - Class E	Class A	C1378

