

# BORGOFORTE

GLAZED PORCELAIN STONEWARE | RECTIFIED

18" x 18"

12" x 12"

**RAGNO**  USA



**AG2H** Siena GR

18" x 18"

**AG2D** Siena GR

12" x 12"



**AG3P** Siena GR Listelli

1 1/2" x 12"



**AG3T** Siena GR Insert

1 1/2" x 1 1/2"



**AG2F** Orvieto BL

18" x 18"

**AG2B** Orvieto BL

12" x 12"



**AG3M** Orvieto BL Listelli

1 1/2" x 12"



**AG3R** Orvieto BL Insert

1 1/2" x 1 1/2"




**AG2E** Cassino BG

18" x 18"

**AG2A** Cassino BG

12" x 12"



**AG2N** Cassino BG Listelli

1 1/2" x 12"



**AG3Q** Cassino BG Insert

1 1/2" x 1 1/2"




**AG2G** Perugia MA

18" x 18"

**AG2C** Perugia MA

12" x 12"



**AG3N** Perugia MA Listelli

1 1/2" x 12"



**AG3S** Perugia MA Insert

1 1/2" x 1 1/2"

## SINGLE BULLNOSE



**AG2M** Siena GR SBN  
**AG2K** Orvieto BL SBN  
**AG2J** Cassino BG SBN  
**AG2L** Perugia MA SBN  
**3" x 12"**



Field Tile



Wall Tile



Decorative Tile



Trim Available



Suitable for Outdoors



Slight Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



Certified No VOC



7% Minimum Pre-Consumer Recycled Content



Contributes to LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	18" x 18"	≥ 250 lbf.	≥ 550 lbf.
	12" x 12"	≥ 250 lbf.	≥ 480 lbf.
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.25 % or +/- 0.8 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.40 % or +/- 1.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.60 ≤ COF < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

\* Whichever is less

