



*live inspired*

# CLEFTSTONE

GLAZED PORCELAIN TILE



**92D1** Cleftstone BI  
20"x20"  
**91S1** Cleftstone BI  
13"x13"  
**91T5** Cleftstone BI  
6 1/2"x6 1/2"



**92D0** Cleftstone BG  
20"x20"  
**91S0** Cleftstone BG  
13"x13"  
**91T4** Cleftstone BG  
6 1/2"x6 1/2"



**92C8** Cleftstone GI  
20"x20"  
**91R8** Cleftstone GI  
13"x13"  
**91T2** Cleftstone GI  
6 1/2"x6 1/2"



**92C7** Cleftstone MT  
20"x20"  
**91R7** Cleftstone MT  
13"x13"  
**91T1** Cleftstone MT  
6 1/2"x6 1/2"



**92C6** Cleftstone VE  
20"x20"  
**91R6** Cleftstone VE  
13"x13"  
**91T0** Cleftstone VE  
6 1/2"x6 1/2"




**92C5** Cleftstone NE  
20"x20"  
**91R5** Cleftstone NE  
13"x13"  
**91S9** Cleftstone NE  
6 1/2"x6 1/2"



**AJ4T** Cleftstone MT  
Mosaic - Square 2"x2"  
13"x13"



**AJ4U** Cleftstone VE  
Mosaic - Square 2"x2"  
13"x13"



**AJ4V** Cleftstone NE  
Mosaic - Square 2"x2"  
13"x13"



**9127** Riverstone RED  
Freccia  
6 1/2"x13"



**9126** Riverstone GREEN  
Freccia  
6 1/2"x13"



**9129** Riverstone RED  
Freccia Corner  
6 1/2"x6 1/2"



**9128** Riverstone GREEN  
Freccia Corner  
6 1/2"x6 1/2"

## TRIMS



**93M9** Stone BI V-Cap Corner  
**93M8** Stone BG V-Cap Corner  
**93M7** Stone GI V-Cap Corner  
**93M6** Stone MT V-Cap Corner  
**93M5** Stone VE V-Cap Corner  
**93M4** Stone NE V-Cap Corner  
1 3/4"x2 1/4"



**93N5** Stone BI V-Cap  
**93N4** Stone BG V-Cap  
**93N3** Stone GI V-Cap  
**93N2** Stone MT V-Cap  
**93N1** Stone VE V-Cap  
**93N0** Stone NE V-Cap  
2 1/4"x13"



**91S8** Stone BI Bullnose  
**91S7** Stone BG Bullnose  
**91S5** Stone GI Bullnose  
**91S4** Stone MT Bullnose  
**91S3** Stone VE Bullnose  
**91S2** Stone NE Bullnose  
3"x13"

- Floor Tile
- Wall Tile
- Modular Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Moderate Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- 21% Minimum Pre-Consumer Recycled Content
- Certified No VOC



Contributes to  
LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 605 lbf.
	13"x13"	≥ 250 lbf.	≥ 635 lbf.
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

\* Whichever is less

