RAGNO USA

live inspired

ARKITESSUTO

COLOR BODY PORCELAIN TILE

R0K1 Arki BI* 24"x24"
R0Q7 Arki BI 24"x24"
R0S3 Arki BI 12"x24"
R0T7 Arki BI 6"x24"
R0T0 Arki BI 12"x12"

R0K4 Arki GR* 24"x24"
R0R0 Arki GR 24"x24"
R0S6 Arki GR 12"x24"
R0U0 Arki GR 6"x24"
R0T3 Arki GR 12"x12"

R0K0 Arki BG* 24"x24"
R0Q6 Arki BG 24"x24"
R0S2 Arki BG 12"x24"
R0T6 Arki BG 6"x24"
R0S9 Arki BG 12"x12"

R0K2 Arki NE* 24"x24"
R0Q8 Arki NE 24"x24"
R0S4 Arki NE 12"x24"
R0T8 Arki NE 6"x24"
R0T1 Arki NE 12"x12"

R0J9 Arki MA* 24"x24"
R0Q5 Arki MA 24"x24"
R0S1 Arki MA 12"x24"
R0T5 Arki MA 6"x24"
R0S8 Arki MA 12"x12"

R0K5 Arki PL* 24"x24"
R0R1 Arki PL 24"x24"
R0S7 Arki PL 12"x24"
R0U1 Arki PL 6"x24"
R0T4 Arki PL 12"x12"

R0K3 Arki GR.CH.* 24"x24"
R0Q9 Arki GR.CH. 24"x24"
R0S5 Arki GR CH. 12"x24"
R0T9 Arki GR CH. 6"x24"
R0T2 Arki GR CH. 12"x12"

R0X0 Onda BG Deco 12"x24"

R0W9 Onda MA Deco 12"x24"

R0X1 Onda GR CH Deco 12"x24"

R0X2 Onda PL Deco 12"x24"

R0R6 Disko AR Insert 6"x6"

R0R5 Disko VE Insert 6"x6"

R0R7 Arki BI Deco 12"x24"

R0R8 Arki BG Deco 12"x24"

R0S0 Arki GR Deco 12"x24"

R0R9 Arki NE Deco 12"x24"

R0R2 Disko NE Insert 6"x6"

R0R3 Disko AL Insert 6"x6"

R0R4 Disko BR Insert 6"x6"

R0X6 Onda BI Deco 12"x24"

R0X5 Ricamo MA Deco 24"x24"

R0X3 Ricamo GR Deco 24"x24"

R0X4 Ricamo PL Deco 24"x24"

R0W1 Ellissi NE Listelli 6"x24"

R0W2 Ellissi AL Listelli 6"x24"

R0W3 Ellissi BR Listelli 6"x24"

TRIMS

R0V6 Arki BI Pencil Liner
R0V5 Arki BG Pencil Liner
R0V4 Arki MA Pencil Liner
R0V8 Arki GR CH. Pencil Liner
R0V9 Arki GR Pencil Liner
R0V7 Arki NE Pencil Liner
R0W0 Arki PL Pencil Liner
1/2"x12"

R0V0 Arki BI Bullnose
R0U9 Arki BG Bullnose
R0U8 Arki MA Bullnose
R0V2 Arki GR CH. Bullnose
R0V3 Arki GR Bullnose
R0V1 Arki NE Bullnose
4"x12"

R0U4 Arki BI Stairtread
R0U3 Arki BG Stairtread
R0U2 Arki MA Stairtread
R0U6 Arki GR CH. Stairtread
R0U7 Arki GR Stairtread
R0U5 Arki NE Stairtread
12"x12"

R0X8 Tre MA Listelli 1 1/4"x24"

R0X9 Tre BG Listelli 1 1/4"x24"

R0X7 Tre NE Listelli 1 1/4"x24"

- Floor Tile
- Wall Tile
- Modular Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- V3 Moderate Variation
- Frost Resistant
- Meets ADA Recommendations
- IV Abrasion Resistance
- 0.6 C.O.F. (Wet)
- 0.7 C.O.F. (Dry)
- VOC Certified No VOC

Contributes to LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION		ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption		≤ 0.50%	≤ 0.50%	C373
Frost Resistance		As Reported	Resistant	C1026
Scratch Resistance		MOHS 1-10	8	MOHS SCALE
Breaking Strength	24"x24"	≥ 250 lbf.	≥ 1065 lbf.	C648
	12"x24"	≥ 250 lbf.	≥ 1386 lbf.	C648
	12"x12"	≥ 250 lbf.	≥ 847 lbf.	C648
Facial Dimension		-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness		≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)		+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)		+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance		Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)		As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)		As Reported	0.60 ≤ COF < 0.70	C1028
Chemical Resistance		Class A - Class E	Class A	C650
Stain Resistance		Class A - Class E	Class A	C1378

* Whichever is less