



live inspired



**R674** Moon Light BI  
20"x20"  
**R687** Moon Light BI  
13"x13"  
**R692** Moon Light BI  
6 1/2"x6 1/2"



**R676** Desert Shade BG  
20"x20"  
**R689** Desert Shade BG  
13"x13"  
**R694** Desert Shade BG  
6 1/2"x6 1/2"



**R686** Solar Coat GI  
20"x20"  
**R691** Solar Coat GI  
13"x13"  
**R696** Solar Coat GI  
6 1/2"x6 1/2"



**AF2H** Moon Light BI  
Mosaic - Square 2"x2"  
13"x13"



**AF2K** Desert Shade BG  
Mosaic - Square 2"x2"  
13"x13"



**AF2M** Solar Coat GI  
Mosaic - Square 2"x2"  
13"x13"



**AF2L** Forest Light NO  
Mosaic - Square 2"x2"  
13"x13"



**R677** Forest Light NO  
20"x20"  
**R690** Forest Light NO  
13"x13"  
**R695** Forest Light NO  
6 1/2"x6 1/2"



**R675** Flaming Sun RS  
20"x20"  
**R688** Flaming Sun RS  
13"x13"  
**R693** Flaming Sun RS  
6 1/2"x6 1/2"



**RE01** Garden Shade VE  
20"x20"  
**RD99** Garden Shade VE  
13"x13"  
**RE00** Garden Shade VE  
6 1/2"x6 1/2"



**AF2J** Flaming Sun RS  
Mosaic - Square 2"x2"  
13"x13"



**AF2N** Garden Shade VE  
Mosaic - Square 2"x2"  
13"x13"

#### TRIMS



**AE29** Space BI V-Cap  
**AE2A** Space RS V-Cap  
**AE2B** Space BG V-Cap  
**AE2D** Space GI V-Cap  
**AE2E** Space VE V-Cap  
2 1/4"x6 1/2"



**AE2M** Space BI Bead  
**AE2N** Space RS Bead  
**AE2P** Space BG Bead  
**AE2Q** Space NO Bead  
**AE2R** Space GI Bead  
**AE2S** Space VE Bead  
1"x6 1/2"



**AE2T** Space BI Beak  
**AE2V** Space BG Beak  
**AE2W** Space NO Beak  
**AE2X** Space GI Beak  
**AE2Y** Space VE Beak  
1"x1"



**R811** Flash BI SBN  
**R812** Flash RS Bullnose  
**R813** Flash BG Bullnose  
**R814** Flash NO Bullnose  
**R815** Flash GI Bullnose  
3"x13"  
SINGLE FIRED



**R658** Flash BI Bullnose  
**R659** Flash RS Bullnose  
**R660** Flash BG Bullnose  
**R661** Flash NO Bullnose  
**R662** Flash GI Bullnose  
**A364** Flash VE Bullnose  
3"x13"  
GLAZED PORCELAIN

- Floor Tile
- Wall Tile
- Modular Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Substantial Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- 21% Minimum Pre-Consumer Recycled Content
- Certified No VOC



Contributes to  
LEED Credits

#### TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 600 lbf.
	13"x13"	≥ 250 lbf.	≥ 450 lbf.
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.60 ≤ COF < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

\* Whichever is less

