



live inspired

LE PIETRE DI SAMARCANDA

GLAZED PORCELAIN TILE



RG00 Zinda BI
24"x24"
RH20 Zinda BI
24"x24" Rectified
RH24 Zinda BI
12"x24" Rectified
RH36 Zinda BI
12"x12" Rectified




RH52 Zinda BI
12"x12" Rectified




RH75 Zinda BI
12"x24" Rectified



RH28 Zinda BI
8"x24" Rectified
RH40 Zinda BI
2"x24" Rectified
RH48 Zinda BI
2"x12" Rectified



RH27 Timur GR
8"x24" Rectified
RH39 Timur GR
2"x24" Rectified
RH47 Timur GR
2"x12" Rectified



RG01 Khiva BG
24"x24"
RH21 Khiva BG
24"x24" Rectified
RH25 Khiva BG
12"x24" Rectified
RH37 Khiva BG
12"x12" Rectified



RH53 Khiva BG
12"x12" Rectified



RH76 Khiva BG
12"x24" Rectified



RH29 Khiva BG
8"x24" Rectified
RH41 Khiva BG
2"x24" Rectified
RH49 Khiva BG
2"x12" Rectified



RH30 Registan NO
8"x24" Rectified
RH42 Registan NO
2"x24" Rectified
RH50 Registan NO
2"x12" Rectified



RF99 Timur GR
24"x24"
RH19 Timur GR
24"x24" Rectified
RH23 Timur GR
12"x24" Rectified
RH35 Timur GR
12"x12" Rectified



RH51 Timur GR
12"x12" Rectified



RH74 Timur GR
12"x24" Rectified



RF93 Net Platino
24"x24" Rectified
RH17 Net Platino
24"x24" Rectified



RH11 Net Platino
12"x12"

RH15 Net Platino L.
1 1/4"x24"

RH13 Net Platino L.
1 1/4"x12"



RF98 Net Bronzo
24"x24" Rectified
RH18 Net Bronzo
24"x24" Rectified



RH12 Net Bronzo
12"x12"

RH16 Net Bronzo L.
1 1/4"x24"

RH14 Net Bronzo L.
1 1/4"x12"



RG02 Registan NO
24"x24"
RH22 Registan NO
24"x24" Rectified
RH26 Registan NO
12"x24" Rectified
RH38 Registan NO
12"x12" Rectified



RH54 Registan NO
12"x12" Rectified



RH77 Registan NO
12"x24" Rectified

TRIMS



RH60 Zinda BI Bullnose
4"x12"
RH61 Khiva BG Bullnose
4"x12"
RH62 Registan NO Bullnose
4"x12"
RH59 Timur GR Bullnose
4"x12"



Floor Tile



Wall Tile



Modular Tile



Rectified Tile



Decorative Tile



Trim Available



Suitable for
Outdoors



Slight Variation



Frost Resistant



Meets ADA
Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



45% Minimum
Pre-Consumer
Recycled Content



Certified No VOC



Contributes to
LEED Credits

SPECIAL ORDER

(Please contact your Ragno USA Customer Service Representative for more details. Minimum quantities may apply.)

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	8	MOHS SCALE
Breaking Strength	24"x24" ≥ 250 lbf.	≥ 1000 lbf.	C648
	12"x24" ≥ 250 lbf.	≥ 850 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

