



live inspired

ETERNAL LIMESTONES

COLOR BODY PORCELAIN TILE | RECTIFIED | 3D PRINTING TECHNIQUE




Limestone AN
AL2F 3¼"x6½" Rectified
AL2C 6"x24" Rectified
AL23 12"x24" Rectified
AL29 13"x13" Rectified
AL26 20"x20" Rectified




Limestone BG
AL2G 3¼"x6½" Rectified
AL2D 6"x24" Rectified
AL24 12"x24" Rectified
AL2A 13"x13" Rectified
AL27 20"x20" Rectified




Limestone BI
AL2E 3¼"x6½" Rectified
AL2B 6"x24" Rectified
AL22 12"x24" Rectified
AL28 13"x13" Rectified
AL25 20"x20" Rectified



Limestone AN
AL2W 13"x13" Mosaic



Limestone BG
AL2X 13"x13" Mosaic



Limestone BI
AL2V 13"x13" Mosaic



Limestone MC
AL33 13"x13" Mix Mosaic



Limestone AN
AL2Z 12"x24" Strip Mosaic



Limestone BG
AL32 12"x24" Strip Mosaic



Limestone BI
AL2Y 12"x24" Strip Mosaic

Grecian Metallic Deco
AL36 2"x13" Trims Available



AL2J Limestone AN
AL2K Limestone BG
AL2H Limestone BI
 3"x13" Bullnose



AL2M Limestone AN
AL2N Limestone BG
AL2L Limestone BI
 6"x12" Cove Base



AL2Q Limestone AN
AL2R Limestone BG
AL2P Limestone BI
 1"x6" Cove Base In Angle



AL2T Limestone AN
AL2U Limestone BG
AL2S Limestone BI
 1"x6" Cove Base Out Angle

- Floor Tile
- Wall Tile
- 3D Printing Technique
- Rectified Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- V3 Moderate Variation
- Frost Resistant
- Meets ADA Recommendations
- IV Abrasion Resistance
- 06 C.O.F. (Wet)
- 07 C.O.F. (Dry)
- Certified No VOC
- 21% Minimum Pre-Consumer Recycled Content



Contributes to
LEED Credits

TECHNICAL SPECIFICATIONS

| DESCRIPTION | ANSI STANDARD | RESULT | ASTM TEST METHOD |
|----------------------|---------------------------|-------------------|------------------|
| Water Absorption | ≤ 0.50% | ≤ 0.50% | C373 |
| Frost Resistance | As Reported | Resistant | C1026 |
| Scratch Resistance | MOHS 1-10 | 7 | MOHS SCALE |
| Breaking Strength | 12"x24" | ≥ 250 lbf. | ≥ 806 lbf. C648 |
| | 20"x20" | ≥ 250 lbf. | ≥ 700 lbf. C648 |
| | 13"x13" | ≥ 250 lbf. | ≥ 535 lbf. C648 |
| Facial Dimension | -3.0 % < Nominal < 2.0 % | Within Standard | C499 |
| Thickness | ≤ 0.04 in (1.02 mm max) | Within Standard | C499 |
| Wedging (Squareness) | +/- 0.25 % or +/- 0.8 mm* | Within Standard | C502 |
| Warpage (Flatness) | +/- 0.40 % or +/- 1.3 mm* | Within Standard | C485 |
| Abrasion Resistance | Class 0 - Class V | Class IV | C1027 |
| C.O.F. (Wet) | As Reported | 0.70 ≤ COF < 0.80 | C1028 |
| C.O.F. (Dry) | As Reported | 0.60 ≤ COF < 0.70 | C1028 |
| Chemical Resistance | Class A - Class E | Class A | C650 |
| Stain Resistance | Class A - Class E | Class A | C1378 |

* Durability Classification / Suggested Applications

Class IV Moderate / Heavy traffic: Tile suggested for residential, medium commercial and light institutional floor and wall applications

** Whichever is less

