



live inspired

KASHMERE

GLAZED PORCELAIN TILE | 3D PRINTING TECHNIQUE



AK2D Kashmere BG
20"x20"
AK2A Kashmere BG
13"x13"
AK2G Kashmere BG
6 1/2"x6 1/2"



AK2E Kashmere BI
20"x20"
AK2B Kashmere BI
13"x13"
AK2H Kashmere BI
6 1/2"x6 1/2"



AK2F Kashmere NO
20"x20"
AK2C Kashmere NO
13"x13"
AK2J Kashmere NO
6 1/2"x6 1/2"



AK2R Kashmere BG
Mosaic - Brick 2"x4"
13"x13"



AK2S Kashmere BI
Mosaic - Brick 2"x4"
13"x13"



AK2T Kashmere NO
Mosaic - Brick 2"x4"
13"x13"

Decorative Options
Studio M Glass Mosaic face mounted on paper sheets

TRIMS



UJ95 Samba
Mosaic - Square 5/8"x5/8"
13"x13"



UJAB Samba
Mosaic - Brick 1 1/4"x5/8"
13"x13"



AK2N Kashmere BG Bullnose
AK2P Kashmere BI Bullnose
AK2Q Kashmere NO Bullnose
3"x13"

- Floor Tile
- Wall Tile
- Modular Tile
- 3d Printing Technique
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Slight Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- 21% Minimum Pre-Consumer Recycled Content
- Certified No VOC



Contributes to
LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength	18"x18" ≥ 250 lbf.	≥ 583 lbf.	C648
	12"x12" ≥ 250 lbf.	≥ 411 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.80 ≤ COF < 0.90	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

