



CLEFTSTONE NE



CLEFTSTONE proposes all the timeless beauty and elegance of bright, light or dark colored natural stone in a practical new version. The technology used is that of fully vitrified stoneware, meaning the product is highly resistant to abrasion from pedestrian traffic, making it the trouble-free solution for residential areas as well as commercial settings subject to limited traffic.





20"x20" 13"x13" 61/2"x61/2"



92D1 Cleftstone BI 20"x20" 91S1 Cleftstone BI 13"x13" **91T5** Cleftstone BI 6^{1/2}"x6^{1/2}"



92C7 Cleftstone MT 20"x20" **91R7** Cleftstone MT 13"x13" **91T1** Cleftstone MT 61/2" x61/2"



AJ4T Cleftstone MT Mosaic - Square 2"x2" 13"x13"



91Z7 Riverstone RED Freccia 6½"x13"



91Z9 Riverstone RED Freccia Corner 61/2" x61/2"



92D0 Cleftstone BG 20"x20" 91S0 Cleftstone BG 13"x13" **91T4** Cleftstone BG 6^{1/2}"x6^{1/2}"



92C6 Cleftstone VE 20"x20" 91R6 Cleftstone VE 13"x13" 91T0 Cleftstone VE 61/2"x61/2"



AJ4U Cleftstone VE Mosaic - Square 2"x2" 13"x13"



92C8 Cleftstone GI 20"x20" 91R8 Cleftstone GI 13"x13" **91T2** Cleftstone GI 6^{1/2}"x6^{1/2}"



92C5 Cleftstone NE 20"x20" 91R5 Cleftstone NE 13"x13" **9159** Cleftstone NE 61/2" x61/2"



AJ4V Cleftstone NE Mosaic - Square 2"x2" 13"x13"



91Z6 Riverstone GREEN Freccia 61/2"x13"



91Z8 Riverstone GREEN Freccia Corner 61/2" x61/2"





93N5 Stone BI V-Cap 93N4 Stone BG V-Cap 93N3 Stone GI V-Cap 93N2 Stone MT V-Cap 93N1 Stone VE V-Cap 93N0 Stone NE V-Cap 21/4"x13"




91S8 Stone BI Bullnose 91S7 Stone BG Bullnose 91S5 Stone GI Bullnose 91S4 Stone MT Bullnose 91S3 Stone VE Bullnose 91S2 Stone NE Bullnose 3"x13"

Shade variations

The color and shade of all tiles vary to some degree. This variance can be from piece to piece and can also occur from production run to production run.

American National Standard Specifications for Ceramic Tile (ANSI) has implemented a guide that rates ceramic tile on a five-point scale and ranges from V0 through V4.

Instituting the ANSI's color shade variation guidelines you will reduce customer complaints and sell the unique and individual beauty of each ceramic tile.



V0 Very Uniform Appearance

Pieces of the same shade value are very uniform and smooth in texture.

V1 Uniform Appearance

Differences among pieces from the same production run are minimal.

V2 Slight Variation

Clearly Distinguishable differences in texture and/ or pattern within similar colors.

V3 Moderate Variation

While the colors and or texture present on a single piece of tile will be indicative of the colors and/or texture to be expected on the other tiles, the amount of colors and/or texture on each piece may vary significantly. It is recommended that the range be viewed before selection.

V4 Substantial Variation

Random color and/or texture differences from tile to tile, so that one tile may have totally different colors and/or texture from that on other tiles. Thus, the final installation will be unique. It is recommended that the range be viewed before selection.

SHADE VARIATION AND APPLICATIONS									
V3		Residential	Commercial	Industrial					
	Floor	•	•						
	Wall	•	•	•					
	Countertop	•	•	•					
MODERATE VARIATION	Pool	•	•	•					

Water, oil, grease, or other fluids create slippery conditions. Floors with exposure to these conditions require extra caution in product selection and proper maintenance.

Care & Maintenance

Cleftstone is a stain-resistant porcelain tile. Routine maintenance will keep your tile looking new for years to come.

Ragno USA's products are typically easy to install and maintain using the following general guidelines:

- Choose tile from same dye lot and caliber whenever possible
- Select tile alternately from several boxes and rotate when installing
- Follow industry-accepted installation practices as detailed by Tile Council of America "Handbook for Ceramic Tile Installation" or those recommended by the Ceramic Tile Institute of America
- Remove all grout residue promptly after application; neither acid cleaning nor sealing is recommended
- Clean regularly with clear water and/or a neutral (soapless) cleaner, wipe dry to lessen slippery conditions

TECHNICAL SPECIFICATIONS									
DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD						
Water Absorption	≤ 0.50%	≤ 0.50%	C373						
Frost Resistance	As Reported	Resistant	C1026						
Scratch Resistance	MOHS 1-10	7	MOHS SCALE						
Breaking Strength 20"x20'	≥ 250 lbf.	≥ 605 lbf.	C648						
13"x13'	≥ 250 lbf.	≥ 635 lbf.	C648						
Facial Dimension	-3.0 % < Nominal < 3.0 %	Within Standard	C499						
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499						
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502						
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485						
Abrasion Resistance	Class 0 - Class V	Class IV	C1027						
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028						
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028						
Chemical Resistance	Class A - Class E	Class A	C650						
Stain Resistance	Class A - Class E	Class A	C1378						

^{*} Whichever is less

PACKAGING										
	SIZE	THICKNESS	вох			PALLET				
			PCS	SQ FT	LBS	BOXES	SQ FT	LBS		
Floor Tile	20"x20"	7/16"	06	16.15	80.00	24	387.60	1920.00		
Floor Tile	13"x13"	5/16"	13	15.52	59.00	44	682.88	2596.00		
Floor Tile	61/2"x61/2"	5/16"	36	10.55	42.00	51	538.05	2131.00		
Mosaic - Square 2"x2"	13"x13"	Compatible	10		39.00					
Freccia	61/2"x13"	Compatible	06		17.00					
Freccia Corner	61/2"x61/2"	Compatible	04		6.00					
V-Cap	21/4"x13"	Compatible	06		5.00					
Bullnose	3"x13"	Compatible	20		26.00					



loor Tile



Wall Tile



Modular Tile



Decorative Tile



Trim Available



Suitable for Outdoors



Moderate Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum Pre-Consumer Recycled Content



Certified No VOC



