



*live inspired*


# BURGUNDY

GLAZED PORCELAIN TILE



**AF3N** Burgundy GR  
20"x20"  
**AF3J** Burgundy GR  
13"x13"  
**AF56** Burgundy GR  
6 1/2"x6 1/2"

**AF62** Burgundy GR Listelli  
1"x13"




**AG58** Burgundy GR  
Mosaic - Square 2"x2"  
13"x13"



**AF3P** Burgundy GO  
20"x20"  
**AF3K** Burgundy GO  
13"x13"  
**AF57** Burgundy GO  
6 1/2"x6 1/2"

**AF63** Burgundy GO Listelli  
1"x13"




**AG59** Burgundy GO  
Mosaic - Square  
2"x2"  
13"x13"



**AF3Q** Burgundy NO  
20"x20"  
**AF3L** Burgundy NO  
13"x13"  
**AF58** Burgundy NO  
6 1/2"x6 1/2"

**AF64** Burgundy NO Listelli  
1"x13"

TRIMS




**AG6A** Burgundy NO  
Mosaic - Square 2"x2"  
13"x13"



**AF3R** Burgundy TC  
20"x20"  
**AF3M** Burgundy TC  
13"x13"  
**AF59** Burgundy TC  
6 1/2"x6 1/2"

**AF65** Burgundy TC Listelli  
1"x13"



**AG6B** Burgundy TC  
Mosaic - Square 2"x2"  
13"x13"

**AF67** Burgundy Corner-Insert  
1"x1"



**AF35** Burgundy GR Bullnose  
**AF3T** Burgundy GO Bullnose  
**AF3U** Burgundy NO Bullnose  
**AF3V** Burgundy TC Bullnose  
3"x13"



**AF5E** Burgundy GR Bead  
**AF5F** Burgundy GO Bead  
**AF5G** Burgundy NO Bead  
**AF5H** Burgundy TC Bead  
1"x6 1/2"



**AF5J** Burgundy GR Beak  
**AF5K** Burgundy GO Beak  
**AF5L** Burgundy NO Beak  
**AF5M** Burgundy TC Beak  
1"x1"



**AF5N** Burgundy GR V-Cap  
**AF5P** Burgundy GO V-Cap  
**AF5Q** Burgundy NO V-Cap  
**AF5R** Burgundy TC V-Cap  
2"x6 1/2"



**AF5S** Burgundy GR V-Cap Corner  
**AF5T** Burgundy GO V-Cap Corner  
**AF5U** Burgundy NO V-Cap Corner  
**AF5V** Burgundy TC V-Cap Corner  
7/8"x2"

- Floor Tile
- Wall Tile
- Modular Tile
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Moderate Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- Certified No VOC
- 21% Minimum Pre-Consumer Recycled Content



Contributes to  
LEED Credits

## TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	18"x18"	≥ 250 lbf.	≥ 530 lbf.
	12"x12"	≥ 250 lbf.	≥ 400 lbf.
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378



\* Whichever is less