

Floor Tile

Wall Tile

Decorative Tile

Frost Resistant

**0.4** C.O.F. (Wet)

**0.6** C.O.F. (Dry)

Ш

Average Variation

Abrasion Resistance




## CRYSTAL STONE MESH MOUNTED GLASS/STONE MOSAICS



**LG4A** lvory 12"x12"



**LG4D** Marine 12"x12"



**LG4G** Purple 12"x12"



LG4B Caramel 12"x12"



LG4E Coffee 12"x12"



**LG4H** Honey 12"x12"



LG4C Breeze 12"x12"



LG4F Walnut 12"x12"







**LG4J** Gold 12"x12"

TECHNICAL SPECIFICATIONS			
DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	2% - 5%	2% - 5%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS SCALE
Breaking Strength	≥ 250 lbf.	N/A	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class III	C1027
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028
C.O.F. (Dry)	As Reported	0.40 ≤ COF < 0.50	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378



