



live inspired

PRINCEPS

GLAZED PORCELAIN TILE



3Y07 Cesare BI
20"x20"
3Y03 Cesare BI
13"x13"



3Y06 Augusto BG
20"x20"
3Y02 Augusto BG
13"x13"



3Y05 Tiberio NO
20"x20"
3Y01 Tiberio NO
13"x13"



3Y08 Aureliano TO
20"x20"
3Y04 Aureliano TO
13"x13"



3W35 Princeps
FR. BI
1 1/2"x1 1/2"



3W33 Princeps
FR. BI
1 9/16"x13"

TRIMS



3X00 Cesare BI Bullnose
3Y99 Augusto BG Bullnose
3Y98 Tiberio NO Bullnose
3X01 Aureliano TO Bullnose
3 1/8"x13"



Floor Tile



Wall Tile



Decorative Tile



Trim Available



Suitable for
Outdoors



Slight Variation



Frost Resistant



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum
Pre-Consumer
Recycled Content



Certified No VOC



Contributes to
LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS SCALE
Breaking Strength 13"x13"	≥ 250 lbf.	≥ 462 lbf.	C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.40 ≤ COF < 0.50	C1028
C.O.F. (Dry)	As Reported	0.70 ≤ COF < 0.80	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

