


MADE IN THE USA





An exotic collage of colors and textures characterize Kashmere

Three widely-ranged colors, loosely defined as beige, white and walnut, are achieved using Ragno's state-of-the-art printing technique, uses the latest in digital print technology, allowing for infinite design capabilities unique to Ragno. Ragno is the only manufacturer in the US that can do digital print up to 360 dpi, direct to tile. At this maximum resolution and with the unique grayscale printing technique, Ragno reaches finer, crisper and smoother definition for printed designs than other digital products. A stunning palette of more than 100 square feet with no repetition, at maximum resolution.




3





Kashmere Bl



Strong focal points are easily achieved with Kashmere's bold combination of textures and shadings.

The juxtaposition of large and small square sizes, with the striking 2"x4" brick mosaic, creates intriguing design transitions for exterior floors, walls, pools and facades. In addition to common and not-so-common indoor applications; think of tiled ceilings, columns and arches, stairways and window seats, as well as traditional walls, floors and countertops.

Manufactured in the USA using 21% pre-consumer recycled materials makes this residentially/commercially rated line not only beautiful and impact resistant but also environmentally friendly and fully capable of contributing to LEED credits.

KASHMERE 3d PRINTING TECHNIQUE

GLAZED PORCELAIN STONEWARE

20"x 20" 13"x 13" 6^{1/2}"x 6^{1/2}"









AK2G Kashmere BG 6^{1/2}"x6^{1/2}"



AK2A Kashmere BG 13"x13"



AK2E Kashmere BI 20"x20"



AK2H Kashmere BI 6^{1/2}"x6^{1/2}"



AK2B Kashmere BI 13"x13"



AK2R Kashmere BG Mosaic - Brick 2"x4" 13"x13"




AK2S Kashmere BI Mosaic - Brick 2"x4" 13"x13"



AK2J Kashmere NO 6^{1/2}"x6^{1/2}"



AK2C Kashmere NO 13"x13"





UJ95 Samba Mosaic - Square ^{5/8}" x^{5/8}" 13" x13"



UJAB Samba Mosaic - Brick 1^{1/4}" x^{5/8}" 13" x13"



AK2T Kashmere NO Mosaic - Brick 2"x4" 13"x13"

AK2F Kashmere NO 20"x20"

TRIMS

BULLNOSE




AK2N Kashmere BG AK2P Kashmere BI AK2Q Kashmere NO 3"x13"

Shade variations

The color and shade of all tiles vary to some degree. This variance can be from piece to piece and can also occur from production run to production run.

American National Standard Specifications for Ceramic Tile (ANSI) has implemented a guide that rates ceramic tile on a five-point scale and ranges from V0 through V4.

Instituting the ANSI's color shade variation guidelines you will reduce customer complaints and sell the unique and individual beauty of each ceramic tile.



V0 Very Uniform Appearance

Pieces of the same shade value are very uniform and smooth in texture.

V1 Uniform Appearance

Differences among pieces from the same production run are minimal.

V2 Slight Variation

Clearly Distinguishable differences in texture and/or pattern within similar colors.

V3 Moderate Variation

While the colors and or texture present on a single piece of tile will be indicative of the colors and/or texture to be expected on the other tiles, the amount of colors and/or texture on each piece may vary significantly. It is recommended that the range be viewed before selection.

V4 Substantial Variation

Random color and/or texture differences from tile to tile, so that one tile may have totally different colors and/or texture from that on other tiles. Thus, the final installation will be unique. It is recommended that the range be viewed before selection.

SHADE VARIATION AND APPLICATIONS									
V2		Residential	Commercial	Industrial					
	Floor	•	•						
	Wall	•	•	•					
	Countertop	•	•	•					
SLIGHT VARIATION	Pool	•	•	•					

Water, oil, grease, or other fluids create slippery conditions. Floors with exposure to these conditions require extra caution in product selection and proper maintenance.

Care & Maintenance

Kashmere is a stain-resistant porcelain tile. Routine maintenance will keep your tile looking new for years to come.

Ragno USA's products are typically easy to install and maintain using the following general guidelines:

- Choose tile from same dye lot and caliber whenever possible
- Select tile alternately from several boxes and rotate when installing
- Follow industry-accepted installation practices as detailed by Tile Council of America "Handbook for Ceramic Tile Installation" or those recommended by the Ceramic Tile Institute of America
- Remove all grout residue promptly after application; neither acid cleaning nor sealing is recommended
- Clean regularly with clear water and/or a neutral (soapless) cleaner, wipe dry to lessen slippery conditions

TECHNICAL SPECIFICATIONS									
DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD						
Water Absorption	≤ 0.50%	≤ 0.50%	C373						
Frost Resistance	As Reported	Resistant	C1026						
Scratch Resistance	MOHS 1-10	7	MOHS SCALE						
Breaking Strength 20"x	0" ≥ 250 lbf.	≥ 583 lbf.	C648						
13"x	3" ≥ 250 lbf.	≥ 411 lbf.	C648						
Facial Dimension	+/- 3.0 % from Nominal	Within Standard	C499						
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499						
Wedging (Squareness)	+/- 0.50 % or 2.0 mm*	Within Standard	C502						
Warpage (Flatness)	+/- 0.75 % or 2.3 mm*	Within Standard	C485						
Abrasion Resistance	Class 0 - Class V	Class IV	C1027						
C.O.F. (Wet)	As Reported	0.60 ≤ COF < 0.70	C1028						
C.O.F. (Dry)	As Reported	0.80 ≤ COF < 0.90	C1028						
Chemical Resistance	Class A - Class E	Class A	C650						
Stain Resistance	Class A - Class E	Class A	C1378						

^{*} Whichever is less

PACKAGING										
	SIZE	THICKNESS	BOX			PALLET				
			PCS	SQ FT	LBS	BOXES	SQ FT	LBS		
Modular Tile	6 ^{1/2} "x6 ^{1/2} "	5/16"	36	10.55	42.00	51	538.05	2142.00		
Modular Tile	13"x13"	5/16"	13	15.52	58.00	44	682.88	2552.00		
Field Tile	20"x20"	7/16"	06	16.15	84.00	24	387.60	2016.00		
Mosaic - Brick 2"x4"	13"x13"	Compatible	10		45.00					
Mosaic - Square 5/8" x5/8"	13"x13"	Compatible	10		29.00					
Mosaic - Square 1 ^{1/4} "x ^{5/8} "	13"x13"	Compatible	10		29.00					
Bullnose	3"x13"	Compatible	20		21.00					



Field Tile



Wall Tile



3d Printing Technique



Decorative Tile



Trim Available



Suitable for Outdoor



Slight Variation



Frost Resistant



Meets ADA Recommendations



Abrasion Resistance



C.O.F. (Wet)



C.O.F. (Dry)



21% Minimum Pre-Consumer Recycled Content



Certified No VOC



