




live inspired

CALABRIA

GLAZED PORCELAIN TILE | 3D PRINTING TECHNIQUE



AK3Q Calabria BR
12"x24"

AK3M Calabria BR
20"x20"

AK3R Calabria BL
12"x24"

AK3N Calabria BL
20"x20"

AK3S Calabria BI
12"x24"

AK3P Calabria BI
20"x20"



AK3J Calabria BR
13"x13"

AK3T Calabria BR
6 1/2"x6 1/2"

AK3K Calabria BL
13"x13"

AK3U Calabria BL
6 1/2"x6 1/2"

AK3L Calabria BI
13"x13"

AK3V Calabria BI
6 1/2"x6 1/2"



AK3Z Calabria BR
Mosaic - Square 2"x2"
13"x13"

AK34 Calabria BR
Brick Liner
13"x13"

AK32 Calabria BL
Mosaic - Square 2"x2"
13"x13"

AK35 Calabria BL
Brick Liner
13"x13"

AK33 Calabria BI
Mosaic - Square 2"x2"
13"x13"

AK36 Calabria BI
Brick Liner
13"x13"

TRIMS



AK3W Calabria BR Bullnose
AK3X Calabria BL Bullnose
AK3Y Calabria BI Bullnose
3"x13"

- Floor Tile
- Wall Tile
- Modular Tile
- 3d Printing Technique
- Decorative Tile
- Trim Available
- Suitable for Outdoors
- Substantial Variation
- Frost Resistant
- Meets ADA Recommendations
- Abrasion Resistance
- C.O.F. (Wet)
- C.O.F. (Dry)
- 21% Minimum Pre-Consumer Recycled Content
- Certified No VOC



Contributes to
LEED Credits

TECHNICAL SPECIFICATIONS

DESCRIPTION	ANSI STANDARD	RESULT	ASTM TEST METHOD
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	8	MOHS SCALE
Breaking Strength	20"x20"	≥ 250 lbf.	≥ 605 lbf. C648
	12"x24"	≥ 250 lbf.	≥ 735 lbf. C648
	13"x13"	≥ 250 lbf.	≥ 408 lbf. C648
Facial Dimension	-3.0 % < Nominal < 2.0 %	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (Squareness)	+/- 0.50 % or +/- 2.0 mm*	Within Standard	C502
Warpage (Flatness)	+/- 0.75 % or +/- 2.3 mm*	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
C.O.F. (Wet)	As Reported	0.70 ≤ COF < 0.80	C1028
C.O.F. (Dry)	As Reported	0.80 ≤ COF < 0.90	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

* Whichever is less

