DICE Embeddings

Release 0.1.3.2

Caglar Demir

Aug 22, 2024

Contents:

1 Dicee Manual **2**

2 Installation **3**
2.1 Installation from Source . . . 3

3 Download Knowledge Graphs **3**

4 Knowledge Graph Embedding Models **3**

5 How to Train **3**

6 Creating an Embedding Vector Database **5**
6.1 Learning Embeddings . . . 5
6.2 Loading Embeddings into Qdrant Vector Database . . . 6
6.3 Launching Webservice . . . 6

7 Answering Complex Queries **6**

8 Predicting Missing Links **8**

9 Downloading Pretrained Models **8**

10 How to Deploy **8**

11 Docker **8**

12 Coverage Report **9**

13 How to cite **10**

14 dicee **12**
14.1 Subpackages . . . 12
14.2 Submodules . . . 115
14.3 Attributes . . . 161
14.4 Classes . . . 161
14.5 Functions . . . 162
14.6 Package Contents . . . 163

Python Module Index **208**

Index **209**

DICE Embeddings[1]: Hardware-agnostic Framework for Large-scale Knowledge Graph Embeddings:

1 Dicee Manual

Version: dicee 0.1.3.2

GitHub repository: https://github.com/dice-group/dice-embeddings

Publisher and maintainer: Caglar Demir[2]

Contact: caglar.demir@upb.de

License: OSI Approved :: MIT License

Dicee is a hardware-agnostic framework for large-scale knowledge graph embeddings.

Knowledge graph embedding research has mainly focused on learning continuous representations of knowledge graphs towards the link prediction problem. Recently developed frameworks can be effectively applied in a wide range of research-related applications. Yet, using these frameworks in real-world applications becomes more challenging as the size of the knowledge graph grows

We developed the DICE Embeddings framework (dicee) to compute embeddings for large-scale knowledge graphs in a hardware-agnostic manner. To achieve this goal, we rely on

1. **Pandas**[3] **& Co.** to use parallelism at preprocessing a large knowledge graph,
2. **PyTorch**[4] **& Co.** to learn knowledge graph embeddings via multi-CPUs, GPUs, TPUs or computing cluster, and
3. **Huggingface**[5] to ease the deployment of pre-trained models.

Why Pandas[6] **& Co. ?** A large knowledge graph can be read and preprocessed (e.g. removing literals) by pandas, modin, or polars in parallel. Through polars, a knowledge graph having more than 1 billion triples can be read in parallel fashion. Importantly, using these frameworks allow us to perform all necessary computations on a single CPU as well as a cluster of computers.

Why PyTorch[7] **& Co. ?** PyTorch is one of the most popular machine learning frameworks available at the time of writing. PytorchLightning facilitates scaling the training procedure of PyTorch without boilerplate. In our framework, we combine PyTorch[8] & PytorchLightning[9]. Users can choose the trainer class (e.g., DDP by Pytorch) to train large knowledge graph embedding models with billions of parameters. PytorchLightning allows us to use state-of-the-art model parallelism techniques (e.g. Fully Sharded Training, FairScale, or DeepSpeed) without extra effort. With our framework, practitioners can directly use PytorchLightning for model parallelism to train gigantic embedding models.

Why Hugging-face Gradio[10]**?** Deploy a pre-trained embedding model without writing a single line of code.

[1] https://github.com/dice-group/dice-embeddings
[2] https://github.com/Demirrr
[3] https://pandas.pydata.org/
[4] https://pytorch.org/
[5] https://huggingface.co/
[6] https://pandas.pydata.org/
[7] https://pytorch.org/
[8] https://pytorch.org/
[9] https://www.pytorchlightning.ai/
[10] https://huggingface.co/gradio

2 Installation

2.1 Installation from Source

```
git clone https://github.com/dice-group/dice-embeddings.git
conda create -n dice python=3.10.13 --no-default-packages && conda activate dice &&␣
↪cd dice-embeddings &&
pip3 install -e .
```

or

```
pip install dicee
```

3 Download Knowledge Graphs

```
wget https://files.dice-research.org/datasets/dice-embeddings/KGs.zip --no-check-
↪certificate && unzip KGs.zip
```

To test the Installation

```
python -m pytest -p no:warnings -x # Runs >114 tests leading to > 15 mins
python -m pytest -p no:warnings --lf # run only the last failed test
python -m pytest -p no:warnings --ff # to run the failures first and then the rest of␣
↪the tests.
```

4 Knowledge Graph Embedding Models

1. TransE, DistMult, ComplEx, ConEx, QMult, OMult, ConvO, ConvQ, Keci
2. All 44 models available in https://github.com/pykeen/pykeen#models

   For more, please refer to `examples`.

5 How to Train

To Train a KGE model (KECI) and evaluate it on the train, validation, and test sets of the UMLS benchmark dataset.

```
from dicee.executer import Execute
from dicee.config import Namespace
args = Namespace()
args.model = 'Keci'
args.scoring_technique = "KvsAll"  # 1vsAll, or AllvsAll, or NegSample
args.dataset_dir = "KGs/UMLS"
args.path_to_store_single_run = "Keci_UMLS"
args.num_epochs = 100
args.embedding_dim = 32
args.batch_size = 1024
reports = Execute(args).start()
print(reports["Train"]["MRR"]) # => 0.9912
```

(continues on next page)

(continued from previous page)

```
print(reports["Test"]["MRR"]) # => 0.8155
# See the Keci_UMLS folder embeddings and all other files
```

where the data is in the following form

```
$ head -3 KGs/UMLS/train.txt
acquired_abnormality    location_of     experimental_model_of_disease
anatomical_abnormality  manifestation_of        physiologic_function
alga    isa     entity
```

A KGE model can also be trained from the command line

```
dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
```

dicee automaticaly detects available GPUs and trains a model with distributed data parallels technique. Under the hood, dicee uses lighning as a default trainer.

```
# Train a model by only using the GPU-0
CUDA_VISIBLE_DEVICES=0 dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model
↪"train_val_test"
# Train a model by only using GPU-1
CUDA_VISIBLE_DEVICES=1 dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model
↪"train_val_test"
NCCL_P2P_DISABLE=1 CUDA_VISIBLE_DEVICES=0,1 python dicee/scripts/run.py --trainer PL -
↪-dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
```

Under the hood, dicee executes run.py script and uses lighning as a default trainer

```
# Two equivalent executions
# (1)
dicee --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H@1': 0.9518788343558282, 'H@3': 0.9988496932515337, 'H@10': 1.0, 'MRR': 0.
↪9753123402351737}
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
↪'MRR': 0.8072362996241839}
# Evaluate Keci on Test set: Evaluate Keci on Test set
# {'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,
↪'MRR': 0.8064032293278861}

# (2)
CUDA_VISIBLE_DEVICES=0,1 python dicee/scripts/run.py --trainer PL --dataset_dir "KGs/
↪UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H@1': 0.9518788343558282, 'H@3': 0.9988496932515337, 'H@10': 1.0, 'MRR': 0.
↪9753123402351737}
# Evaluate Keci on Train set: Evaluate Keci on Train set
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
↪'MRR': 0.8072362996241839}
# Evaluate Keci on Test set: Evaluate Keci on Test set
# {'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,
↪'MRR': 0.8064032293278861}
```

Similarly, models can be easily trained with torchrun

```
torchrun --standalone --nnodes=1 --nproc_per_node=gpu dicee/scripts/run.py --trainer␣
↪torchDDP --dataset_dir "KGs/UMLS" --model Keci --eval_model "train_val_test"
# Evaluate Keci on Train set: Evaluate Keci on Train set: Evaluate Keci on Train set
# {'H@1': 0.9518788343558282, 'H@3': 0.9988496932515337, 'H@10': 1.0, 'MRR': 0.
↪9753123402351737}
# Evaluate Keci on Validation set: Evaluate Keci on Validation set
# {'H@1': 0.6932515337423313, 'H@3': 0.9041411042944786, 'H@10': 0.9754601226993865,
↪'MRR': 0.8072499937521418}
# Evaluate Keci on Test set: Evaluate Keci on Test set
{'H@1': 0.6951588502269289, 'H@3': 0.9039334341906202, 'H@10': 0.9750378214826021,
↪'MRR': 0.8064032293278861}
```

You can also train a model in multi-node multi-gpu setting.

```
torchrun --nnodes 2 --nproc_per_node=gpu  --node_rank 0 --rdzv_id 455 --rdzv_backend␣
↪c10d --rdzv_endpoint=nebula  dicee/scripts/run.py --trainer torchDDP --dataset_dir␣
↪KGs/UMLS
torchrun --nnodes 2 --nproc_per_node=gpu  --node_rank 1 --rdzv_id 455 --rdzv_backend␣
↪c10d --rdzv_endpoint=nebula dicee/scripts/run.py --trainer torchDDP --dataset_dir␣
↪KGs/UMLS
```

Train a KGE model by providing the path of a single file and store all parameters under newly created directory called `KeciFamilyRun`.

```
dicee --path_single_kg "KGs/Family/family-benchmark_rich_background.owl" --model Keci␣
↪--path_to_store_single_run KeciFamilyRun --backend rdflib
```

where the data is in the following form

```
$ head -3 KGs/Family/train.txt
_:1 <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> <http://www.w3.org/2002/07/owl
↪#Ontology> .
<http://www.benchmark.org/family#hasChild> <http://www.w3.org/1999/02/22-rdf-syntax-ns
↪#type> <http://www.w3.org/2002/07/owl#ObjectProperty> .
<http://www.benchmark.org/family#hasParent> <http://www.w3.org/1999/02/22-rdf-syntax-
↪ns#type> <http://www.w3.org/2002/07/owl#ObjectProperty> .
```

Apart from n-triples or standard link prediction dataset formats, we support [“owl”, “nt”, “turtle”, “rdf/xml”, “n3”]*. Moreover, a KGE model can be also trained by providing **an endpoint of a triple store**.

```
dicee --sparql_endpoint "http://localhost:3030/mutagenesis/" --model Keci
```

For more, please refer to `examples`.

6 Creating an Embedding Vector Database

6.1 Learning Embeddings

```
# Train an embedding model
dicee --dataset_dir KGs/Countries-S1 --path_to_store_single_run CountryEmbeddings --
↪model Keci --p 0 --q 1 --embedding_dim 32 --adaptive_swa
```

6.2 Loading Embeddings into Qdrant Vector Database

```
# Ensure that Qdrant available
# docker pull qdrant/qdrant && docker run -p 6333:6333 -p 6334:6334      -v $(pwd)/
↪qdrant_storage:/qdrant/storage:z      qdrant/qdrant
diceeindex --path_model "CountryEmbeddings" --collection_name "dummy" --location
↪"localhost"
```

6.3 Launching Webservice

```
diceeserve --path_model "CountryEmbeddings" --collection_name "dummy" --collection_
↪location "localhost"
```

Retrieve and Search

Get embedding of germany

```
curl -X 'GET' 'http://0.0.0.0:8000/api/get?q=germany' -H 'accept: application/json'
```

Get most similar things to europe

```
curl -X 'GET' 'http://0.0.0.0:8000/api/search?q=europe' -H 'accept: application/json'
{"result":[{"hit":"europe","score":1.0},
{"hit":"northern_europe","score":0.67126536},
{"hit":"western_europe","score":0.6010134},
{"hit":"puerto_rico","score":0.5051694},
{"hit":"southern_europe","score":0.4829831}]}
```

7 Answering Complex Queries

```
# pip install dicee
# wget https://files.dice-research.org/datasets/dice-embeddings/KGs.zip --no-check-
↪certificate & unzip KGs.zip
from dicee.executer import Execute
from dicee.config import Namespace
from dicee.knowledge_graph_embeddings import KGE
# (1) Train a KGE model
args = Namespace()
args.model = 'Keci'
args.p=0
args.q=1
args.optim = 'Adam'
args.scoring_technique = "AllvsAll"
args.path_single_kg = "KGs/Family/family-benchmark_rich_background.owl"
args.backend = "rdflib"
args.num_epochs = 200
args.batch_size = 1024
args.lr = 0.1
args.embedding_dim = 512
result = Execute(args).start()
# (2) Load the pre-trained model
```

(continues on next page)

(continued from previous page)

```
pre_trained_kge = KGE(path=result['path_experiment_folder'])
# (3) Single-hop query answering
# Query: ?E : \exist E.hasSibling(E, F9M167)
# Question: Who are the siblings of F9M167?
# Answer: [F9M157, F9F141], as (F9M167, hasSibling, F9M157) and (F9M167, hasSibling, F9F141)
predictions = pre_trained_kge.answer_multi_hop_query(query_type="1p",
                                                     query=('http://www.benchmark.org/family#F9M167',
                                                            ('http://www.benchmark.org/family#hasSibling',)),
                                                     tnorm="min", k=3)
top_entities = [topk_entity for topk_entity, query_score in predictions]
assert "http://www.benchmark.org/family#F9F141" in top_entities
assert "http://www.benchmark.org/family#F9M157" in top_entities
# (2) Two-hop query answering
# Query: ?D : \exist E.Married(D, E) \land hasSibling(E, F9M167)
# Question: To whom a sibling of F9M167 is married to?
# Answer: [F9F158, F9M142] as (F9M157 #married F9F158) and (F9F141 #married F9M142)
predictions = pre_trained_kge.answer_multi_hop_query(query_type="2p",
                                                     query=("http://www.benchmark.org/family#F9M167",
                                                            ("http://www.benchmark.org/family#hasSibling",
                                                             "http://www.benchmark.org/family#married")),
                                                     tnorm="min", k=3)
top_entities = [topk_entity for topk_entity, query_score in predictions]
assert "http://www.benchmark.org/family#F9M142" in top_entities
assert "http://www.benchmark.org/family#F9F158" in top_entities
# (3) Three-hop query answering
# Query: ?T : \exist D.type(D,T) \land Married(D,E) \land hasSibling(E, F9M167)
# Question: What are the type of people who are married to a sibling of F9M167?
# (3) Answer: [Person, Male, Father] since  F9M157 is [Brother Father Grandfather Male] and F9M142 is [Male Grandfather Father]

predictions = pre_trained_kge.answer_multi_hop_query(query_type="3p", query=("http://www.benchmark.org/family#F9M167",
                                                                             ("http://www.benchmark.org/family#hasSibling",
                                                                              "http://www.benchmark.org/family#married",
                                                                              "http://www.w3.org/1999/02/22-rdf-syntax-ns#type")),
                                                     tnorm="min", k=5)
top_entities = [topk_entity for topk_entity, query_score in predictions]
print(top_entities)
assert "http://www.benchmark.org/family#Person" in top_entities
assert "http://www.benchmark.org/family#Father" in top_entities
assert "http://www.benchmark.org/family#Male" in top_entities
```

For more, please refer to `examples/multi_hop_query_answering`.

8 Predicting Missing Links

```
from dicee import KGE
# (1) Train a knowledge graph embedding model..
# (2) Load a pretrained model
pre_trained_kge = KGE(path='..')
# (3) Predict missing links through head entity rankings
pre_trained_kge.predict_topk(h=[".."],r=[".."],topk=10)
# (4) Predict missing links through relation rankings
pre_trained_kge.predict_topk(h=[".."],t=[".."],topk=10)
# (5) Predict missing links through tail entity rankings
pre_trained_kge.predict_topk(r=[".."],t=[".."],topk=10)
```

9 Downloading Pretrained Models

```
from dicee import KGE
# (1) Load a pretrained ConEx on DBpedia
model = KGE(url="https://files.dice-research.org/projects/DiceEmbeddings/KINSHIP-Keci-
↪dim128-epoch256-KvsAll")
```

- For more please look at dice-research.org/projects/DiceEmbeddings/[11]

10 How to Deploy

```
from dicee import KGE
KGE(path='...').deploy(share=True,top_k=10)
```

11 Docker

To build the Docker image:

```
docker build -t dice-embeddings .
```

To test the Docker image:

```
docker run --rm -v ~/.local/share/dicee/KGs:/dicee/KGs dice-embeddings ./main.py --
↪model AConEx --embedding_dim 16
```

[11] https://files.dice-research.org/projects/DiceEmbeddings/

12 Coverage Report

The coverage report is generated using coverage.py[12]:

```
Name                                                    Stmts   Miss  Cover   Missing
-----------------------------------------------------------------------------------
dicee/__init__.py                                           7      0   100%
dicee/abstracts.py                                        201     82    59%   104-105,␣
↪123, 146-147, 152, 165, 197, 240-254, 257-260, 263-266, 301, 314-317, 320-324, 364-
↪375, 390-398, 413, 424-428, 555-575, 581-585, 589-591
dicee/callbacks.py                                        245    102    58%   50-55,␣
↪67-73, 76, 88-93, 98-103, 106-109, 116-133, 138-142, 146-147, 276-280, 286-287, 305-
↪311, 314, 319-320, 332-338, 344-353, 358-360, 405, 416-429, 433-468, 480-486
dicee/config.py                                            93      2    98%   141-142
dicee/dataset_classes.py                                  299     74    75%   41, 54,␣
↪87, 93, 99-106, 109, 112, 115-139, 195-201, 204, 207-209, 314, 325-328, 344, 410-
↪411, 429, 528-536, 539, 543-557, 700-707, 710-714
dicee/eval_static_funcs.py                                227     95    58%   101, 106,
↪ 111, 258-353, 360-411
dicee/evaluator.py                                        262     51    81%   46, 51,␣
↪56, 84, 89-90, 93, 109, 126, 137, 141, 146, 177-188, 195-206, 314, 344-367, 455,␣
↪465, 482-487
dicee/executer.py                                         113      4    96%   116, 258-
↪259, 291
dicee/knowledge_graph.py                                   65      3    95%   79, 110,␣
↪114
dicee/knowledge_graph_embeddings.py                       636    443    30%   27, 30-
↪31, 39-52, 57-90, 93-127, 131-139, 170-184, 215-228, 254-274, 324-327, 330-333, 346,
↪ 381-426, 484-486, 502-503, 509-517, 522-525, 528-533, 538, 547, 592-598, 630, 688-
↪1053, 1084-1145, 1149-1177, 1200, 1227-1265
dicee/models/__init__.py                                    9      0   100%
dicee/models/base_model.py                                234     31    87%   54, 56,␣
↪82, 88-103, 157, 190, 230, 236, 245, 248, 252, 259, 263, 265, 280, 288-289, 296-297,
↪ 351, 354, 427, 439
dicee/models/clifford.py                                  556    357    36%   31-42,␣
↪68-117, 122-133, 156-168, 190-220, 235, 237, 241, 248-249, 276-280, 303-311, 325-
↪327, 332-333, 364-384, 406, 413, 417-478, 495-499, 511, 514, 519, 524, 571-607, 625-
↪631, 644, 647, 652, 657, 686-692, 705, 708, 713, 718, 728-737, 753-754, 774-845,␣
↪856-859, 884-909, 933-966, 1002-1006, 1019, 1029, 1032, 1037, 1042, 1047, 1051,␣
↪1055, 1064-1065, 1095, 1102, 1107, 1135-1139, 1167-1176, 1186-1194, 1212-1214, 1232-
↪1234, 1250-1252
dicee/models/complex.py                                   151     15    90%   86-109
dicee/models/dualE.py                                      59     10    83%   93-102,␣
↪142-156
dicee/models/function_space.py                            262    221    16%   10-24,␣
↪28-37, 40-49, 53-70, 77-86, 89-98, 101-110, 114-126, 134-156, 159-165, 168-185, 188-
↪194, 197-205, 208, 213-234, 243-246, 250-254, 258-267, 271-292, 301-307, 311-328,␣
↪332-335, 344-352, 355, 366-372, 392-406, 424-438, 443-453, 461-465, 474-478
dicee/models/octonion.py                                  227     83    63%   21-44,␣
↪320-329, 334-345, 348-370, 374-416, 426-474
dicee/models/pykeen_models.py                              50      5    90%   60-63,␣
↪118
dicee/models/quaternion.py                                192     69    64%   7-21, 30-
↪55, 68-72, 107, 185, 328-342, 345-364, 368-389, 399-426
dicee/models/real.py                                       61     12    80%   36-39,␣
```

(continues on next page)

[12] https://coverage.readthedocs.io/en/7.6.0/

(continued from previous page)

```
↪66-69, 87, 103-106
dicee/models/static_funcs.py                                10      0   100%
dicee/models/transformers.py                               236    189    20%   24-43,␣
↪46, 60-75, 84-102, 105-116, 123-125, 128, 134-151, 155-180, 186-190, 193-197, 203-
↪207, 210-212, 229-256, 265-268, 271-276, 279-304, 310-315, 319-372, 376-398, 404-414
dicee/query_generator.py                                   374    346     7%   18-52,␣
↪56, 62-65, 69-70, 78-92, 100-147, 155-188, 192-206, 212-269, 274-303, 307-443, 453-
↪472, 480-501, 508-512, 517, 522-528
dicee/read_preprocess_save_load_kg/__init__.py               3      0   100%
dicee/read_preprocess_save_load_kg/preprocess.py           256     41    84%   34, 40,␣
↪78, 102-127, 133, 138-151, 184, 214, 388-389, 444
dicee/read_preprocess_save_load_kg/read_from_disk.py        36     11    69%   33, 38-
↪40, 47, 55, 58-72
dicee/read_preprocess_save_load_kg/save_load_disk.py        45     18    60%   39-60
dicee/read_preprocess_save_load_kg/util.py                 219    126    42%   65-67,␣
↪72-73, 91-97, 100-102, 107-109, 121, 134, 140-143, 148-156, 161-167, 172-177, 182-
↪187, 199-220, 226-282, 286-290, 294-295, 299, 303-304, 334, 351, 356, 363-364
dicee/sanity_checkers.py                                    54     23    57%   8-12, 21-
↪31, 46, 51, 58, 64-79, 85, 89, 96
dicee/static_funcs.py                                      418    163    61%   40, 50,␣
↪56-61, 83, 105-106, 115, 138, 152, 157-159, 163-165, 167, 194-198, 246, 254, 263-
↪268, 290-304, 316-336, 340-357, 362, 386-387, 392-393, 410-411, 413-414, 416-417,␣
↪419-420, 428, 446-450, 467-470, 474-479, 483-487, 491-492, 498-500, 526-527, 539-
↪542, 547-550, 559-610, 615-627, 644-658, 661-669
dicee/static_funcs_training.py                             123     63    49%   118-215,␣
↪223-224
dicee/static_preprocess_funcs.py                           100     44    56%   17-25,␣
↪52, 56, 64, 67, 78, 91-115, 120-123, 128-131, 136-139
dicee/trainer/__init__.py                                    1      0   100%
dicee/trainer/dice_trainer.py                              126     13    90%   27-32,␣
↪91, 98, 103-108, 147
dicee/trainer/torch_trainer.py                              79      4    95%   31, 196,␣
↪207-208
dicee/trainer/torch_trainer_ddp.py                         152    128    16%   13-14,␣
↪43, 47-72, 83-112, 131-137, 140-149, 164-194, 204-217, 226-246, 251-260, 263-272,␣
↪275-299, 302-309
-------------------------------------------------------------------------------------
TOTAL                                                     6181   2828    54%
```

13 How to cite

Currently, we are working on our manuscript describing our framework. If you really like our work and want to cite it now, feel free to chose one :)

```
# Keci
@inproceedings{demir2023clifford,
  title={Clifford Embeddings--A Generalized Approach for Embedding in Normed Algebras}
↪,
  author={Demir, Caglar and Ngonga Ngomo, Axel-Cyrille},
  booktitle={Joint European Conference on Machine Learning and Knowledge Discovery in␣
↪Databases},
  pages={567--582},
  year={2023},
  organization={Springer}
```

(continues on next page)

(continued from previous page)

```
}
# LitCQD
@inproceedings{demir2023litcqd,
  title={LitCQD: Multi-Hop Reasoning in Incomplete Knowledge Graphs with Numeric␣
↪Literals},
  author={Demir, Caglar and Wiebesiek, Michel and Lu, Renzhong and Ngonga Ngomo, Axel-
↪Cyrille and Heindorf, Stefan},
  booktitle={Joint European Conference on Machine Learning and Knowledge Discovery in␣
↪Databases},
  pages={617--633},
  year={2023},
  organization={Springer}
}
# DICE Embedding Framework
@article{demir2022hardware,
  title={Hardware-agnostic computation for large-scale knowledge graph embeddings},
  author={Demir, Caglar and Ngomo, Axel-Cyrille Ngonga},
  journal={Software Impacts},
  year={2022},
  publisher={Elsevier}
}
# KronE
@inproceedings{demir2022kronecker,
  title={Kronecker decomposition for knowledge graph embeddings},
  author={Demir, Caglar and Lienen, Julian and Ngonga Ngomo, Axel-Cyrille},
  booktitle={Proceedings of the 33rd ACM Conference on Hypertext and Social Media},
  pages={1--10},
  year={2022}
}
# QMult, OMult, ConvQ, ConvO
@InProceedings{pmlr-v157-demir21a,
  title =          {Convolutional Hypercomplex Embeddings for Link Prediction},
  author =       {Demir, Caglar and Moussallem, Diego and Heindorf, Stefan and Ngonga␣
↪Ngomo, Axel-Cyrille},
  booktitle =          {Proceedings of The 13th Asian Conference on Machine Learning},
  pages =          {656--671},
  year =          {2021},
  editor =          {Balasubramanian, Vineeth N. and Tsang, Ivor},
  volume =          {157},
  series =          {Proceedings of Machine Learning Research},
  month =          {17--19 Nov},
  publisher =    {PMLR},
  pdf =          {https://proceedings.mlr.press/v157/demir21a/demir21a.pdf},
  url =          {https://proceedings.mlr.press/v157/demir21a.html},
}
# ConEx
@inproceedings{demir2021convolutional,
title={Convolutional Complex Knowledge Graph Embeddings},
author={Caglar Demir and Axel-Cyrille Ngonga Ngomo},
booktitle={Eighteenth Extended Semantic Web Conference - Research Track},
year={2021},
url={https://openreview.net/forum?id=6T45-4TFqaX}}
# Shallom
@inproceedings{demir2021shallow,
  title={A shallow neural model for relation prediction},
  author={Demir, Caglar and Moussallem, Diego and Ngomo, Axel-Cyrille Ngonga},
  booktitle={2021 IEEE 15th International Conference on Semantic Computing (ICSC)},
```

(continues on next page)

(continued from previous page)

```
  pages={179--182},
  year={2021},
  organization={IEEE}
```

For any questions or wishes, please contact: caglar.demir@upb.de

14 dicee

14.1 Subpackages

dicee.models

Submodules

dicee.models.base_model

Classes

BaseKGELightning	Base class for all neural network modules.
BaseKGE	Base class for all neural network modules.
IdentityClass	Base class for all neural network modules.

Module Contents

class dicee.models.base_model.**BaseKGELightning**(**args*, ***kwargs*)

Bases: lightning.LightningModule

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call to(), etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

training_step_outputs = []

mem_of_model() → Dict

Size of model in MB and number of params

training_step(*batch*, *batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- `Tensor` - The loss tensor
- `dict` - A dictionary which can include any keys, but must include the key `'loss'` in the case of automatic optimization.
- `None` - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False


# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
```

(continues on next page)

(continued from previous page)

```
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

> **Note**
>
> When `accumulate_grad_batches` > 1, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

loss_function(*yhat_batch: torch.FloatTensor*, *y_batch: torch.FloatTensor*)

Parameters

- **yhat_batch**
- **y_batch**

on_train_epoch_end(**args*, ***kwargs*)

Called in the training loop at the very end of the epoch.

To access all batch outputs at the end of the epoch, you can cache step outputs as an attribute of the `LightningModule` and access them in this hook:

```
class MyLightningModule(L.LightningModule):
    def __init__(self):
        super().__init__()
        self.training_step_outputs = []

    def training_step(self):
        loss = ...
        self.training_step_outputs.append(loss)
        return loss

    def on_train_epoch_end(self):
        # do something with all training_step outputs, for example:
        epoch_mean = torch.stack(self.training_step_outputs).mean()
        self.log("training_epoch_mean", epoch_mean)
        # free up the memory
        self.training_step_outputs.clear()
```

test_epoch_end(*outputs: List[Any]*)

test_dataloader() → None

An iterable or collection of iterables specifying test samples.

For more information about multiple dataloaders, see this section.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in prepare_data

- `test()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

Note

If you don't need a test dataset and a `test_step()`, you don't need to implement this method.

`val_dataloader``()` → None

An iterable or collection of iterables specifying validation samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:paramref:`~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `fit()`
- `validate()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

Note

If you don't need a validation dataset and a `validation_step()`, you don't need to implement this method.

`predict_dataloader``()` → None

An iterable or collection of iterables specifying prediction samples.

For more information about multiple dataloaders, see this section.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `predict()`
- `prepare_data()`
- `setup()`

> **Note**
>
> Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

Returns

A `torch.utils.data.DataLoader` or a sequence of them specifying prediction samples.

`train_dataloader``()` → None

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:paramref:`~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

> **Warning**
>
> do not assign state in prepare_data

- `fit()`
- `prepare_data()`
- `setup()`

> **Note**
>
> Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

`configure_optimizers`(*parameters=None*)

Choose what optimizers and learning-rate schedulers to use in your optimization. Normally you'd need one. But in the case of GANs or similar you might have multiple. Optimization with multiple optimizers only works in the manual optimization mode.

Returns

Any of these 6 options.

- **Single optimizer**.
- **List or Tuple** of optimizers.
- **Two lists** - The first list has multiple optimizers, and the second has multiple LR schedulers (or multiple `lr_scheduler_config`).
- **Dictionary**, with an `"optimizer"` key, and (optionally) a `"lr_scheduler"` key whose value is a single LR scheduler or `lr_scheduler_config`.
- **None** - Fit will run without any optimizer.

The `lr_scheduler_config` is a dictionary which contains the scheduler and its associated configuration. The default configuration is shown below.

```
lr_scheduler_config = {
    # REQUIRED: The scheduler instance
    "scheduler": lr_scheduler,
    # The unit of the scheduler's step size, could also be 'step'.
    # 'epoch' updates the scheduler on epoch end whereas 'step'
    # updates it after a optimizer update.
    "interval": "epoch",
    # How many epochs/steps should pass between calls to
    # `scheduler.step()`. 1 corresponds to updating the learning
    # rate after every epoch/step.
    "frequency": 1,
    # Metric to to monitor for schedulers like `ReduceLROnPlateau`
    "monitor": "val_loss",
    # If set to `True`, will enforce that the value specified 'monitor'
    # is available when the scheduler is updated, thus stopping
    # training if not found. If set to `False`, it will only produce a warning
    "strict": True,
    # If using the `LearningRateMonitor` callback to monitor the
    # learning rate progress, this keyword can be used to specify
    # a custom logged name
    "name": None,
}
```

When there are schedulers in which the `.step()` method is conditioned on a value, such as the `torch.optim.lr_scheduler.ReduceLROnPlateau` scheduler, Lightning requires that the `lr_scheduler_config` contains the keyword `"monitor"` set to the metric name that the scheduler should be conditioned on.

Metrics can be made available to monitor by simply logging it using `self.log('metric_to_track', metric_val)` in your `LightningModule`.

Note

Some things to know:

- Lightning calls `.backward()` and `.step()` automatically in case of automatic optimization.
- If a learning rate scheduler is specified in `configure_optimizers()` with key `"interval"` (default "epoch") in the scheduler configuration, Lightning will call the scheduler's `.step()` method automatically in case of automatic optimization.
- If you use 16-bit precision (`precision=16`), Lightning will automatically handle the optimizer.

- If you use `torch.optim.LBFGS`, Lightning handles the closure function automatically for you.
- If you use multiple optimizers, you will have to switch to 'manual optimization' mode and step them yourself.
- If you need to control how often the optimizer steps, override the `optimizer_step()` hook.

class dicee.models.base_model.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters
x (*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters
----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*, *y_idx: torch.LongTensor = None*)

Parameters

- **x**
- **y_idx**

- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b** (*x shape*)
- **3**
- **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*)
→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters
x (*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.base_model.**IdentityClass**(*args=None*)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call to(), etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables
training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

__call__(*x*)

static forward(*x*)

dicee.models.clifford

Classes

CMult	Cl_(0,0) => Real Numbers
Keci	Base class for all neural network modules.
KeciBase	Without learning dimension scaling
DeCaL	Base class for all neural network modules.

Module Contents

class dicee.models.clifford.**CMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Cl_(0,0) => Real Numbers

Cl_(0,1) =>
A multivector mathbf{a} = a_0 + a_1 e_1 A multivector mathbf{b} = b_0 + b_1 e_1

multiplication is isomorphic to the product of two complex numbers

mathbf{a} imes mathbf{b} = a_0 b_0 + a_0b_1 e1 + a_1 b_1 e_1 e_1
= (a_0 b_0 - a_1 b_1) + (a_0 b_1 + a_1 b_0) e_1

Cl_(2,0) =>
A multivector mathbf{a} = a_0 + a_1 e_1 + a_2 e_2 + a_{12} e_1 e_2 A multivector mathbf{b} = b_0 + b_1 e_1 + b_2 e_2 + b_{12} e_1 e_2

mathbf{a} imes mathbf{b} = a_0b_0 + a_0b_1 e_1 + a_0b_2e_2 + a_0 b_12 e_1 e_2

- a_1 b_0 e_1 + a_1b_1 e_1_e1 ..

Cl_(0,2) => Quaternions

name = 'CMult'

entity_embeddings

relation_embeddings

p

q

clifford_mul (*x: torch.FloatTensor*, *y: torch.FloatTensor*, *p: int*, *q: int*) → tuple

Clifford multiplication Cl_{p,q} (mathbb{R})

ei ^2 = +1 for i =< i =< p ej ^2 = -1 for p < j =< p+q ei ej = -eje1 for i

eq j

x: torch.FloatTensor with (n,d) shape

y: torch.FloatTensor with (n,d) shape

p: a non-negative integer p>= 0 q: a non-negative integer q>= 0

score (*head_ent_emb*, *rel_ent_emb*, *tail_ent_emb*)

forward_triples (*x: torch.LongTensor*) → torch.FloatTensor

Compute batch triple scores

Parameter

x: torch.LongTensor with shape n by 3

rtype
torch.LongTensor with shape n

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Compute batch KvsAll triple scores

Parameter

x: torch.LongTensor with shape n by 3

rtype
torch.LongTensor with shape n

class dicee.models.clifford.**Keci** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)

(continued from previous page)

```
    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'Keci'

p

q

r

requires_grad_for_interactions = True

compute_sigma_pp(*hp*, *rp*)

Compute sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):
results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq(*hq*, *rq*)

Compute sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):
results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_pq (*, *hp*, *hq*, *rp*, *rq*)

sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

apply_coefficients (*h0*, *hp*, *hq*, *r0*, *rp*, *rq*)

Multiplying a base vector with its scalar coefficient

clifford_multiplication (*h0*, *hp*, *hq*, *r0*, *rp*, *rq*)

Compute our CL multiplication

h = h_0 + sum_{i=1}^p h_i e_i + sum_{j=p+1}^{p+q} h_j e_j r = r_0 + sum_{i=1}^p r_i e_i + sum_{j=p+1}^{p+q} r_j e_j

ei ^2 = +1 for i =< i =< p ej ^2 = -1 for p < j =< p+q ei ej = -eje1 for i

eq j

h r = sigma_0 + sigma_p + sigma_q + sigma_{pp} + sigma_{q}+ sigma_{pq} where

(1) sigma_0 = h_0 r_0 + sum_{i=1}^p (h_0 r_i) e_i - sum_{j=p+1}^{p+q} (h_j r_j) e_j

(2) sigma_p = sum_{i=1}^p (h_0 r_i + h_i r_0) e_i

(3) sigma_q = sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j

(4) sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k

(5) sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k

(6) sigma_{pq} = sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j

construct_cl_multivector (*x: torch.FloatTensor*, *r: int*, *p: int*, *q: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors Cl_{p,q}(mathbb{R}^d)

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor with (n,r) shape*)
- **ap** (*torch.FloatTensor with (n,r,p) shape*)
- **aq** (*torch.FloatTensor with (n,r,q) shape*)

forward_k_vs_with_explicit (*x: torch.Tensor*)

k_vs_all_score (*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations mathbb{R}^d .

(2) Construct head entity and relation embeddings according to Cl_{p,q}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter ——— x: torch.LongTensor with (n,2) shape :rtype: torch.FloatTensor with (n, |E|) shape

forward_k_vs_sample(*x: torch.LongTensor*, *target_entity_idx: torch.LongTensor*)
→ torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations mathbb{R}^d .

(2) Construct head entity and relation embeddings according to Cl_{p,q}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

Parameter

x: torch.LongTensor with (n,2) shape

rtype
torch.FloatTensor with (n, |E|) shape

score(*h*, *r*, *t*)

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,3) shape

rtype
torch.FloatTensor with (n) shape

class dicee.models.clifford.**KeciBase**(*args*)

Bases: *Keci*

Without learning dimension scaling

name = 'KeciBase'

requires_grad_for_interactions = False

class dicee.models.clifford.**DeCaL**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'DeCaL'

entity_embeddings

relation_embeddings

p

q

r

re

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

cl_pqr(*a: torch.tensor*) → torch.tensor

Input: tensor(batch_size, emb_dim) —> output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q +r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

compute_sigmas_single (*list_h_emb*, *list_r_emb*, *list_t_emb*)

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^{p} h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^{q} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t$$

and return:

$$sigma_0 t = \sigma_0 \cdot t_0 = s0 + s1 - s2 s3, s4 and s5$$

compute_sigmas_multivect (*list_h_emb*, *list_r_emb*)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^{p} (h_i r_{i'} - h_{i'} r_i)(models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'}$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i)(interactions n between e_i and e_j for 1 <= i <= p and p+1 <= j <= p+q) \sigma_p r = \sum_{i=}$$

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations

(2) Construct head entity and relation embeddings according to Cl_{p,q, r}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter ——— x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, |E|) shape

apply_coefficients (*h0*, *hp*, *hq*, *hk*, *r0*, *rp*, *rq*, *rk*)

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (*x: torch.FloatTensor*, *re: int*, *p: int*, *q: int*, *r: int*) → tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors Cl_{p,q,r}(mathbb{R}^d)

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor*)
- **ap** (*torch.FloatTensor*)
- **aq** (*torch.FloatTensor*)
- **ar** (*torch.FloatTensor*)

compute_sigma_pp(*hp*, *rp*)

Compute .. math:

```
\sigma_{p,p}^* = \sum_{i=1}^{p-1}\sum_{i'=i+1}^{p}(x_iy_{i'}-x_{i'}y_i)
```

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):
results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq(*hq*, *rq*)

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1}\sum_{j'=j+1}^{p+q}(x_jy_{j'} - x_{j'}y_j) Eq.16$$

sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):
results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_rr(*hk*, *rk*)

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1}\sum_{k'=k+1}^{p}(x_ky_{k'} - x_{k'}y_k)$$

compute_sigma_pq(*, *hp*, *hq*, *rp*, *rq*)

Compute

$$\sum_{i=1}^{p}\sum_{j=p+1}^{p+q}(h_ir_j - h_jr_i)e_ie_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

compute_sigma_pr(*, *hp*, *hk*, *rp*, *rk*)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

compute_sigma_qr(*, *hq*, *hk*, *rq*, *rk*)

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

dicee.models.complex

Classes

ConEx	Convolutional ComplEx Knowledge Graph Embeddings
AConEx	Additive Convolutional ComplEx Knowledge Graph Embeddings
ComplEx	Base class for all neural network modules.

Module Contents

class dicee.models.complex.**ConEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional ComplEx Knowledge Graph Embeddings

name = 'ConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution(*C_1: Tuple[torch.Tensor, torch.Tensor]*, *C_2: Tuple[torch.Tensor, torch.Tensor]*) → torch.FloatTensor

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameters
x

forward_k_vs_sample(*x: torch.Tensor*, *target_entity_idx: torch.Tensor*)

class dicee.models.complex.**AConEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional ComplEx Knowledge Graph Embeddings

name = 'AConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution(*C_1: Tuple[torch.Tensor, torch.Tensor]*, *C_2: Tuple[torch.Tensor, torch.Tensor]*) → torch.FloatTensor

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameters
x

forward_k_vs_sample(*x: torch.Tensor*, *target_entity_idx: torch.Tensor*)

class dicee.models.complex.**ComplEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ComplEx'

static score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

static k_vs_all_score(*emb_h: torch.FloatTensor*, *emb_r: torch.FloatTensor*, *emb_E: torch.FloatTensor*)

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

forward_k_vs_all(*x: torch.LongTensor*) → torch.FloatTensor

dicee.models.dualE

Classes

DualE	Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

Module Contents

class dicee.models.dualE.**DualE**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent

kvsall_score(*e_1_h*, *e_2_h*, *e_3_h*, *e_4_h*, *e_5_h*, *e_6_h*, *e_7_h*, *e_8_h*, *e_1_t*, *e_2_t*, *e_3_t*, *e_4_t*, *e_5_t*, *e_6_t*, *e_7_t*, *e_8_t*, *r_1*, *r_2*, *r_3*, *r_4*, *r_5*, *r_6*, *r_7*, *r_8*) → torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_triples(*idx_triple: torch.tensor*) → torch.tensor

Negative Sampling forward pass:

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_k_vs_all(*x*)

KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

T (*x: torch.tensor*) → torch.tensor

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

dicee.models.function_space

Classes

FMult	Learning Knowledge Neural Graphs
GFMult	Learning Knowledge Neural Graphs
FMult2	Learning Knowledge Neural Graphs
LFMult1	Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
LFMult	Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:

Module Contents

class dicee.models.function_space.**FMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Learning Knowledge Neural Graphs

name = 'FMult'

entity_embeddings

relation_embeddings

k

num_sample = 50

gamma

roots

weights

compute_func(*weights: torch.FloatTensor*, *x*) → torch.FloatTensor

chain_func(*weights*, *x: torch.FloatTensor*)

forward_triples(*idx_triple: torch.Tensor*) → torch.Tensor

Parameters
x

class dicee.models.function_space.**GFMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Learning Knowledge Neural Graphs

name = 'GFMult'

entity_embeddings

relation_embeddings

k

num_sample = 250

roots

weights

compute_func(*weights: torch.FloatTensor*, *x*) → torch.FloatTensor

chain_func(*weights*, *x: torch.FloatTensor*)

forward_triples(*idx_triple: torch.Tensor*) → torch.Tensor

Parameters
x

class dicee.models.function_space.**FMult2**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Learning Knowledge Neural Graphs

name = 'FMult2'

n_layers = 3

tuned_embedding_dim = False

k

n = 50

score_func = 'compositional'

discrete_points

entity_embeddings

relation_embeddings

build_func(*Vec*)

build_chain_funcs(*list_Vec*)

compute_func(*W*, *b*, *x*) → torch.FloatTensor

function(*list_W*, *list_b*)

trapezoid(*list_W*, *list_b*)

forward_triples(*idx_triple: torch.Tensor*) → torch.Tensor

Parameters
x

class dicee.models.function_space.**LFMult1**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding with trigonometric functions. We represent all entities and relations in the complex number space as: f(x) = sum_{k=0}^{k=d-1}wk e^{kix}. and use the three differents scoring function as in the paper to evaluate the score

name = 'LFMult1'

entity_embeddings

relation_embeddings

forward_triples(*idx_triple*)

Parameters
x

tri_score(*h*, *r*, *t*)

vtp_score(*h*, *r*, *t*)

class dicee.models.function_space.**LFMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: f(x) = sum_{i=0}^{d-1} a_k x^{i%d} and use the three differents scoring function as in the paper to evaluate the score. We also consider combining with Neural Networks.

name = 'LFMult'

entity_embeddings

relation_embeddings

degree

m

x_values

forward_triples(*idx_triple*)

Parameters
x

construct_multi_coeff(*x*)

poly_NN(*x*, *coefh*, *coefr*, *coeft*)

Constructing a 2 layers NN to represent the embeddings. h = sigma(wh^T x + bh), r = sigma(wr^T x + br), t = sigma(wt^T x + bt)

linear(*x*, *w*, *b*)

scalar_batch_NN(*a*, *b*, *c*)

element wise multiplication between a,b and c: Inputs : a, b, c ====> torch.tensor of size batch_size x m x d Output : a tensor of size batch_size x d

tri_score(*coeff_h*, *coeff_r*, *coeff_t*)

this part implement the trilinear scoring techniques:

score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k = 0}^{d-1} dfrac{a_i*b_j*c_k}{1+(i+j+k)%d}

1. generate the range for i,j and k from [0 d-1]
2. perform dfrac{a_i*b_j*c_k}{1+(i+j+k)%d} in parallel for every batch
3. take the sum over each batch

vtp_score(*h*, *r*, *t*)

this part implement the vector triple product scoring techniques:

score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k = 0}^{d-1} dfrac{a_i*c_j*b_k - b_i*c_j*a_k}{(1+(i+j)%d)(1+k)}

1. generate the range for i,j and k from [0 d-1]
2. Compute the first and second terms of the sum
3. Multiply with then denominator and take the sum
4. take the sum over each batch

comp_func(*h*, *r*, *t*)

this part implement the function composition scoring techniques: i.e. score = <hor, t>

polynomial(*coeff*, *x*, *degree*)

This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer [0,1,…d] and return a vector tensor (coeff[0][0] + coeff[0][1]x +…+ coeff[0][d]x^d,

coeff[1][0] + coeff[1][1]x +…+ coeff[1][d]x^d)

pop(*coeff*, *x*, *degree*)

This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,…d]

and return a tensor (coeff[0][0] + coeff[0][1]x +…+ coeff[0][d]x^d,

coeff[1][0] + coeff[1][1]x +…+ coeff[1][d]x^d)

dicee.models.octonion

Classes

OMult	Base class for all neural network modules.
ConvO	Base class for all neural network modules.
AConvO	Additive Convolutional Octonion Knowledge Graph Embeddings

Functions

octonion_mul(*, O_1, O_2)
octonion_mul_norm(*, O_1, O_2)

Module Contents

dicee.models.octonion.**octonion_mul**(*, *O_1*, *O_2*)

dicee.models.octonion.**octonion_mul_norm**(*, *O_1*, *O_2*)

class dicee.models.octonion.**OMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'OMult'

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

score (*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

k_vs_all_score (*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

forward_k_vs_all (*x*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.octonion.**ConvO** (*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

residual_convolution(*O_1*, *O_2*)

forward_triples(*x: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.models.octonion.**AConvO**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional Octonion Knowledge Graph Embeddings

name = 'AConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

residual_convolution(*O_1*, *O_2*)

forward_triples(*x: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

dicee.models.pykeen_models

Classes

PykeenKGE	A class for using knowledge graph embedding models implemented in Pykeen

Module Contents

class dicee.models.pykeen_models.**PykeenKGE**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

A class for using knowledge graph embedding models implemented in Pykeen

Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Pykeen_HolE:

model_kwargs

name

model

loss_history = []

args

entity_embeddings = None

relation_embeddings = None

forward_k_vs_all(*x: torch.LongTensor*)

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r = self.get_head_relation_representation(x) # (2) Reshape (1). if self.last_dim > 0:

h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim)

(3) Reshape all entities. if self.last_dim > 0:

t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)

else:

t = self.entity_embeddings.weight

(4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r, all_entities=t, slice_size=1)

forward_triples(*x: torch.LongTensor*) → torch.FloatTensor

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t = self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:

h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)

(3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice_size=None, slice_dim=0)

abstract forward_k_vs_sample(*x: torch.LongTensor*, *target_entity_idx*)

dicee.models.quaternion

Classes

QMult	Base class for all neural network modules.
ConvQ	Convolutional Quaternion Knowledge Graph Embeddings
AConvQ	Additive Convolutional Quaternion Knowledge Graph Embeddings

Functions

quaternion_mul_with_unit_norm(*, Q_1, Q_2)	

Module Contents

dicee.models.quaternion.**quaternion_mul_with_unit_norm**(*, *Q_1*, *Q_2*)

class dicee.models.quaternion.**QMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'QMult'

explicit = True

quaternion_multiplication_followed_by_inner_product(*h*, *r*, *t*)

Parameters

- **h** – shape: (**batch_dims*, dim) The head representations.
- **r** – shape: (**batch_dims*, dim) The head representations.
- **t** – shape: (**batch_dims*, dim) The tail representations.

Returns

Triple scores.

static quaternion_normalizer(*x: torch.FloatTensor*) → torch.FloatTensor

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a + bi + cj + dk| = \sqrt{a^2 + b^2 + c^2 + d^2}$$

L2 norm of quaternion vector:

$$\|x\|^2 = \sum_{i=1}^{d} |x_i|^2 = \sum_{i=1}^{d} (x_i.re^2 + x_i.im_1^2 + x_i.im_2^2 + x_i.im_3^2)$$

Parameters

x – The vector.

Returns

The normalized vector.

score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

k_vs_all_score(*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

Parameters

- **bpe_head_ent_emb**
- **bpe_rel_ent_emb**
- **E**

forward_k_vs_all(*x*)

Parameters

x

forward_k_vs_sample(*x*, *target_entity_idx*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.quaternion.**ConvQ**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional Quaternion Knowledge Graph Embeddings

name = 'ConvQ'

entity_embeddings

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution(*Q_1*, *Q_2*)

forward_triples(*indexed_triple: torch.Tensor*) → torch.Tensor

Parameters

x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.quaternion.**AConvQ**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional Quaternion Knowledge Graph Embeddings

name = 'AConvQ'

entity_embeddings

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution(*Q_1*, *Q_2*)

forward_triples(*indexed_triple: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

dicee.models.real

Classes

DistMult	Embedding Entities and Relations for Learning and Inference in Knowledge Bases
TransE	Translating Embeddings for Modeling
Shallom	A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
Pyke	A Physical Embedding Model for Knowledge Graphs

Module Contents

class dicee.models.real.**DistMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575

name = 'DistMult'

k_vs_all_score(*emb_h: torch.FloatTensor*, *emb_r: torch.FloatTensor*, *emb_E: torch.FloatTensor*)

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

forward_k_vs_all(*x: torch.LongTensor*)

forward_k_vs_sample(*x: torch.LongTensor*, *target_entity_idx: torch.LongTensor*)

score(*h*, *r*, *t*)

class dicee.models.real.**TransE**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Translating Embeddings for Modeling Multi-relational Data https://proceedings.neurips.cc/paper/2013/file/1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf

name = 'TransE'

margin = 4

score(*head_ent_emb*, *rel_ent_emb*, *tail_ent_emb*)

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

class dicee.models.real.**Shallom**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)

name = 'Shallom'

shallom_width

shallom

get_embeddings() → Tuple[numpy.ndarray, None]

forward_k_vs_all(*x*) → torch.FloatTensor

forward_triples(*x*) → torch.FloatTensor

Parameters
x

Returns

class dicee.models.real.**Pyke**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

A Physical Embedding Model for Knowledge Graphs

name = 'Pyke'

dist_func

margin = 1.0

forward_triples(*x: torch.LongTensor*)

Parameters
x

dicee.models.static_funcs

Functions

quaternion_mul(→ torch.Tensor, ...)	Tuple[torch.Tensor,	Perform quaternion multiplication

Module Contents

dicee.models.static_funcs.**quaternion_mul**(*, *Q_1*, *Q_2*)
→ Tuple[torch.Tensor, torch.Tensor, torch.Tensor, torch.Tensor]

Perform quaternion multiplication :param Q_1: :param Q_2: :return:

dicee.models.transformers

Classes

BytE	Base class for all neural network modules.
LayerNorm	LayerNorm but with an optional bias. PyTorch doesn't support simply bias=False
CausalSelfAttention	Base class for all neural network modules.
MLP	Base class for all neural network modules.
Block	Base class for all neural network modules.
GPTConfig	
GPT	Base class for all neural network modules.

Module Contents

class dicee.models.transformers.**BytE**(**args*, ***kwargs*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'BytE'

config

temperature = 0.5

topk = 2

transformer

lm_head

weight

loss_function(*yhat_batch*, *y_batch*)

Parameters

- **yhat_batch**
- **y_batch**

forward(*x: torch.LongTensor*)

Parameters

x (*B by T tensor*)

generate(*idx*, *max_new_tokens*, *temperature=1.0*, *top_k=None*)

Take a conditioning sequence of indices idx (LongTensor of shape (b,t)) and complete the sequence max_new_tokens times, feeding the predictions back into the model each time. Most likely you'll want to make sure to be in model.eval() mode of operation for this.

training_step(*batch*, *batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- `Tensor` - The loss tensor
- `dict` - A dictionary which can include any keys, but must include the key `'loss'` in the case of automatic optimization.
- `None` - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False


# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

Note

When `accumulate_grad_batches` > 1, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

class dicee.models.transformers.**LayerNorm**(*ndim*, *bias*)

Bases: `torch.nn.Module`

LayerNorm but with an optional bias. PyTorch doesn't support simply bias=False

weight

bias

forward(*input*)

class dicee.models.transformers.**CausalSelfAttention**(*config*)

Bases: `torch.nn.Module`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F
```

(continues on next page)

(continued from previous page)

```
class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

c_attn

c_proj

attn_dropout

resid_dropout

n_head

n_embd

dropout

flash

forward(*x*)

class dicee.models.transformers.**MLP**(*config*)

Bases: `torch.nn.Module`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
```

(continues on next page)

(continued from previous page)

```
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

c_fc

gelu

c_proj

dropout

forward(*x*)

class dicee.models.transformers.**Block**(*config*)

Bases: `torch.nn.Module`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables
training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

ln_1

attn

ln_2

mlp

forward(*x*)

class dicee.models.transformers.**GPTConfig**

block_size: int = 1024

vocab_size: int = 50304

n_layer: int = 12

n_head: int = 12

n_embd: int = 768

dropout: float = 0.0

bias: bool = False

class dicee.models.transformers.**GPT**(*config*)

Bases: `torch.nn.Module`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

config

transformer

lm_head

weight

get_num_params(*non_embedding=True*)

Return the number of parameters in the model. For non-embedding count (default), the position embeddings get subtracted. The token embeddings would too, except due to the parameter sharing these params are actually used as weights in the final layer, so we include them.

forward(*idx*, *targets=None*)

crop_block_size(*block_size*)

classmethod from_pretrained(*model_type*, *override_args=None*)

configure_optimizers(*weight_decay*, *learning_rate*, *betas*, *device_type*)

estimate_mfu(*fwdbwd_per_iter*, *dt*)

estimate model flops utilization (MFU) in units of A100 bfloat16 peak FLOPS

Classes

BaseKGELightning	Base class for all neural network modules.
BaseKGE	Base class for all neural network modules.
IdentityClass	Base class for all neural network modules.
BaseKGE	Base class for all neural network modules.
DistMult	Embedding Entities and Relations for Learning and Inference in Knowledge Bases
TransE	Translating Embeddings for Modeling
Shallom	A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
Pyke	A Physical Embedding Model for Knowledge Graphs
BaseKGE	Base class for all neural network modules.
ConEx	Convolutional ComplEx Knowledge Graph Embeddings
AConEx	Additive Convolutional ComplEx Knowledge Graph Embeddings
ComplEx	Base class for all neural network modules.

continues on next page

Table 1 – continued from previous page

BaseKGE	Base class for all neural network modules.
IdentityClass	Base class for all neural network modules.
QMult	Base class for all neural network modules.
ConvQ	Convolutional Quaternion Knowledge Graph Embeddings
AConvQ	Additive Convolutional Quaternion Knowledge Graph Embeddings
BaseKGE	Base class for all neural network modules.
IdentityClass	Base class for all neural network modules.
OMult	Base class for all neural network modules.
ConvO	Base class for all neural network modules.
AConvO	Additive Convolutional Octonion Knowledge Graph Embeddings
Keci	Base class for all neural network modules.
KeciBase	Without learning dimension scaling
CMult	Cl_(0,0) => Real Numbers
DeCaL	Base class for all neural network modules.
BaseKGE	Base class for all neural network modules.
PykeenKGE	A class for using knowledge graph embedding models implemented in Pykeen
BaseKGE	Base class for all neural network modules.
FMult	Learning Knowledge Neural Graphs
GFMult	Learning Knowledge Neural Graphs
FMult2	Learning Knowledge Neural Graphs
LFMult1	Embedding with trigonometric functions. We represent all entities and relations in the complex number space as:
LFMult	Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:
DualE	Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

Functions

quaternion_mul(→ Tuple[torch.Tensor, torch.Tensor, ...)	Perform quaternion multiplication
quaternion_mul_with_unit_norm(*, Q_1, Q_2)	
octonion_mul(*, O_1, O_2)	
octonion_mul_norm(*, O_1, O_2)	

Package Contents

class dicee.models.**BaseKGELightning**(**args*, ***kwargs*)

Bases: lightning.LightningModule

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

training_step_outputs = []

mem_of_model() → Dict

Size of model in MB and number of params

training_step(*batch*, *batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- `Tensor` - The loss tensor
- `dict` - A dictionary which can include any keys, but must include the key `'loss'` in the case of automatic optimization.

- `None` - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False


# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

Note

When `accumulate_grad_batches` > 1, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

loss_function(*yhat_batch: torch.FloatTensor*, *y_batch: torch.FloatTensor*)

Parameters

- **yhat_batch**
- **y_batch**

on_train_epoch_end(**args*, ***kwargs*)

Called in the training loop at the very end of the epoch.

To access all batch outputs at the end of the epoch, you can cache step outputs as an attribute of the `LightningModule` and access them in this hook:

```
class MyLightningModule(L.LightningModule):
    def __init__(self):
        super().__init__()
        self.training_step_outputs = []
```

(continues on next page)

(continued from previous page)

```
    def training_step(self):
        loss = ...
        self.training_step_outputs.append(loss)
        return loss

    def on_train_epoch_end(self):
        # do something with all training_step outputs, for example:
        epoch_mean = torch.stack(self.training_step_outputs).mean()
        self.log("training_epoch_mean", epoch_mean)
        # free up the memory
        self.training_step_outputs.clear()
```

test_epoch_end(*outputs: List[Any]*)

test_dataloader() → None

An iterable or collection of iterables specifying test samples.

For more information about multiple dataloaders, see this section.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

Warning

do not assign state in prepare_data

- `test()`
- `prepare_data()`
- `setup()`

Note

Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

Note

If you don't need a test dataset and a `test_step()`, you don't need to implement this method.

val_dataloader() → None

An iterable or collection of iterables specifying validation samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:paramref:`~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `fit()`
- `validate()`
- `prepare_data()`
- `setup()`

> **Note**
>
> Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

> **Note**
>
> If you don't need a validation dataset and a `validation_step()`, you don't need to implement this method.

`predict_dataloader``()` → None

An iterable or collection of iterables specifying prediction samples.

For more information about multiple dataloaders, see this section.

It's recommended that all data downloads and preparation happen in `prepare_data()`.

- `predict()`
- `prepare_data()`
- `setup()`

> **Note**
>
> Lightning tries to add the correct sampler for distributed and arbitrary hardware There is no need to set it yourself.

Returns

A `torch.utils.data.DataLoader` or a sequence of them specifying prediction samples.

`train_dataloader``()` → None

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:paramref:`~lightning.pytorch.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

For data processing use the following pattern:

- download in `prepare_data()`
- process and split in `setup()`

However, the above are only necessary for distributed processing.

> **Warning**
>
> do not assign state in prepare_data

- `fit()`
- `prepare_data()`
- `setup()`

> **Note**
>
> Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

`configure_optimizers` (*parameters=None*)

Choose what optimizers and learning-rate schedulers to use in your optimization. Normally you'd need one. But in the case of GANs or similar you might have multiple. Optimization with multiple optimizers only works in the manual optimization mode.

Returns

Any of these 6 options.

- **Single optimizer**.
- **List or Tuple** of optimizers.
- **Two lists** - The first list has multiple optimizers, and the second has multiple LR schedulers (or multiple `lr_scheduler_config`).
- **Dictionary**, with an `"optimizer"` key, and (optionally) a `"lr_scheduler"` key whose value is a single LR scheduler or `lr_scheduler_config`.
- **None** - Fit will run without any optimizer.

The `lr_scheduler_config` is a dictionary which contains the scheduler and its associated configuration. The default configuration is shown below.

```
lr_scheduler_config = {
    # REQUIRED: The scheduler instance
    "scheduler": lr_scheduler,
    # The unit of the scheduler's step size, could also be 'step'.
    # 'epoch' updates the scheduler on epoch end whereas 'step'
    # updates it after a optimizer update.
    "interval": "epoch",
    # How many epochs/steps should pass between calls to
    # `scheduler.step()`. 1 corresponds to updating the learning
    # rate after every epoch/step.
    "frequency": 1,
    # Metric to to monitor for schedulers like `ReduceLROnPlateau`
    "monitor": "val_loss",
    # If set to `True`, will enforce that the value specified 'monitor'
    # is available when the scheduler is updated, thus stopping
    # training if not found. If set to `False`, it will only produce a warning
```

(continues on next page)

(continued from previous page)

```
    "strict": True,
    # If using the `LearningRateMonitor` callback to monitor the
    # learning rate progress, this keyword can be used to specify
    # a custom logged name
    "name": None,
}
```

When there are schedulers in which the `.step()` method is conditioned on a value, such as the `torch.optim.lr_scheduler.ReduceLROnPlateau` scheduler, Lightning requires that the `lr_scheduler_config` contains the keyword `"monitor"` set to the metric name that the scheduler should be conditioned on.

Metrics can be made available to monitor by simply logging it using `self.log('metric_to_track', metric_val)` in your `LightningModule`.

Note

Some things to know:

- Lightning calls `.backward()` and `.step()` automatically in case of automatic optimization.
- If a learning rate scheduler is specified in `configure_optimizers()` with key `"interval"` (default "epoch") in the scheduler configuration, Lightning will call the scheduler's `.step()` method automatically in case of automatic optimization.
- If you use 16-bit precision (`precision=16`), Lightning will automatically handle the optimizer.
- If you use `torch.optim.LBFGS`, Lightning handles the closure function automatically for you.
- If you use multiple optimizers, you will have to switch to 'manual optimization' mode and step them yourself.
- If you need to control how often the optimizer steps, override the `optimizer_step()` hook.

class dicee.models.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call

`to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters
x(*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters
----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*,
y_idx: torch.LongTensor = None)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b**(*x shape*)
- **3**
- **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*)
→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters
x(*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.**IdentityClass**(*args=None*)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call to(), etc.

> **Note**
>
> As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

__call__(*x*)

static forward(*x*)

class dicee.models.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
```

(continues on next page)

(continued from previous page)

```
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters
x (*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters
----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*, *y_idx: torch.LongTensor = None*)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b** (*x shape*)
- **3**

- **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*) → Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters
x (*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.**DistMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575

name = 'DistMult'

k_vs_all_score(*emb_h: torch.FloatTensor*, *emb_r: torch.FloatTensor*, *emb_E: torch.FloatTensor*)

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

forward_k_vs_all(*x: torch.LongTensor*)

forward_k_vs_sample(*x: torch.LongTensor*, *target_entity_idx: torch.LongTensor*)

score(*h*, *r*, *t*)

class dicee.models.**TransE**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Translating Embeddings for Modeling Multi-relational Data https://proceedings.neurips.cc/paper/2013/file/1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf

name = 'TransE'

margin = 4

score(*head_ent_emb*, *rel_ent_emb*, *tail_ent_emb*)

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

class dicee.models.**Shallom**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)

name = 'Shallom'

shallom_width

shallom

get_embeddings() → Tuple[numpy.ndarray, None]

forward_k_vs_all(*x*) → torch.FloatTensor

forward_triples(*x*) → torch.FloatTensor

Parameters
x

Returns

class dicee.models.**Pyke**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

A Physical Embedding Model for Knowledge Graphs

name = 'Pyke'

dist_func

margin = 1.0

forward_triples(*x: torch.LongTensor*)

Parameters
x

class dicee.models.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables
training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all (*x: torch.LongTensor*)

Parameters

x (*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters

----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*, *y_idx: torch.LongTensor = None*)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters

x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b**(*x shape*)
- **3**
- **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*)
→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters

x(*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.**ConEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional ComplEx Knowledge Graph Embeddings

name = 'ConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution(*C_1: Tuple[torch.Tensor, torch.Tensor]*, *C_2: Tuple[torch.Tensor, torch.Tensor]*) → torch.FloatTensor

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameters

x

forward_k_vs_sample(*x: torch.Tensor*, *target_entity_idx: torch.Tensor*)

class dicee.models.**AConEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional ComplEx Knowledge Graph Embeddings

name = 'AConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution(*C_1: Tuple[torch.Tensor, torch.Tensor]*, *C_2: Tuple[torch.Tensor, torch.Tensor]*) → torch.FloatTensor

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameters

x

forward_k_vs_sample(*x: torch.Tensor*, *target_entity_idx: torch.Tensor*)

class dicee.models.**ComplEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ComplEx'

static score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

static k_vs_all_score(*emb_h: torch.FloatTensor*, *emb_r: torch.FloatTensor*, *emb_E: torch.FloatTensor*)

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

forward_k_vs_all(*x: torch.LongTensor*) → torch.FloatTensor

dicee.models.**quaternion_mul**(*, *Q_1*, *Q_2*)
→ Tuple[torch.Tensor, torch.Tensor, torch.Tensor, torch.Tensor]

Perform quaternion multiplication :param Q_1: :param Q_2: :return:

class dicee.models.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters
x (*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters
----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*, *y_idx: torch.LongTensor = None*)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b** (*x shape*)
- **3**
- **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*)
→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters
x (*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.**IdentityClass**(*args=None*)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call to(), etc.

Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables
training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

__call__(*x*)

static forward(*x*)

dicee.models.**quaternion_mul_with_unit_norm**(**, Q_1, Q_2*)

class dicee.models.**QMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'QMult'

explicit = True

quaternion_multiplication_followed_by_inner_product(*h*, *r*, *t*)

Parameters

- **h** – shape: (**batch_dims*, dim) The head representations.
- **r** – shape: (**batch_dims*, dim) The head representations.
- **t** – shape: (**batch_dims*, dim) The tail representations.

Returns

Triple scores.

static quaternion_normalizer(*x: torch.FloatTensor*) → torch.FloatTensor

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a + bi + cj + dk| = \sqrt{a^2 + b^2 + c^2 + d^2}$$

L2 norm of quaternion vector:

$$\|x\|^2 = \sum_{i=1}^{d} |x_i|^2 = \sum_{i=1}^{d} (x_i.re^2 + x_i.im_1^2 + x_i.im_2^2 + x_i.im_3^2)$$

Parameters
x – The vector.

Returns
The normalized vector.

score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

k_vs_all_score(*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

Parameters

- **bpe_head_ent_emb**
- **bpe_rel_ent_emb**
- **E**

forward_k_vs_all(*x*)

Parameters
x

forward_k_vs_sample(*x*, *target_entity_idx*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.**ConvQ**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional Quaternion Knowledge Graph Embeddings

name = 'ConvQ'

entity_embeddings

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution(*Q_1*, *Q_2*)

forward_triples(*indexed_triple: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.models.**AConvQ**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional Quaternion Knowledge Graph Embeddings

name = 'AConvQ'

entity_embeddings

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution(*Q_1*, *Q_2*)

forward_triples(*indexed_triple: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.models.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
```

(continues on next page)

(continued from previous page)

```
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters
x (*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters
----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*, *y_idx: torch.LongTensor = None*)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b** (*x shape*)
- **3**

• **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*) → Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters
x (*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.**IdentityClass**(*args=None*)

Bases: torch.nn.Module

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call to(), etc.

Note

As per the example above, an __init__() call to the parent class must be made before assignment on the child.

Variables
training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

__call__(*x*)

static forward(*x*)

dicee.models.**octonion_mul**(*, *O_1*, *O_2*)

dicee.models.**octonion_mul_norm**(*, *O_1*, *O_2*)

class dicee.models.**OMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'OMult'

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

k_vs_all_score(*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

forward_k_vs_all(*x*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.models.**ConvO**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F
```

(continues on next page)

(continued from previous page)

```
class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

residual_convolution(*O_1*, *O_2*)

forward_triples(*x: torch.Tensor*) → torch.Tensor

Parameters

x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.models.**AConvO**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional Octonion Knowledge Graph Embeddings

name = 'AConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

residual_convolution(*O_1*, *O_2*)

forward_triples(*x: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.models.**Keci**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'Keci'

p

q

r

requires_grad_for_interactions = True

compute_sigma_pp(*hp*, *rp*)

Compute sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):
results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq(*hq*, *rq*)

Compute sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):
results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_pq(*, *hp*, *hq*, *rp*, *rq*)

sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

apply_coefficients (*h0*, *hp*, *hq*, *r0*, *rp*, *rq*)

Multiplying a base vector with its scalar coefficient

clifford_multiplication (*h0*, *hp*, *hq*, *r0*, *rp*, *rq*)

Compute our CL multiplication

h = h_0 + sum_{i=1}^p h_i e_i + sum_{j=p+1}^{p+q} h_j e_j r = r_0 + sum_{i=1}^p r_i e_i + sum_{j=p+1}^{p+q} r_j e_j

ei ^2 = +1 for i =< i =< p ej ^2 = -1 for p < j =< p+q ei ej = -eje1 for i

eq j

h r = sigma_0 + sigma_p + sigma_q + sigma_{pp} + sigma_{q}+ sigma_{pq} where

(1) sigma_0 = h_0 r_0 + sum_{i=1}^p (h_0 r_i) e_i - sum_{j=p+1}^{p+q} (h_j r_j) e_j

(2) sigma_p = sum_{i=1}^p (h_0 r_i + h_i r_0) e_i

(3) sigma_q = sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j

(4) sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k

(5) sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k

(6) sigma_{pq} = sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j

construct_cl_multivector (*x: torch.FloatTensor*, *r: int*, *p: int*, *q: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors Cl_{p,q}(mathbb{R}^d)

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor with (n,r) shape*)
- **ap** (*torch.FloatTensor with (n,r,p) shape*)
- **aq** (*torch.FloatTensor with (n,r,q) shape*)

forward_k_vs_with_explicit (*x: torch.Tensor*)

k_vs_all_score (*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations mathbb{R}^d .

(2) Construct head entity and relation embeddings according to Cl_{p,q}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter ——— x: torch.LongTensor with (n,2) shape :rtype: torch.FloatTensor with (n, |E|) shape

forward_k_vs_sample(*x: torch.LongTensor*, *target_entity_idx: torch.LongTensor*)
→ torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations mathbb{R}^d .

(2) Construct head entity and relation embeddings according to Cl_{p,q}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

Parameter

x: torch.LongTensor with (n,2) shape

rtype
torch.FloatTensor with (n, |E|) shape

score(*h*, *r*, *t*)

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,3) shape

rtype
torch.FloatTensor with (n) shape

class dicee.models.**KeciBase**(*args*)

Bases: *Keci*

Without learning dimension scaling

name = 'KeciBase'

requires_grad_for_interactions = False

class dicee.models.**CMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Cl_(0,0) => Real Numbers

Cl_(0,1) =>
A multivector mathbf{a} = a_0 + a_1 e_1 A multivector mathbf{b} = b_0 + b_1 e_1

multiplication is isomorphic to the product of two complex numbers

mathbf{a} imes mathbf{b} = a_0 b_0 + a_0b_1 e1 + a_1 b_1 e_1 e_1
= (a_0 b_0 - a_1 b_1) + (a_0 b_1 + a_1 b_0) e_1

Cl_(2,0) =>
A multivector mathbf{a} = a_0 + a_1 e_1 + a_2 e_2 + a_{12} e_1 e_2 A multivector mathbf{b} = b_0 + b_1 e_1 + b_2 e_2 + b_{12} e_1 e_2

mathbf{a} imes mathbf{b} = a_0b_0 + a_0b_1 e_1 + a_0b_2e_2 + a_0 b_12 e_1 e_2

- a_1 b_0 e_1 + a_1b_1 e_1_e1 ..

Cl_(0,2) => Quaternions

name = 'CMult'

entity_embeddings

relation_embeddings

p

q

clifford_mul (*x: torch.FloatTensor*, *y: torch.FloatTensor*, *p: int*, *q: int*) → tuple

Clifford multiplication Cl_{p,q} (mathbb{R})

ei ^2 = +1 for i =< i =< p ej ^2 = -1 for p < j =< p+q ei ej = -eje1 for i

eq j

x: torch.FloatTensor with (n,d) shape

y: torch.FloatTensor with (n,d) shape

p: a non-negative integer p>= 0 q: a non-negative integer q>= 0

score (*head_ent_emb*, *rel_ent_emb*, *tail_ent_emb*)

forward_triples (*x: torch.LongTensor*) → torch.FloatTensor

Compute batch triple scores

Parameter

x: torch.LongTensor with shape n by 3

rtype
torch.LongTensor with shape n

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Compute batch KvsAll triple scores

Parameter

x: torch.LongTensor with shape n by 3

rtype
torch.LongTensor with shape n

class dicee.models.**DeCaL**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

`training` (*`bool`*) – Boolean represents whether this module is in training or evaluation mode.

`name = 'DeCaL'`

`entity_embeddings`

`relation_embeddings`

`p`

`q`

`r`

`re`

`forward_triples`(*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype

torch.FloatTensor with (n) shape

`cl_pqr`(*a: torch.tensor*) → torch.tensor

Input: tensor(batch_size, emb_dim) —> output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q +r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

compute_sigmas_single (*list_h_emb*, *list_r_emb*, *list_t_emb*)

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^{p} h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^{q} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t$$

and return:

$$sigma_0 t = \sigma_0 \cdot t_0 = s0 + s1 - s2 s3, s4 and s5$$

compute_sigmas_multivect (*list_h_emb*, *list_r_emb*)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^{p} (h_i r_{i'} - h_{i'} r_i)(models the interactions between e_i and e_i' for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'}$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i)(interactions n between e_i and e_j for 1 <= i <= p and p+1 <= j <= p+q) \sigma_p r = \sum_{i=}$$

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations

(2) Construct head entity and relation embeddings according to Cl_{p,q, r}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter ——— x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, |E|) shape

apply_coefficients (*h0*, *hp*, *hq*, *hk*, *r0*, *rp*, *rq*, *rk*)

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (*x: torch.FloatTensor*, *re: int*, *p: int*, *q: int*, *r: int*) → tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors Cl_{p,q,r}(mathbb{R}^d)

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor*)
- **ap** (*torch.FloatTensor*)
- **aq** (*torch.FloatTensor*)
- **ar** (*torch.FloatTensor*)

compute_sigma_pp(*hp*, *rp*)

Compute .. math:

```
\sigma_{p,p}^* = \sum_{i=1}^{p-1}\sum_{i'=i+1}^{p}(x_iy_{i'}-x_{i'}y_i)
```

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):
results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq(*hq*, *rq*)

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) Eq.16$$

sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):
results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_rr(*hk*, *rk*)

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^{p} (x_k y_{k'} - x_{k'} y_k)$$

compute_sigma_pq(*, *hp*, *hq*, *rp*, *rq*)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

compute_sigma_pr(*, *hp*, *hk*, *rp*, *rk*)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

compute_sigma_qr(*, *hq*, *hk*, *rq*, *rk*)

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

class dicee.models.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters
x(*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters
----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*,
y_idx: torch.LongTensor = None)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b**(*x shape*)
- **3**
- **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*)
→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters
x(*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.**PykeenKGE**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

A class for using knowledge graph embedding models implemented in Pykeen

Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Pykeen_HolE:

model_kwargs

name

model

loss_history = []

args

entity_embeddings = None

relation_embeddings = None

forward_k_vs_all(*x: torch.LongTensor*)

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r = self.get_head_relation_representation(x) # (2) Reshape (1). if self.last_dim > 0:

h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim)

(3) Reshape all entities. if self.last_dim > 0:

t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)

else:

t = self.entity_embeddings.weight

(4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r, all_entities=t, slice_size=1)

forward_triples(*x: torch.LongTensor*) → torch.FloatTensor

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t = self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:

h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)

(3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice_size=None, slice_dim=0)

abstract forward_k_vs_sample(*x: torch.LongTensor*, *target_entity_idx*)

class dicee.models.**BaseKGE**(*args: dict*)

Bases: *BaseKGELightning*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
```

(continues on next page)

(continued from previous page)

```
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters
x (*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters
----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*, *y_idx: torch.LongTensor = None*)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b** (*x shape*)
- **3**

• **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*) → Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters
x (*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

class dicee.models.**FMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Learning Knowledge Neural Graphs

name = 'FMult'

entity_embeddings

relation_embeddings

k

num_sample = 50

gamma

roots

weights

compute_func(*weights: torch.FloatTensor*, *x*) → torch.FloatTensor

chain_func(*weights*, *x: torch.FloatTensor*)

forward_triples(*idx_triple: torch.Tensor*) → torch.Tensor

Parameters
x

class dicee.models.**GFMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Learning Knowledge Neural Graphs

name = 'GFMult'

entity_embeddings

relation_embeddings

k

num_sample = 250

roots

weights

compute_func(*weights: torch.FloatTensor*, *x*) → torch.FloatTensor

chain_func(*weights*, *x: torch.FloatTensor*)

forward_triples(*idx_triple: torch.Tensor*) → torch.Tensor

Parameters
x

class dicee.models.**FMult2**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Learning Knowledge Neural Graphs

name = 'FMult2'

n_layers = 3

tuned_embedding_dim = False

k

n = 50

score_func = 'compositional'

discrete_points

entity_embeddings

relation_embeddings

build_func(*Vec*)

build_chain_funcs(*list_Vec*)

compute_func(*W*, *b*, *x*) → torch.FloatTensor

function(*list_W*, *list_b*)

trapezoid(*list_W*, *list_b*)

forward_triples(*idx_triple: torch.Tensor*) → torch.Tensor

Parameters
x

class dicee.models.**LFMult1**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding with trigonometric functions. We represent all entities and relations in the complex number space as: f(x) = sum_{k=0}^{k=d-1}wk e^{kix}. and use the three differents scoring function as in the paper to evaluate the score

name = 'LFMult1'

entity_embeddings

relation_embeddings

forward_triples(*idx_triple*)

Parameters
x

tri_score(*h*, *r*, *t*)

vtp_score(*h*, *r*, *t*)

class dicee.models.**LFMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: f(x) = sum_{i=0}^{d-1} a_k x^{i%d} and use the three differents scoring function as in the paper to evaluate the score. We also consider combining with Neural Networks.

name = 'LFMult'

entity_embeddings

relation_embeddings

degree

m

x_values

forward_triples(*idx_triple*)

Parameters
x

construct_multi_coeff(*x*)

poly_NN(*x*, *coefh*, *coefr*, *coeft*)

Constructing a 2 layers NN to represent the embeddings. h = sigma(wh^T x + bh), r = sigma(wr^T x + br), t = sigma(wt^T x + bt)

linear(*x*, *w*, *b*)

scalar_batch_NN(*a*, *b*, *c*)

element wise multiplication between a,b and c: Inputs : a, b, c ====> torch.tensor of size batch_size x m x d Output : a tensor of size batch_size x d

tri_score(*coeff_h*, *coeff_r*, *coeff_t*)

this part implement the trilinear scoring techniques:

score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k = 0}^{d-1} dfrac{a_i*b_j*c_k}{1+(i+j+k)%d}

1. generate the range for i,j and k from [0 d-1]
2. perform dfrac{a_i*b_j*c_k}{1+(i+j+k)%d} in parallel for every batch
3. take the sum over each batch

vtp_score(*h*, *r*, *t*)

this part implement the vector triple product scoring techniques:

score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k = 0}^{d-1} dfrac{a_i*c_j*b_k - b_i*c_j*a_k}{(1+(i+j)%d)(1+k)}

1. generate the range for i,j and k from [0 d-1]
2. Compute the first and second terms of the sum
3. Multiply with then denominator and take the sum

4. take the sum over each batch

comp_func(*h*, *r*, *t*)

this part implement the function composition scoring techniques: i.e. score = <hor, t>

polynomial(*coeff*, *x*, *degree*)

This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer [0,1,…d] and return a vector tensor (coeff[0][0] + coeff[0][1]x +…+ coeff[0][d]x^d,

coeff[1][0] + coeff[1][1]x +…+ coeff[1][d]x^d)

pop(*coeff*, *x*, *degree*)

This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,…d]

and return a tensor (coeff[0][0] + coeff[0][1]x +…+ coeff[0][d]x^d,

coeff[1][0] + coeff[1][1]x +…+ coeff[1][d]x^d)

class dicee.models.**DualE**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent

kvsall_score(*e_1_h*, *e_2_h*, *e_3_h*, *e_4_h*, *e_5_h*, *e_6_h*, *e_7_h*, *e_8_h*, *e_1_t*, *e_2_t*, *e_3_t*, *e_4_t*, *e_5_t*, *e_6_t*, *e_7_t*, *e_8_t*, *r_1*, *r_2*, *r_3*, *r_4*, *r_5*, *r_6*, *r_7*, *r_8*) → torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_triples(*idx_triple: torch.tensor*) → torch.tensor

Negative Sampling forward pass:

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_k_vs_all(*x*)

KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

T(*x: torch.tensor*) → torch.tensor

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

dicee.read_preprocess_save_load_kg

Submodules

dicee.read_preprocess_save_load_kg.preprocess

Classes

PreprocessKG	Preprocess the data in memory

Module Contents

class dicee.read_preprocess_save_load_kg.preprocess.**PreprocessKG**(*kg*)

Preprocess the data in memory

kg

start() → None

Preprocess train, valid and test datasets stored in knowledge graph instance

Parameter

rtype
None

preprocess_with_byte_pair_encoding()

preprocess_with_byte_pair_encoding_with_padding() → None

preprocess_with_pandas() → None

Preprocess train, valid and test datasets stored in knowledge graph instance with pandas

(1) Add recipriocal or noisy triples

(2) Construct vocabulary

(3) Index datasets

Parameter

rtype
None

preprocess_with_polars() → None

sequential_vocabulary_construction() → None

(1) Read input data into memory

(2) Remove triples with a condition

(3) **Serialize vocabularies in a pandas dataframe where**
=> the index is integer and => a single column is string (e.g. URI)

remove_triples_from_train_with_condition()

dicee.read_preprocess_save_load_kg.read_from_disk

Classes

ReadFromDisk	Read the data from disk into memory

Module Contents

class dicee.read_preprocess_save_load_kg.read_from_disk.**ReadFromDisk**(*kg*)

Read the data from disk into memory

kg

start() → None

Read a knowledge graph from disk into memory

Data will be available at the train_set, test_set, valid_set attributes.

Parameter

None

rtype
None

add_noisy_triples_into_training()

dicee.read_preprocess_save_load_kg.save_load_disk

Classes

LoadSaveToDisk

Module Contents

class dicee.read_preprocess_save_load_kg.save_load_disk.**LoadSaveToDisk**(*kg*)

kg

save()

load()

dicee.read_preprocess_save_load_kg.util

Functions

apply_reciprical_or_noise(add_reciprical, eval_model)	
timeit(func)	
read_with_polars(→ polars.DataFrame)	Load and Preprocess via Polars
read_with_pandas(data_path[, read_only_few, ...])	
read_from_disk(data_path[, read_only_few, ...])	
read_from_triple_store([endpoint])	Read triples from triple store into pandas dataframe
get_er_vocab(data[, file_path])	
get_re_vocab(data[, file_path])	
get_ee_vocab(data[, file_path])	
create_constraints(triples[, file_path])	
load_with_pandas(→ None)	Deserialize data
save_numpy_ndarray(*, data, file_path)	
load_numpy_ndarray(*, file_path)	
save_pickle(*, data[, file_path])	
load_pickle(*[, file_path])	
create_recipriocal_triples(x)	Add inverse triples into dask dataframe
index_triples_with_pandas(→ pandas.core.frame.DataFrame)	
dataset_sanity_checking(→ None)	

Module Contents

dicee.read_preprocess_save_load_kg.util.**apply_reciprical_or_noise**(*add_reciprical: bool*, *eval_model: str*, *df: object = None*, *info: str = None*)

(1) Add reciprocal triples (2) Add noisy triples

dicee.read_preprocess_save_load_kg.util.**timeit**(*func*)

dicee.read_preprocess_save_load_kg.util.**read_with_polars**(*data_path*, *read_only_few: int = None*, *sample_triples_ratio: float = None*) → polars.DataFrame

Load and Preprocess via Polars

dicee.read_preprocess_save_load_kg.util.**read_with_pandas**(*data_path*, *read_only_few: int = None*, *sample_triples_ratio: float = None*)

dicee.read_preprocess_save_load_kg.util.**read_from_disk**(*data_path: str*, *read_only_few: int = None*, *sample_triples_ratio: float = None*, *backend=None*)

dicee.read_preprocess_save_load_kg.util.**read_from_triple_store**(*endpoint: str = None*)

Read triples from triple store into pandas dataframe

dicee.read_preprocess_save_load_kg.util.**get_er_vocab**(*data*, *file_path: str = None*)

dicee.read_preprocess_save_load_kg.util.**get_re_vocab**(*data*, *file_path: str = None*)

dicee.read_preprocess_save_load_kg.util.**get_ee_vocab**(*data*, *file_path: str = None*)

dicee.read_preprocess_save_load_kg.util.**create_constraints**(*triples*, *file_path: str = None*)

(1) Extract domains and ranges of relations

(2) Store a mapping from relations to entities that are outside of the domain and range. Crete constrainted entities based on the range of relations :param triples: :return: Tuple[dict, dict]

dicee.read_preprocess_save_load_kg.util.**load_with_pandas**(*self*) → None

Deserialize data

dicee.read_preprocess_save_load_kg.util.**save_numpy_ndarray**(*, *data: numpy.ndarray*, *file_path: str*)

dicee.read_preprocess_save_load_kg.util.**load_numpy_ndarray**(*, *file_path: str*)

dicee.read_preprocess_save_load_kg.util.**save_pickle**(*, *data: object*, *file_path=str*)

dicee.read_preprocess_save_load_kg.util.**load_pickle**(*, *file_path=str*)

dicee.read_preprocess_save_load_kg.util.**create_recipriocal_triples**(*x*)

Add inverse triples into dask dataframe :param x: :return:

dicee.read_preprocess_save_load_kg.util.**index_triples_with_pandas**(*train_set*, *entity_to_idx: dict*, *relation_to_idx: dict*) → pandas.core.frame.DataFrame

Parameters

- **train_set** – pandas dataframe
- **entity_to_idx** – a mapping from str to integer index
- **relation_to_idx** – a mapping from str to integer index
- **num_core** – number of cores to be used

Returns

indexed triples, i.e., pandas dataframe

dicee.read_preprocess_save_load_kg.util.**dataset_sanity_checking**(*train_set: numpy.ndarray*, *num_entities: int*, *num_relations: int*) → None

Parameters

- **train_set**
- **num_entities**
- **num_relations**

Returns

Classes

PreprocessKG	Preprocess the data in memory
LoadSaveToDisk	
ReadFromDisk	Read the data from disk into memory

Package Contents

class dicee.read_preprocess_save_load_kg.**PreprocessKG**(*kg*)

Preprocess the data in memory

kg

start() → None

Preprocess train, valid and test datasets stored in knowledge graph instance

Parameter

rtype
None

preprocess_with_byte_pair_encoding()

preprocess_with_byte_pair_encoding_with_padding() → None

preprocess_with_pandas() → None

Preprocess train, valid and test datasets stored in knowledge graph instance with pandas

(1) Add recipriocal or noisy triples

(2) Construct vocabulary

(3) Index datasets

Parameter

rtype
None

preprocess_with_polars() → None

sequential_vocabulary_construction() → None

(1) Read input data into memory

(2) Remove triples with a condition

(3) **Serialize vocabularies in a pandas dataframe where**
=> the index is integer and => a single column is string (e.g. URI)

remove_triples_from_train_with_condition()

class dicee.read_preprocess_save_load_kg.**LoadSaveToDisk**(*kg*)

kg

save()

load()

class dicee.read_preprocess_save_load_kg.**ReadFromDisk**(*kg*)

Read the data from disk into memory

kg

start() → None

Read a knowledge graph from disk into memory

Data will be available at the train_set, test_set, valid_set attributes.

Parameter

None

rtype
None

add_noisy_triples_into_training()

dicee.scripts

Submodules

dicee.scripts.index

Functions

get_default_arguments()
main()

Module Contents

dicee.scripts.index.**get_default_arguments**()

dicee.scripts.index.**main**()

dicee.scripts.run

Functions

get_default_arguments([description])	Extends pytorch_lightning Trainer's arguments with ours
main()	

Module Contents

dicee.scripts.run.**get_default_arguments**(*description=None*)

Extends pytorch_lightning Trainer's arguments with ours

dicee.scripts.run.**main**()

dicee.scripts.serve

Attributes

app
neural_searcher

Classes

NeuralSearcher

Functions

get_default_arguments()
root()
search_embeddings(q)
retrieve_embeddings(q)
main()

Module Contents

dicee.scripts.serve.**app**

dicee.scripts.serve.**neural_searcher = None**

dicee.scripts.serve.**get_default_arguments**()

async dicee.scripts.serve.**root**()

async dicee.scripts.serve.**search_embeddings**(*q: str*)

async dicee.scripts.serve.**retrieve_embeddings**(*q: str*)

class dicee.scripts.serve.**NeuralSearcher**(*args*)

collection_name

model

qdrant_client

get(*entity: str*)

search(*entity: str*)

dicee.scripts.serve.**main**()

dicee.trainer

Submodules

dicee.trainer.dice_trainer

Classes

DICE_Trainer	DICE_Trainer implement

Functions

initialize_trainer(args, callbacks)	
get_callbacks(args)	

Module Contents

dicee.trainer.dice_trainer.**initialize_trainer**(*args*, *callbacks*)

dicee.trainer.dice_trainer.**get_callbacks**(*args*)

class dicee.trainer.dice_trainer.**DICE_Trainer**(*args*, *is_continual_training*, *storage_path*, *evaluator=None*)

DICE_Trainer implement

1- Pytorch Lightning trainer (https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html) 2- Multi-GPU Trainer(https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.html) 3- CPU Trainer

args

is_continual_training:bool

storage_path:str

evaluator:

report:dict

report

args

trainer = None

is_continual_training

storage_path

evaluator

form_of_labelling = None

continual_start()

(1) Initialize training.

(2) Load model

(3) Load trainer (3) Fit model

Parameter

returns

- *model*
- **form_of_labelling** (*str*)

initialize_trainer(*callbacks: List*) → lightning.Trainer

Initialize Trainer from input arguments

initialize_or_load_model()

initialize_dataloader(*dataset: torch.utils.data.Dataset*) → torch.utils.data.DataLoader

initialize_dataset(*dataset: dicee.knowledge_graph.KG*, *form_of_labelling*)
→ torch.utils.data.Dataset

start(*knowledge_graph: dicee.knowledge_graph.KG*) → Tuple[*dicee.models.base_model.BaseKGE*, str]

Train selected model via the selected training strategy

k_fold_cross_validation(*dataset*) → Tuple[*dicee.models.base_model.BaseKGE*, str]

Perform K-fold Cross-Validation

1. Obtain K train and test splits.
2. **For each split,**
   2.1 initialize trainer and model 2.2. Train model with configuration provided in args. 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.
3. Report the mean and average MRR .

Parameters

- **self**
- **dataset**

Returns
model

dicee.trainer.torch_trainer

Classes

TorchTrainer	TorchTrainer for using single GPU or multi CPUs on a single node

Module Contents

class dicee.trainer.torch_trainer.**TorchTrainer**(*args*, *callbacks*)

Bases: *dicee.abstracts.AbstractTrainer*

TorchTrainer for using single GPU or multi CPUs on a single node

Arguments

callbacks: list of Abstract callback instances

loss_function = None

optimizer = None

model = None

train_dataloaders = None

training_step = None

process

fit (**args*, *train_dataloaders*, ***kwargs*) → None

Training starts

Arguments

kwargs:Tuple
empty dictionary

Return type
batch loss (float)

forward_backward_update (*x_batch: torch.Tensor*, *y_batch: torch.Tensor*) → torch.Tensor

Compute forward, loss, backward, and parameter update

Arguments

Return type
batch loss (float)

extract_input_outputs_set_device (*batch: list*) → Tuple

Construct inputs and outputs from a batch of inputs with outputs From a batch of inputs and put

Arguments

Return type
(tuple) mini-batch on select device

dicee.trainer.torch_trainer_ddp

Classes

TorchDDPTrainer	A Trainer based on torch.nn.parallel.DistributedDataParallel
NodeTrainer	
DDPTrainer	

Functions

print_peak_memory(prefix, device)	

Module Contents

dicee.trainer.torch_trainer_ddp.**print_peak_memory**(*prefix*, *device*)

class dicee.trainer.torch_trainer_ddp.**TorchDDPTrainer**(*args*, *callbacks*)

Bases: *dicee.abstracts.AbstractTrainer*

A Trainer based on torch.nn.parallel.DistributedDataParallel

Arguments

entity_idxs
mapping.

relation_idxs
mapping.

form
?

store
?

label_smoothing_rate
Using hard targets (0,1) drives weights to infinity. An outlier produces enormous gradients.

Return type
torch.utils.data.Dataset

fit(**args*, ***kwargs*)

Train model

class dicee.trainer.torch_trainer_ddp.**NodeTrainer**(*trainer*, *model: torch.nn.Module*, *train_dataset_loader: torch.utils.data.DataLoader*, *optimizer: torch.optim.Optimizer*, *callbacks*, *num_epochs: int*)

trainer

local_rank

global_rank

model

train_dataset_loader

loss_func

optimizer

callbacks

num_epochs

loss_history = []

extract_input_outputs(*z: list*)

train()

Training loop for DDP

class dicee.trainer.torch_trainer_ddp.**DDPTrainer**(*model: torch.nn.Module*, *train_dataset_loader: torch.utils.data.DataLoader*, *optimizer: torch.optim.Optimizer*, *gpu_id: int*, *callbacks*, *num_epochs*)

gpu_id

model

train_dataset_loader

loss_func

optimizer

callbacks

num_epochs

loss_history = []

extract_input_outputs(*z: list*)

train()

Classes

DICE_Trainer	DICE_Trainer implement

Package Contents

class dicee.trainer.**DICE_Trainer**(*args*, *is_continual_training*, *storage_path*, *evaluator=None*)

DICE_Trainer implement

1- Pytorch Lightning trainer (https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html) 2- Multi-GPU Trainer(https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.html) 3- CPU Trainer

args

is_continual_training:bool

storage_path:str

evaluator:

report:dict

report

args

trainer = None

is_continual_training

storage_path

evaluator

form_of_labelling = None

continual_start()

(1) Initialize training.

(2) Load model

(3) Load trainer (3) Fit model

Parameter

returns

- *model*
- **form_of_labelling** (*str*)

initialize_trainer(*callbacks: List*) → lightning.Trainer

Initialize Trainer from input arguments

initialize_or_load_model()

initialize_dataloader(*dataset: torch.utils.data.Dataset*) → torch.utils.data.DataLoader

initialize_dataset(*dataset: dicee.knowledge_graph.KG*, *form_of_labelling*)
→ torch.utils.data.Dataset

start(*knowledge_graph: dicee.knowledge_graph.KG*) → Tuple[*dicee.models.base_model.BaseKGE*, str]

Train selected model via the selected training strategy

k_fold_cross_validation(*dataset*) → Tuple[*dicee.models.base_model.BaseKGE*, str]

Perform K-fold Cross-Validation

1. Obtain K train and test splits.
2. **For each split,**
   2.1 initialize trainer and model 2.2. Train model with configuration provided in args. 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.
3. Report the mean and average MRR .

Parameters

- **self**
- **dataset**

Returns

model

14.2 Submodules

dicee.abstracts

Classes

AbstractTrainer	Abstract class for Trainer class for knowledge graph embedding models
BaseInteractiveKGE	Abstract/base class for using knowledge graph embedding models interactively.
AbstractCallback	Abstract class for Callback class for knowledge graph embedding models
AbstractPPECallback	Abstract class for Callback class for knowledge graph embedding models

Module Contents

class dicee.abstracts.**AbstractTrainer**(*args*, *callbacks*)

Abstract class for Trainer class for knowledge graph embedding models

Parameter

args
[str] ?

callbacks: list
?

attributes

callbacks

is_global_zero = True

strategy = None

on_fit_start(**args*, ***kwargs*)

A function to call callbacks before the training starts.

Parameter

args

kwargs

rtype
None

on_fit_end(**args*, ***kwargs*)

A function to call callbacks at the ned of the training.

Parameter

args

kwargs

rtype
None

on_train_epoch_end(**args*, ***kwargs*)

A function to call callbacks at the end of an epoch.

Parameter

args

kwargs

rtype
None

on_train_batch_end(**args*, ***kwargs*)

A function to call callbacks at the end of each mini-batch during training.

Parameter

args

kwargs

rtype
None

static save_checkpoint(*full_path: str*, *model*) → None

A static function to save a model into disk

Parameter

full_path : str

model:

rtype
None

class dicee.abstracts.**BaseInteractiveKGE**(*path: str = None*, *url: str = None*, *construct_ensemble: bool = False*, *model_name: str = None*, *apply_semantic_constraint: bool = False*)

Abstract/base class for using knowledge graph embedding models interactively.

Parameter

path_of_pretrained_model_dir
[str] ?

construct_ensemble: boolean
?

model_name: str apply_semantic_constraint : boolean

construct_ensemble

apply_semantic_constraint

configs

get_eval_report() → dict

get_bpe_token_representation(*str_entity_or_relation: List[str] | str*)
→ List[List[int]] | List[int]

Parameters
str_entity_or_relation(*corresponds to a str or a list of strings to be tokenized via BPE and shaped.*)

Return type
A list integer(s) or a list of lists containing integer(s)

get_padded_bpe_triple_representation(*triples: List[List[str]]*) → Tuple[List, List, List]

Parameters
triples

set_model_train_mode() → None
Setting the model into training mode

Parameter

set_model_eval_mode() → None
Setting the model into eval mode

Parameter

property name

sample_entity(*n: int*) → List[str]

sample_relation(*n: int*) → List[str]

is_seen(*entity: str = None*, *relation: str = None*) → bool

save() → None

get_entity_index(*x: str*)

get_relation_index(*x: str*)

index_triple(*head_entity: List[str]*, *relation: List[str]*, *tail_entity: List[str]*)
→ Tuple[torch.LongTensor, torch.LongTensor, torch.LongTensor]

Index Triple

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

pytorch tensor of triple score

add_new_entity_embeddings(*entity_name: str = None*, *embeddings: torch.FloatTensor = None*)

get_entity_embeddings(*items: List[str]*)

Return embedding of an entity given its string representation

Parameter

items:
entities

get_relation_embeddings(*items: List[str]*)

Return embedding of a relation given its string representation

Parameter

items:
relations

construct_input_and_output(*head_entity: List[str]*, *relation: List[str]*, *tail_entity: List[str]*, *labels*)

Construct a data point :param head_entity: :param relation: :param tail_entity: :param labels: :return:

parameters()

class dicee.abstracts.**AbstractCallback**

Bases: abc.ABC, lightning.pytorch.callbacks.Callback

Abstract class for Callback class for knowledge graph embedding models

Parameter

on_init_start (**args*, ***kwargs*)

Parameter

trainer:

model:

rtype
None

on_init_end (**args*, ***kwargs*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

on_fit_start (*trainer*, *model*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

on_train_epoch_end (*trainer*, *model*)

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype
None

on_train_batch_end (**args*, ***kwargs*)

Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype
None

on_fit_end(**args*, ***kwargs*)
Call at the end of the training.

Parameter

trainer:

model:

rtype
None

class dicee.abstracts.**AbstractPPECallback**(*num_epochs*, *path*, *epoch_to_start*, *last_percent_to_consider*)
Bases: *AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

num_epochs

path

sample_counter = 0

epoch_count = 0

alphas = None

on_fit_start(*trainer*, *model*)
Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

on_fit_end(*trainer*, *model*)
Call at the end of the training.

Parameter

trainer:

model:

rtype
None

store_ensemble(*param_ensemble*) → None

dicee.analyse_experiments

This script should be moved to dicee/scripts

Classes

Experiment

Functions

get_default_arguments()
analyse(args)

Module Contents

dicee.analyse_experiments.**get_default_arguments**()

class dicee.analyse_experiments.**Experiment**

model_name = []

callbacks = []

embedding_dim = []

num_params = []

num_epochs = []

batch_size = []

lr = []

byte_pair_encoding = []

aswa = []

```
    path_dataset_folder = []
    full_storage_path = []
    pq = []
    train_mrr = []
    train_h1 = []
    train_h3 = []
    train_h10 = []
    val_mrr = []
    val_h1 = []
    val_h3 = []
    val_h10 = []
    test_mrr = []
    test_h1 = []
    test_h3 = []
    test_h10 = []
    runtime = []
    normalization = []
    scoring_technique = []
    save_experiment(x)
    to_df()
```

dicee.analyse_experiments.**analyse**(*args*)

dicee.callbacks

Classes

AccumulateEpochLossCallback	Abstract class for Callback class for knowledge graph embedding models
PrintCallback	Abstract class for Callback class for knowledge graph embedding models
KGESaveCallback	Abstract class for Callback class for knowledge graph embedding models
PseudoLabellingCallback	Abstract class for Callback class for knowledge graph embedding models
ASWA	Adaptive stochastic weight averaging
Eval	Abstract class for Callback class for knowledge graph embedding models
KronE	Abstract class for Callback class for knowledge graph embedding models
Perturb	A callback for a three-Level Perturbation

Functions

estimate_q(eps)	estimate rate of convergence q from sequence esp
compute_convergence(seq, i)	

Module Contents

class dicee.callbacks.**AccumulateEpochLossCallback**(*path: str*)

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

path

on_fit_end(*trainer*, *model*) → None

Store epoch loss

Parameter

trainer:

model:

rtype
None

class dicee.callbacks.**PrintCallback**

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

start_time

on_fit_start(*trainer*, *pl_module*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

on_fit_end(*trainer*, *pl_module*)

Call at the end of the training.

Parameter

trainer:

model:

rtype
None

on_train_batch_end(**args*, ***kwargs*)

Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype
None

on_train_epoch_end(**args*, ***kwargs*)

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype
None

class dicee.callbacks.**KGESaveCallback**(*every_x_epoch: int*, *max_epochs: int*, *path: str*)

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

every_x_epoch

max_epochs

epoch_counter = 0

path

on_train_batch_end(**args*, ***kwargs*)

Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype
None

on_fit_start(*trainer*, *pl_module*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

on_train_epoch_end(**args*, ***kwargs*)

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype
None

on_fit_end(**args*, ***kwargs*)

Call at the end of the training.

Parameter

trainer:

model:

rtype
None

on_epoch_end(*model*, *trainer*, ***kwargs*)

class dicee.callbacks.**PseudoLabellingCallback**(*data_module*, *kg*, *batch_size*)

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

data_module

kg

num_of_epochs = 0

unlabelled_size

batch_size

create_random_data()

on_epoch_end(*trainer*, *model*)

dicee.callbacks.**estimate_q**(*eps*)

estimate rate of convergence q from sequence esp

dicee.callbacks.**compute_convergence**(*seq*, *i*)

class dicee.callbacks.**ASWA**(*num_epochs*, *path*)

Bases: *dicee.abstracts.AbstractCallback*

Adaptive stochastic weight averaging ASWE keeps track of the validation performance and update s the ensemble model accordingly.

path

num_epochs

initial_eval_setting = None

epoch_count = 0

alphas = []

val_aswa

on_fit_end(*trainer*, *model*)

Call at the end of the training.

Parameter

trainer:

model:

rtype
None

static compute_mrr(*trainer*, *model*) → float

get_aswa_state_dict(*model*)

decide(*running_model_state_dict*, *ensemble_state_dict*, *val_running_model*, *mrr_updated_ensemble_model*)

Perform Hard Update, software or rejection

Parameters

- **running_model_state_dict**
- **ensemble_state_dict**
- **val_running_model**
- **mrr_updated_ensemble_model**

on_train_epoch_end(*trainer*, *model*)

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype
None

class dicee.callbacks.**Eval**(*path*, *epoch_ratio: int = None*)

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

path

reports = []

epoch_ratio

epoch_counter = 0

on_fit_start (*trainer*, *model*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

on_fit_end (*trainer*, *model*)

Call at the end of the training.

Parameter

trainer:

model:

rtype
None

on_train_epoch_end (*trainer*, *model*)

Call at the end of each epoch during training.

Parameter

trainer:

model:

rtype
None

on_train_batch_end (**args*, ***kwargs*)

Call at the end of each mini-batch during the training.

Parameter

trainer:

model:

rtype
None

class dicee.callbacks.**KronE**

Bases: *dicee.abstracts.AbstractCallback*

Abstract class for Callback class for knowledge graph embedding models

Parameter

f = None

static batch_kronecker_product(*a*, *b*)

Kronecker product of matrices a and b with leading batch dimensions. Batch dimensions are broadcast. The number of them mush :type a: torch.Tensor :type b: torch.Tensor :rtype: torch.Tensor

get_kronecker_triple_representation(*indexed_triple: torch.LongTensor*)

Get kronecker embeddings

on_fit_start(*trainer*, *model*)

Call at the beginning of the training.

Parameter

trainer:

model:

rtype
None

class dicee.callbacks.**Perturb**(*level: str = 'input'*, *ratio: float = 0.0*, *method: str = None*, *scaler: float = None*, *frequency=None*)

Bases: *dicee.abstracts.AbstractCallback*

A callback for a three-Level Perturbation

Input Perturbation: During training an input x is perturbed by randomly replacing its element. In the context of knowledge graph embedding models, x can denote a triple, a tuple of an entity and a relation, or a tuple of two entities. A perturbation means that a component of x is randomly replaced by an entity or a relation.

Parameter Perturbation:

Output Perturbation:

level

ratio

method

scaler

frequency

on_train_batch_start (*trainer*, *model*, *batch*, *batch_idx*)

Called when the train batch begins.

dicee.config

Classes

Namespace	Simple object for storing attributes.

Module Contents

class dicee.config.**Namespace**(***kwargs*)

Bases: argparse.Namespace

Simple object for storing attributes.

Implements equality by attribute names and values, and provides a simple string representation.

dataset_dir: str = None

The path of a folder containing train.txt, and/or valid.txt and/or test.txt

save_embeddings_as_csv: bool = False

Embeddings of entities and relations are stored into CSV files to facilitate easy usage.

storage_path: str = 'Experiments'

A directory named with time of execution under –storage_path that contains related data about embeddings.

path_to_store_single_run: str = None

A single directory created that contains related data about embeddings.

path_single_kg = None

Path of a file corresponding to the input knowledge graph

sparql_endpoint = None

An endpoint of a triple store.

model: str = 'Keci'

KGE model

optim: str = 'Adam'

Optimizer

embedding_dim: int = 64

Size of continuous vector representation of an entity/relation

num_epochs: int = 150

Number of pass over the training data

batch_size: int = 1024

Mini-batch size if it is None, an automatic batch finder technique applied

lr: float = 0.1

Learning rate

add_noise_rate: float = None

The ratio of added random triples into training dataset

gpus = None

Number GPUs to be used during training

callbacks

10}}

Type

Callbacks, e.g., {“PPE”

Type

{ “last_percent_to_consider”

backend: str = 'pandas'

Backend to read, process, and index input knowledge graph. pandas, polars and rdflib available

trainer: str = 'torchCPUTrainer'

Trainer for knowledge graph embedding model

scoring_technique: str = 'KvsAll'

Scoring technique for knowledge graph embedding models

neg_ratio: int = 0

Negative ratio for a true triple in NegSample training_technique

weight_decay: float = 0.0

Weight decay for all trainable params

normalization: str = 'None'

LayerNorm, BatchNorm1d, or None

init_param: str = None

xavier_normal or None

gradient_accumulation_steps: int = 0

Not tested e

num_folds_for_cv: int = 0

Number of folds for CV

eval_model: str = 'train_val_test'

[“None”, “train”, “train_val”, “train_val_test”, “test”]

Type

Evaluate trained model choices

save_model_at_every_epoch: int = None

Not tested

label_smoothing_rate: float = 0.0

num_core: int = 0

Number of CPUs to be used in the mini-batch loading process

random_seed: int = 0

Random Seed

sample_triples_ratio: float = None

Read some triples that are uniformly at random sampled. Ratio being between 0 and 1

read_only_few: int = None

Read only first few triples

pykeen_model_kwargs

Additional keyword arguments for pykeen models

kernel_size: int = 3

Size of a square kernel in a convolution operation

num_of_output_channels: int = 32

Number of slices in the generated feature map by convolution.

p: int = 0

P parameter of Clifford Embeddings

q: int = 1

Q parameter of Clifford Embeddings

input_dropout_rate: float = 0.0

Dropout rate on embeddings of input triples

hidden_dropout_rate: float = 0.0

Dropout rate on hidden representations of input triples

feature_map_dropout_rate: float = 0.0

Dropout rate on a feature map generated by a convolution operation

byte_pair_encoding: bool = False

Byte pair encoding

Type
WIP

adaptive_swa: bool = False

Adaptive stochastic weight averaging

swa: bool = False

Stochastic weight averaging

block_size: int = None

block size of LLM

continual_learning = None

Path of a pretrained model size of LLM

__iter__()

dicee.dataset_classes

Classes

BPE_NegativeSamplingDataset	An abstract class representing a Dataset.
MultiLabelDataset	An abstract class representing a Dataset.
MultiClassClassificationDataset	Dataset for the 1vsALL training strategy
OnevsAllDataset	Dataset for the 1vsALL training strategy
KvsAll	Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.
AllvsAll	Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.
KvsSampleDataset	KvsSample a Dataset:
NegSampleDataset	An abstract class representing a Dataset.
TriplePredictionDataset	Triple Dataset
CVDataModule	Create a Dataset for cross validation

Functions

reload_dataset(path, form_of_labelling, ...)	Reload the files from disk to construct the Pytorch dataset
construct_dataset(→ torch.utils.data.Dataset)	

Module Contents

dicee.dataset_classes.**reload_dataset**(*path: str*, *form_of_labelling*, *scoring_technique*, *neg_ratio*, *label_smoothing_rate*)

Reload the files from disk to construct the Pytorch dataset

dicee.dataset_classes.**construct_dataset**(*, *train_set: numpy.ndarray | list*, *valid_set=None*, *test_set=None*, *ordered_bpe_entities=None*, *train_target_indices=None*, *target_dim: int = None*, *entity_to_idx: dict*, *relation_to_idx: dict*, *form_of_labelling: str*, *scoring_technique: str*, *neg_ratio: int*, *label_smoothing_rate: float*, *byte_pair_encoding=None*, *block_size: int = None*) → torch.utils.data.Dataset

class dicee.dataset_classes.**BPE_NegativeSamplingDataset**(*train_set: torch.LongTensor*, *ordered_shaped_bpe_entities: torch.LongTensor*, *neg_ratio: int*)

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite *__getitem__()*, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite *__len__()*, which is expected to return the size of the dataset by many Sampler implementations and the default options of DataLoader. Subclasses could also optionally implement __getitems__(), for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

> **Note**
>
> `DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

train_set

ordered_bpe_entities

num_bpe_entities

neg_ratio

num_datapoints

__len__()

__getitem__(*idx*)

collate_fn(*batch_shaped_bpe_triples: List[Tuple[torch.Tensor, torch.Tensor]]*)

class dicee.dataset_classes.**MultiLabelDataset**(*train_set: torch.LongTensor*, *train_indices_target: torch.LongTensor*, *target_dim: int*, *torch_ordered_shaped_bpe_entities: torch.LongTensor*)

Bases: `torch.utils.data.Dataset`

An abstract class representing a `Dataset`.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite *`__getitem__()`*, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite *`__len__()`*, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

> **Note**
>
> `DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

train_set

train_indices_target

target_dim

num_datapoints

torch_ordered_shaped_bpe_entities

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.dataset_classes.**MultiClassClassificationDataset**(
subword_units: numpy.ndarray, *block_size: int = 8*)

Bases: `torch.utils.data.Dataset`

Dataset for the 1vsALL training strategy

Parameters

- **train_set_idx** – Indexed triples for the training.
- **entity_idxs** – mapping.
- **relation_idxs** – mapping.
- **form** – ?
- **num_workers** – int for https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader

Return type
torch.utils.data.Dataset

train_data

block_size

num_of_data_points

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.dataset_classes.**OnevsAllDataset**(*train_set_idx: numpy.ndarray*, *entity_idxs*)

Bases: `torch.utils.data.Dataset`

Dataset for the 1vsALL training strategy

Parameters

- **train_set_idx** – Indexed triples for the training.
- **entity_idxs** – mapping.
- **relation_idxs** – mapping.
- **form** – ?
- **num_workers** – int for https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader

Return type
torch.utils.data.Dataset

train_data

target_dim

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.dataset_classes.**KvsAll**(*train_set_idx: numpy.ndarray*, *entity_idxs*, *relation_idxs*, *form*, *store=None*, *label_smoothing_rate: float = 0.0*)

Bases: torch.utils.data.Dataset

Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for KvsAll training and be defined as D:= {(x,y)_i}_i ^N, where x: (h,r) is an unique tuple of an entity h in E and a relation r in R that has been seed in the input graph. y: denotes a multi-label vector in [0,1]^{|E|} is a binary label.

orall y_i =1 s.t. (h r E_i) in KG

> **Note**
>
> TODO

train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity_idxs

[dictonary] string representation of an entity to its integer id

relation_idxs

[dictonary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = KvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.dataset_classes.**AllvsAll**(*train_set_idx: numpy.ndarray*, *entity_idxs*, *relation_idxs*, *label_smoothing_rate=0.0*)

Bases: torch.utils.data.Dataset

Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for AllvsAll training and be defined as D:= {(x,y)_i}_i ^N, where x: (h,r) is a possible unique tuple of an entity h in E and a relation r in R. Hence N = |E| x |R| y: denotes a multi-label vector in [0,1]^{|E|} is a binary label.

orall y_i =1 s.t. (h r E_i) in KG

> **Note**

AllvsAll extends KvsAll via none existing (h,r). Hence, it adds data points that are labelled without 1s,
only with 0s.

train_set_idx
[numpy.ndarray] n by 3 array representing n triples

entity_idxs
[dictonary] string representation of an entity to its integer id

relation_idxs
[dictonary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = AllvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

collate_fn = None

target_dim

store

__len__()

__getitem__(*idx*)

class dicee.dataset_classes.**KvsSampleDataset**(*train_set: numpy.ndarray*, *num_entities*, *num_relations*, *neg_sample_ratio: int = None*, *label_smoothing_rate: float = 0.0*)

Bases: torch.utils.data.Dataset

KvsSample a Dataset:

D:= {(x,y)_i}_i ^N, where
. x:(h,r) is a unique h in E and a relation r in R and . y in [0,1]^{|E|} is a binary label.

orall y_i =1 s.t. (h r E_i) in KG

At each mini-batch construction, we subsample(y), hence n
|new_y| << **|E|** new_y contains all 1's if sum(y)< neg_sample ratio new_y contains

train_set_idx
Indexed triples for the training.

entity_idxs
mapping.

relation_idxs
mapping.

form
?

store
?

label_smoothing_rate
?

torch.utils.data.Dataset

train_data

num_entities

num_relations

neg_sample_ratio

label_smoothing_rate

collate_fn = None

store

train_target

__len__()

__getitem__(*idx*)

class dicee.dataset_classes.**NegSampleDataset**(*train_set: numpy.ndarray*, *num_entities: int*, *num_relations: int*, *neg_sample_ratio: int = 1*)

Bases: torch.utils.data.Dataset

An abstract class representing a Dataset.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite *__getitem__()*, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite *__len__()*, which is expected to return the size of the dataset by many Sampler implementations and the default options of DataLoader. Subclasses could also optionally implement __getitems__(), for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

DataLoader by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

neg_sample_ratio

train_set

length

num_entities

num_relations

__len__()

__getitem__(*idx*)

class dicee.dataset_classes.**TriplePredictionDataset**(*train_set: numpy.ndarray*, *num_entities: int*, *num_relations: int*, *neg_sample_ratio: int = 1*, *label_smoothing_rate: float = 0.0*)

Bases: torch.utils.data.Dataset

Triple Dataset

D:= {(x)_i}_i ^N, where
. x:(h,r, t) in KG is a unique h in E and a relation r in R and . collact_fn => Generates negative triples

collect_fn:

orall (h,r,t) in G obtain, create negative triples{(h,r,x),(,r,t),(h,m,t)}

y:labels are represented in torch.float16

train_set_idx
Indexed triples for the training.

entity_idxs
mapping.

relation_idxs
mapping.

form
?

store
?

label_smoothing_rate

collate_fn: batch:List[torch.IntTensor] Returns ——- torch.utils.data.Dataset

label_smoothing_rate

neg_sample_ratio

train_set

length

num_entities

num_relations

__len__()

__getitem__(*idx*)

collate_fn(*batch: List[torch.Tensor]*)

class dicee.dataset_classes.**CVDataModule**(*train_set_idx: numpy.ndarray*, *num_entities*, *num_relations*, *neg_sample_ratio*, *batch_size*, *num_workers*)

Bases: pytorch_lightning.LightningDataModule

Create a Dataset for cross validation

Parameters

- **train_set_idx** – Indexed triples for the training.
- **num_entities** – entity to index mapping.
- **num_relations** – relation to index mapping.
- **batch_size** – int
- **form** – ?
- **num_workers** – int for https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader

Return type

?

train_set_idx

num_entities

num_relations

neg_sample_ratio

batch_size

num_workers

train_dataloader() → torch.utils.data.DataLoader

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:paramref:`~pytorch_lightning.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

For data processing use the following pattern:

- download in *prepare_data()*
- process and split in *setup()*

However, the above are only necessary for distributed processing.

> **Warning**
>
> do not assign state in prepare_data

- fit()
- *prepare_data()*
- *setup()*

> **Note**
>
> Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

setup(**args*, ***kwargs*)

Called at the beginning of fit (train + validate), validate, test, or predict. This is a good hook when you need to build models dynamically or adjust something about them. This hook is called on every process when using DDP.

Parameters

stage – either `'fit'`, `'validate'`, `'test'`, or `'predict'`

Example:

```
class LitModel(...):
    def __init__(self):
        self.l1 = None

    def prepare_data(self):
        download_data()
        tokenize()

        # don't do this
        self.something = else

    def setup(self, stage):
        data = load_data(...)
        self.l1 = nn.Linear(28, data.num_classes)
```

transfer_batch_to_device(**args*, ***kwargs*)

Override this hook if your `DataLoader` returns tensors wrapped in a custom data structure.

The data types listed below (and any arbitrary nesting of them) are supported out of the box:

- `torch.Tensor` or anything that implements *.to(...)*
- `list`
- `dict`
- `tuple`

For anything else, you need to define how the data is moved to the target device (CPU, GPU, TPU, …).

> **Note**
>
> This hook should only transfer the data and not modify it, nor should it move the data to any other device than the one passed in as argument (unless you know what you are doing). To check the current state of execution of this hook you can use `self.trainer.training/testing/validating/predicting` so that you can add different logic as per your requirement.

Parameters

- **batch** – A batch of data that needs to be transferred to a new device.
- **device** – The target device as defined in PyTorch.

- **dataloader_idx** – The index of the dataloader to which the batch belongs.

Returns

A reference to the data on the new device.

Example:

```
def transfer_batch_to_device(self, batch, device, dataloader_idx):
    if isinstance(batch, CustomBatch):
        # move all tensors in your custom data structure to the device
        batch.samples = batch.samples.to(device)
        batch.targets = batch.targets.to(device)
    elif dataloader_idx == 0:
        # skip device transfer for the first dataloader or anything you wish
        pass
    else:
        batch = super().transfer_batch_to_device(batch, device, dataloader_
↪idx)
    return batch
```

See also

- `move_data_to_device()`
- `apply_to_collection()`

prepare_data(**args*, ***kwargs*)

Use this to download and prepare data. Downloading and saving data with multiple processes (distributed settings) will result in corrupted data. Lightning ensures this method is called only within a single process, so you can safely add your downloading logic within.

Warning

DO NOT set state to the model (use `setup` instead) since this is NOT called on every device

Example:

```
def prepare_data(self):
    # good
    download_data()
    tokenize()
    etc()

    # bad
    self.split = data_split
    self.some_state = some_other_state()
```

In a distributed environment, `prepare_data` can be called in two ways (using prepare_data_per_node)

1. Once per node. This is the default and is only called on LOCAL_RANK=0.
2. Once in total. Only called on GLOBAL_RANK=0.

Example:

```
# DEFAULT
# called once per node on LOCAL_RANK=0 of that node
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = True


# call on GLOBAL_RANK=0 (great for shared file systems)
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = False
```

This is called before requesting the dataloaders:

```
model.prepare_data()
initialize_distributed()
model.setup(stage)
model.train_dataloader()
model.val_dataloader()
model.test_dataloader()
model.predict_dataloader()
```

dicee.eval_static_funcs

Functions

evaluate_link_prediction_performance(→ Dict)	
evaluate_link_prediction_performance_w	
evaluate_link_prediction_performance_w	
evaluate_link_prediction_performance_w ...)	
evaluate_lp_bpe_k_vs_all(model, triples[, er_vocab, ...])	

Module Contents

dicee.eval_static_funcs.**evaluate_link_prediction_performance**(*model: dicee.knowledge_graph_embeddings.KGE*, *triples*, *er_vocab: Dict[Tuple, List]*, *re_vocab: Dict[Tuple, List]*) → Dict

Parameters

- **model**
- **triples**
- **er_vocab**

- **re_vocab**

dicee.eval_static_funcs.**evaluate_link_prediction_performance_with_reciprocals**(*model: dicee.knowledge_graph_embeddings.KGE*, *triples*, *er_vocab: Dict[Tuple, List]*)

dicee.eval_static_funcs.**evaluate_link_prediction_performance_with_bpe_reciprocals**(*model: dicee.knowledge_graph_embeddings.KGE*, *within_entities: List[str]*, *triples: List[List[str]]*, *er_vocab: Dict[Tuple, List]*)

dicee.eval_static_funcs.**evaluate_link_prediction_performance_with_bpe**(*model: dicee.knowledge_graph_embeddings.KGE*, *within_entities: List[str]*, *triples: List[Tuple[str]]*, *er_vocab: Dict[Tuple, List]*, *re_vocab: Dict[Tuple, List]*)

Parameters

- **model**
- **triples**
- **within_entities**
- **er_vocab**
- **re_vocab**

dicee.eval_static_funcs.**evaluate_lp_bpe_k_vs_all**(*model*, *triples: List[List[str]]*, *er_vocab=None*, *batch_size=None*, *func_triple_to_bpe_representation: Callable = None*, *str_to_bpe_entity_to_idx=None*)

dicee.evaluator

Classes

Evaluator	Evaluator class to evaluate KGE models in various downstream tasks

Module Contents

class dicee.evaluator.**Evaluator**(*args*, *is_continual_training=None*)

Evaluator class to evaluate KGE models in various downstream tasks

Arguments

re_vocab = None

er_vocab = None

ee_vocab = None

func_triple_to_bpe_representation = None

is_continual_training

num_entities = None

num_relations = None

args

report

during_training = False

vocab_preparation(*dataset*) → None

A function to wait future objects for the attributes of executor

Return type
None

eval(*dataset: dicee.knowledge_graph.KG*, *trained_model*, *form_of_labelling*, *during_training=False*) → None

eval_rank_of_head_and_tail_entity(*, *train_set*, *valid_set=None*, *test_set=None*, *trained_model*)

eval_rank_of_head_and_tail_byte_pair_encoded_entity(*, *train_set=None*, *valid_set=None*, *test_set=None*, *ordered_bpe_entities*, *trained_model*)

eval_with_byte(*, *raw_train_set*, *raw_valid_set=None*, *raw_test_set=None*, *trained_model*, *form_of_labelling*) → None

Evaluate model after reciprocal triples are added

eval_with_bpe_vs_all(*, *raw_train_set*, *raw_valid_set=None*, *raw_test_set=None*, *trained_model*, *form_of_labelling*) → None

Evaluate model after reciprocal triples are added

eval_with_vs_all(*, *train_set*, *valid_set=None*, *test_set=None*, *trained_model*, *form_of_labelling*) → None

Evaluate model after reciprocal triples are added

evaluate_lp_k_vs_all(*model*, *triple_idx*, *info=None*, *form_of_labelling=None*)

Filtered link prediction evaluation. :param model: :param triple_idx: test triples :param info: :param form_of_labelling: :return:

evaluate_lp_with_byte(*model*, *triples: List[List[str]]*, *info=None*)

evaluate_lp_bpe_k_vs_all(*model*, *triples: List[List[str]]*, *info=None*, *form_of_labelling=None*)

Parameters

- **model**
- **triples**(*List of lists*)
- **info**
- **form_of_labelling**

evaluate_lp(*model*, *triple_idx*, *info: str*)

dummy_eval(*trained_model*, *form_of_labelling: str*)

eval_with_data(*dataset*, *trained_model*, *triple_idx: numpy.ndarray*, *form_of_labelling: str*)

dicee.executer

Classes

Execute	A class for Training, Retraining and Evaluation a model.
ContinuousExecute	A subclass of Execute Class for retraining

Module Contents

class dicee.executer.**Execute**(*args*, *continuous_training=False*)

A class for Training, Retraining and Evaluation a model.

(1) Loading & Preprocessing & Serializing input data.

(2) Training & Validation & Testing

(3) Storing all necessary info

args

is_continual_training

trainer = None

trained_model = None

knowledge_graph = None

report

evaluator = None

start_time = None

read_or_load_kg()

read_preprocess_index_serialize_data() → None

Read & Preprocess & Index & Serialize Input Data

(1) Read or load the data from disk into memory.

(2) Store the statistics of the data.

Parameter

rtype
None

load_indexed_data() → None

Load the indexed data from disk into memory

Parameter

rtype
None

save_trained_model() → None
Save a knowledge graph embedding model

(1) Send model to eval mode and cpu.

(2) Store the memory footprint of the model.

(3) Save the model into disk.

(4) Update the stats of KG again ?

Parameter

rtype
None

end(*form_of_labelling: str*) → dict
End training

(1) Store trained model.

(2) Report runtimes.

(3) Eval model if required.

Parameter

rtype
A dict containing information about the training and/or evaluation

write_report() → None
Report training related information in a report.json file

start() → dict
Start training

(1) Loading the Data # (2) Create an evaluator object. # (3) Create a trainer object. # (4) Start the training

Parameter

rtype
A dict containing information about the training and/or evaluation

class dicee.executer.**ContinuousExecute**(*args*)
Bases: *Execute*

A subclass of Execute Class for retraining

(1) Loading & Preprocessing & Serializing input data.

(2) Training & Validation & Testing

(3) Storing all necessary info

During the continual learning we can only modify * **num_epochs** * parameter. Trained model stored in the same folder as the seed model for the training. Trained model is noted with the current time.

previous_args

args

continual_start() → dict

Start Continual Training

(1) Initialize training.

(2) Start continual training.

(3) Save trained model.

Parameter

rtype
A dict containing information about the training and/or evaluation

dicee.knowledge_graph

Classes

KG	Knowledge Graph

Module Contents

class dicee.knowledge_graph.**KG**(*dataset_dir: str = None*, *byte_pair_encoding: bool = False*, *padding: bool = False*, *add_noise_rate: float = None*, *sparql_endpoint: str = None*, *path_single_kg: str = None*, *path_for_deserialization: str = None*, *add_reciprical: bool = None*, *eval_model: str = None*, *read_only_few: int = None*, *sample_triples_ratio: float = None*, *path_for_serialization: str = None*, *entity_to_idx=None*, *relation_to_idx=None*, *backend=None*, *training_technique: str = None*)

Knowledge Graph

dataset_dir

byte_pair_encoding

ordered_shaped_bpe_tokens = None

sparql_endpoint

add_noise_rate

num_entities = None

num_relations = None

path_single_kg

path_for_deserialization

add_reciprical

eval_model

read_only_few

sample_triples_ratio

path_for_serialization

entity_to_idx

relation_to_idx

backend

training_technique

idx_entity_to_bpe_shaped

enc

num_tokens

num_bpe_entities = None

padding

dummy_id

max_length_subword_tokens = None

train_set_target = None

target_dim = None

train_target_indices = None

ordered_bpe_entities = None

property entities_str: List

property relations_str: List

func_triple_to_bpe_representation(*triple: List[str]*)

dicee.knowledge_graph_embeddings

Classes

KGE	Knowledge Graph Embedding Class for interactive usage of pre-trained models

Module Contents

class dicee.knowledge_graph_embeddings.**KGE**(*path=None*, *url=None*, *construct_ensemble=False*, *model_name=None*)

Bases: *dicee.abstracts.BaseInteractiveKGE*

Knowledge Graph Embedding Class for interactive usage of pre-trained models

__str__()

Return str(self).

to(*device: str*) → None

get_transductive_entity_embeddings(*indices: torch.LongTensor | List[str]*, *as_pytorch=False*, *as_numpy=False*, *as_list=True*) → torch.FloatTensor | numpy.ndarray | List[float]

create_vector_database(*collection_name: str*, *distance: str*, *location: str = 'localhost'*, *port: int = 6333*)

generate(*h=''*, *r=''*)

eval_lp_performance(*dataset=List[Tuple[str, str, str]]*, *filtered=True*)

predict_missing_head_entity(*relation: List[str] | str*, *tail_entity: List[str] | str*, *within=None*) → Tuple

Given a relation and a tail entity, return top k ranked head entity.

argmax_{e in E } f(e,r,t), where r in R, t in E.

Parameter

relation: Union[List[str], str]

String representation of selected relations.

tail_entity: Union[List[str], str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_relations(*head_entity: List[str] | str*, *tail_entity: List[str] | str*, *within=None*) → Tuple

Given a head entity and a tail entity, return top k ranked relations.

argmax_{r in R } f(h,r,t), where h, t in E.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_tail_entity(*head_entity: List[str] | str*, *relation: List[str] | str*, *within: List[str] = None*) → torch.FloatTensor

Given a head entity and a relation, return top k ranked entities

argmax_{e in E } f(h,r,e), where h in E and r in R.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

scores

predict(*, *h: List[str] | str = None*, *r: List[str] | str = None*, *t: List[str] | str = None*, *within=None*, *logits=True*) → torch.FloatTensor

Parameters

- **logits**
- **h**

- **r**
- **t**
- **within**

predict_topk (*, *h: List[str] = None*, *r: List[str] = None*, *t: List[str] = None*, *topk: int = 10*, *within: List[str] = None*)

Predict missing item in a given triple.

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

k: int

Highest ranked k item.

Returns: Tuple

Highest K scores and items

triple_score (*h: List[str] | str = None*, *r: List[str] | str = None*, *t: List[str] | str = None*, *logits=False*) → torch.FloatTensor

Predict triple score

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

logits: bool

If logits is True, unnormalized score returned

Returns: Tuple

pytorch tensor of triple score

t_norm(*tens_1: torch.Tensor*, *tens_2: torch.Tensor*, *tnorm: str = 'min'*) → torch.Tensor

tensor_t_norm(*subquery_scores: torch.FloatTensor*, *tnorm: str = 'min'*) → torch.FloatTensor

Compute T-norm over [0,1] ^{n imes d} where n denotes the number of hops and d denotes number of entities

t_conorm(*tens_1: torch.Tensor*, *tens_2: torch.Tensor*, *tconorm: str = 'min'*) → torch.Tensor

negnorm(*tens_1: torch.Tensor*, *lambda_: float*, *neg_norm: str = 'standard'*) → torch.Tensor

return_multi_hop_query_results(*aggregated_query_for_all_entities*, *k: int*, *only_scores*)

single_hop_query_answering(*query: tuple*, *only_scores: bool = True*, *k: int = None*)

answer_multi_hop_query(*query_type: str = None*,
query: Tuple[str | Tuple[str, str], Ellipsis] = None,
queries: List[Tuple[str | Tuple[str, str], Ellipsis]] = None, *tnorm: str = 'prod'*,
neg_norm: str = 'standard', *lambda_: float = 0.0*, *k: int = 10*, *only_scores=False*)
→ List[Tuple[str, torch.Tensor]]

@TODO: Refactoring is needed # @TODO: Score computation for each query type should be done in a static function

Find an answer set for EPFO queries including negation and disjunction

Parameter

query_type: str The type of the query, e.g., “2p”.

query: Union[str, Tuple[str, Tuple[str, str]]] The query itself, either a string or a nested tuple.

queries: List of Tuple[Union[str, Tuple[str, str]], …]

tnorm: str The t-norm operator.

neg_norm: str The negation norm.

lambda_: float lambda parameter for sugeno and yager negation norms

k: int The top-k substitutions for intermediate variables.

returns

- *List[Tuple[str, torch.Tensor]]*
- *Entities and corresponding scores sorted in the descening order of scores*

find_missing_triples(*confidence: float*, *entities: List[str] = None*, *relations: List[str] = None*,
topk: int = 10, *at_most: int = sys.maxsize*) → Set

Find missing triples

Iterative over a set of entities E and a set of relation R :

orall e in E and orall r in R f(e,r,x)

Return (e,r,x)

otin G and f(e,r,x) > confidence

confidence: float

A threshold for an output of a sigmoid function given a triple.

topk: int

Highest ranked k item to select triples with f(e,r,x) > confidence .

at_most: int

Stop after finding at_most missing triples

{(e,r,x) | f(e,r,x) > confidence land (e,r,x)

otin G

deploy (*share: bool = False*, *top_k: int = 10*)

train_triples (*h: List[str]*, *r: List[str]*, *t: List[str]*, *labels: List[float]*, *iteration=2*, *optimizer=None*)

train_k_vs_all (*h*, *r*, *iteration=1*, *lr=0.001*)

Train k vs all :param head_entity: :param relation: :param iteration: :param lr: :return:

train (*kg*, *lr=0.1*, *epoch=10*, *batch_size=32*, *neg_sample_ratio=10*, *num_workers=1*) → None

Retrained a pretrain model on an input KG via negative sampling.

dicee.query_generator

Classes

QueryGenerator

Module Contents

class dicee.query_generator.**QueryGenerator** (*train_path*, *val_path: str*, *test_path: str*, *ent2id: Dict = None*, *rel2id: Dict = None*, *seed: int = 1*, *gen_valid: bool = False*, *gen_test: bool = True*)

train_path

val_path

test_path

gen_valid

gen_test

seed

max_ans_num = 1000000.0

mode

ent2id

rel2id: Dict

ent_in: Dict

ent_out: Dict

query_name_to_struct

list2tuple(*list_data*)

tuple2list(*x: List | Tuple*) → List | Tuple

Convert a nested tuple to a nested list.

set_global_seed(*seed: int*)

Set seed

construct_graph(*paths: List[str]*) → Tuple[Dict, Dict]

Construct graph from triples Returns dicts with incoming and outgoing edges

fill_query(*query_structure: List[str | List]*, *ent_in: Dict*, *ent_out: Dict*, *answer: int*) → bool

Private method for fill_query logic.

achieve_answer(*query: List[str | List]*, *ent_in: Dict*, *ent_out: Dict*) → set

Private method for achieve_answer logic. @TODO: Document the code

write_links(*ent_out*, *small_ent_out*)

ground_queries(*query_structure: List[str | List]*, *ent_in: Dict*, *ent_out: Dict*, *small_ent_in: Dict*, *small_ent_out: Dict*, *gen_num: int*, *query_name: str*)

Generating queries and achieving answers

unmap(*query_type*, *queries*, *tp_answers*, *fp_answers*, *fn_answers*)

unmap_query(*query_structure*, *query*, *id2ent*, *id2rel*)

generate_queries(*query_struct: List*, *gen_num: int*, *query_type: str*)

Passing incoming and outgoing edges to ground queries depending on mode [train valid or text] and getting queries and answers in return @ TODO: create a class for each single query struct

save_queries(*query_type: str*, *gen_num: int*, *save_path: str*)

abstract load_queries(*path*)

get_queries(*query_type: str*, *gen_num: int*)

static save_queries_and_answers(*path: str*, *data: List[Tuple[str, Tuple[collections.defaultdict]]]*) → None

Save Queries into Disk

static load_queries_and_answers(*path: str*) → List[Tuple[str, Tuple[collections.defaultdict]]]

Load Queries from Disk to Memory

dicee.sanity_checkers

Functions

is_sparql_endpoint_alive([sparql_endpoint])	
validate_knowledge_graph(args)	Validating the source of knowledge graph
sanity_checking_with_arguments(args)	

Module Contents

dicee.sanity_checkers.**is_sparql_endpoint_alive**(*sparql_endpoint: str = None*)

dicee.sanity_checkers.**validate_knowledge_graph**(*args*)

Validating the source of knowledge graph

dicee.sanity_checkers.**sanity_checking_with_arguments**(*args*)

dicee.static_funcs

Functions

create_recipriocal_triples(x)	Add inverse triples into dask dataframe
get_er_vocab(data[, file_path])	
get_re_vocab(data[, file_path])	
get_ee_vocab(data[, file_path])	
timeit(func)	
save_pickle(*[, data, file_path])	
load_pickle([file_path])	
select_model(args[, is_continual_training, storage_path])	
load_model(→ Tuple[object, Tuple[dict, dict]])	Load weights and initialize pytorch module from namespace arguments
load_model_ensemble(...)	Construct Ensemble Of weights and initialize pytorch module from namespace arguments
save_numpy_ndarray(*, data, file_path)	
numpy_data_type_changer(→ numpy.ndarray)	Detect most efficient data type for a given triples
save_checkpoint_model(→ None)	Store Pytorch model into disk
store(→ None)	Store trained_model model and save embeddings into csv file.

continues on next page

Table 2 – continued from previous page

add_noisy_triples(→ pandas.DataFrame)	Add randomly constructed triples
read_or_load_kg(args, cls)	
intialize_model(→ Tuple[object, str])	
load_json(→ dict)	
save_embeddings(→ None)	Save it as CSV if memory allows.
random_prediction(pre_trained_kge)	
deploy_triple_prediction(pre_trained_kge, str_subject, ...)	
deploy_tail_entity_prediction(pre_trained_ ...)	
deploy_head_entity_prediction(pre_trained_ ...)	
deploy_relation_prediction(pre_trained_kge, ...)	
vocab_to_parquet(vocab_to_idx, name, ...)	
create_experiment_folder([folder_name])	
continual_training_setup_executor(→ None)	storage_path:str A path leading to a parent directory, where a subdirectory containing KGE related data
exponential_function(→ torch.FloatTensor)	
load_numpy(→ numpy.ndarray)	
evaluate(entity_to_idx, scores, easy_answers, hard_answers)	# @TODO: CD: Renamed this function
download_file(url[, destination_folder])	
download_files_from_url(→ None)	
download_pretrained_model(→ str)	

Module Contents

dicee.static_funcs.**create_recipriocal_triples**(*x*)

Add inverse triples into dask dataframe :param x: :return:

dicee.static_funcs.**get_er_vocab**(*data*, *file_path: str = None*)

dicee.static_funcs.**get_re_vocab**(*data*, *file_path: str = None*)

dicee.static_funcs.**get_ee_vocab**(*data*, *file_path: str = None*)

dicee.static_funcs.**timeit**(*func*)

dicee.static_funcs.**save_pickle**(*, *data: object = None*, *file_path=str*)

dicee.static_funcs.**load_pickle**(*file_path=str*)

dicee.static_funcs.**select_model**(*args: dict*, *is_continual_training: bool = None*, *storage_path: str = None*)

dicee.static_funcs.**load_model**(*path_of_experiment_folder: str*, *model_name='model.pt'*, *verbose=0*) → Tuple[object, Tuple[dict, dict]]

Load weights and initialize pytorch module from namespace arguments

dicee.static_funcs.**load_model_ensemble**(*path_of_experiment_folder: str*) → Tuple[*dicee.models.base_model.BaseKGE*, Tuple[pandas.DataFrame, pandas.DataFrame]]

Construct Ensemble Of weights and initialize pytorch module from namespace arguments

(1) Detect models under given path

(2) Accumulate parameters of detected models

(3) Normalize parameters

(4) Insert (3) into model.

dicee.static_funcs.**save_numpy_ndarray**(*, *data: numpy.ndarray*, *file_path: str*)

dicee.static_funcs.**numpy_data_type_changer**(*train_set: numpy.ndarray*, *num: int*) → numpy.ndarray

Detect most efficient data type for a given triples :param train_set: :param num: :return:

dicee.static_funcs.**save_checkpoint_model**(*model*, *path: str*) → None

Store Pytorch model into disk

dicee.static_funcs.**store**(*trainer*, *trained_model*, *model_name: str = 'model'*, *full_storage_path: str = None*, *save_embeddings_as_csv=False*) → None

Store trained_model model and save embeddings into csv file. :param trainer: an instance of trainer class :param full_storage_path: path to save parameters. :param model_name: string representation of the name of the model. :param trained_model: an instance of BaseKGE see core.models.base_model . :param save_embeddings_as_csv: for easy access of embeddings. :return:

dicee.static_funcs.**add_noisy_triples**(*train_set: pandas.DataFrame*, *add_noise_rate: float*) → pandas.DataFrame

Add randomly constructed triples :param train_set: :param add_noise_rate: :return:

dicee.static_funcs.**read_or_load_kg**(*args*, *cls*)

dicee.static_funcs.**intialize_model**(*args: dict*, *verbose=0*) → Tuple[object, str]

dicee.static_funcs.**load_json**(*p: str*) → dict

dicee.static_funcs.**save_embeddings**(*embeddings: numpy.ndarray*, *indexes*, *path: str*) → None

Save it as CSV if memory allows. :param embeddings: :param indexes: :param path: :return:

dicee.static_funcs.**random_prediction**(*pre_trained_kge*)

dicee.static_funcs.**deploy_triple_prediction**(*pre_trained_kge*, *str_subject*, *str_predicate*, *str_object*)

dicee.static_funcs.**deploy_tail_entity_prediction**(*pre_trained_kge*, *str_subject*, *str_predicate*, *top_k*)

dicee.static_funcs.**deploy_head_entity_prediction**(*pre_trained_kge*, *str_object*, *str_predicate*, *top_k*)

dicee.static_funcs.**deploy_relation_prediction**(*pre_trained_kge*, *str_subject*, *str_object*, *top_k*)

dicee.static_funcs.**vocab_to_parquet**(*vocab_to_idx*, *name*, *path_for_serialization*, *print_into*)

dicee.static_funcs.**create_experiment_folder**(*folder_name='Experiments'*)

dicee.static_funcs.**continual_training_setup_executor**(*executor*) → None

storage_path:str A path leading to a parent directory, where a subdirectory containing KGE related data

full_storage_path:str A path leading to a subdirectory containing KGE related data

dicee.static_funcs.**exponential_function**(*x: numpy.ndarray*, *lam: float*, *ascending_order=True*) → torch.FloatTensor

dicee.static_funcs.**load_numpy**(*path*) → numpy.ndarray

dicee.static_funcs.**evaluate**(*entity_to_idx*, *scores*, *easy_answers*, *hard_answers*)

@TODO: CD: Renamed this function Evaluate multi hop query answering on different query types

dicee.static_funcs.**download_file**(*url*, *destination_folder='.'*)

dicee.static_funcs.**download_files_from_url**(*base_url: str*, *destination_folder='.'*) → None

Parameters

- **base_url** (e.g. "https://files.dice-research.org/projects/DiceEmbeddings/KINSHIP-Keci-dim128-epoch256-KvsAll")
- **destination_folder**(*e.g. "KINSHIP-Keci-dim128-epoch256-KvsAll"*)

dicee.static_funcs.**download_pretrained_model**(*url: str*) → str

dicee.static_funcs_training

Functions

evaluate_lp(model, triple_idx, num_entities, er_vocab, ...)	Evaluate model in a standard link prediction task
evaluate_bpe_lp(model, triple_idx, ...[, info])	
efficient_zero_grad(model)	

Module Contents

dicee.static_funcs_training.**evaluate_lp**(*model*, *triple_idx*, *num_entities*, *er_vocab: Dict[Tuple, List]*, *re_vocab: Dict[Tuple, List]*, *info='Eval Starts'*)

Evaluate model in a standard link prediction task

for each triple the rank is computed by taking the mean of the filtered missing head entity rank and the filtered missing tail entity rank :param model: :param triple_idx: :param info: :return:

dicee.static_funcs_training.**evaluate_bpe_lp**(*model*, *triple_idx: List[Tuple]*, *all_bpe_shaped_entities*, *er_vocab: Dict[Tuple, List]*, *re_vocab: Dict[Tuple, List]*, *info='Eval Starts'*)

dicee.static_funcs_training.**efficient_zero_grad**(*model*)

dicee.static_preprocess_funcs

Attributes

enable_log

Functions

timeit(func)	
preprocesses_input_args(args)	Sanity Checking in input arguments
create_constraints(→ Tuple[dict, dict, dict, dict])	
get_er_vocab(data)	
get_re_vocab(data)	
get_ee_vocab(data)	
mapping_from_first_two_cols_to_third(tra	

Module Contents

dicee.static_preprocess_funcs.**enable_log = False**

dicee.static_preprocess_funcs.**timeit**(*func*)

dicee.static_preprocess_funcs.**preprocesses_input_args**(*args*)

Sanity Checking in input arguments

dicee.static_preprocess_funcs.**create_constraints**(*triples: numpy.ndarray*) → Tuple[dict, dict, dict, dict]

(1) Extract domains and ranges of relations

(2) Store a mapping from relations to entities that are outside of the domain and range. Create constraints entities based on the range of relations :param triples: :return:

dicee.static_preprocess_funcs.**get_er_vocab**(*data*)

dicee.static_preprocess_funcs.**get_re_vocab**(*data*)

dicee.static_preprocess_funcs.**get_ee_vocab**(*data*)

dicee.static_preprocess_funcs.**mapping_from_first_two_cols_to_third**(*train_set_idx*)

14.3 Attributes

__version__	

14.4 Classes

CMult	Cl_(0,0) => Real Numbers
Pyke	A Physical Embedding Model for Knowledge Graphs
DistMult	Embedding Entities and Relations for Learning and Inference in Knowledge Bases
KeciBase	Without learning dimension scaling
Keci	Base class for all neural network modules.
TransE	Translating Embeddings for Modeling
DeCaL	Base class for all neural network modules.
DualE	Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)
ComplEx	Base class for all neural network modules.
AConEx	Additive Convolutional ComplEx Knowledge Graph Embeddings
AConvO	Additive Convolutional Octonion Knowledge Graph Embeddings
AConvQ	Additive Convolutional Quaternion Knowledge Graph Embeddings
ConvQ	Convolutional Quaternion Knowledge Graph Embeddings
ConvO	Base class for all neural network modules.
ConEx	Convolutional ComplEx Knowledge Graph Embeddings
QMult	Base class for all neural network modules.
OMult	Base class for all neural network modules.
Shallom	A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)
LFMult	Embedding with polynomial functions. We represent all entities and relations in the polynomial space as:
PykeenKGE	A class for using knowledge graph embedding models implemented in Pykeen
BytE	Base class for all neural network modules.
BaseKGE	Base class for all neural network modules.
DICE_Trainer	DICE_Trainer implement
KGE	Knowledge Graph Embedding Class for interactive usage of pre-trained models
Execute	A class for Training, Retraining and Evaluation a model.
BPE_NegativeSamplingDataset	An abstract class representing a `Dataset`.

continues on next page

Table 3 – continued from previous page

MultiLabelDataset	An abstract class representing a `Dataset`.
MultiClassClassificationDataset	Dataset for the 1vsALL training strategy
OnevsAllDataset	Dataset for the 1vsALL training strategy
KvsAll	Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.
AllvsAll	Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.
KvsSampleDataset	KvsSample a Dataset:
NegSampleDataset	An abstract class representing a `Dataset`.
TriplePredictionDataset	Triple Dataset
CVDataModule	Create a Dataset for cross validation
QueryGenerator	

14.5 Functions

create_recipriocal_triples(x)	Add inverse triples into dask dataframe
get_er_vocab(data[, file_path])	
get_re_vocab(data[, file_path])	
get_ee_vocab(data[, file_path])	
timeit(func)	
save_pickle(*[, data, file_path])	
load_pickle([file_path])	
select_model(args[, is_continual_training, storage_path])	
load_model(→ Tuple[object, Tuple[dict, dict]])	Load weights and initialize pytorch module from namespace arguments
load_model_ensemble(...)	Construct Ensemble Of weights and initialize pytorch module from namespace arguments
save_numpy_ndarray(*, data, file_path)	
numpy_data_type_changer(→ numpy.ndarray)	Detect most efficient data type for a given triples
save_checkpoint_model(→ None)	Store Pytorch model into disk
store(→ None)	Store trained_model model and save embeddings into csv file.
add_noisy_triples(→ pandas.DataFrame)	Add randomly constructed triples
read_or_load_kg(args, cls)	
intialize_model(→ Tuple[object, str])	
load_json(→ dict)	
save_embeddings(→ None)	Save it as CSV if memory allows.

continues on next page

Table 4 – continued from previous page

random_prediction(pre_trained_kge)	
deploy_triple_prediction(pre_trained_kge, str_subject, ...)	
deploy_tail_entity_prediction(pre_trained_ ...)	
deploy_head_entity_prediction(pre_trained_ ...)	
deploy_relation_prediction(pre_trained_kge, ...)	
vocab_to_parquet(vocab_to_idx, name, ...)	
create_experiment_folder([folder_name])	
continual_training_setup_executor(→ None)	storage_path:str A path leading to a parent directory, where a subdirectory containing KGE related data
exponential_function(→ torch.FloatTensor)	
load_numpy(→ numpy.ndarray)	
evaluate(entity_to_idx, scores, easy_answers, hard_answers)	# @TODO: CD: Renamed this function
download_file(url[, destination_folder])	
download_files_from_url(→ None)	
download_pretrained_model(→ str)	
mapping_from_first_two_cols_to_third(tra	
timeit(func)	
load_pickle([file_path])	
reload_dataset(path, form_of_labelling, ...)	Reload the files from disk to construct the Pytorch dataset
construct_dataset(→ torch.utils.data.Dataset)	

14.6 Package Contents

class dicee.**CMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Cl_(0,0) => Real Numbers

Cl_(0,1) =>

A multivector mathbf{a} = a_0 + a_1 e_1 A multivector mathbf{b} = b_0 + b_1 e_1

multiplication is isomorphic to the product of two complex numbers

mathbf{a} imes mathbf{b} = a_0 b_0 + a_0b_1 e1 + a_1 b_1 e_1 e_1
= (a_0 b_0 - a_1 b_1) + (a_0 b_1 + a_1 b_0) e_1

Cl_(2,0) =>

A multivector mathbf{a} = a_0 + a_1 e_1 + a_2 e_2 + a_{12} e_1 e_2 A multivector mathbf{b} = b_0 + b_1 e_1 + b_2 e_2 + b_{12} e_1 e_2

mathbf{a} imes mathbf{b} = a_0b_0 + a_0b_1 e_1 + a_0b_2e_2 + a_0 b_12 e_1 e_2

- a_1 b_0 e_1 + a_1b_1 e_1_e1 ..

Cl_(0,2) => Quaternions

name = 'CMult'

entity_embeddings

relation_embeddings

p

q

clifford_mul (*x: torch.FloatTensor*, *y: torch.FloatTensor*, *p: int*, *q: int*) → tuple

Clifford multiplication Cl_{p,q} (mathbb{R})

ei ^2 = +1 for i =< i =< p ej ^2 = -1 for p < j =< p+q ei ej = -eje1 for i

eq j

x: torch.FloatTensor with (n,d) shape

y: torch.FloatTensor with (n,d) shape

p: a non-negative integer p>= 0 q: a non-negative integer q>= 0

score (*head_ent_emb*, *rel_ent_emb*, *tail_ent_emb*)

forward_triples (*x: torch.LongTensor*) → torch.FloatTensor

Compute batch triple scores

Parameter

x: torch.LongTensor with shape n by 3

rtype
torch.LongTensor with shape n

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Compute batch KvsAll triple scores

Parameter

x: torch.LongTensor with shape n by 3

rtype
torch.LongTensor with shape n

class dicee.**Pyke**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

A Physical Embedding Model for Knowledge Graphs

name = 'Pyke'

dist_func

margin = 1.0

forward_triples(*x: torch.LongTensor*)

Parameters
x

class dicee.**DistMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding Entities and Relations for Learning and Inference in Knowledge Bases https://arxiv.org/abs/1412.6575

name = 'DistMult'

k_vs_all_score(*emb_h: torch.FloatTensor*, *emb_r: torch.FloatTensor*, *emb_E: torch.FloatTensor*)

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

forward_k_vs_all(*x: torch.LongTensor*)

forward_k_vs_sample(*x: torch.LongTensor*, *target_entity_idx: torch.LongTensor*)

score(*h*, *r*, *t*)

class dicee.**KeciBase**(*args*)

Bases: *Keci*

Without learning dimension scaling

name = 'KeciBase'

requires_grad_for_interactions = False

class dicee.**Keci**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)

(continued from previous page)

```
    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'Keci'

p

q

r

requires_grad_for_interactions = True

compute_sigma_pp(*hp*, *rp*)

Compute sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):
results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq(*hq*, *rq*)

Compute sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):
results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_pq (*, *hp*, *hq*, *rp*, *rq*)

sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

apply_coefficients (*h0*, *hp*, *hq*, *r0*, *rp*, *rq*)

Multiplying a base vector with its scalar coefficient

clifford_multiplication (*h0*, *hp*, *hq*, *r0*, *rp*, *rq*)

Compute our CL multiplication

h = h_0 + sum_{i=1}^p h_i e_i + sum_{j=p+1}^{p+q} h_j e_j r = r_0 + sum_{i=1}^p r_i e_i + sum_{j=p+1}^{p+q} r_j e_j

ei ^2 = +1 for i =< i =< p ej ^2 = -1 for p < j =< p+q ei ej = -eje1 for i

eq j

h r = sigma_0 + sigma_p + sigma_q + sigma_{pp} + sigma_{q}+ sigma_{pq} where

(1) sigma_0 = h_0 r_0 + sum_{i=1}^p (h_0 r_i) e_i - sum_{j=p+1}^{p+q} (h_j r_j) e_j

(2) sigma_p = sum_{i=1}^p (h_0 r_i + h_i r_0) e_i

(3) sigma_q = sum_{j=p+1}^{p+q} (h_0 r_j + h_j r_0) e_j

(4) sigma_{pp} = sum_{i=1}^{p-1} sum_{k=i+1}^p (h_i r_k - h_k r_i) e_i e_k

(5) sigma_{qq} = sum_{j=1}^{p+q-1} sum_{k=j+1}^{p+q} (h_j r_k - h_k r_j) e_j e_k

(6) sigma_{pq} = sum_{i=1}^{p} sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j

construct_cl_multivector (*x: torch.FloatTensor*, *r: int*, *p: int*, *q: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors Cl_{p,q}(mathbb{R}^d)

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor with (n,r) shape*)
- **ap** (*torch.FloatTensor with (n,r,p) shape*)
- **aq** (*torch.FloatTensor with (n,r,q) shape*)

forward_k_vs_with_explicit (*x: torch.Tensor*)

k_vs_all_score (*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations mathbb{R}^d .

(2) Construct head entity and relation embeddings according to Cl_{p,q}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter ——— x: torch.LongTensor with (n,2) shape :rtype: torch.FloatTensor with (n, |E|) shape

forward_k_vs_sample (*x: torch.LongTensor*, *target_entity_idx: torch.LongTensor*) → torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations mathbb{R}^d .

(2) Construct head entity and relation embeddings according to Cl_{p,q}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

Parameter

x: torch.LongTensor with (n,2) shape

rtype
torch.FloatTensor with (n, |E|) shape

score (*h*, *r*, *t*)

forward_triples (*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,3) shape

rtype
torch.FloatTensor with (n) shape

class dicee.**TransE** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Translating Embeddings for Modeling Multi-relational Data https://proceedings.neurips.cc/paper/2013/file/1cecc7a77928ca8133fa24680a88d2f9-Paper.pdf

name = 'TransE'

margin = 4

score (*head_ent_emb*, *rel_ent_emb*, *tail_ent_emb*)

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

class dicee.**DeCaL**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'DeCaL'

entity_embeddings

relation_embeddings

p

q

r

re

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameter

x: torch.LongTensor with (n,) shape

rtype
torch.FloatTensor with (n) shape

cl_pqr (*a: torch.tensor*) → torch.tensor

Input: tensor(batch_size, emb_dim) —> output: tensor with 1+p+q+r components with size (batch_size, emb_dim/(1+p+q+r)) each.

1) takes a tensor of size (batch_size, emb_dim), split it into 1 + p + q +r components, hence 1+p+q+r must be a divisor of the emb_dim. 2) Return a list of the 1+p+q+r components vectors, each are tensors of size (batch_size, emb_dim/(1+p+q+r))

compute_sigmas_single (*list_h_emb*, *list_r_emb*, *list_t_emb*)

here we compute all the sums with no others vectors interaction taken with the scalar product with t, that is,

$$s0 = h_0 r_0 t_0 s1 = \sum_{i=1}^{p} h_i r_i t_0 s2 = \sum_{j=p+1}^{p+q} h_j r_j t_0 s3 = \sum_{i=1}^{q} (h_0 r_i t_i + h_i r_0 t_i) s4 = \sum_{i=p+1}^{p+q} (h_0 r_i t_i + h_i r_0 t_i) s5 = \sum_{i=p+q+1}^{p+q+r} (h_0 r_i t$$

and return:

$$sigma_0 t = \sigma_0 \cdot t_0 = s0 + s1 - s2 s3, s4 and s5$$

compute_sigmas_multivect (*list_h_emb*, *list_r_emb*)

Here we compute and return all the sums with vectors interaction for the same and different bases.

For same bases vectors interaction we have

$$\sigma_p p = \sum_{i=1}^{p-1} \sum_{i'=i+1}^{p} (h_i r_{i'} - h_{i'} r_i)(models the interactions between e_i and e'_i for 1 <= i, i' <= p) \sigma_q q = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (h_j r_{j'}$$

For different base vector interactions, we have

$$\sigma_p q = \sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i)(interactions n between e_i and e_j for 1 <= i <= p and p+1 <= j <= p+q) \sigma_p r = \sum_{i=}^{}$$

forward_k_vs_all (*x: torch.Tensor*) → torch.FloatTensor

Kvsall training

(1) Retrieve real-valued embedding vectors for heads and relations

(2) Construct head entity and relation embeddings according to Cl_{p,q, r}(mathbb{R}^d) .

(3) Perform Cl multiplication

(4) Inner product of (3) and all entity embeddings

forward_k_vs_with_explicit and this funcitons are identical Parameter ——— x: torch.LongTensor with (n,) shape :rtype: torch.FloatTensor with (n, |E|) shape

apply_coefficients (*h0*, *hp*, *hq*, *hk*, *r0*, *rp*, *rq*, *rk*)

Multiplying a base vector with its scalar coefficient

construct_cl_multivector (*x: torch.FloatTensor*, *re: int*, *p: int*, *q: int*, *r: int*)
→ tuple[torch.FloatTensor, torch.FloatTensor, torch.FloatTensor]

Construct a batch of multivectors Cl_{p,q,r}(mathbb{R}^d)

Parameter

x: torch.FloatTensor with (n,d) shape

returns

- **a0** (*torch.FloatTensor*)
- **ap** (*torch.FloatTensor*)
- **aq** (*torch.FloatTensor*)
- **ar** (*torch.FloatTensor*)

compute_sigma_pp(*hp*, *rp*)

Compute .. math:

```
\sigma_{p,p}^* = \sum_{i=1}^{p-1}\sum_{i'=i+1}^{p}(x_iy_{i'}-x_{i'}y_i)
```

sigma_{pp} captures the interactions between along p bases For instance, let p e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for i in range(p - 1):

for k in range(i + 1, p):
results.append(hp[:, :, i] * rp[:, :, k] - hp[:, :, k] * rp[:, :, i])

sigma_pp = torch.stack(results, dim=2) assert sigma_pp.shape == (b, r, int((p * (p - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_qq(*hq*, *rq*)

Compute

$$\sigma_{q,q}^* = \sum_{j=p+1}^{p+q-1} \sum_{j'=j+1}^{p+q} (x_j y_{j'} - x_{j'} y_j) Eq.16$$

sigma_{q} captures the interactions between along q bases For instance, let q e_1, e_2, e_3, we compute interactions between e_1 e_2, e_1 e_3 , and e_2 e_3 This can be implemented with a nested two for loops

results = [] for j in range(q - 1):

for k in range(j + 1, q):
results.append(hq[:, :, j] * rq[:, :, k] - hq[:, :, k] * rq[:, :, j])

sigma_qq = torch.stack(results, dim=2) assert sigma_qq.shape == (b, r, int((q * (q - 1)) / 2))

Yet, this computation would be quite inefficient. Instead, we compute interactions along all p, e.g., e1e1, e1e2, e1e3,

e2e1, e2e2, e2e3, e3e1, e3e2, e3e3

Then select the triangular matrix without diagonals: e1e2, e1e3, e2e3.

compute_sigma_rr(*hk*, *rk*)

$$\sigma_{r,r}^* = \sum_{k=p+q+1}^{p+q+r-1} \sum_{k'=k+1}^{p} (x_k y_{k'} - x_{k'} y_k)$$

compute_sigma_pq(*, *hp*, *hq*, *rp*, *rq*)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

compute_sigma_pr(*, *hp*, *hk*, *rp*, *rk*)

Compute

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

compute_sigma_qr(*, *hq*, *hk*, *rq*, *rk*)

$$\sum_{i=1}^{p} \sum_{j=p+1}^{p+q} (h_i r_j - h_j r_i) e_i e_j$$

results = [] sigma_pq = torch.zeros(b, r, p, q) for i in range(p):

for j in range(q):
sigma_pq[:, :, i, j] = hp[:, :, i] * rq[:, :, j] - hq[:, :, j] * rp[:, :, i]

print(sigma_pq.shape)

class dicee.**DualE**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Dual Quaternion Knowledge Graph Embeddings (https://ojs.aaai.org/index.php/AAAI/article/download/16850/16657)

name = 'DualE'

entity_embeddings

relation_embeddings

num_ent

kvsall_score(*e_1_h*, *e_2_h*, *e_3_h*, *e_4_h*, *e_5_h*, *e_6_h*, *e_7_h*, *e_8_h*, *e_1_t*, *e_2_t*, *e_3_t*, *e_4_t*, *e_5_t*, *e_6_t*, *e_7_t*, *e_8_t*, *r_1*, *r_2*, *r_3*, *r_4*, *r_5*, *r_6*, *r_7*, *r_8*) → torch.tensor

KvsAll scoring function

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_triples (*idx_triple: torch.tensor*) → torch.tensor

Negative Sampling forward pass:

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

forward_k_vs_all (*x*)

KvsAll forward pass

Input

x: torch.LongTensor with (n,) shape

Output

torch.FloatTensor with (n) shape

T (*x: torch.tensor*) → torch.tensor

Transpose function

Input: Tensor with shape (nxm) Output: Tensor with shape (mxn)

class dicee.**ComplEx** (*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)
```

(continues on next page)

(continued from previous page)

```
    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ComplEx'

static score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

static k_vs_all_score(*emb_h: torch.FloatTensor*, *emb_r: torch.FloatTensor*, *emb_E: torch.FloatTensor*)

Parameters

- **emb_h**
- **emb_r**
- **emb_E**

forward_k_vs_all(*x: torch.LongTensor*) → torch.FloatTensor

class dicee.**AConEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional ComplEx Knowledge Graph Embeddings

name = 'AConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution(*C_1: Tuple[torch.Tensor, torch.Tensor]*, *C_2: Tuple[torch.Tensor, torch.Tensor]*) → torch.FloatTensor

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameters
x

forward_k_vs_sample(*x: torch.Tensor*, *target_entity_idx: torch.Tensor*)

class dicee.**AConvO**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional Octonion Knowledge Graph Embeddings

name = 'AConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

residual_convolution(*O_1*, *O_2*)

forward_triples(*x: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, **|Entities|**) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.**AConvQ**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Additive Convolutional Quaternion Knowledge Graph Embeddings

name = 'AConvQ'

entity_embeddings

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution(*Q_1*, *Q_2*)

forward_triples(*indexed_triple: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.**ConvQ**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional Quaternion Knowledge Graph Embeddings

name = 'ConvQ'

entity_embeddings

relation_embeddings

conv2d

fc_num_input

fc1

bn_conv1

bn_conv2

feature_map_dropout

residual_convolution(*Q_1*, *Q_2*)

forward_triples(*indexed_triple: torch.Tensor*) → torch.Tensor

Parameters
x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.**ConvO**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'ConvO'

conv2d

fc_num_input

fc1

bn_conv2d

norm_fc1

feature_map_dropout

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

residual_convolution(*O_1*, *O_2*)

forward_triples(*x: torch.Tensor*) → torch.Tensor

Parameters

x

forward_k_vs_all(*x: torch.Tensor*)

Given a head entity and a relation (h,r), we compute scores for all entities. [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,|Entities|)

class dicee.**ConEx**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Convolutional ComplEx Knowledge Graph Embeddings

name = 'ConEx'

conv2d

fc_num_input

fc1

norm_fc1

bn_conv2d

feature_map_dropout

residual_convolution(*C_1: Tuple[torch.Tensor, torch.Tensor]*, *C_2: Tuple[torch.Tensor, torch.Tensor]*) → torch.FloatTensor

Compute residual score of two complex-valued embeddings. :param C_1: a tuple of two pytorch tensors that corresponds complex-valued embeddings :param C_2: a tuple of two pytorch tensors that corresponds complex-valued embeddings :return:

forward_k_vs_all(*x: torch.Tensor*) → torch.FloatTensor

forward_triples(*x: torch.Tensor*) → torch.FloatTensor

Parameters

x

forward_k_vs_sample(*x: torch.Tensor*, *target_entity_idx: torch.Tensor*)

class dicee.**QMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'QMult'

explicit = True

quaternion_multiplication_followed_by_inner_product(*h*, *r*, *t*)

Parameters

- **h** – shape: (**batch_dims*, dim) The head representations.
- **r** – shape: (**batch_dims*, dim) The head representations.
- **t** – shape: (**batch_dims*, dim) The tail representations.

Returns

Triple scores.

static quaternion_normalizer(*x: torch.FloatTensor*) → torch.FloatTensor

Normalize the length of relation vectors, if the forward constraint has not been applied yet.

Absolute value of a quaternion

$$|a + bi + cj + dk| = \sqrt{a^2 + b^2 + c^2 + d^2}$$

L2 norm of quaternion vector:

$$\|x\|^2 = \sum_{i=1}^{d} |x_i|^2 = \sum_{i=1}^{d} (x_i.re^2 + x_i.im_1^2 + x_i.im_2^2 + x_i.im_3^2)$$

Parameters

x – The vector.

Returns

The normalized vector.

score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

k_vs_all_score(*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

Parameters

- **bpe_head_ent_emb**
- **bpe_rel_ent_emb**
- **E**

forward_k_vs_all(*x*)

Parameters

x

forward_k_vs_sample(*x*, *target_entity_idx*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.**OMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

> **Note**
>
> As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'OMult'

static octonion_normalizer(*emb_rel_e0*, *emb_rel_e1*, *emb_rel_e2*, *emb_rel_e3*, *emb_rel_e4*, *emb_rel_e5*, *emb_rel_e6*, *emb_rel_e7*)

score(*head_ent_emb: torch.FloatTensor*, *rel_ent_emb: torch.FloatTensor*, *tail_ent_emb: torch.FloatTensor*)

k_vs_all_score(*bpe_head_ent_emb*, *bpe_rel_ent_emb*, *E*)

forward_k_vs_all(*x*)

Completed. Given a head entity and a relation (h,r), we compute scores for all possible triples,i.e., [score(h,r,x)|x in Entities] => [0.0,0.1,…,0.8], shape=> (1, |Entities|) Given a batch of head entities and relations => shape (size of batch,| Entities|)

class dicee.**Shallom**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

A shallow neural model for relation prediction (https://arxiv.org/abs/2101.09090)

name = 'Shallom'

shallom_width

shallom

get_embeddings() → Tuple[numpy.ndarray, None]

forward_k_vs_all(*x*) → torch.FloatTensor

forward_triples(*x*) → torch.FloatTensor

Parameters
x

Returns

class dicee.**LFMult**(*args*)

Bases: *dicee.models.base_model.BaseKGE*

Embedding with polynomial functions. We represent all entities and relations in the polynomial space as: f(x) = sum_{i=0}^{d-1} a_k x^{i%d} and use the three differents scoring function as in the paper to evaluate the score. We also consider combining with Neural Networks.

name = 'LFMult'

entity_embeddings

relation_embeddings

degree

m

x_values

forward_triples(*idx_triple*)

Parameters
x

construct_multi_coeff(*x*)

poly_NN(*x*, *coefh*, *coefr*, *coeft*)

Constructing a 2 layers NN to represent the embeddings. h = sigma(wh^T x + bh), r = sigma(wr^T x + br), t = sigma(wt^T x + bt)

linear(*x*, *w*, *b*)

scalar_batch_NN(*a*, *b*, *c*)

element wise multiplication between a,b and c: Inputs : a, b, c ====> torch.tensor of size batch_size x m x d Output : a tensor of size batch_size x d

tri_score(*coeff_h*, *coeff_r*, *coeff_t*)

this part implement the trilinear scoring techniques:

score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k = 0}^{d-1} dfrac{a_i*b_j*c_k}{1+(i+j+k)%d}

1. generate the range for i,j and k from [0 d-1]
2. perform dfrac{a_i*b_j*c_k}{1+(i+j+k)%d} in parallel for every batch
3. take the sum over each batch

vtp_score(*h*, *r*, *t*)

this part implement the vector triple product scoring techniques:

score(h,r,t) = int_{0}{1} h(x)r(x)t(x) dx = sum_{i,j,k = 0}^{d-1} dfrac{a_i*c_j*b_k - b_i*c_j*a_k}{(1+(i+j)%d)(1+k)}

1. generate the range for i,j and k from [0 d-1]
2. Compute the first and second terms of the sum
3. Multiply with then denominator and take the sum
4. take the sum over each batch

comp_func(*h*, *r*, *t*)

this part implement the function composition scoring techniques: i.e. score = <hor, t>

polynomial(*coeff*, *x*, *degree*)

This function takes a matrix tensor of coefficients (coeff), a tensor vector of points x and range of integer [0,1,…d] and return a vector tensor (coeff[0][0] + coeff[0][1]x +…+ coeff[0][d]x^d,

coeff[1][0] + coeff[1][1]x +…+ coeff[1][d]x^d)

pop(*coeff*, *x*, *degree*)

This function allow us to evaluate the composition of two polynomes without for loops :) it takes a matrix tensor of coefficients (coeff), a matrix tensor of points x and range of integer [0,1,…d]

and return a tensor (coeff[0][0] + coeff[0][1]x +…+ coeff[0][d]x^d,

coeff[1][0] + coeff[1][1]x +…+ coeff[1][d]x^d)

class dicee.**PykeenKGE**(*args: dict*)

Bases: *dicee.models.base_model.BaseKGE*

A class for using knowledge graph embedding models implemented in Pykeen

Notes: Pykeen_DistMult: C Pykeen_ComplEx: Pykeen_QuatE: Pykeen_MuRE: Pykeen_CP: Pykeen_HolE: Pykeen_HolE:

model_kwargs

name

model

loss_history = []

args

entity_embeddings = None

relation_embeddings = None

forward_k_vs_all(*x: torch.LongTensor*)

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads and relations + apply Dropout & Normalization if given. h, r = self.get_head_relation_representation(x) # (2) Reshape (1). if self.last_dim > 0:

h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim)

(3) Reshape all entities. if self.last_dim > 0:

t = self.entity_embeddings.weight.reshape(self.num_entities, self.embedding_dim, self.last_dim)

else:

t = self.entity_embeddings.weight

(4) Call the score_t from interactions to generate triple scores. return self.interaction.score_t(h=h, r=r, all_entities=t, slice_size=1)

forward_triples (*x: torch.LongTensor*) → torch.FloatTensor

=> Explicit version by this we can apply bn and dropout

(1) Retrieve embeddings of heads, relations and tails and apply Dropout & Normalization if given. h, r, t = self.get_triple_representation(x) # (2) Reshape (1). if self.last_dim > 0:

h = h.reshape(len(x), self.embedding_dim, self.last_dim) r = r.reshape(len(x), self.embedding_dim, self.last_dim) t = t.reshape(len(x), self.embedding_dim, self.last_dim)

(3) Compute the triple score return self.interaction.score(h=h, r=r, t=t, slice_size=None, slice_dim=0)

abstract forward_k_vs_sample (*x: torch.LongTensor*, *target_entity_idx*)

class dicee.**BytE**(**args*, ***kwargs*)

Bases: *dicee.models.base_model.BaseKGE*

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

name = 'BytE'

config

temperature = 0.5

topk = 2

transformer

lm_head

weight

loss_function(*yhat_batch*, *y_batch*)

Parameters

- **yhat_batch**
- **y_batch**

forward(*x: torch.LongTensor*)

Parameters

x (*B by T tensor*)

generate(*idx*, *max_new_tokens*, *temperature=1.0*, *top_k=None*)

Take a conditioning sequence of indices idx (LongTensor of shape (b,t)) and complete the sequence max_new_tokens times, feeding the predictions back into the model each time. Most likely you'll want to make sure to be in model.eval() mode of operation for this.

training_step(*batch*, *batch_idx=None*)

Here you compute and return the training loss and some additional metrics for e.g. the progress bar or logger.

Parameters

- **batch** – The output of your data iterable, normally a `DataLoader`.
- **batch_idx** – The index of this batch.
- **dataloader_idx** – The index of the dataloader that produced this batch. (only if multiple dataloaders used)

Returns

- `Tensor` - The loss tensor
- `dict` - A dictionary which can include any keys, but must include the key `'loss'` in the case of automatic optimization.
- `None` - In automatic optimization, this will skip to the next batch (but is not supported for multi-GPU, TPU, or DeepSpeed). For manual optimization, this has no special meaning, as returning the loss is not required.

In this step you'd normally do the forward pass and calculate the loss for a batch. You can also do fancier things like multiple forward passes or something model specific.

Example:

```
def training_step(self, batch, batch_idx):
    x, y, z = batch
    out = self.encoder(x)
    loss = self.loss(out, x)
    return loss
```

To use multiple optimizers, you can switch to 'manual optimization' and control their stepping:

```
def __init__(self):
    super().__init__()
    self.automatic_optimization = False


# Multiple optimizers (e.g.: GANs)
def training_step(self, batch, batch_idx):
    opt1, opt2 = self.optimizers()

    # do training_step with encoder
    ...
    opt1.step()
    # do training_step with decoder
    ...
    opt2.step()
```

Note

When `accumulate_grad_batches` > 1, the loss returned here will be automatically normalized by `accumulate_grad_batches` internally.

class dicee.**BaseKGE**(*args: dict*)

Bases: `BaseKGELightning`

Base class for all neural network modules.

Your models should also subclass this class.

Modules can also contain other Modules, allowing to nest them in a tree structure. You can assign the submodules as regular attributes:

```
import torch.nn as nn
import torch.nn.functional as F

class Model(nn.Module):
    def __init__(self):
        super().__init__()
        self.conv1 = nn.Conv2d(1, 20, 5)
        self.conv2 = nn.Conv2d(20, 20, 5)

    def forward(self, x):
        x = F.relu(self.conv1(x))
        return F.relu(self.conv2(x))
```

Submodules assigned in this way will be registered, and will have their parameters converted too when you call `to()`, etc.

Note

As per the example above, an `__init__()` call to the parent class must be made before assignment on the child.

Variables

training (*bool*) – Boolean represents whether this module is in training or evaluation mode.

args

embedding_dim = None

num_entities = None

num_relations = None

num_tokens = None

learning_rate = None

apply_unit_norm = None

input_dropout_rate = None

hidden_dropout_rate = None

optimizer_name = None

feature_map_dropout_rate = None

kernel_size = None

num_of_output_channels = None

weight_decay = None

loss

selected_optimizer = None

normalizer_class = None

normalize_head_entity_embeddings

normalize_relation_embeddings

normalize_tail_entity_embeddings

hidden_normalizer

param_init

input_dp_ent_real

input_dp_rel_real

hidden_dropout

loss_history = []

byte_pair_encoding

max_length_subword_tokens

block_size

forward_byte_pair_encoded_k_vs_all(*x: torch.LongTensor*)

Parameters

x (*B x 2 x T*)

forward_byte_pair_encoded_triple(*x: Tuple[torch.LongTensor, torch.LongTensor]*)

byte pair encoded neural link predictors

Parameters

----

init_params_with_sanity_checking()

forward(*x: torch.LongTensor | Tuple[torch.LongTensor, torch.LongTensor]*, *y_idx: torch.LongTensor = None*)

Parameters

- **x**
- **y_idx**
- **ordered_bpe_entities**

forward_triples(*x: torch.LongTensor*) → torch.Tensor

Parameters

x

forward_k_vs_all(**args*, ***kwargs*)

forward_k_vs_sample(**args*, ***kwargs*)

get_triple_representation(*idx_hrt*)

get_head_relation_representation(*indexed_triple*)

get_sentence_representation(*x: torch.LongTensor*)

Parameters

- **(b** (*x shape*)
- **3**
- **t)**

get_bpe_head_and_relation_representation(*x: torch.LongTensor*)
→ Tuple[torch.FloatTensor, torch.FloatTensor]

Parameters

x (*B x 2 x T*)

get_embeddings() → Tuple[numpy.ndarray, numpy.ndarray]

dicee.**create_recipriocal_triples**(*x*)

Add inverse triples into dask dataframe :param x: :return:

dicee.**get_er_vocab**(*data*, *file_path: str = None*)

dicee.**get_re_vocab**(*data*, *file_path: str = None*)

dicee.**get_ee_vocab**(*data*, *file_path: str = None*)

dicee.**timeit**(*func*)

dicee.**save_pickle**(***, *data: object = None*, *file_path=str*)

dicee.**load_pickle**(*file_path=str*)

dicee.**select_model**(*args: dict*, *is_continual_training: bool = None*, *storage_path: str = None*)

dicee.**load_model**(*path_of_experiment_folder: str*, *model_name='model.pt'*, *verbose=0*)
→ Tuple[object, Tuple[dict, dict]]

Load weights and initialize pytorch module from namespace arguments

dicee.**load_model_ensemble**(*path_of_experiment_folder: str*)
→ Tuple[*dicee.models.base_model.BaseKGE*, Tuple[pandas.DataFrame, pandas.DataFrame]]

Construct Ensemble Of weights and initialize pytorch module from namespace arguments

(1) Detect models under given path

(2) Accumulate parameters of detected models

(3) Normalize parameters

(4) Insert (3) into model.

dicee.**save_numpy_ndarray**(*, *data: numpy.ndarray*, *file_path: str*)

dicee.**numpy_data_type_changer**(*train_set: numpy.ndarray*, *num: int*) → numpy.ndarray

Detect most efficient data type for a given triples :param train_set: :param num: :return:

dicee.**save_checkpoint_model**(*model*, *path: str*) → None

Store Pytorch model into disk

dicee.**store**(*trainer*, *trained_model*, *model_name: str = 'model'*, *full_storage_path: str = None*, *save_embeddings_as_csv=False*) → None

Store trained_model model and save embeddings into csv file. :param trainer: an instance of trainer class :param full_storage_path: path to save parameters. :param model_name: string representation of the name of the model. :param trained_model: an instance of BaseKGE see core.models.base_model . :param save_embeddings_as_csv: for easy access of embeddings. :return:

dicee.**add_noisy_triples**(*train_set: pandas.DataFrame*, *add_noise_rate: float*) → pandas.DataFrame

Add randomly constructed triples :param train_set: :param add_noise_rate: :return:

dicee.**read_or_load_kg**(*args*, *cls*)

dicee.**intialize_model**(*args: dict*, *verbose=0*) → Tuple[object, str]

dicee.**load_json**(*p: str*) → dict

dicee.**save_embeddings**(*embeddings: numpy.ndarray*, *indexes*, *path: str*) → None

Save it as CSV if memory allows. :param embeddings: :param indexes: :param path: :return:

dicee.**random_prediction**(*pre_trained_kge*)

dicee.**deploy_triple_prediction**(*pre_trained_kge*, *str_subject*, *str_predicate*, *str_object*)

dicee.**deploy_tail_entity_prediction**(*pre_trained_kge*, *str_subject*, *str_predicate*, *top_k*)

dicee.**deploy_head_entity_prediction**(*pre_trained_kge*, *str_object*, *str_predicate*, *top_k*)

dicee.**deploy_relation_prediction**(*pre_trained_kge*, *str_subject*, *str_object*, *top_k*)

dicee.**vocab_to_parquet**(*vocab_to_idx*, *name*, *path_for_serialization*, *print_into*)

dicee.**create_experiment_folder**(*folder_name='Experiments'*)

dicee.**continual_training_setup_executor**(*executor*) → None

storage_path:str A path leading to a parent directory, where a subdirectory containing KGE related data

full_storage_path:str A path leading to a subdirectory containing KGE related data

dicee.**exponential_function**(*x: numpy.ndarray*, *lam: float*, *ascending_order=True*) → torch.FloatTensor

dicee.**load_numpy**(*path*) → numpy.ndarray

dicee.**evaluate**(*entity_to_idx*, *scores*, *easy_answers*, *hard_answers*)

@TODO: CD: Renamed this function Evaluate multi hop query answering on different query types

dicee.**download_file**(*url*, *destination_folder='.'*)

dicee.**download_files_from_url**(*base_url: str*, *destination_folder='.'*) → None

Parameters

- **base_url** (e.g. "https://files.dice-research.org/projects/DiceEmbeddings/KINSHIP-Keci-dim128-epoch256-KvsAll")
- **destination_folder**(*e.g. "KINSHIP-Keci-dim128-epoch256-KvsAll"*)

dicee.**download_pretrained_model**(*url: str*) → str

class dicee.**DICE_Trainer**(*args*, *is_continual_training*, *storage_path*, *evaluator=None*)

DICE_Trainer implement

1- Pytorch Lightning trainer (https://pytorch-lightning.readthedocs.io/en/stable/common/trainer.html) 2- Multi-GPU Trainer(https://pytorch.org/docs/stable/generated/torch.nn.parallel.DistributedDataParallel.html) 3- CPU Trainer

args

is_continual_training:bool

storage_path:str

evaluator:

report:dict

report

args

trainer = None

is_continual_training

storage_path

evaluator

form_of_labelling = None

continual_start()

(1) Initialize training.

(2) Load model

(3) Load trainer (3) Fit model

Parameter

returns

- *model*
- **form_of_labelling** (*str*)

initialize_trainer(*callbacks: List*) → lightning.Trainer

Initialize Trainer from input arguments

initialize_or_load_model()

initialize_dataloader(*dataset: torch.utils.data.Dataset*) → torch.utils.data.DataLoader

initialize_dataset(*dataset: dicee.knowledge_graph.KG*, *form_of_labelling*)
→ torch.utils.data.Dataset

start(*knowledge_graph: dicee.knowledge_graph.KG*) → Tuple[*dicee.models.base_model.BaseKGE*, str]

Train selected model via the selected training strategy

k_fold_cross_validation(*dataset*) → Tuple[*dicee.models.base_model.BaseKGE*, str]

Perform K-fold Cross-Validation

1. Obtain K train and test splits.
2. **For each split,**
   2.1 initialize trainer and model 2.2. Train model with configuration provided in args. 2.3. Compute the mean reciprocal rank (MRR) score of the model on the test respective split.
3. Report the mean and average MRR .

Parameters

- **self**
- **dataset**

Returns
model

class dicee.**KGE**(*path=None*, *url=None*, *construct_ensemble=False*, *model_name=None*)

Bases: *dicee.abstracts.BaseInteractiveKGE*

Knowledge Graph Embedding Class for interactive usage of pre-trained models

__str__()

Return str(self).

to(*device: str*) → None

get_transductive_entity_embeddings(*indices: torch.LongTensor | List[str]*,
as_pytorch=False, *as_numpy=False*, *as_list=True*)
→ torch.FloatTensor | numpy.ndarray | List[float]

create_vector_database(*collection_name: str*, *distance: str*, *location: str = 'localhost'*,
port: int = 6333)

generate(*h=''*, *r=''*)

eval_lp_performance(*dataset=List[Tuple[str, str, str]]*, *filtered=True*)

predict_missing_head_entity(*relation: List[str] | str*, *tail_entity: List[str] | str*, *within=None*) → Tuple

Given a relation and a tail entity, return top k ranked head entity.

argmax_{e in E } f(e,r,t), where r in R, t in E.

Parameter

relation: Union[List[str], str]

String representation of selected relations.

tail_entity: Union[List[str], str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_relations(*head_entity: List[str] | str*, *tail_entity: List[str] | str*, *within=None*) → Tuple

Given a head entity and a tail entity, return top k ranked relations.

argmax_{r in R } f(h,r,t), where h, t in E.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

k: int

Highest ranked k entities.

Returns: Tuple

Highest K scores and entities

predict_missing_tail_entity(*head_entity: List[str] | str*, *relation: List[str] | str*, *within: List[str] = None*) → torch.FloatTensor

Given a head entity and a relation, return top k ranked entities

argmax_{e in E } f(h,r,e), where h in E and r in R.

Parameter

head_entity: List[str]

String representation of selected entities.

tail_entity: List[str]

String representation of selected entities.

Returns: Tuple

scores

predict (*, *h: List[str] | str = None*, *r: List[str] | str = None*, *t: List[str] | str = None*, *within=None*, *logits=True*) → torch.FloatTensor

Parameters

- **logits**
- **h**
- **r**
- **t**
- **within**

predict_topk (*, *h: List[str] = None*, *r: List[str] = None*, *t: List[str] = None*, *topk: int = 10*, *within: List[str] = None*)

Predict missing item in a given triple.

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

k: int

Highest ranked k item.

Returns: Tuple

Highest K scores and items

triple_score(*h: List[str] | str = None*, *r: List[str] | str = None*, *t: List[str] | str = None*, *logits=False*)
→ torch.FloatTensor

Predict triple score

Parameter

head_entity: List[str]

String representation of selected entities.

relation: List[str]

String representation of selected relations.

tail_entity: List[str]

String representation of selected entities.

logits: bool

If logits is True, unnormalized score returned

Returns: Tuple

pytorch tensor of triple score

t_norm(*tens_1: torch.Tensor*, *tens_2: torch.Tensor*, *tnorm: str = 'min'*) → torch.Tensor

tensor_t_norm(*subquery_scores: torch.FloatTensor*, *tnorm: str = 'min'*) → torch.FloatTensor

Compute T-norm over [0,1] ^{n imes d} where n denotes the number of hops and d denotes number of entities

t_conorm(*tens_1: torch.Tensor*, *tens_2: torch.Tensor*, *tconorm: str = 'min'*) → torch.Tensor

negnorm(*tens_1: torch.Tensor*, *lambda_: float*, *neg_norm: str = 'standard'*) → torch.Tensor

return_multi_hop_query_results(*aggregated_query_for_all_entities*, *k: int*, *only_scores*)

single_hop_query_answering(*query: tuple*, *only_scores: bool = True*, *k: int = None*)

answer_multi_hop_query(*query_type: str = None*,
query: Tuple[str | Tuple[str, str], Ellipsis] = None,
queries: List[Tuple[str | Tuple[str, str], Ellipsis]] = None, *tnorm: str = 'prod'*,
neg_norm: str = 'standard', *lambda_: float = 0.0*, *k: int = 10*, *only_scores=False*)
→ List[Tuple[str, torch.Tensor]]

@TODO: Refactoring is needed # @TODO: Score computation for each query type should be done in a static function

Find an answer set for EPFO queries including negation and disjunction

Parameter

query_type: str The type of the query, e.g., “2p”.

query: Union[str, Tuple[str, Tuple[str, str]]] The query itself, either a string or a nested tuple.

queries: List of Tuple[Union[str, Tuple[str, str]], …]

tnorm: str The t-norm operator.

neg_norm: str The negation norm.

lambda_: float lambda parameter for sugeno and yager negation norms

k: int The top-k substitutions for intermediate variables.

returns

- *List[Tuple[str, torch.Tensor]]*
- *Entities and corresponding scores sorted in the descening order of scores*

find_missing_triples (*confidence: float*, *entities: List[str] = None*, *relations: List[str] = None*, *topk: int = 10*, *at_most: int = sys.maxsize*) → Set

Find missing triples

Iterative over a set of entities E and a set of relation R :

orall e in E and orall r in R f(e,r,x)

Return (e,r,x)

otin G and f(e,r,x) > confidence

confidence: float

A threshold for an output of a sigmoid function given a triple.

topk: int

Highest ranked k item to select triples with f(e,r,x) > confidence .

at_most: int

Stop after finding at_most missing triples

{(e,r,x) | f(e,r,x) > confidence land (e,r,x)

otin G

deploy (*share: bool = False*, *top_k: int = 10*)

train_triples (*h: List[str]*, *r: List[str]*, *t: List[str]*, *labels: List[float]*, *iteration=2*, *optimizer=None*)

train_k_vs_all (*h*, *r*, *iteration=1*, *lr=0.001*)

Train k vs all :param head_entity: :param relation: :param iteration: :param lr: :return:

train (*kg*, *lr=0.1*, *epoch=10*, *batch_size=32*, *neg_sample_ratio=10*, *num_workers=1*) → None

Retrained a pretrain model on an input KG via negative sampling.

class dicee.**Execute** (*args*, *continuous_training=False*)

A class for Training, Retraining and Evaluation a model.

(1) Loading & Preprocessing & Serializing input data.

(2) Training & Validation & Testing

(3) Storing all necessary info

args

is_continual_training

trainer = None

trained_model = None

knowledge_graph = None

report

evaluator = None

start_time = None

read_or_load_kg()

read_preprocess_index_serialize_data() → None

Read & Preprocess & Index & Serialize Input Data

(1) Read or load the data from disk into memory.

(2) Store the statistics of the data.

Parameter

rtype
None

load_indexed_data() → None

Load the indexed data from disk into memory

Parameter

rtype
None

save_trained_model() → None

Save a knowledge graph embedding model

(1) Send model to eval mode and cpu.

(2) Store the memory footprint of the model.

(3) Save the model into disk.

(4) Update the stats of KG again ?

Parameter

rtype
None

end(*form_of_labelling: str*) → dict

End training

(1) Store trained model.

(2) Report runtimes.

(3) Eval model if required.

Parameter

rtype
A dict containing information about the training and/or evaluation

write_report() → None

Report training related information in a report.json file

start() → dict

Start training

(1) Loading the Data # (2) Create an evaluator object. # (3) Create a trainer object. # (4) Start the training

Parameter

rtype
A dict containing information about the training and/or evaluation

dicee.**mapping_from_first_two_cols_to_third**(*train_set_idx*)

dicee.**timeit**(*func*)

dicee.**load_pickle**(*file_path=str*)

dicee.**reload_dataset**(*path: str*, *form_of_labelling*, *scoring_technique*, *neg_ratio*, *label_smoothing_rate*)

Reload the files from disk to construct the Pytorch dataset

dicee.**construct_dataset**(*, *train_set: numpy.ndarray | list*, *valid_set=None*, *test_set=None*, *ordered_bpe_entities=None*, *train_target_indices=None*, *target_dim: int = None*, *entity_to_idx: dict*, *relation_to_idx: dict*, *form_of_labelling: str*, *scoring_technique: str*, *neg_ratio: int*, *label_smoothing_rate: float*, *byte_pair_encoding=None*, *block_size: int = None*) → torch.utils.data.Dataset

class dicee.**BPE_NegativeSamplingDataset**(*train_set: torch.LongTensor*, *ordered_shaped_bpe_entities: torch.LongTensor*, *neg_ratio: int*)

Bases: `torch.utils.data.Dataset`

An abstract class representing a `Dataset`.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite *__getitem__()*, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite *__len__()*, which is expected to return the size of the dataset by many `Sampler` implementations and the

default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

> **Note**
>
> `DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

train_set

ordered_bpe_entities

num_bpe_entities

neg_ratio

num_datapoints

__len__()

__getitem__(*idx*)

collate_fn(*batch_shaped_bpe_triples: List[Tuple[torch.Tensor, torch.Tensor]]*)

class dicee.**MultiLabelDataset**(*train_set: torch.LongTensor*, *train_indices_target: torch.LongTensor*, *target_dim: int*, *torch_ordered_shaped_bpe_entities: torch.LongTensor*)

Bases: `torch.utils.data.Dataset`

An abstract class representing a `Dataset`.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite *__getitem__()*, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite *__len__()*, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

> **Note**
>
> `DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

train_set

train_indices_target

target_dim

num_datapoints

torch_ordered_shaped_bpe_entities

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.**MultiClassClassificationDataset**(*subword_units: numpy.ndarray*, *block_size: int = 8*)

Bases: `torch.utils.data.Dataset`

Dataset for the 1vsALL training strategy

Parameters

- **train_set_idx** – Indexed triples for the training.
- **entity_idxs** – mapping.
- **relation_idxs** – mapping.
- **form** – ?
- **num_workers** – int for https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader

Return type
torch.utils.data.Dataset

train_data

block_size

num_of_data_points

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.**OnevsAllDataset**(*train_set_idx: numpy.ndarray*, *entity_idxs*)

Bases: `torch.utils.data.Dataset`

Dataset for the 1vsALL training strategy

Parameters

- **train_set_idx** – Indexed triples for the training.
- **entity_idxs** – mapping.
- **relation_idxs** – mapping.
- **form** – ?
- **num_workers** – int for https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader

Return type
torch.utils.data.Dataset

train_data

target_dim

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.**KvsAll**(*train_set_idx: numpy.ndarray*, *entity_idxs*, *relation_idxs*, *form*, *store=None*, *label_smoothing_rate: float = 0.0*)

Bases: `torch.utils.data.Dataset`

Creates a dataset for KvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for KvsAll training and be defined as D:= {(x,y)_i}_i ^N, where x: (h,r) is an unique tuple of an entity h in E and a relation r in R that has been seed in the input graph. y: denotes a multi-label vector in [0,1]^{|E|} is a binary label.

orall y_i =1 s.t. (h r E_i) in KG

> **Note**
>
> TODO

train_set_idx

[numpy.ndarray] n by 3 array representing n triples

entity_idxs

[dictonary] string representation of an entity to its integer id

relation_idxs

[dictonary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = KvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

collate_fn = None

__len__()

__getitem__(*idx*)

class dicee.**AllvsAll**(*train_set_idx: numpy.ndarray*, *entity_idxs*, *relation_idxs*, *label_smoothing_rate=0.0*)

Bases: `torch.utils.data.Dataset`

Creates a dataset for AllvsAll training by inheriting from torch.utils.data.Dataset.

Let D denote a dataset for AllvsAll training and be defined as D:= {(x,y)_i}_i ^N, where x: (h,r) is a possible unique tuple of an entity h in E and a relation r in R. Hence N = |E| x |R| y: denotes a multi-label vector in [0,1]^{|E|} is a binary label.

orall y_i =1 s.t. (h r E_i) in KG

> **Note**

AllvsAll extends KvsAll via none existing (h,r). Hence, it adds data points that are labelled without 1s,
only with 0s.

train_set_idx
[numpy.ndarray] n by 3 array representing n triples

entity_idxs
[dictonary] string representation of an entity to its integer id

relation_idxs
[dictonary] string representation of a relation to its integer id

self : torch.utils.data.Dataset

```
>>> a = AllvsAll()
>>> a
? array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

train_data = None

train_target = None

label_smoothing_rate

collate_fn = None

target_dim

store

__len__()

__getitem__(*idx*)

class dicee.**KvsSampleDataset**(*train_set: numpy.ndarray*, *num_entities*, *num_relations*, *neg_sample_ratio: int = None*, *label_smoothing_rate: float = 0.0*)

Bases: torch.utils.data.Dataset

KvsSample a Dataset:

D:= {(x,y)_i}_i ^N, where
. x:(h,r) is a unique h in E and a relation r in R and . y in [0,1]^{|E|} is a binary label.

orall y_i =1 s.t. (h r E_i) in KG

At each mini-batch construction, we subsample(y), hence n
|new_y| << **|E|** new_y contains all 1's if sum(y)< neg_sample ratio new_y contains

train_set_idx
Indexed triples for the training.

entity_idxs
mapping.

relation_idxs
mapping.

form
?

store
?

label_smoothing_rate
?

torch.utils.data.Dataset

train_data

num_entities

num_relations

neg_sample_ratio

label_smoothing_rate

collate_fn = None

store

train_target

__len__()

__getitem__(*idx*)

class dicee.**NegSampleDataset**(*train_set: numpy.ndarray*, *num_entities: int*, *num_relations: int*, *neg_sample_ratio: int = 1*)

Bases: `torch.utils.data.Dataset`

An abstract class representing a `Dataset`.

All datasets that represent a map from keys to data samples should subclass it. All subclasses should overwrite *`__getitem__()`*, supporting fetching a data sample for a given key. Subclasses could also optionally overwrite *`__len__()`*, which is expected to return the size of the dataset by many `Sampler` implementations and the default options of `DataLoader`. Subclasses could also optionally implement `__getitems__()`, for speedup batched samples loading. This method accepts list of indices of samples of batch and returns list of samples.

Note

`DataLoader` by default constructs an index sampler that yields integral indices. To make it work with a map-style dataset with non-integral indices/keys, a custom sampler must be provided.

neg_sample_ratio

train_set

length

num_entities

num_relations

__len__()

__getitem__(*idx*)

class dicee.**TriplePredictionDataset**(*train_set: numpy.ndarray*, *num_entities: int*, *num_relations: int*, *neg_sample_ratio: int = 1*, *label_smoothing_rate: float = 0.0*)

Bases: torch.utils.data.Dataset

Triple Dataset

D:= {(x)_i}_i ^N, where
. x:(h,r, t) in KG is a unique h in E and a relation r in R and . collact_fn => Generates negative triples

collect_fn:

orall (h,r,t) in G obtain, create negative triples{(h,r,x),(,r,t),(h,m,t)}

y:labels are represented in torch.float16

train_set_idx
Indexed triples for the training.

entity_idxs
mapping.

relation_idxs
mapping.

form
?

store
?

label_smoothing_rate

collate_fn: batch:List[torch.IntTensor] Returns ——- torch.utils.data.Dataset

label_smoothing_rate

neg_sample_ratio

train_set

length

num_entities

num_relations

__len__()

__getitem__(*idx*)

collate_fn(*batch: List[torch.Tensor]*)

class dicee.**CVDataModule**(*train_set_idx: numpy.ndarray*, *num_entities*, *num_relations*, *neg_sample_ratio*, *batch_size*, *num_workers*)

Bases: pytorch_lightning.LightningDataModule

Create a Dataset for cross validation

Parameters

- **train_set_idx** – Indexed triples for the training.
- **num_entities** – entity to index mapping.
- **num_relations** – relation to index mapping.
- **batch_size** – int
- **form** – ?
- **num_workers** – int for https://pytorch.org/docs/stable/data.html#torch.utils.data.DataLoader

Return type

?

train_set_idx

num_entities

num_relations

neg_sample_ratio

batch_size

num_workers

train_dataloader() → torch.utils.data.DataLoader

An iterable or collection of iterables specifying training samples.

For more information about multiple dataloaders, see this section.

The dataloader you return will not be reloaded unless you set **:paramref:`~pytorch_lightning.trainer.trainer.Trainer.reload_dataloaders_every_n_epochs`** to a positive integer.

For data processing use the following pattern:

- download in *prepare_data()*
- process and split in *setup()*

However, the above are only necessary for distributed processing.

> **Warning**
>
> do not assign state in prepare_data

- fit()
- *prepare_data()*
- *setup()*

> **Note**
>
> Lightning tries to add the correct sampler for distributed and arbitrary hardware. There is no need to set it yourself.

setup(**args*, ***kwargs*)

Called at the beginning of fit (train + validate), validate, test, or predict. This is a good hook when you need to build models dynamically or adjust something about them. This hook is called on every process when using DDP.

Parameters

stage – either `'fit'`, `'validate'`, `'test'`, or `'predict'`

Example:

```
class LitModel(...):
    def __init__(self):
        self.l1 = None

    def prepare_data(self):
        download_data()
        tokenize()

        # don't do this
        self.something = else

    def setup(self, stage):
        data = load_data(...)
        self.l1 = nn.Linear(28, data.num_classes)
```

transfer_batch_to_device(**args*, ***kwargs*)

Override this hook if your `DataLoader` returns tensors wrapped in a custom data structure.

The data types listed below (and any arbitrary nesting of them) are supported out of the box:

- `torch.Tensor` or anything that implements *.to(...)*
- `list`
- `dict`
- `tuple`

For anything else, you need to define how the data is moved to the target device (CPU, GPU, TPU, …).

> **Note**
>
> This hook should only transfer the data and not modify it, nor should it move the data to any other device than the one passed in as argument (unless you know what you are doing). To check the current state of execution of this hook you can use `self.trainer.training/testing/validating/predicting` so that you can add different logic as per your requirement.

Parameters

- **batch** – A batch of data that needs to be transferred to a new device.
- **device** – The target device as defined in PyTorch.

- **dataloader_idx** – The index of the dataloader to which the batch belongs.

Returns

A reference to the data on the new device.

Example:

```
def transfer_batch_to_device(self, batch, device, dataloader_idx):
    if isinstance(batch, CustomBatch):
        # move all tensors in your custom data structure to the device
        batch.samples = batch.samples.to(device)
        batch.targets = batch.targets.to(device)
    elif dataloader_idx == 0:
        # skip device transfer for the first dataloader or anything you wish
        pass
    else:
        batch = super().transfer_batch_to_device(batch, device, dataloader_
↪idx)
    return batch
```

See also

- `move_data_to_device()`
- `apply_to_collection()`

prepare_data(**args*, ***kwargs*)

Use this to download and prepare data. Downloading and saving data with multiple processes (distributed settings) will result in corrupted data. Lightning ensures this method is called only within a single process, so you can safely add your downloading logic within.

Warning

DO NOT set state to the model (use `setup` instead) since this is NOT called on every device

Example:

```
def prepare_data(self):
    # good
    download_data()
    tokenize()
    etc()

    # bad
    self.split = data_split
    self.some_state = some_other_state()
```

In a distributed environment, `prepare_data` can be called in two ways (using prepare_data_per_node)

1. Once per node. This is the default and is only called on LOCAL_RANK=0.
2. Once in total. Only called on GLOBAL_RANK=0.

Example:

```
# DEFAULT
# called once per node on LOCAL_RANK=0 of that node
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = True


# call on GLOBAL_RANK=0 (great for shared file systems)
class LitDataModule(LightningDataModule):
    def __init__(self):
        super().__init__()
        self.prepare_data_per_node = False
```

This is called before requesting the dataloaders:

```
model.prepare_data()
initialize_distributed()
model.setup(stage)
model.train_dataloader()
model.val_dataloader()
model.test_dataloader()
model.predict_dataloader()
```

class dicee.**QueryGenerator**(*train_path*, *val_path: str*, *test_path: str*, *ent2id: Dict = None*, *rel2id: Dict = None*, *seed: int = 1*, *gen_valid: bool = False*, *gen_test: bool = True*)

train_path

val_path

test_path

gen_valid

gen_test

seed

max_ans_num = 1000000.0

mode

ent2id

rel2id: Dict

ent_in: Dict

ent_out: Dict

query_name_to_struct

list2tuple(*list_data*)

tuple2list(*x: List | Tuple*) → List | Tuple

Convert a nested tuple to a nested list.

set_global_seed(*seed: int*)

Set seed

construct_graph(*paths: List[str]*) → Tuple[Dict, Dict]

Construct graph from triples Returns dicts with incoming and outgoing edges

fill_query(*query_structure: List[str | List]*, *ent_in: Dict*, *ent_out: Dict*, *answer: int*) → bool

Private method for fill_query logic.

achieve_answer(*query: List[str | List]*, *ent_in: Dict*, *ent_out: Dict*) → set

Private method for achieve_answer logic. @TODO: Document the code

write_links(*ent_out*, *small_ent_out*)

ground_queries(*query_structure: List[str | List]*, *ent_in: Dict*, *ent_out: Dict*, *small_ent_in: Dict*, *small_ent_out: Dict*, *gen_num: int*, *query_name: str*)

Generating queries and achieving answers

unmap(*query_type*, *queries*, *tp_answers*, *fp_answers*, *fn_answers*)

unmap_query(*query_structure*, *query*, *id2ent*, *id2rel*)

generate_queries(*query_struct: List*, *gen_num: int*, *query_type: str*)

Passing incoming and outgoing edges to ground queries depending on mode [train valid or text] and getting queries and answers in return @ TODO: create a class for each single query struct

save_queries(*query_type: str*, *gen_num: int*, *save_path: str*)

abstract load_queries(*path*)

get_queries(*query_type: str*, *gen_num: int*)

static save_queries_and_answers(*path: str*, *data: List[Tuple[str, Tuple[collections.defaultdict]]]*) → None

Save Queries into Disk

static load_queries_and_answers(*path: str*) → List[Tuple[str, Tuple[collections.defaultdict]]]

Load Queries from Disk to Memory

dicee.**__version__ = '0.1.4'**

Python Module Index

d

dicee, 12
dicee.abstracts, 115
dicee.analyse_experiments, 121
dicee.callbacks, 122
dicee.config, 130
dicee.dataset_classes, 133
dicee.eval_static_funcs, 143
dicee.evaluator, 144
dicee.executer, 146
dicee.knowledge_graph, 148
dicee.knowledge_graph_embeddings, 150
dicee.models, 12
dicee.models.base_model, 12
dicee.models.clifford, 21
dicee.models.complex, 29
dicee.models.dualE, 31
dicee.models.function_space, 33
dicee.models.octonion, 36
dicee.models.pykeen_models, 39
dicee.models.quaternion, 41
dicee.models.real, 44
dicee.models.static_funcs, 45
dicee.models.transformers, 46
dicee.query_generator, 154
dicee.read_preprocess_save_load_kg, 100
dicee.read_preprocess_save_load_kg.preprocess, 100
dicee.read_preprocess_save_load_kg.read_from_disk, 101
dicee.read_preprocess_save_load_kg.save_load_disk, 102
dicee.read_preprocess_save_load_kg.util, 103
dicee.sanity_checkers, 156
dicee.scripts, 106
dicee.scripts.index, 106
dicee.scripts.run, 107
dicee.scripts.serve, 107
dicee.static_funcs, 156
dicee.static_funcs_training, 159
dicee.static_preprocess_funcs, 160
dicee.trainer, 108
dicee.trainer.dice_trainer, 108
dicee.trainer.torch_trainer, 110
dicee.trainer.torch_trainer_ddp, 111

Index

Non-alphabetical

__call__() (*dicee.models.base_model.IdentityClass method*), 21
__call__() (*dicee.models.IdentityClass method*), 62, 73, 79
__getitem__() (*dicee.AllvsAll method*), 200
__getitem__() (*dicee.BPE_NegativeSamplingDataset method*), 197
__getitem__() (*dicee.dataset_classes.AllvsAll method*), 137
__getitem__() (*dicee.dataset_classes.BPE_NegativeSamplingDataset method*), 134
__getitem__() (*dicee.dataset_classes.KvsAll method*), 136
__getitem__() (*dicee.dataset_classes.KvsSampleDataset method*), 138
__getitem__() (*dicee.dataset_classes.MultiClassClassificationDataset method*), 135
__getitem__() (*dicee.dataset_classes.MultiLabelDataset method*), 134
__getitem__() (*dicee.dataset_classes.NegSampleDataset method*), 139
__getitem__() (*dicee.dataset_classes.OnevsAllDataset method*), 135
__getitem__() (*dicee.dataset_classes.TriplePredictionDataset method*), 139
__getitem__() (*dicee.KvsAll method*), 199
__getitem__() (*dicee.KvsSampleDataset method*), 201
__getitem__() (*dicee.MultiClassClassificationDataset method*), 198
__getitem__() (*dicee.MultiLabelDataset method*), 197
__getitem__() (*dicee.NegSampleDataset method*), 202
__getitem__() (*dicee.OnevsAllDataset method*), 198
__getitem__() (*dicee.TriplePredictionDataset method*), 202
__iter__() (*dicee.config.Namespace method*), 132
__len__() (*dicee.AllvsAll method*), 200
__len__() (*dicee.BPE_NegativeSamplingDataset method*), 197
__len__() (*dicee.dataset_classes.AllvsAll method*), 137
__len__() (*dicee.dataset_classes.BPE_NegativeSamplingDataset method*), 134
__len__() (*dicee.dataset_classes.KvsAll method*), 136
__len__() (*dicee.dataset_classes.KvsSampleDataset method*), 138
__len__() (*dicee.dataset_classes.MultiClassClassificationDataset method*), 135
__len__() (*dicee.dataset_classes.MultiLabelDataset method*), 134
__len__() (*dicee.dataset_classes.NegSampleDataset method*), 138
__len__() (*dicee.dataset_classes.OnevsAllDataset method*), 135
__len__() (*dicee.dataset_classes.TriplePredictionDataset method*), 139
__len__() (*dicee.KvsAll method*), 199
__len__() (*dicee.KvsSampleDataset method*), 201
__len__() (*dicee.MultiClassClassificationDataset method*), 198
__len__() (*dicee.MultiLabelDataset method*), 197
__len__() (*dicee.NegSampleDataset method*), 201
__len__() (*dicee.OnevsAllDataset method*), 198
__len__() (*dicee.TriplePredictionDataset method*), 202
__str__() (*dicee.KGE method*), 190
__str__() (*dicee.knowledge_graph_embeddings.KGE method*), 150
__version__ (*in module dicee*), 207

A

AbstractCallback (*class in dicee.abstracts*), 118
AbstractPPECallback (*class in dicee.abstracts*), 120
AbstractTrainer (*class in dicee.abstracts*), 115
AccumulateEpochLossCallback (*class in dicee.callbacks*), 123
achieve_answer() (*dicee.query_generator.QueryGenerator method*), 155
achieve_answer() (*dicee.QueryGenerator method*), 207
AConEx (*class in dicee*), 174
AConEx (*class in dicee.models*), 69
AConEx (*class in dicee.models.complex*), 30
AConvO (*class in dicee*), 175
AConvO (*class in dicee.models*), 81
AConvO (*class in dicee.models.octonion*), 39
AConvQ (*class in dicee*), 175
AConvQ (*class in dicee.models*), 76
AConvQ (*class in dicee.models.quaternion*), 43
adaptive_swa (*dicee.config.Namespace attribute*), 132
add_new_entity_embeddings() (*dicee.abstracts.BaseInteractiveKGE method*), 118
add_noise_rate (*dicee.config.Namespace attribute*), 131
add_noise_rate (*dicee.knowledge_graph.KG attribute*), 148

add_noisy_triples() (*in module dicee*), 188
add_noisy_triples() (*in module dicee.static_funcs*), 158
add_noisy_triples_into_training() (*dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk method*), 102
add_noisy_triples_into_training() (*dicee.read_preprocess_save_load_kg.ReadFromDisk method*), 106
add_reciprical (*dicee.knowledge_graph.KG attribute*), 149
AllvsAll (*class in dicee*), 199
AllvsAll (*class in dicee.dataset_classes*), 136
alphas (*dicee.abstracts.AbstractPPECallback attribute*), 120
alphas (*dicee.callbacks.ASWA attribute*), 127
analyse() (*in module dicee.analyse_experiments*), 122
answer_multi_hop_query() (*dicee.KGE method*), 193
answer_multi_hop_query() (*dicee.knowledge_graph_embeddings.KGE method*), 153
app (*in module dicee.scripts.serve*), 108
apply_coefficients() (*dicee.DeCaL method*), 170
apply_coefficients() (*dicee.Keci method*), 167
apply_coefficients() (*dicee.models.clifford.DeCaL method*), 27
apply_coefficients() (*dicee.models.clifford.Keci method*), 24
apply_coefficients() (*dicee.models.DeCaL method*), 88
apply_coefficients() (*dicee.models.Keci method*), 83
apply_reciprical_or_noise() (*in module dicee.read_preprocess_save_load_kg.util*), 103
apply_semantic_constraint (*dicee.abstracts.BaseInteractiveKGE attribute*), 117
apply_unit_norm (*dicee.BaseKGE attribute*), 186
apply_unit_norm (*dicee.models.base_model.BaseKGE attribute*), 18
apply_unit_norm (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
args (*dicee.BaseKGE attribute*), 186
args (*dicee.DICE_Trainer attribute*), 189
args (*dicee.evaluator.Evaluator attribute*), 145
args (*dicee.Execute attribute*), 195
args (*dicee.executer.ContinuousExecute attribute*), 148
args (*dicee.executer.Execute attribute*), 146
args (*dicee.models.base_model.BaseKGE attribute*), 18
args (*dicee.models.base_model.IdentityClass attribute*), 21
args (*dicee.models.BaseKGE attribute*), 60, 63, 66, 71, 77, 91, 94
args (*dicee.models.IdentityClass attribute*), 62, 73, 79
args (*dicee.models.pykeen_models.PykeenKGE attribute*), 40
args (*dicee.models.PykeenKGE attribute*), 93
args (*dicee.PykeenKGE attribute*), 182
args (*dicee.trainer.DICE_Trainer attribute*), 113
args (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 109
ASWA (*class in dicee.callbacks*), 126
aswa (*dicee.analyse_experiments.Experiment attribute*), 121
attn (*dicee.models.transformers.Block attribute*), 51
attn_dropout (*dicee.models.transformers.CausalSelfAttention attribute*), 49
attributes (*dicee.abstracts.AbstractTrainer attribute*), 115

B

backend (*dicee.config.Namespace attribute*), 131
backend (*dicee.knowledge_graph.KG attribute*), 149
BaseInteractiveKGE (*class in dicee.abstracts*), 116
BaseKGE (*class in dicee*), 185
BaseKGE (*class in dicee.models*), 59, 62, 66, 70, 76, 90, 93
BaseKGE (*class in dicee.models.base_model*), 18
BaseKGELightning (*class in dicee.models*), 54
BaseKGELightning (*class in dicee.models.base_model*), 12
batch_kronecker_product() (*dicee.callbacks.KronE static method*), 129
batch_size (*dicee.analyse_experiments.Experiment attribute*), 121
batch_size (*dicee.callbacks.PseudoLabellingCallback attribute*), 126
batch_size (*dicee.config.Namespace attribute*), 130
batch_size (*dicee.CVDataModule attribute*), 203
batch_size (*dicee.dataset_classes.CVDataModule attribute*), 140
bias (*dicee.models.transformers.GPTConfig attribute*), 51
bias (*dicee.models.transformers.LayerNorm attribute*), 48
Block (*class in dicee.models.transformers*), 50
block_size (*dicee.BaseKGE attribute*), 186
block_size (*dicee.config.Namespace attribute*), 132
block_size (*dicee.dataset_classes.MultiClassClassificationDataset attribute*), 135
block_size (*dicee.models.base_model.BaseKGE attribute*), 19

block_size (*dicee.models.BaseKGE attribute*), 61, 64, 67, 72, 78, 91, 95
block_size (*dicee.models.transformers.GPTConfig attribute*), 51
block_size (*dicee.MultiClassClassificationDataset attribute*), 198
bn_conv1 (*dicee.AConvQ attribute*), 175
bn_conv1 (*dicee.ConvQ attribute*), 176
bn_conv1 (*dicee.models.AConvQ attribute*), 76
bn_conv1 (*dicee.models.ConvQ attribute*), 75
bn_conv1 (*dicee.models.quaternion.AConvQ attribute*), 43
bn_conv1 (*dicee.models.quaternion.ConvQ attribute*), 43
bn_conv2 (*dicee.AConvQ attribute*), 175
bn_conv2 (*dicee.ConvQ attribute*), 176
bn_conv2 (*dicee.models.AConvQ attribute*), 76
bn_conv2 (*dicee.models.ConvQ attribute*), 75
bn_conv2 (*dicee.models.quaternion.AConvQ attribute*), 43
bn_conv2 (*dicee.models.quaternion.ConvQ attribute*), 43
bn_conv2d (*dicee.AConEx attribute*), 174
bn_conv2d (*dicee.AConvO attribute*), 175
bn_conv2d (*dicee.ConEx attribute*), 178
bn_conv2d (*dicee.ConvO attribute*), 177
bn_conv2d (*dicee.models.AConEx attribute*), 69
bn_conv2d (*dicee.models.AConvO attribute*), 82
bn_conv2d (*dicee.models.complex.AConEx attribute*), 30
bn_conv2d (*dicee.models.complex.ConEx attribute*), 29
bn_conv2d (*dicee.models.ConEx attribute*), 69
bn_conv2d (*dicee.models.ConvO attribute*), 81
bn_conv2d (*dicee.models.octonion.AConvO attribute*), 39
bn_conv2d (*dicee.models.octonion.ConvO attribute*), 38
BPE_NegativeSamplingDataset (*class in dicee*), 196
BPE_NegativeSamplingDataset (*class in dicee.dataset_classes*), 133
build_chain_funcs() (*dicee.models.FMult2 method*), 97
build_chain_funcs() (*dicee.models.function_space.FMult2 method*), 34
build_func() (*dicee.models.FMult2 method*), 97
build_func() (*dicee.models.function_space.FMult2 method*), 34
BytE (*class in dicee*), 183
BytE (*class in dicee.models.transformers*), 46
byte_pair_encoding (*dicee.analyse_experiments.Experiment attribute*), 121
byte_pair_encoding (*dicee.BaseKGE attribute*), 186
byte_pair_encoding (*dicee.config.Namespace attribute*), 132
byte_pair_encoding (*dicee.knowledge_graph.KG attribute*), 148
byte_pair_encoding (*dicee.models.base_model.BaseKGE attribute*), 19
byte_pair_encoding (*dicee.models.BaseKGE attribute*), 61, 64, 67, 72, 78, 91, 95

C

c_attn (*dicee.models.transformers.CausalSelfAttention attribute*), 49
c_fc (*dicee.models.transformers.MLP attribute*), 50
c_proj (*dicee.models.transformers.CausalSelfAttention attribute*), 49
c_proj (*dicee.models.transformers.MLP attribute*), 50
callbacks (*dicee.abstracts.AbstractTrainer attribute*), 115
callbacks (*dicee.analyse_experiments.Experiment attribute*), 121
callbacks (*dicee.config.Namespace attribute*), 131
callbacks (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
callbacks (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
CausalSelfAttention (*class in dicee.models.transformers*), 48
chain_func() (*dicee.models.FMult method*), 96
chain_func() (*dicee.models.function_space.FMult method*), 33
chain_func() (*dicee.models.function_space.GFMult method*), 34
chain_func() (*dicee.models.GFMult method*), 96
cl_pqr() (*dicee.DeCaL method*), 170
cl_pqr() (*dicee.models.clifford.DeCaL method*), 26
cl_pqr() (*dicee.models.DeCaL method*), 87
clifford_mul() (*dicee.CMult method*), 164
clifford_mul() (*dicee.models.clifford.CMult method*), 22
clifford_mul() (*dicee.models.CMult method*), 86
clifford_multiplication() (*dicee.Keci method*), 167
clifford_multiplication() (*dicee.models.clifford.Keci method*), 24
clifford_multiplication() (*dicee.models.Keci method*), 84
CMult (*class in dicee*), 163

CMult (*class in dicee.models*), 85
CMult (*class in dicee.models.clifford*), 21
collate_fn (*dicee.AllvsAll attribute*), 200
collate_fn (*dicee.dataset_classes.AllvsAll attribute*), 137
collate_fn (*dicee.dataset_classes.KvsAll attribute*), 136
collate_fn (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
collate_fn (*dicee.dataset_classes.MultiClassClassificationDataset attribute*), 135
collate_fn (*dicee.dataset_classes.MultiLabelDataset attribute*), 134
collate_fn (*dicee.dataset_classes.OnevsAllDataset attribute*), 135
collate_fn (*dicee.KvsAll attribute*), 199
collate_fn (*dicee.KvsSampleDataset attribute*), 201
collate_fn (*dicee.MultiClassClassificationDataset attribute*), 198
collate_fn (*dicee.MultiLabelDataset attribute*), 197
collate_fn (*dicee.OnevsAllDataset attribute*), 198
collate_fn() (*dicee.BPE_NegativeSamplingDataset method*), 197
collate_fn() (*dicee.dataset_classes.BPE_NegativeSamplingDataset method*), 134
collate_fn() (*dicee.dataset_classes.TriplePredictionDataset method*), 139
collate_fn() (*dicee.TriplePredictionDataset method*), 202
collection_name (*dicee.scripts.serve.NeuralSearcher attribute*), 108
comp_func() (*dicee.LFMult method*), 182
comp_func() (*dicee.models.function_space.LFMult method*), 36
comp_func() (*dicee.models.LFMult method*), 99
ComplEx (*class in dicee*), 173
ComplEx (*class in dicee.models*), 69
ComplEx (*class in dicee.models.complex*), 30
compute_convergence() (*in module dicee.callbacks*), 126
compute_func() (*dicee.models.FMult method*), 96
compute_func() (*dicee.models.FMult2 method*), 97
compute_func() (*dicee.models.function_space.FMult method*), 33
compute_func() (*dicee.models.function_space.FMult2 method*), 34
compute_func() (*dicee.models.function_space.GFMult method*), 34
compute_func() (*dicee.models.GFMult method*), 96
compute_mrr() (*dicee.callbacks.ASWA static method*), 127
compute_sigma_pp() (*dicee.DeCaL method*), 171
compute_sigma_pp() (*dicee.Keci method*), 166
compute_sigma_pp() (*dicee.models.clifford.DeCaL method*), 27
compute_sigma_pp() (*dicee.models.clifford.Keci method*), 23
compute_sigma_pp() (*dicee.models.DeCaL method*), 88
compute_sigma_pp() (*dicee.models.Keci method*), 83
compute_sigma_pq() (*dicee.DeCaL method*), 172
compute_sigma_pq() (*dicee.Keci method*), 167
compute_sigma_pq() (*dicee.models.clifford.DeCaL method*), 28
compute_sigma_pq() (*dicee.models.clifford.Keci method*), 24
compute_sigma_pq() (*dicee.models.DeCaL method*), 89
compute_sigma_pq() (*dicee.models.Keci method*), 83
compute_sigma_pr() (*dicee.DeCaL method*), 172
compute_sigma_pr() (*dicee.models.clifford.DeCaL method*), 29
compute_sigma_pr() (*dicee.models.DeCaL method*), 90
compute_sigma_qq() (*dicee.DeCaL method*), 171
compute_sigma_qq() (*dicee.Keci method*), 166
compute_sigma_qq() (*dicee.models.clifford.DeCaL method*), 28
compute_sigma_qq() (*dicee.models.clifford.Keci method*), 23
compute_sigma_qq() (*dicee.models.DeCaL method*), 89
compute_sigma_qq() (*dicee.models.Keci method*), 83
compute_sigma_qr() (*dicee.DeCaL method*), 172
compute_sigma_qr() (*dicee.models.clifford.DeCaL method*), 29
compute_sigma_qr() (*dicee.models.DeCaL method*), 90
compute_sigma_rr() (*dicee.DeCaL method*), 171
compute_sigma_rr() (*dicee.models.clifford.DeCaL method*), 28
compute_sigma_rr() (*dicee.models.DeCaL method*), 89
compute_sigmas_multivect() (*dicee.DeCaL method*), 170
compute_sigmas_multivect() (*dicee.models.clifford.DeCaL method*), 27
compute_sigmas_multivect() (*dicee.models.DeCaL method*), 88
compute_sigmas_single() (*dicee.DeCaL method*), 170
compute_sigmas_single() (*dicee.models.clifford.DeCaL method*), 26
compute_sigmas_single() (*dicee.models.DeCaL method*), 87
ConEx (*class in dicee*), 177
ConEx (*class in dicee.models*), 68

ConEx (*class in dicee.models.complex*), 29
config (*dicee.BytE attribute*), 183
config (*dicee.models.transformers.BytE attribute*), 47
config (*dicee.models.transformers.GPT attribute*), 52
configs (*dicee.abstracts.BaseInteractiveKGE attribute*), 117
configure_optimizers() (*dicee.models.base_model.BaseKGELightning method*), 16
configure_optimizers() (*dicee.models.BaseKGELightning method*), 58
configure_optimizers() (*dicee.models.transformers.GPT method*), 52
construct_cl_multivector() (*dicee.DeCaL method*), 170
construct_cl_multivector() (*dicee.Keci method*), 167
construct_cl_multivector() (*dicee.models.clifford.DeCaL method*), 27
construct_cl_multivector() (*dicee.models.clifford.Keci method*), 24
construct_cl_multivector() (*dicee.models.DeCaL method*), 88
construct_cl_multivector() (*dicee.models.Keci method*), 84
construct_dataset() (*in module dicee*), 196
construct_dataset() (*in module dicee.dataset_classes*), 133
construct_ensemble (*dicee.abstracts.BaseInteractiveKGE attribute*), 117
construct_graph() (*dicee.query_generator.QueryGenerator method*), 155
construct_graph() (*dicee.QueryGenerator method*), 207
construct_input_and_output() (*dicee.abstracts.BaseInteractiveKGE method*), 118
construct_multi_coeff() (*dicee.LFMult method*), 181
construct_multi_coeff() (*dicee.models.function_space.LFMult method*), 35
construct_multi_coeff() (*dicee.models.LFMult method*), 98
continual_learning (*dicee.config.Namespace attribute*), 132
continual_start() (*dicee.DICE_Trainer method*), 189
continual_start() (*dicee.executer.ContinuousExecute method*), 148
continual_start() (*dicee.trainer.DICE_Trainer method*), 114
continual_start() (*dicee.trainer.dice_trainer.DICE_Trainer method*), 109
continual_training_setup_executor() (*in module dicee*), 188
continual_training_setup_executor() (*in module dicee.static_funcs*), 159
ContinuousExecute (*class in dicee.executer*), 147
conv2d (*dicee.AConEx attribute*), 174
conv2d (*dicee.AConvO attribute*), 175
conv2d (*dicee.AConvQ attribute*), 175
conv2d (*dicee.ConEx attribute*), 178
conv2d (*dicee.ConvO attribute*), 177
conv2d (*dicee.ConvQ attribute*), 176
conv2d (*dicee.models.AConEx attribute*), 69
conv2d (*dicee.models.AConvO attribute*), 81
conv2d (*dicee.models.AConvQ attribute*), 76
conv2d (*dicee.models.complex.AConEx attribute*), 30
conv2d (*dicee.models.complex.ConEx attribute*), 29
conv2d (*dicee.models.ConEx attribute*), 68
conv2d (*dicee.models.ConvO attribute*), 81
conv2d (*dicee.models.ConvQ attribute*), 75
conv2d (*dicee.models.octonion.AConvO attribute*), 39
conv2d (*dicee.models.octonion.ConvO attribute*), 38
conv2d (*dicee.models.quaternion.AConvQ attribute*), 43
conv2d (*dicee.models.quaternion.ConvQ attribute*), 43
ConvO (*class in dicee*), 176
ConvO (*class in dicee.models*), 80
ConvO (*class in dicee.models.octonion*), 38
ConvQ (*class in dicee*), 176
ConvQ (*class in dicee.models*), 75
ConvQ (*class in dicee.models.quaternion*), 42
create_constraints() (*in module dicee.read_preprocess_save_load_kg.util*), 104
create_constraints() (*in module dicee.static_preprocess_funcs*), 160
create_experiment_folder() (*in module dicee*), 188
create_experiment_folder() (*in module dicee.static_funcs*), 159
create_random_data() (*dicee.callbacks.PseudoLabellingCallback method*), 126
create_recipriocal_triples() (*in module dicee*), 187
create_recipriocal_triples() (*in module dicee.read_preprocess_save_load_kg.util*), 104
create_recipriocal_triples() (*in module dicee.static_funcs*), 157
create_vector_database() (*dicee.KGE method*), 190
create_vector_database() (*dicee.knowledge_graph_embeddings.KGE method*), 150
crop_block_size() (*dicee.models.transformers.GPT method*), 52
CVDataModule (*class in dicee*), 202
CVDataModule (*class in dicee.dataset_classes*), 139

D

data_module (*dicee.callbacks.PseudoLabellingCallback attribute*), 126
dataset_dir (*dicee.config.Namespace attribute*), 130
dataset_dir (*dicee.knowledge_graph.KG attribute*), 148
dataset_sanity_checking() (*in module dicee.read_preprocess_save_load_kg.util*), 104
DDPTrainer (*class in dicee.trainer.torch_trainer_ddp*), 113
DeCaL (*class in dicee*), 168
DeCaL (*class in dicee.models*), 86
DeCaL (*class in dicee.models.clifford*), 25
decide() (*dicee.callbacks.ASWA method*), 127
degree (*dicee.LFMult attribute*), 181
degree (*dicee.models.function_space.LFMult attribute*), 35
degree (*dicee.models.LFMult attribute*), 98
deploy() (*dicee.KGE method*), 194
deploy() (*dicee.knowledge_graph_embeddings.KGE method*), 154
deploy_head_entity_prediction() (*in module dicee*), 188
deploy_head_entity_prediction() (*in module dicee.static_funcs*), 158
deploy_relation_prediction() (*in module dicee*), 188
deploy_relation_prediction() (*in module dicee.static_funcs*), 158
deploy_tail_entity_prediction() (*in module dicee*), 188
deploy_tail_entity_prediction() (*in module dicee.static_funcs*), 158
deploy_triple_prediction() (*in module dicee*), 188
deploy_triple_prediction() (*in module dicee.static_funcs*), 158
DICE_Trainer (*class in dicee*), 189
DICE_Trainer (*class in dicee.trainer*), 113
DICE_Trainer (*class in dicee.trainer.dice_trainer*), 109
dicee
    module, 12
dicee.abstracts
    module, 115
dicee.analyse_experiments
    module, 121
dicee.callbacks
    module, 122
dicee.config
    module, 130
dicee.dataset_classes
    module, 133
dicee.eval_static_funcs
    module, 143
dicee.evaluator
    module, 144
dicee.executer
    module, 146
dicee.knowledge_graph
    module, 148
dicee.knowledge_graph_embeddings
    module, 150
dicee.models
    module, 12
dicee.models.base_model
    module, 12
dicee.models.clifford
    module, 21
dicee.models.complex
    module, 29
dicee.models.dualE
    module, 31
dicee.models.function_space
    module, 33
dicee.models.octonion
    module, 36
dicee.models.pykeen_models
    module, 39
dicee.models.quaternion
    module, 41
dicee.models.real
    module, 44

dicee.models.static_funcs
    module, 45
dicee.models.transformers
    module, 46
dicee.query_generator
    module, 154
dicee.read_preprocess_save_load_kg
    module, 100
dicee.read_preprocess_save_load_kg.preprocess
    module, 100
dicee.read_preprocess_save_load_kg.read_from_disk
    module, 101
dicee.read_preprocess_save_load_kg.save_load_disk
    module, 102
dicee.read_preprocess_save_load_kg.util
    module, 103
dicee.sanity_checkers
    module, 156
dicee.scripts
    module, 106
dicee.scripts.index
    module, 106
dicee.scripts.run
    module, 107
dicee.scripts.serve
    module, 107
dicee.static_funcs
    module, 156
dicee.static_funcs_training
    module, 159
dicee.static_preprocess_funcs
    module, 160
dicee.trainer
    module, 108
dicee.trainer.dice_trainer
    module, 108
dicee.trainer.torch_trainer
    module, 110
dicee.trainer.torch_trainer_ddp
    module, 111
discrete_points (*dicee.models.FMult2 attribute*), 97
discrete_points (*dicee.models.function_space.FMult2 attribute*), 34
dist_func (*dicee.models.Pyke attribute*), 66
dist_func (*dicee.models.real.Pyke attribute*), 45
dist_func (*dicee.Pyke attribute*), 165
DistMult (*class in dicee*), 165
DistMult (*class in dicee.models*), 65
DistMult (*class in dicee.models.real*), 44
download_file() (*in module dicee*), 189
download_file() (*in module dicee.static_funcs*), 159
download_files_from_url() (*in module dicee*), 189
download_files_from_url() (*in module dicee.static_funcs*), 159
download_pretrained_model() (*in module dicee*), 189
download_pretrained_model() (*in module dicee.static_funcs*), 159
dropout (*dicee.models.transformers.CausalSelfAttention attribute*), 49
dropout (*dicee.models.transformers.GPTConfig attribute*), 51
dropout (*dicee.models.transformers.MLP attribute*), 50
DualE (*class in dicee*), 172
DualE (*class in dicee.models*), 99
DualE (*class in dicee.models.dualE*), 32
dummy_eval() (*dicee.evaluator.Evaluator method*), 145
dummy_id (*dicee.knowledge_graph.KG attribute*), 149
during_training (*dicee.evaluator.Evaluator attribute*), 145

E

ee_vocab (*dicee.evaluator.Evaluator attribute*), 144
efficient_zero_grad() (*in module dicee.static_funcs_training*), 160

embedding_dim (*dicee.analyse_experiments.Experiment attribute*), 121
embedding_dim (*dicee.BaseKGE attribute*), 186
embedding_dim (*dicee.config.Namespace attribute*), 130
embedding_dim (*dicee.models.base_model.BaseKGE attribute*), 18
embedding_dim (*dicee.models.BaseKGE attribute*), 60, 63, 66, 71, 77, 91, 94
enable_log (*in module dicee.static_preprocess_funcs*), 160
enc (*dicee.knowledge_graph.KG attribute*), 149
end() (*dicee.Execute method*), 196
end() (*dicee.executer.Execute method*), 147
ent2id (*dicee.query_generator.QueryGenerator attribute*), 154
ent2id (*dicee.QueryGenerator attribute*), 206
ent_in (*dicee.query_generator.QueryGenerator attribute*), 155
ent_in (*dicee.QueryGenerator attribute*), 206
ent_out (*dicee.query_generator.QueryGenerator attribute*), 155
ent_out (*dicee.QueryGenerator attribute*), 206
entities_str (*dicee.knowledge_graph.KG property*), 149
entity_embeddings (*dicee.AConvQ attribute*), 175
entity_embeddings (*dicee.CMult attribute*), 164
entity_embeddings (*dicee.ConvQ attribute*), 176
entity_embeddings (*dicee.DeCaL attribute*), 169
entity_embeddings (*dicee.DualE attribute*), 172
entity_embeddings (*dicee.LFMult attribute*), 181
entity_embeddings (*dicee.models.AConvQ attribute*), 76
entity_embeddings (*dicee.models.clifford.CMult attribute*), 21
entity_embeddings (*dicee.models.clifford.DeCaL attribute*), 26
entity_embeddings (*dicee.models.CMult attribute*), 86
entity_embeddings (*dicee.models.ConvQ attribute*), 75
entity_embeddings (*dicee.models.DeCaL attribute*), 87
entity_embeddings (*dicee.models.DualE attribute*), 99
entity_embeddings (*dicee.models.dualE.DualE attribute*), 32
entity_embeddings (*dicee.models.FMult attribute*), 96
entity_embeddings (*dicee.models.FMult2 attribute*), 97
entity_embeddings (*dicee.models.function_space.FMult attribute*), 33
entity_embeddings (*dicee.models.function_space.FMult2 attribute*), 34
entity_embeddings (*dicee.models.function_space.GFMult attribute*), 34
entity_embeddings (*dicee.models.function_space.LFMult attribute*), 35
entity_embeddings (*dicee.models.function_space.LFMult1 attribute*), 35
entity_embeddings (*dicee.models.GFMult attribute*), 96
entity_embeddings (*dicee.models.LFMult attribute*), 98
entity_embeddings (*dicee.models.LFMult1 attribute*), 97
entity_embeddings (*dicee.models.pykeen_models.PykeenKGE attribute*), 40
entity_embeddings (*dicee.models.PykeenKGE attribute*), 93
entity_embeddings (*dicee.models.quaternion.AConvQ attribute*), 43
entity_embeddings (*dicee.models.quaternion.ConvQ attribute*), 43
entity_embeddings (*dicee.PykeenKGE attribute*), 182
entity_to_idx (*dicee.knowledge_graph.KG attribute*), 149
epoch_count (*dicee.abstracts.AbstractPPECallback attribute*), 120
epoch_count (*dicee.callbacks.ASWA attribute*), 127
epoch_counter (*dicee.callbacks.Eval attribute*), 128
epoch_counter (*dicee.callbacks.KGESaveCallback attribute*), 125
epoch_ratio (*dicee.callbacks.Eval attribute*), 128
er_vocab (*dicee.evaluator.Evaluator attribute*), 144
estimate_mfu() (*dicee.models.transformers.GPT method*), 52
estimate_q() (*in module dicee.callbacks*), 126
Eval (*class in dicee.callbacks*), 127
eval() (*dicee.evaluator.Evaluator method*), 145
eval_lp_performance() (*dicee.KGE method*), 190
eval_lp_performance() (*dicee.knowledge_graph_embeddings.KGE method*), 150
eval_model (*dicee.config.Namespace attribute*), 131
eval_model (*dicee.knowledge_graph.KG attribute*), 149
eval_rank_of_head_and_tail_byte_pair_encoded_entity() (*dicee.evaluator.Evaluator method*), 145
eval_rank_of_head_and_tail_entity() (*dicee.evaluator.Evaluator method*), 145
eval_with_bpe_vs_all() (*dicee.evaluator.Evaluator method*), 145
eval_with_byte() (*dicee.evaluator.Evaluator method*), 145
eval_with_data() (*dicee.evaluator.Evaluator method*), 145
eval_with_vs_all() (*dicee.evaluator.Evaluator method*), 145
evaluate() (*in module dicee*), 189
evaluate() (*in module dicee.static_funcs*), 159

evaluate_bpe_lp() (*in module dicee.static_funcs_training*), 159
evaluate_link_prediction_performance() (*in module dicee.eval_static_funcs*), 143
evaluate_link_prediction_performance_with_bpe() (*in module dicee.eval_static_funcs*), 144
evaluate_link_prediction_performance_with_bpe_reciprocals() (*in module dicee.eval_static_funcs*), 144
evaluate_link_prediction_performance_with_reciprocals() (*in module dicee.eval_static_funcs*), 144
evaluate_lp() (*dicee.evaluator.Evaluator method*), 145
evaluate_lp() (*in module dicee.static_funcs_training*), 159
evaluate_lp_bpe_k_vs_all() (*dicee.evaluator.Evaluator method*), 145
evaluate_lp_bpe_k_vs_all() (*in module dicee.eval_static_funcs*), 144
evaluate_lp_k_vs_all() (*dicee.evaluator.Evaluator method*), 145
evaluate_lp_with_byte() (*dicee.evaluator.Evaluator method*), 145
Evaluator (*class in dicee.evaluator*), 144
evaluator (*dicee.DICE_Trainer attribute*), 189
evaluator (*dicee.Execute attribute*), 195
evaluator (*dicee.executer.Execute attribute*), 146
evaluator (*dicee.trainer.DICE_Trainer attribute*), 114
evaluator (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 109
every_x_epoch (*dicee.callbacks.KGESaveCallback attribute*), 125
Execute (*class in dicee*), 194
Execute (*class in dicee.executer*), 146
Experiment (*class in dicee.analyse_experiments*), 121
explicit (*dicee.models.QMult attribute*), 74
explicit (*dicee.models.quaternion.QMult attribute*), 42
explicit (*dicee.QMult attribute*), 179
exponential_function() (*in module dicee*), 189
exponential_function() (*in module dicee.static_funcs*), 159
extract_input_outputs() (*dicee.trainer.torch_trainer_ddp.DDPTrainer method*), 113
extract_input_outputs() (*dicee.trainer.torch_trainer_ddp.NodeTrainer method*), 112
extract_input_outputs_set_device() (*dicee.trainer.torch_trainer.TorchTrainer method*), 111

F

f (*dicee.callbacks.KronE attribute*), 129
fc1 (*dicee.AConEx attribute*), 174
fc1 (*dicee.AConvO attribute*), 175
fc1 (*dicee.AConvQ attribute*), 175
fc1 (*dicee.ConEx attribute*), 178
fc1 (*dicee.ConvO attribute*), 177
fc1 (*dicee.ConvQ attribute*), 176
fc1 (*dicee.models.AConEx attribute*), 69
fc1 (*dicee.models.AConvO attribute*), 82
fc1 (*dicee.models.AConvQ attribute*), 76
fc1 (*dicee.models.complex.AConEx attribute*), 30
fc1 (*dicee.models.complex.ConEx attribute*), 29
fc1 (*dicee.models.ConEx attribute*), 68
fc1 (*dicee.models.ConvO attribute*), 81
fc1 (*dicee.models.ConvQ attribute*), 75
fc1 (*dicee.models.octonion.AConvO attribute*), 39
fc1 (*dicee.models.octonion.ConvO attribute*), 38
fc1 (*dicee.models.quaternion.AConvQ attribute*), 43
fc1 (*dicee.models.quaternion.ConvQ attribute*), 43
fc_num_input (*dicee.AConEx attribute*), 174
fc_num_input (*dicee.AConvO attribute*), 175
fc_num_input (*dicee.AConvQ attribute*), 175
fc_num_input (*dicee.ConEx attribute*), 178
fc_num_input (*dicee.ConvO attribute*), 177
fc_num_input (*dicee.ConvQ attribute*), 176
fc_num_input (*dicee.models.AConEx attribute*), 69
fc_num_input (*dicee.models.AConvO attribute*), 82
fc_num_input (*dicee.models.AConvQ attribute*), 76
fc_num_input (*dicee.models.complex.AConEx attribute*), 30
fc_num_input (*dicee.models.complex.ConEx attribute*), 29
fc_num_input (*dicee.models.ConEx attribute*), 68
fc_num_input (*dicee.models.ConvO attribute*), 81
fc_num_input (*dicee.models.ConvQ attribute*), 75
fc_num_input (*dicee.models.octonion.AConvO attribute*), 39
fc_num_input (*dicee.models.octonion.ConvO attribute*), 38
fc_num_input (*dicee.models.quaternion.AConvQ attribute*), 43

fc_num_input (*dicee.models.quaternion.ConvQ attribute*), 43
feature_map_dropout (*dicee.AConEx attribute*), 174
feature_map_dropout (*dicee.AConvO attribute*), 175
feature_map_dropout (*dicee.AConvQ attribute*), 176
feature_map_dropout (*dicee.ConEx attribute*), 178
feature_map_dropout (*dicee.ConvO attribute*), 177
feature_map_dropout (*dicee.ConvQ attribute*), 176
feature_map_dropout (*dicee.models.AConEx attribute*), 69
feature_map_dropout (*dicee.models.AConvO attribute*), 82
feature_map_dropout (*dicee.models.AConvQ attribute*), 76
feature_map_dropout (*dicee.models.complex.AConEx attribute*), 30
feature_map_dropout (*dicee.models.complex.ConEx attribute*), 30
feature_map_dropout (*dicee.models.ConEx attribute*), 69
feature_map_dropout (*dicee.models.ConvO attribute*), 81
feature_map_dropout (*dicee.models.ConvQ attribute*), 75
feature_map_dropout (*dicee.models.octonion.AConvO attribute*), 39
feature_map_dropout (*dicee.models.octonion.ConvO attribute*), 38
feature_map_dropout (*dicee.models.quaternion.AConvQ attribute*), 43
feature_map_dropout (*dicee.models.quaternion.ConvQ attribute*), 43
feature_map_dropout_rate (*dicee.BaseKGE attribute*), 186
feature_map_dropout_rate (*dicee.config.Namespace attribute*), 132
feature_map_dropout_rate (*dicee.models.base_model.BaseKGE attribute*), 19
feature_map_dropout_rate (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
fill_query() (*dicee.query_generator.QueryGenerator method*), 155
fill_query() (*dicee.QueryGenerator method*), 207
find_missing_triples() (*dicee.KGE method*), 194
find_missing_triples() (*dicee.knowledge_graph_embeddings.KGE method*), 153
fit() (*dicee.trainer.torch_trainer_ddp.TorchDDPTrainer method*), 112
fit() (*dicee.trainer.torch_trainer.TorchTrainer method*), 110
flash (*dicee.models.transformers.CausalSelfAttention attribute*), 49
FMult (*class in dicee.models*), 96
FMult (*class in dicee.models.function_space*), 33
FMult2 (*class in dicee.models*), 97
FMult2 (*class in dicee.models.function_space*), 34
form_of_labelling (*dicee.DICE_Trainer attribute*), 189
form_of_labelling (*dicee.trainer.DICE_Trainer attribute*), 114
form_of_labelling (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 109
forward() (*dicee.BaseKGE method*), 187
forward() (*dicee.BytE method*), 184
forward() (*dicee.models.base_model.BaseKGE method*), 19
forward() (*dicee.models.base_model.IdentityClass static method*), 21
forward() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
forward() (*dicee.models.IdentityClass static method*), 62, 73, 79
forward() (*dicee.models.transformers.Block method*), 51
forward() (*dicee.models.transformers.BytE method*), 47
forward() (*dicee.models.transformers.CausalSelfAttention method*), 49
forward() (*dicee.models.transformers.GPT method*), 52
forward() (*dicee.models.transformers.LayerNorm method*), 48
forward() (*dicee.models.transformers.MLP method*), 50
forward_backward_update() (*dicee.trainer.torch_trainer.TorchTrainer method*), 111
forward_byte_pair_encoded_k_vs_all() (*dicee.BaseKGE method*), 186
forward_byte_pair_encoded_k_vs_all() (*dicee.models.base_model.BaseKGE method*), 19
forward_byte_pair_encoded_k_vs_all() (*dicee.models.BaseKGE method*), 61, 64, 67, 72, 78, 91, 95
forward_byte_pair_encoded_triple() (*dicee.BaseKGE method*), 186
forward_byte_pair_encoded_triple() (*dicee.models.base_model.BaseKGE method*), 19
forward_byte_pair_encoded_triple() (*dicee.models.BaseKGE method*), 61, 64, 67, 72, 78, 92, 95
forward_k_vs_all() (*dicee.AConEx method*), 174
forward_k_vs_all() (*dicee.AConvO method*), 175
forward_k_vs_all() (*dicee.AConvQ method*), 176
forward_k_vs_all() (*dicee.BaseKGE method*), 187
forward_k_vs_all() (*dicee.CMult method*), 164
forward_k_vs_all() (*dicee.ComplEx method*), 174
forward_k_vs_all() (*dicee.ConEx method*), 178
forward_k_vs_all() (*dicee.ConvO method*), 177
forward_k_vs_all() (*dicee.ConvQ method*), 176
forward_k_vs_all() (*dicee.DeCaL method*), 170
forward_k_vs_all() (*dicee.DistMult method*), 165
forward_k_vs_all() (*dicee.DualE method*), 173

forward_k_vs_all() (*dicee.Keci method*), 167
forward_k_vs_all() (*dicee.models.AConEx method*), 69
forward_k_vs_all() (*dicee.models.AConvO method*), 82
forward_k_vs_all() (*dicee.models.AConvQ method*), 76
forward_k_vs_all() (*dicee.models.base_model.BaseKGE method*), 20
forward_k_vs_all() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
forward_k_vs_all() (*dicee.models.clifford.CMult method*), 22
forward_k_vs_all() (*dicee.models.clifford.DeCaL method*), 27
forward_k_vs_all() (*dicee.models.clifford.Keci method*), 24
forward_k_vs_all() (*dicee.models.CMult method*), 86
forward_k_vs_all() (*dicee.models.ComplEx method*), 70
forward_k_vs_all() (*dicee.models.complex.AConEx method*), 30
forward_k_vs_all() (*dicee.models.complex.ComplEx method*), 31
forward_k_vs_all() (*dicee.models.complex.ConEx method*), 30
forward_k_vs_all() (*dicee.models.ConEx method*), 69
forward_k_vs_all() (*dicee.models.ConvO method*), 81
forward_k_vs_all() (*dicee.models.ConvQ method*), 76
forward_k_vs_all() (*dicee.models.DeCaL method*), 88
forward_k_vs_all() (*dicee.models.DistMult method*), 65
forward_k_vs_all() (*dicee.models.DualE method*), 100
forward_k_vs_all() (*dicee.models.dualE.DualE method*), 32
forward_k_vs_all() (*dicee.models.Keci method*), 84
forward_k_vs_all() (*dicee.models.octonion.AConvO method*), 39
forward_k_vs_all() (*dicee.models.octonion.ConvO method*), 39
forward_k_vs_all() (*dicee.models.octonion.OMult method*), 38
forward_k_vs_all() (*dicee.models.OMult method*), 80
forward_k_vs_all() (*dicee.models.pykeen_models.PykeenKGE method*), 40
forward_k_vs_all() (*dicee.models.PykeenKGE method*), 93
forward_k_vs_all() (*dicee.models.QMult method*), 75
forward_k_vs_all() (*dicee.models.quaternion.AConvQ method*), 44
forward_k_vs_all() (*dicee.models.quaternion.ConvQ method*), 43
forward_k_vs_all() (*dicee.models.quaternion.QMult method*), 42
forward_k_vs_all() (*dicee.models.real.DistMult method*), 44
forward_k_vs_all() (*dicee.models.real.Shallom method*), 45
forward_k_vs_all() (*dicee.models.real.TransE method*), 45
forward_k_vs_all() (*dicee.models.Shallom method*), 65
forward_k_vs_all() (*dicee.models.TransE method*), 65
forward_k_vs_all() (*dicee.OMult method*), 180
forward_k_vs_all() (*dicee.PykeenKGE method*), 182
forward_k_vs_all() (*dicee.QMult method*), 179
forward_k_vs_all() (*dicee.Shallom method*), 181
forward_k_vs_all() (*dicee.TransE method*), 168
forward_k_vs_sample() (*dicee.AConEx method*), 175
forward_k_vs_sample() (*dicee.BaseKGE method*), 187
forward_k_vs_sample() (*dicee.ConEx method*), 178
forward_k_vs_sample() (*dicee.DistMult method*), 165
forward_k_vs_sample() (*dicee.Keci method*), 168
forward_k_vs_sample() (*dicee.models.AConEx method*), 69
forward_k_vs_sample() (*dicee.models.base_model.BaseKGE method*), 20
forward_k_vs_sample() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
forward_k_vs_sample() (*dicee.models.clifford.Keci method*), 25
forward_k_vs_sample() (*dicee.models.complex.AConEx method*), 30
forward_k_vs_sample() (*dicee.models.complex.ConEx method*), 30
forward_k_vs_sample() (*dicee.models.ConEx method*), 69
forward_k_vs_sample() (*dicee.models.DistMult method*), 65
forward_k_vs_sample() (*dicee.models.Keci method*), 84
forward_k_vs_sample() (*dicee.models.pykeen_models.PykeenKGE method*), 40
forward_k_vs_sample() (*dicee.models.PykeenKGE method*), 93
forward_k_vs_sample() (*dicee.models.QMult method*), 75
forward_k_vs_sample() (*dicee.models.quaternion.QMult method*), 42
forward_k_vs_sample() (*dicee.models.real.DistMult method*), 44
forward_k_vs_sample() (*dicee.PykeenKGE method*), 183
forward_k_vs_sample() (*dicee.QMult method*), 179
forward_k_vs_with_explicit() (*dicee.Keci method*), 167
forward_k_vs_with_explicit() (*dicee.models.clifford.Keci method*), 24
forward_k_vs_with_explicit() (*dicee.models.Keci method*), 84
forward_triples() (*dicee.AConEx method*), 175
forward_triples() (*dicee.AConvO method*), 175

forward_triples() (*dicee.AConvQ method*), 176
forward_triples() (*dicee.BaseKGE method*), 187
forward_triples() (*dicee.CMult method*), 164
forward_triples() (*dicee.ConEx method*), 178
forward_triples() (*dicee.ConvO method*), 177
forward_triples() (*dicee.ConvQ method*), 176
forward_triples() (*dicee.DeCaL method*), 169
forward_triples() (*dicee.DualE method*), 173
forward_triples() (*dicee.Keci method*), 168
forward_triples() (*dicee.LFMult method*), 181
forward_triples() (*dicee.models.AConEx method*), 69
forward_triples() (*dicee.models.AConvO method*), 82
forward_triples() (*dicee.models.AConvQ method*), 76
forward_triples() (*dicee.models.base_model.BaseKGE method*), 20
forward_triples() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
forward_triples() (*dicee.models.clifford.CMult method*), 22
forward_triples() (*dicee.models.clifford.DeCaL method*), 26
forward_triples() (*dicee.models.clifford.Keci method*), 25
forward_triples() (*dicee.models.CMult method*), 86
forward_triples() (*dicee.models.complex.AConEx method*), 30
forward_triples() (*dicee.models.complex.ConEx method*), 30
forward_triples() (*dicee.models.ConEx method*), 69
forward_triples() (*dicee.models.ConvO method*), 81
forward_triples() (*dicee.models.ConvQ method*), 75
forward_triples() (*dicee.models.DeCaL method*), 87
forward_triples() (*dicee.models.DualE method*), 99
forward_triples() (*dicee.models.dualE.DualE method*), 32
forward_triples() (*dicee.models.FMult method*), 96
forward_triples() (*dicee.models.FMult2 method*), 97
forward_triples() (*dicee.models.function_space.FMult method*), 33
forward_triples() (*dicee.models.function_space.FMult2 method*), 35
forward_triples() (*dicee.models.function_space.GFMult method*), 34
forward_triples() (*dicee.models.function_space.LFMult method*), 35
forward_triples() (*dicee.models.function_space.LFMult1 method*), 35
forward_triples() (*dicee.models.GFMult method*), 96
forward_triples() (*dicee.models.Keci method*), 85
forward_triples() (*dicee.models.LFMult method*), 98
forward_triples() (*dicee.models.LFMult1 method*), 97
forward_triples() (*dicee.models.octonion.AConvO method*), 39
forward_triples() (*dicee.models.octonion.ConvO method*), 39
forward_triples() (*dicee.models.Pyke method*), 66
forward_triples() (*dicee.models.pykeen_models.PykeenKGE method*), 40
forward_triples() (*dicee.models.PykeenKGE method*), 93
forward_triples() (*dicee.models.quaternion.AConvQ method*), 43
forward_triples() (*dicee.models.quaternion.ConvQ method*), 43
forward_triples() (*dicee.models.real.Pyke method*), 45
forward_triples() (*dicee.models.real.Shallom method*), 45
forward_triples() (*dicee.models.Shallom method*), 65
forward_triples() (*dicee.Pyke method*), 165
forward_triples() (*dicee.PykeenKGE method*), 183
forward_triples() (*dicee.Shallom method*), 181
frequency (*dicee.callbacks.Perturb attribute*), 130
from_pretrained() (*dicee.models.transformers.GPT class method*), 52
full_storage_path (*dicee.analyse_experiments.Experiment attribute*), 122
func_triple_to_bpe_representation (*dicee.evaluator.Evaluator attribute*), 144
func_triple_to_bpe_representation() (*dicee.knowledge_graph.KG method*), 149
function() (*dicee.models.FMult2 method*), 97
function() (*dicee.models.function_space.FMult2 method*), 34

G

gamma (*dicee.models.FMult attribute*), 96
gamma (*dicee.models.function_space.FMult attribute*), 33
gelu (*dicee.models.transformers.MLP attribute*), 50
gen_test (*dicee.query_generator.QueryGenerator attribute*), 154
gen_test (*dicee.QueryGenerator attribute*), 206
gen_valid (*dicee.query_generator.QueryGenerator attribute*), 154
gen_valid (*dicee.QueryGenerator attribute*), 206

generate() (*dicee.BytE method*), 184
generate() (*dicee.KGE method*), 190
generate() (*dicee.knowledge_graph_embeddings.KGE method*), 150
generate() (*dicee.models.transformers.BytE method*), 47
generate_queries() (*dicee.query_generator.QueryGenerator method*), 155
generate_queries() (*dicee.QueryGenerator method*), 207
get() (*dicee.scripts.serve.NeuralSearcher method*), 108
get_aswa_state_dict() (*dicee.callbacks.ASWA method*), 127
get_bpe_head_and_relation_representation() (*dicee.BaseKGE method*), 187
get_bpe_head_and_relation_representation() (*dicee.models.base_model.BaseKGE method*), 20
get_bpe_head_and_relation_representation() (*dicee.models.BaseKGE method*), 61, 65, 68, 73, 79, 92, 96
get_bpe_token_representation() (*dicee.abstracts.BaseInteractiveKGE method*), 117
get_callbacks() (*in module dicee.trainer.dice_trainer*), 109
get_default_arguments() (*in module dicee.analyse_experiments*), 121
get_default_arguments() (*in module dicee.scripts.index*), 106
get_default_arguments() (*in module dicee.scripts.run*), 107
get_default_arguments() (*in module dicee.scripts.serve*), 108
get_ee_vocab() (*in module dicee*), 187
get_ee_vocab() (*in module dicee.read_preprocess_save_load_kg.util*), 104
get_ee_vocab() (*in module dicee.static_funcs*), 157
get_ee_vocab() (*in module dicee.static_preprocess_funcs*), 160
get_embeddings() (*dicee.BaseKGE method*), 187
get_embeddings() (*dicee.models.base_model.BaseKGE method*), 20
get_embeddings() (*dicee.models.BaseKGE method*), 61, 65, 68, 73, 79, 92, 96
get_embeddings() (*dicee.models.real.Shallom method*), 45
get_embeddings() (*dicee.models.Shallom method*), 65
get_embeddings() (*dicee.Shallom method*), 181
get_entity_embeddings() (*dicee.abstracts.BaseInteractiveKGE method*), 118
get_entity_index() (*dicee.abstracts.BaseInteractiveKGE method*), 117
get_er_vocab() (*in module dicee*), 187
get_er_vocab() (*in module dicee.read_preprocess_save_load_kg.util*), 104
get_er_vocab() (*in module dicee.static_funcs*), 157
get_er_vocab() (*in module dicee.static_preprocess_funcs*), 160
get_eval_report() (*dicee.abstracts.BaseInteractiveKGE method*), 117
get_head_relation_representation() (*dicee.BaseKGE method*), 187
get_head_relation_representation() (*dicee.models.base_model.BaseKGE method*), 20
get_head_relation_representation() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
get_kronecker_triple_representation() (*dicee.callbacks.KronE method*), 129
get_num_params() (*dicee.models.transformers.GPT method*), 52
get_padded_bpe_triple_representation() (*dicee.abstracts.BaseInteractiveKGE method*), 117
get_queries() (*dicee.query_generator.QueryGenerator method*), 155
get_queries() (*dicee.QueryGenerator method*), 207
get_re_vocab() (*in module dicee*), 187
get_re_vocab() (*in module dicee.read_preprocess_save_load_kg.util*), 104
get_re_vocab() (*in module dicee.static_funcs*), 157
get_re_vocab() (*in module dicee.static_preprocess_funcs*), 160
get_relation_embeddings() (*dicee.abstracts.BaseInteractiveKGE method*), 118
get_relation_index() (*dicee.abstracts.BaseInteractiveKGE method*), 117
get_sentence_representation() (*dicee.BaseKGE method*), 187
get_sentence_representation() (*dicee.models.base_model.BaseKGE method*), 20
get_sentence_representation() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
get_transductive_entity_embeddings() (*dicee.KGE method*), 190
get_transductive_entity_embeddings() (*dicee.knowledge_graph_embeddings.KGE method*), 150
get_triple_representation() (*dicee.BaseKGE method*), 187
get_triple_representation() (*dicee.models.base_model.BaseKGE method*), 20
get_triple_representation() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
GFMult (*class in dicee.models*), 96
GFMult (*class in dicee.models.function_space*), 34
global_rank (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
GPT (*class in dicee.models.transformers*), 51
GPTConfig (*class in dicee.models.transformers*), 51
gpu_id (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
gpus (*dicee.config.Namespace attribute*), 131
gradient_accumulation_steps (*dicee.config.Namespace attribute*), 131
ground_queries() (*dicee.query_generator.QueryGenerator method*), 155
ground_queries() (*dicee.QueryGenerator method*), 207

H

hidden_dropout (*dicee.BaseKGE attribute*), 186
hidden_dropout (*dicee.models.base_model.BaseKGE attribute*), 19
hidden_dropout (*dicee.models.BaseKGE attribute*), 60, 64, 67, 72, 78, 91, 95
hidden_dropout_rate (*dicee.BaseKGE attribute*), 186
hidden_dropout_rate (*dicee.config.Namespace attribute*), 132
hidden_dropout_rate (*dicee.models.base_model.BaseKGE attribute*), 18
hidden_dropout_rate (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
hidden_normalizer (*dicee.BaseKGE attribute*), 186
hidden_normalizer (*dicee.models.base_model.BaseKGE attribute*), 19
hidden_normalizer (*dicee.models.BaseKGE attribute*), 60, 64, 67, 72, 78, 91, 95

I

IdentityClass (*class in dicee.models*), 62, 73, 79
IdentityClass (*class in dicee.models.base_model*), 20
idx_entity_to_bpe_shaped (*dicee.knowledge_graph.KG attribute*), 149
index_triple() (*dicee.abstracts.BaseInteractiveKGE method*), 117
index_triples_with_pandas() (*in module dicee.read_preprocess_save_load_kg.util*), 104
init_param (*dicee.config.Namespace attribute*), 131
init_params_with_sanity_checking() (*dicee.BaseKGE method*), 187
init_params_with_sanity_checking() (*dicee.models.base_model.BaseKGE method*), 19
init_params_with_sanity_checking() (*dicee.models.BaseKGE method*), 61, 64, 68, 72, 78, 92, 95
initial_eval_setting (*dicee.callbacks.ASWA attribute*), 127
initialize_dataloader() (*dicee.DICE_Trainer method*), 190
initialize_dataloader() (*dicee.trainer.DICE_Trainer method*), 114
initialize_dataloader() (*dicee.trainer.dice_trainer.DICE_Trainer method*), 109
initialize_dataset() (*dicee.DICE_Trainer method*), 190
initialize_dataset() (*dicee.trainer.DICE_Trainer method*), 114
initialize_dataset() (*dicee.trainer.dice_trainer.DICE_Trainer method*), 109
initialize_or_load_model() (*dicee.DICE_Trainer method*), 190
initialize_or_load_model() (*dicee.trainer.DICE_Trainer method*), 114
initialize_or_load_model() (*dicee.trainer.dice_trainer.DICE_Trainer method*), 109
initialize_trainer() (*dicee.DICE_Trainer method*), 190
initialize_trainer() (*dicee.trainer.DICE_Trainer method*), 114
initialize_trainer() (*dicee.trainer.dice_trainer.DICE_Trainer method*), 109
initialize_trainer() (*in module dicee.trainer.dice_trainer*), 109
input_dp_ent_real (*dicee.BaseKGE attribute*), 186
input_dp_ent_real (*dicee.models.base_model.BaseKGE attribute*), 19
input_dp_ent_real (*dicee.models.BaseKGE attribute*), 60, 64, 67, 72, 78, 91, 95
input_dp_rel_real (*dicee.BaseKGE attribute*), 186
input_dp_rel_real (*dicee.models.base_model.BaseKGE attribute*), 19
input_dp_rel_real (*dicee.models.BaseKGE attribute*), 60, 64, 67, 72, 78, 91, 95
input_dropout_rate (*dicee.BaseKGE attribute*), 186
input_dropout_rate (*dicee.config.Namespace attribute*), 132
input_dropout_rate (*dicee.models.base_model.BaseKGE attribute*), 18
input_dropout_rate (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
intialize_model() (*in module dicee*), 188
intialize_model() (*in module dicee.static_funcs*), 158
is_continual_training (*dicee.DICE_Trainer attribute*), 189
is_continual_training (*dicee.evaluator.Evaluator attribute*), 144
is_continual_training (*dicee.Execute attribute*), 195
is_continual_training (*dicee.executer.Execute attribute*), 146
is_continual_training (*dicee.trainer.DICE_Trainer attribute*), 113
is_continual_training (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 109
is_global_zero (*dicee.abstracts.AbstractTrainer attribute*), 115
is_seen() (*dicee.abstracts.BaseInteractiveKGE method*), 117
is_sparql_endpoint_alive() (*in module dicee.sanity_checkers*), 156

K

k (*dicee.models.FMult attribute*), 96
k (*dicee.models.FMult2 attribute*), 97
k (*dicee.models.function_space.FMult attribute*), 33
k (*dicee.models.function_space.FMult2 attribute*), 34
k (*dicee.models.function_space.GFMult attribute*), 34
k (*dicee.models.GFMult attribute*), 96
k_fold_cross_validation() (*dicee.DICE_Trainer method*), 190

k_fold_cross_validation() (*dicee.trainer.DICE_Trainer method*), 114
k_fold_cross_validation() (*dicee.trainer.dice_trainer.DICE_Trainer method*), 110
k_vs_all_score() (*dicee.ComplEx static method*), 174
k_vs_all_score() (*dicee.DistMult method*), 165
k_vs_all_score() (*dicee.Keci method*), 167
k_vs_all_score() (*dicee.models.clifford.Keci method*), 24
k_vs_all_score() (*dicee.models.ComplEx static method*), 70
k_vs_all_score() (*dicee.models.complex.ComplEx static method*), 31
k_vs_all_score() (*dicee.models.DistMult method*), 65
k_vs_all_score() (*dicee.models.Keci method*), 84
k_vs_all_score() (*dicee.models.octonion.OMult method*), 38
k_vs_all_score() (*dicee.models.OMult method*), 80
k_vs_all_score() (*dicee.models.QMult method*), 75
k_vs_all_score() (*dicee.models.quaternion.QMult method*), 42
k_vs_all_score() (*dicee.models.real.DistMult method*), 44
k_vs_all_score() (*dicee.OMult method*), 180
k_vs_all_score() (*dicee.QMult method*), 179
Keci (*class in dicee*), 165
Keci (*class in dicee.models*), 82
Keci (*class in dicee.models.clifford*), 22
KeciBase (*class in dicee*), 165
KeciBase (*class in dicee.models*), 85
KeciBase (*class in dicee.models.clifford*), 25
kernel_size (*dicee.BaseKGE attribute*), 186
kernel_size (*dicee.config.Namespace attribute*), 132
kernel_size (*dicee.models.base_model.BaseKGE attribute*), 19
kernel_size (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
KG (*class in dicee.knowledge_graph*), 148
kg (*dicee.callbacks.PseudoLabellingCallback attribute*), 126
kg (*dicee.read_preprocess_save_load_kg.LoadSaveToDisk attribute*), 106
kg (*dicee.read_preprocess_save_load_kg.PreprocessKG attribute*), 105
kg (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG attribute*), 100
kg (*dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk attribute*), 101
kg (*dicee.read_preprocess_save_load_kg.ReadFromDisk attribute*), 106
kg (*dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk attribute*), 102
KGE (*class in dicee*), 190
KGE (*class in dicee.knowledge_graph_embeddings*), 150
KGESaveCallback (*class in dicee.callbacks*), 125
knowledge_graph (*dicee.Execute attribute*), 195
knowledge_graph (*dicee.executer.Execute attribute*), 146
KronE (*class in dicee.callbacks*), 129
KvsAll (*class in dicee*), 198
KvsAll (*class in dicee.dataset_classes*), 135
kvsall_score() (*dicee.DualE method*), 172
kvsall_score() (*dicee.models.DualE method*), 99
kvsall_score() (*dicee.models.dualE.DualE method*), 32
KvsSampleDataset (*class in dicee*), 200
KvsSampleDataset (*class in dicee.dataset_classes*), 137

L

label_smoothing_rate (*dicee.AllvsAll attribute*), 200
label_smoothing_rate (*dicee.config.Namespace attribute*), 131
label_smoothing_rate (*dicee.dataset_classes.AllvsAll attribute*), 137
label_smoothing_rate (*dicee.dataset_classes.KvsAll attribute*), 136
label_smoothing_rate (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
label_smoothing_rate (*dicee.dataset_classes.TriplePredictionDataset attribute*), 139
label_smoothing_rate (*dicee.KvsAll attribute*), 199
label_smoothing_rate (*dicee.KvsSampleDataset attribute*), 201
label_smoothing_rate (*dicee.TriplePredictionDataset attribute*), 202
LayerNorm (*class in dicee.models.transformers*), 48
learning_rate (*dicee.BaseKGE attribute*), 186
learning_rate (*dicee.models.base_model.BaseKGE attribute*), 18
learning_rate (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
length (*dicee.dataset_classes.NegSampleDataset attribute*), 138
length (*dicee.dataset_classes.TriplePredictionDataset attribute*), 139
length (*dicee.NegSampleDataset attribute*), 201
length (*dicee.TriplePredictionDataset attribute*), 202

level (*dicee.callbacks.Perturb attribute*), 129
LFMult (*class in dicee*), 181
LFMult (*class in dicee.models*), 98
LFMult (*class in dicee.models.function_space*), 35
LFMult1 (*class in dicee.models*), 97
LFMult1 (*class in dicee.models.function_space*), 35
linear() (*dicee.LFMult method*), 181
linear() (*dicee.models.function_space.LFMult method*), 35
linear() (*dicee.models.LFMult method*), 98
list2tuple() (*dicee.query_generator.QueryGenerator method*), 155
list2tuple() (*dicee.QueryGenerator method*), 206
lm_head (*dicee.BytE attribute*), 184
lm_head (*dicee.models.transformers.BytE attribute*), 47
lm_head (*dicee.models.transformers.GPT attribute*), 52
ln_1 (*dicee.models.transformers.Block attribute*), 51
ln_2 (*dicee.models.transformers.Block attribute*), 51
load() (*dicee.read_preprocess_save_load_kg.LoadSaveToDisk method*), 106
load() (*dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk method*), 102
load_indexed_data() (*dicee.Execute method*), 195
load_indexed_data() (*dicee.executer.Execute method*), 146
load_json() (*in module dicee*), 188
load_json() (*in module dicee.static_funcs*), 158
load_model() (*in module dicee*), 188
load_model() (*in module dicee.static_funcs*), 158
load_model_ensemble() (*in module dicee*), 188
load_model_ensemble() (*in module dicee.static_funcs*), 158
load_numpy() (*in module dicee*), 189
load_numpy() (*in module dicee.static_funcs*), 159
load_numpy_ndarray() (*in module dicee.read_preprocess_save_load_kg.util*), 104
load_pickle() (*in module dicee*), 187, 196
load_pickle() (*in module dicee.read_preprocess_save_load_kg.util*), 104
load_pickle() (*in module dicee.static_funcs*), 157
load_queries() (*dicee.query_generator.QueryGenerator method*), 155
load_queries() (*dicee.QueryGenerator method*), 207
load_queries_and_answers() (*dicee.query_generator.QueryGenerator static method*), 155
load_queries_and_answers() (*dicee.QueryGenerator static method*), 207
load_with_pandas() (*in module dicee.read_preprocess_save_load_kg.util*), 104
LoadSaveToDisk (*class in dicee.read_preprocess_save_load_kg*), 105
LoadSaveToDisk (*class in dicee.read_preprocess_save_load_kg.save_load_disk*), 102
local_rank (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
loss (*dicee.BaseKGE attribute*), 186
loss (*dicee.models.base_model.BaseKGE attribute*), 19
loss (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
loss_func (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
loss_func (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
loss_function (*dicee.trainer.torch_trainer.TorchTrainer attribute*), 110
loss_function() (*dicee.BytE method*), 184
loss_function() (*dicee.models.base_model.BaseKGELightning method*), 14
loss_function() (*dicee.models.BaseKGELightning method*), 55
loss_function() (*dicee.models.transformers.BytE method*), 47
loss_history (*dicee.BaseKGE attribute*), 186
loss_history (*dicee.models.base_model.BaseKGE attribute*), 19
loss_history (*dicee.models.BaseKGE attribute*), 61, 64, 67, 72, 78, 91, 95
loss_history (*dicee.models.pykeen_models.PykeenKGE attribute*), 40
loss_history (*dicee.models.PykeenKGE attribute*), 93
loss_history (*dicee.PykeenKGE attribute*), 182
loss_history (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
loss_history (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
lr (*dicee.analyse_experiments.Experiment attribute*), 121
lr (*dicee.config.Namespace attribute*), 130

M

m (*dicee.LFMult attribute*), 181
m (*dicee.models.function_space.LFMult attribute*), 35
m (*dicee.models.LFMult attribute*), 98
main() (*in module dicee.scripts.index*), 106
main() (*in module dicee.scripts.run*), 107

main() (*in module dicee.scripts.serve*), 108
mapping_from_first_two_cols_to_third() (*in module dicee*), 196
mapping_from_first_two_cols_to_third() (*in module dicee.static_preprocess_funcs*), 161
margin (*dicee.models.Pyke attribute*), 66
margin (*dicee.models.real.Pyke attribute*), 45
margin (*dicee.models.real.TransE attribute*), 44
margin (*dicee.models.TransE attribute*), 65
margin (*dicee.Pyke attribute*), 165
margin (*dicee.TransE attribute*), 168
max_ans_num (*dicee.query_generator.QueryGenerator attribute*), 154
max_ans_num (*dicee.QueryGenerator attribute*), 206
max_epochs (*dicee.callbacks.KGESaveCallback attribute*), 125
max_length_subword_tokens (*dicee.BaseKGE attribute*), 186
max_length_subword_tokens (*dicee.knowledge_graph.KG attribute*), 149
max_length_subword_tokens (*dicee.models.base_model.BaseKGE attribute*), 19
max_length_subword_tokens (*dicee.models.BaseKGE attribute*), 61, 64, 67, 72, 78, 91, 95
mem_of_model() (*dicee.models.base_model.BaseKGELightning method*), 13
mem_of_model() (*dicee.models.BaseKGELightning method*), 54
method (*dicee.callbacks.Perturb attribute*), 129
MLP (*class in dicee.models.transformers*), 49
mlp (*dicee.models.transformers.Block attribute*), 51
mode (*dicee.query_generator.QueryGenerator attribute*), 154
mode (*dicee.QueryGenerator attribute*), 206
model (*dicee.config.Namespace attribute*), 130
model (*dicee.models.pykeen_models.PykeenKGE attribute*), 40
model (*dicee.models.PykeenKGE attribute*), 93
model (*dicee.PykeenKGE attribute*), 182
model (*dicee.scripts.serve.NeuralSearcher attribute*), 108
model (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
model (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
model (*dicee.trainer.torch_trainer.TorchTrainer attribute*), 110
model_kwargs (*dicee.models.pykeen_models.PykeenKGE attribute*), 40
model_kwargs (*dicee.models.PykeenKGE attribute*), 92
model_kwargs (*dicee.PykeenKGE attribute*), 182
model_name (*dicee.analyse_experiments.Experiment attribute*), 121
module
    dicee, 12
    dicee.abstracts, 115
    dicee.analyse_experiments, 121
    dicee.callbacks, 122
    dicee.config, 130
    dicee.dataset_classes, 133
    dicee.eval_static_funcs, 143
    dicee.evaluator, 144
    dicee.executer, 146
    dicee.knowledge_graph, 148
    dicee.knowledge_graph_embeddings, 150
    dicee.models, 12
    dicee.models.base_model, 12
    dicee.models.clifford, 21
    dicee.models.complex, 29
    dicee.models.dualE, 31
    dicee.models.function_space, 33
    dicee.models.octonion, 36
    dicee.models.pykeen_models, 39
    dicee.models.quaternion, 41
    dicee.models.real, 44
    dicee.models.static_funcs, 45
    dicee.models.transformers, 46
    dicee.query_generator, 154
    dicee.read_preprocess_save_load_kg, 100
    dicee.read_preprocess_save_load_kg.preprocess, 100
    dicee.read_preprocess_save_load_kg.read_from_disk, 101
    dicee.read_preprocess_save_load_kg.save_load_disk, 102
    dicee.read_preprocess_save_load_kg.util, 103
    dicee.sanity_checkers, 156
    dicee.scripts, 106
    dicee.scripts.index, 106

dicee.scripts.run, 107
dicee.scripts.serve, 107
dicee.static_funcs, 156
dicee.static_funcs_training, 159
dicee.static_preprocess_funcs, 160
dicee.trainer, 108
dicee.trainer.dice_trainer, 108
dicee.trainer.torch_trainer, 110
dicee.trainer.torch_trainer_ddp, 111
MultiClassClassificationDataset (*class in dicee*), 197
MultiClassClassificationDataset (*class in dicee.dataset_classes*), 134
MultiLabelDataset (*class in dicee*), 197
MultiLabelDataset (*class in dicee.dataset_classes*), 134

N

n (*dicee.models.FMult2 attribute*), 97
n (*dicee.models.function_space.FMult2 attribute*), 34
n_embd (*dicee.models.transformers.CausalSelfAttention attribute*), 49
n_embd (*dicee.models.transformers.GPTConfig attribute*), 51
n_head (*dicee.models.transformers.CausalSelfAttention attribute*), 49
n_head (*dicee.models.transformers.GPTConfig attribute*), 51
n_layer (*dicee.models.transformers.GPTConfig attribute*), 51
n_layers (*dicee.models.FMult2 attribute*), 97
n_layers (*dicee.models.function_space.FMult2 attribute*), 34
name (*dicee.abstracts.BaseInteractiveKGE property*), 117
name (*dicee.AConEx attribute*), 174
name (*dicee.AConvO attribute*), 175
name (*dicee.AConvQ attribute*), 175
name (*dicee.BytE attribute*), 183
name (*dicee.CMult attribute*), 164
name (*dicee.ComplEx attribute*), 174
name (*dicee.ConEx attribute*), 177
name (*dicee.ConvO attribute*), 177
name (*dicee.ConvQ attribute*), 176
name (*dicee.DeCaL attribute*), 169
name (*dicee.DistMult attribute*), 165
name (*dicee.DualE attribute*), 172
name (*dicee.Keci attribute*), 166
name (*dicee.KeciBase attribute*), 165
name (*dicee.LFMult attribute*), 181
name (*dicee.models.AConEx attribute*), 69
name (*dicee.models.AConvO attribute*), 81
name (*dicee.models.AConvQ attribute*), 76
name (*dicee.models.clifford.CMult attribute*), 21
name (*dicee.models.clifford.DeCaL attribute*), 26
name (*dicee.models.clifford.Keci attribute*), 23
name (*dicee.models.clifford.KeciBase attribute*), 25
name (*dicee.models.CMult attribute*), 85
name (*dicee.models.ComplEx attribute*), 70
name (*dicee.models.complex.AConEx attribute*), 30
name (*dicee.models.complex.ComplEx attribute*), 31
name (*dicee.models.complex.ConEx attribute*), 29
name (*dicee.models.ConEx attribute*), 68
name (*dicee.models.ConvO attribute*), 81
name (*dicee.models.ConvQ attribute*), 75
name (*dicee.models.DeCaL attribute*), 87
name (*dicee.models.DistMult attribute*), 65
name (*dicee.models.DualE attribute*), 99
name (*dicee.models.dualE.DualE attribute*), 32
name (*dicee.models.FMult attribute*), 96
name (*dicee.models.FMult2 attribute*), 97
name (*dicee.models.function_space.FMult attribute*), 33
name (*dicee.models.function_space.FMult2 attribute*), 34
name (*dicee.models.function_space.GFMult attribute*), 34
name (*dicee.models.function_space.LFMult attribute*), 35
name (*dicee.models.function_space.LFMult1 attribute*), 35
name (*dicee.models.GFMult attribute*), 96

name (*dicee.models.Keci attribute*), 83
name (*dicee.models.KeciBase attribute*), 85
name (*dicee.models.LFMult attribute*), 98
name (*dicee.models.LFMult1 attribute*), 97
name (*dicee.models.octonion.AConvO attribute*), 39
name (*dicee.models.octonion.ConvO attribute*), 38
name (*dicee.models.octonion.OMult attribute*), 37
name (*dicee.models.OMult attribute*), 80
name (*dicee.models.Pyke attribute*), 66
name (*dicee.models.pykeen_models.PykeenKGE attribute*), 40
name (*dicee.models.PykeenKGE attribute*), 93
name (*dicee.models.QMult attribute*), 74
name (*dicee.models.quaternion.AConvQ attribute*), 43
name (*dicee.models.quaternion.ConvQ attribute*), 43
name (*dicee.models.quaternion.QMult attribute*), 42
name (*dicee.models.real.DistMult attribute*), 44
name (*dicee.models.real.Pyke attribute*), 45
name (*dicee.models.real.Shallom attribute*), 45
name (*dicee.models.real.TransE attribute*), 44
name (*dicee.models.Shallom attribute*), 65
name (*dicee.models.TransE attribute*), 65
name (*dicee.models.transformers.BytE attribute*), 47
name (*dicee.OMult attribute*), 180
name (*dicee.Pyke attribute*), 164
name (*dicee.PykeenKGE attribute*), 182
name (*dicee.QMult attribute*), 179
name (*dicee.Shallom attribute*), 180
name (*dicee.TransE attribute*), 168
Namespace (*class in dicee.config*), 130
neg_ratio (*dicee.BPE_NegativeSamplingDataset attribute*), 197
neg_ratio (*dicee.config.Namespace attribute*), 131
neg_ratio (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 134
neg_sample_ratio (*dicee.CVDataModule attribute*), 203
neg_sample_ratio (*dicee.dataset_classes.CVDataModule attribute*), 140
neg_sample_ratio (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
neg_sample_ratio (*dicee.dataset_classes.NegSampleDataset attribute*), 138
neg_sample_ratio (*dicee.dataset_classes.TriplePredictionDataset attribute*), 139
neg_sample_ratio (*dicee.KvsSampleDataset attribute*), 201
neg_sample_ratio (*dicee.NegSampleDataset attribute*), 201
neg_sample_ratio (*dicee.TriplePredictionDataset attribute*), 202
negnorm() (*dicee.KGE method*), 193
negnorm() (*dicee.knowledge_graph_embeddings.KGE method*), 153
NegSampleDataset (*class in dicee*), 201
NegSampleDataset (*class in dicee.dataset_classes*), 138
neural_searcher (*in module dicee.scripts.serve*), 108
NeuralSearcher (*class in dicee.scripts.serve*), 108
NodeTrainer (*class in dicee.trainer.torch_trainer_ddp*), 112
norm_fc1 (*dicee.AConEx attribute*), 174
norm_fc1 (*dicee.AConvO attribute*), 175
norm_fc1 (*dicee.ConEx attribute*), 178
norm_fc1 (*dicee.ConvO attribute*), 177
norm_fc1 (*dicee.models.AConEx attribute*), 69
norm_fc1 (*dicee.models.AConvO attribute*), 82
norm_fc1 (*dicee.models.complex.AConEx attribute*), 30
norm_fc1 (*dicee.models.complex.ConEx attribute*), 29
norm_fc1 (*dicee.models.ConEx attribute*), 68
norm_fc1 (*dicee.models.ConvO attribute*), 81
norm_fc1 (*dicee.models.octonion.AConvO attribute*), 39
norm_fc1 (*dicee.models.octonion.ConvO attribute*), 38
normalization (*dicee.analyse_experiments.Experiment attribute*), 122
normalization (*dicee.config.Namespace attribute*), 131
normalize_head_entity_embeddings (*dicee.BaseKGE attribute*), 186
normalize_head_entity_embeddings (*dicee.models.base_model.BaseKGE attribute*), 19
normalize_head_entity_embeddings (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
normalize_relation_embeddings (*dicee.BaseKGE attribute*), 186
normalize_relation_embeddings (*dicee.models.base_model.BaseKGE attribute*), 19
normalize_relation_embeddings (*dicee.models.BaseKGE attribute*), 60, 63, 67, 72, 77, 91, 94
normalize_tail_entity_embeddings (*dicee.BaseKGE attribute*), 186

normalize_tail_entity_embeddings (*dicee.models.base_model.BaseKGE attribute*), 19
normalize_tail_entity_embeddings (*dicee.models.BaseKGE attribute*), 60, 63, 67, 72, 77, 91, 94
normalizer_class (*dicee.BaseKGE attribute*), 186
normalizer_class (*dicee.models.base_model.BaseKGE attribute*), 19
normalizer_class (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
num_bpe_entities (*dicee.BPE_NegativeSamplingDataset attribute*), 197
num_bpe_entities (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 134
num_bpe_entities (*dicee.knowledge_graph.KG attribute*), 149
num_core (*dicee.config.Namespace attribute*), 131
num_datapoints (*dicee.BPE_NegativeSamplingDataset attribute*), 197
num_datapoints (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 134
num_datapoints (*dicee.dataset_classes.MultiLabelDataset attribute*), 134
num_datapoints (*dicee.MultiLabelDataset attribute*), 197
num_ent (*dicee.DualE attribute*), 172
num_ent (*dicee.models.DualE attribute*), 99
num_ent (*dicee.models.dualE.DualE attribute*), 32
num_entities (*dicee.BaseKGE attribute*), 186
num_entities (*dicee.CVDataModule attribute*), 203
num_entities (*dicee.dataset_classes.CVDataModule attribute*), 140
num_entities (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
num_entities (*dicee.dataset_classes.NegSampleDataset attribute*), 138
num_entities (*dicee.dataset_classes.TriplePredictionDataset attribute*), 139
num_entities (*dicee.evaluator.Evaluator attribute*), 144
num_entities (*dicee.knowledge_graph.KG attribute*), 148
num_entities (*dicee.KvsSampleDataset attribute*), 201
num_entities (*dicee.models.base_model.BaseKGE attribute*), 18
num_entities (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
num_entities (*dicee.NegSampleDataset attribute*), 201
num_entities (*dicee.TriplePredictionDataset attribute*), 202
num_epochs (*dicee.abstracts.AbstractPPECallback attribute*), 120
num_epochs (*dicee.analyse_experiments.Experiment attribute*), 121
num_epochs (*dicee.callbacks.ASWA attribute*), 126
num_epochs (*dicee.config.Namespace attribute*), 130
num_epochs (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
num_epochs (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
num_folds_for_cv (*dicee.config.Namespace attribute*), 131
num_of_data_points (*dicee.dataset_classes.MultiClassClassificationDataset attribute*), 135
num_of_data_points (*dicee.MultiClassClassificationDataset attribute*), 198
num_of_epochs (*dicee.callbacks.PseudoLabellingCallback attribute*), 126
num_of_output_channels (*dicee.BaseKGE attribute*), 186
num_of_output_channels (*dicee.config.Namespace attribute*), 132
num_of_output_channels (*dicee.models.base_model.BaseKGE attribute*), 19
num_of_output_channels (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
num_params (*dicee.analyse_experiments.Experiment attribute*), 121
num_relations (*dicee.BaseKGE attribute*), 186
num_relations (*dicee.CVDataModule attribute*), 203
num_relations (*dicee.dataset_classes.CVDataModule attribute*), 140
num_relations (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
num_relations (*dicee.dataset_classes.NegSampleDataset attribute*), 138
num_relations (*dicee.dataset_classes.TriplePredictionDataset attribute*), 139
num_relations (*dicee.evaluator.Evaluator attribute*), 145
num_relations (*dicee.knowledge_graph.KG attribute*), 148
num_relations (*dicee.KvsSampleDataset attribute*), 201
num_relations (*dicee.models.base_model.BaseKGE attribute*), 18
num_relations (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
num_relations (*dicee.NegSampleDataset attribute*), 201
num_relations (*dicee.TriplePredictionDataset attribute*), 202
num_sample (*dicee.models.FMult attribute*), 96
num_sample (*dicee.models.function_space.FMult attribute*), 33
num_sample (*dicee.models.function_space.GFMult attribute*), 34
num_sample (*dicee.models.GFMult attribute*), 96
num_tokens (*dicee.BaseKGE attribute*), 186
num_tokens (*dicee.knowledge_graph.KG attribute*), 149
num_tokens (*dicee.models.base_model.BaseKGE attribute*), 18
num_tokens (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
num_workers (*dicee.CVDataModule attribute*), 203
num_workers (*dicee.dataset_classes.CVDataModule attribute*), 140
numpy_data_type_changer() (*in module dicee*), 188

numpy_data_type_changer() (*in module dicee.static_funcs*), 158

O

octonion_mul() (*in module dicee.models*), 79
octonion_mul() (*in module dicee.models.octonion*), 37
octonion_mul_norm() (*in module dicee.models*), 79
octonion_mul_norm() (*in module dicee.models.octonion*), 37
octonion_normalizer() (*dicee.AConvO static method*), 175
octonion_normalizer() (*dicee.ConvO static method*), 177
octonion_normalizer() (*dicee.models.AConvO static method*), 82
octonion_normalizer() (*dicee.models.ConvO static method*), 81
octonion_normalizer() (*dicee.models.octonion.AConvO static method*), 39
octonion_normalizer() (*dicee.models.octonion.ConvO static method*), 38
octonion_normalizer() (*dicee.models.octonion.OMult static method*), 37
octonion_normalizer() (*dicee.models.OMult static method*), 80
octonion_normalizer() (*dicee.OMult static method*), 180
OMult (*class in dicee*), 179
OMult (*class in dicee.models*), 79
OMult (*class in dicee.models.octonion*), 37
on_epoch_end() (*dicee.callbacks.KGESaveCallback method*), 126
on_epoch_end() (*dicee.callbacks.PseudoLabellingCallback method*), 126
on_fit_end() (*dicee.abstracts.AbstractCallback method*), 120
on_fit_end() (*dicee.abstracts.AbstractPPECallback method*), 120
on_fit_end() (*dicee.abstracts.AbstractTrainer method*), 115
on_fit_end() (*dicee.callbacks.AccumulateEpochLossCallback method*), 123
on_fit_end() (*dicee.callbacks.ASWA method*), 127
on_fit_end() (*dicee.callbacks.Eval method*), 128
on_fit_end() (*dicee.callbacks.KGESaveCallback method*), 126
on_fit_end() (*dicee.callbacks.PrintCallback method*), 124
on_fit_start() (*dicee.abstracts.AbstractCallback method*), 119
on_fit_start() (*dicee.abstracts.AbstractPPECallback method*), 120
on_fit_start() (*dicee.abstracts.AbstractTrainer method*), 115
on_fit_start() (*dicee.callbacks.Eval method*), 128
on_fit_start() (*dicee.callbacks.KGESaveCallback method*), 125
on_fit_start() (*dicee.callbacks.KronE method*), 129
on_fit_start() (*dicee.callbacks.PrintCallback method*), 124
on_init_end() (*dicee.abstracts.AbstractCallback method*), 119
on_init_start() (*dicee.abstracts.AbstractCallback method*), 119
on_train_batch_end() (*dicee.abstracts.AbstractCallback method*), 119
on_train_batch_end() (*dicee.abstracts.AbstractTrainer method*), 116
on_train_batch_end() (*dicee.callbacks.Eval method*), 128
on_train_batch_end() (*dicee.callbacks.KGESaveCallback method*), 125
on_train_batch_end() (*dicee.callbacks.PrintCallback method*), 124
on_train_batch_start() (*dicee.callbacks.Perturb method*), 130
on_train_epoch_end() (*dicee.abstracts.AbstractCallback method*), 119
on_train_epoch_end() (*dicee.abstracts.AbstractTrainer method*), 116
on_train_epoch_end() (*dicee.callbacks.ASWA method*), 127
on_train_epoch_end() (*dicee.callbacks.Eval method*), 128
on_train_epoch_end() (*dicee.callbacks.KGESaveCallback method*), 125
on_train_epoch_end() (*dicee.callbacks.PrintCallback method*), 124
on_train_epoch_end() (*dicee.models.base_model.BaseKGELightning method*), 14
on_train_epoch_end() (*dicee.models.BaseKGELightning method*), 55
OnevsAllDataset (*class in dicee*), 198
OnevsAllDataset (*class in dicee.dataset_classes*), 135
optim (*dicee.config.Namespace attribute*), 130
optimizer (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
optimizer (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
optimizer (*dicee.trainer.torch_trainer.TorchTrainer attribute*), 110
optimizer_name (*dicee.BaseKGE attribute*), 186
optimizer_name (*dicee.models.base_model.BaseKGE attribute*), 19
optimizer_name (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
ordered_bpe_entities (*dicee.BPE_NegativeSamplingDataset attribute*), 197
ordered_bpe_entities (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 134
ordered_bpe_entities (*dicee.knowledge_graph.KG attribute*), 149
ordered_shaped_bpe_tokens (*dicee.knowledge_graph.KG attribute*), 148

P

p (*dicee.CMult attribute*), 164
p (*dicee.config.Namespace attribute*), 132
p (*dicee.DeCaL attribute*), 169
p (*dicee.Keci attribute*), 166
p (*dicee.models.clifford.CMult attribute*), 21
p (*dicee.models.clifford.DeCaL attribute*), 26
p (*dicee.models.clifford.Keci attribute*), 23
p (*dicee.models.CMult attribute*), 86
p (*dicee.models.DeCaL attribute*), 87
p (*dicee.models.Keci attribute*), 83
padding (*dicee.knowledge_graph.KG attribute*), 149
param_init (*dicee.BaseKGE attribute*), 186
param_init (*dicee.models.base_model.BaseKGE attribute*), 19
param_init (*dicee.models.BaseKGE attribute*), 60, 64, 67, 72, 78, 91, 95
parameters() (*dicee.abstracts.BaseInteractiveKGE method*), 118
path (*dicee.abstracts.AbstractPPECallback attribute*), 120
path (*dicee.callbacks.AccumulateEpochLossCallback attribute*), 123
path (*dicee.callbacks.ASWA attribute*), 126
path (*dicee.callbacks.Eval attribute*), 128
path (*dicee.callbacks.KGESaveCallback attribute*), 125
path_dataset_folder (*dicee.analyse_experiments.Experiment attribute*), 121
path_for_deserialization (*dicee.knowledge_graph.KG attribute*), 149
path_for_serialization (*dicee.knowledge_graph.KG attribute*), 149
path_single_kg (*dicee.config.Namespace attribute*), 130
path_single_kg (*dicee.knowledge_graph.KG attribute*), 149
path_to_store_single_run (*dicee.config.Namespace attribute*), 130
Perturb (*class in dicee.callbacks*), 129
poly_NN() (*dicee.LFMult method*), 181
poly_NN() (*dicee.models.function_space.LFMult method*), 35
poly_NN() (*dicee.models.LFMult method*), 98
polynomial() (*dicee.LFMult method*), 182
polynomial() (*dicee.models.function_space.LFMult method*), 36
polynomial() (*dicee.models.LFMult method*), 99
pop() (*dicee.LFMult method*), 182
pop() (*dicee.models.function_space.LFMult method*), 36
pop() (*dicee.models.LFMult method*), 99
pq (*dicee.analyse_experiments.Experiment attribute*), 122
predict() (*dicee.KGE method*), 192
predict() (*dicee.knowledge_graph_embeddings.KGE method*), 151
predict_dataloader() (*dicee.models.base_model.BaseKGELightning method*), 15
predict_dataloader() (*dicee.models.BaseKGELightning method*), 57
predict_missing_head_entity() (*dicee.KGE method*), 191
predict_missing_head_entity() (*dicee.knowledge_graph_embeddings.KGE method*), 150
predict_missing_relations() (*dicee.KGE method*), 191
predict_missing_relations() (*dicee.knowledge_graph_embeddings.KGE method*), 151
predict_missing_tail_entity() (*dicee.KGE method*), 191
predict_missing_tail_entity() (*dicee.knowledge_graph_embeddings.KGE method*), 151
predict_topk() (*dicee.KGE method*), 192
predict_topk() (*dicee.knowledge_graph_embeddings.KGE method*), 152
prepare_data() (*dicee.CVDataModule method*), 205
prepare_data() (*dicee.dataset_classes.CVDataModule method*), 142
preprocess_with_byte_pair_encoding() (*dicee.read_preprocess_save_load_kg.PreprocessKG method*), 105
preprocess_with_byte_pair_encoding() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 101
preprocess_with_byte_pair_encoding_with_padding() (*dicee.read_preprocess_save_load_kg.PreprocessKG method*), 105
preprocess_with_byte_pair_encoding_with_padding() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 101
preprocess_with_pandas() (*dicee.read_preprocess_save_load_kg.PreprocessKG method*), 105
preprocess_with_pandas() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 101
preprocess_with_polars() (*dicee.read_preprocess_save_load_kg.PreprocessKG method*), 105
preprocess_with_polars() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 101
preprocesses_input_args() (*in module dicee.static_preprocess_funcs*), 160
PreprocessKG (*class in dicee.read_preprocess_save_load_kg*), 105
PreprocessKG (*class in dicee.read_preprocess_save_load_kg.preprocess*), 100
previous_args (*dicee.executer.ContinuousExecute attribute*), 148
print_peak_memory() (*in module dicee.trainer.torch_trainer_ddp*), 112
PrintCallback (*class in dicee.callbacks*), 123
process (*dicee.trainer.torch_trainer.TorchTrainer attribute*), 110

PseudoLabellingCallback (*class in dicee.callbacks*), 126
Pyke (*class in dicee*), 164
Pyke (*class in dicee.models*), 66
Pyke (*class in dicee.models.real*), 45
pykeen_model_kwargs (*dicee.config.Namespace attribute*), 132
PykeenKGE (*class in dicee*), 182
PykeenKGE (*class in dicee.models*), 92
PykeenKGE (*class in dicee.models.pykeen_models*), 40

Q

q (*dicee.CMult attribute*), 164
q (*dicee.config.Namespace attribute*), 132
q (*dicee.DeCaL attribute*), 169
q (*dicee.Keci attribute*), 166
q (*dicee.models.clifford.CMult attribute*), 22
q (*dicee.models.clifford.DeCaL attribute*), 26
q (*dicee.models.clifford.Keci attribute*), 23
q (*dicee.models.CMult attribute*), 86
q (*dicee.models.DeCaL attribute*), 87
q (*dicee.models.Keci attribute*), 83
qdrant_client (*dicee.scripts.serve.NeuralSearcher attribute*), 108
QMult (*class in dicee*), 178
QMult (*class in dicee.models*), 73
QMult (*class in dicee.models.quaternion*), 41
quaternion_mul() (*in module dicee.models*), 70
quaternion_mul() (*in module dicee.models.static_funcs*), 46
quaternion_mul_with_unit_norm() (*in module dicee.models*), 73
quaternion_mul_with_unit_norm() (*in module dicee.models.quaternion*), 41
quaternion_multiplication_followed_by_inner_product() (*dicee.models.QMult method*), 74
quaternion_multiplication_followed_by_inner_product() (*dicee.models.quaternion.QMult method*), 42
quaternion_multiplication_followed_by_inner_product() (*dicee.QMult method*), 179
quaternion_normalizer() (*dicee.models.QMult static method*), 74
quaternion_normalizer() (*dicee.models.quaternion.QMult static method*), 42
quaternion_normalizer() (*dicee.QMult static method*), 179
query_name_to_struct (*dicee.query_generator.QueryGenerator attribute*), 155
query_name_to_struct (*dicee.QueryGenerator attribute*), 206
QueryGenerator (*class in dicee*), 206
QueryGenerator (*class in dicee.query_generator*), 154

R

r (*dicee.DeCaL attribute*), 169
r (*dicee.Keci attribute*), 166
r (*dicee.models.clifford.DeCaL attribute*), 26
r (*dicee.models.clifford.Keci attribute*), 23
r (*dicee.models.DeCaL attribute*), 87
r (*dicee.models.Keci attribute*), 83
random_prediction() (*in module dicee*), 188
random_prediction() (*in module dicee.static_funcs*), 158
random_seed (*dicee.config.Namespace attribute*), 131
ratio (*dicee.callbacks.Perturb attribute*), 129
re (*dicee.DeCaL attribute*), 169
re (*dicee.models.clifford.DeCaL attribute*), 26
re (*dicee.models.DeCaL attribute*), 87
re_vocab (*dicee.evaluator.Evaluator attribute*), 144
read_from_disk() (*in module dicee.read_preprocess_save_load_kg.util*), 103
read_from_triple_store() (*in module dicee.read_preprocess_save_load_kg.util*), 104
read_only_few (*dicee.config.Namespace attribute*), 132
read_only_few (*dicee.knowledge_graph.KG attribute*), 149
read_or_load_kg() (*dicee.Execute method*), 195
read_or_load_kg() (*dicee.executer.Execute method*), 146
read_or_load_kg() (*in module dicee*), 188
read_or_load_kg() (*in module dicee.static_funcs*), 158
read_preprocess_index_serialize_data() (*dicee.Execute method*), 195
read_preprocess_index_serialize_data() (*dicee.executer.Execute method*), 146
read_with_pandas() (*in module dicee.read_preprocess_save_load_kg.util*), 103
read_with_polars() (*in module dicee.read_preprocess_save_load_kg.util*), 103
ReadFromDisk (*class in dicee.read_preprocess_save_load_kg*), 106

ReadFromDisk (*class in dicee.read_preprocess_save_load_kg.read_from_disk*), 101
rel2id (*dicee.query_generator.QueryGenerator attribute*), 154
rel2id (*dicee.QueryGenerator attribute*), 206
relation_embeddings (*dicee.AConvQ attribute*), 175
relation_embeddings (*dicee.CMult attribute*), 164
relation_embeddings (*dicee.ConvQ attribute*), 176
relation_embeddings (*dicee.DeCaL attribute*), 169
relation_embeddings (*dicee.DualE attribute*), 172
relation_embeddings (*dicee.LFMult attribute*), 181
relation_embeddings (*dicee.models.AConvQ attribute*), 76
relation_embeddings (*dicee.models.clifford.CMult attribute*), 21
relation_embeddings (*dicee.models.clifford.DeCaL attribute*), 26
relation_embeddings (*dicee.models.CMult attribute*), 86
relation_embeddings (*dicee.models.ConvQ attribute*), 75
relation_embeddings (*dicee.models.DeCaL attribute*), 87
relation_embeddings (*dicee.models.DualE attribute*), 99
relation_embeddings (*dicee.models.dualE.DualE attribute*), 32
relation_embeddings (*dicee.models.FMult attribute*), 96
relation_embeddings (*dicee.models.FMult2 attribute*), 97
relation_embeddings (*dicee.models.function_space.FMult attribute*), 33
relation_embeddings (*dicee.models.function_space.FMult2 attribute*), 34
relation_embeddings (*dicee.models.function_space.GFMult attribute*), 34
relation_embeddings (*dicee.models.function_space.LFMult attribute*), 35
relation_embeddings (*dicee.models.function_space.LFMult1 attribute*), 35
relation_embeddings (*dicee.models.GFMult attribute*), 96
relation_embeddings (*dicee.models.LFMult attribute*), 98
relation_embeddings (*dicee.models.LFMult1 attribute*), 97
relation_embeddings (*dicee.models.pykeen_models.PykeenKGE attribute*), 40
relation_embeddings (*dicee.models.PykeenKGE attribute*), 93
relation_embeddings (*dicee.models.quaternion.AConvQ attribute*), 43
relation_embeddings (*dicee.models.quaternion.ConvQ attribute*), 43
relation_embeddings (*dicee.PykeenKGE attribute*), 182
relation_to_idx (*dicee.knowledge_graph.KG attribute*), 149
relations_str (*dicee.knowledge_graph.KG property*), 149
reload_dataset() (*in module dicee*), 196
reload_dataset() (*in module dicee.dataset_classes*), 133
remove_triples_from_train_with_condition() (*dicee.read_preprocess_save_load_kg.PreprocessKG method*), 105
remove_triples_from_train_with_condition() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 101
report (*dicee.DICE_Trainer attribute*), 189
report (*dicee.evaluator.Evaluator attribute*), 145
report (*dicee.Execute attribute*), 195
report (*dicee.executer.Execute attribute*), 146
report (*dicee.trainer.DICE_Trainer attribute*), 113
report (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 109
reports (*dicee.callbacks.Eval attribute*), 128
requires_grad_for_interactions (*dicee.Keci attribute*), 166
requires_grad_for_interactions (*dicee.KeciBase attribute*), 165
requires_grad_for_interactions (*dicee.models.clifford.Keci attribute*), 23
requires_grad_for_interactions (*dicee.models.clifford.KeciBase attribute*), 25
requires_grad_for_interactions (*dicee.models.Keci attribute*), 83
requires_grad_for_interactions (*dicee.models.KeciBase attribute*), 85
resid_dropout (*dicee.models.transformers.CausalSelfAttention attribute*), 49
residual_convolution() (*dicee.AConEx method*), 174
residual_convolution() (*dicee.AConvO method*), 175
residual_convolution() (*dicee.AConvQ method*), 176
residual_convolution() (*dicee.ConEx method*), 178
residual_convolution() (*dicee.ConvO method*), 177
residual_convolution() (*dicee.ConvQ method*), 176
residual_convolution() (*dicee.models.AConEx method*), 69
residual_convolution() (*dicee.models.AConvO method*), 82
residual_convolution() (*dicee.models.AConvQ method*), 76
residual_convolution() (*dicee.models.complex.AConEx method*), 30
residual_convolution() (*dicee.models.complex.ConEx method*), 30
residual_convolution() (*dicee.models.ConEx method*), 69
residual_convolution() (*dicee.models.ConvO method*), 81
residual_convolution() (*dicee.models.ConvQ method*), 75
residual_convolution() (*dicee.models.octonion.AConvO method*), 39
residual_convolution() (*dicee.models.octonion.ConvO method*), 39

residual_convolution() (*dicee.models.quaternion.AConvQ method*), 43
residual_convolution() (*dicee.models.quaternion.ConvQ method*), 43
retrieve_embeddings() (*in module dicee.scripts.serve*), 108
return_multi_hop_query_results() (*dicee.KGE method*), 193
return_multi_hop_query_results() (*dicee.knowledge_graph_embeddings.KGE method*), 153
root() (*in module dicee.scripts.serve*), 108
roots (*dicee.models.FMult attribute*), 96
roots (*dicee.models.function_space.FMult attribute*), 33
roots (*dicee.models.function_space.GFMult attribute*), 34
roots (*dicee.models.GFMult attribute*), 96
runtime (*dicee.analyse_experiments.Experiment attribute*), 122

S

sample_counter (*dicee.abstracts.AbstractPPECallback attribute*), 120
sample_entity() (*dicee.abstracts.BaseInteractiveKGE method*), 117
sample_relation() (*dicee.abstracts.BaseInteractiveKGE method*), 117
sample_triples_ratio (*dicee.config.Namespace attribute*), 132
sample_triples_ratio (*dicee.knowledge_graph.KG attribute*), 149
sanity_checking_with_arguments() (*in module dicee.sanity_checkers*), 156
save() (*dicee.abstracts.BaseInteractiveKGE method*), 117
save() (*dicee.read_preprocess_save_load_kg.LoadSaveToDisk method*), 106
save() (*dicee.read_preprocess_save_load_kg.save_load_disk.LoadSaveToDisk method*), 102
save_checkpoint() (*dicee.abstracts.AbstractTrainer static method*), 116
save_checkpoint_model() (*in module dicee*), 188
save_checkpoint_model() (*in module dicee.static_funcs*), 158
save_embeddings() (*in module dicee*), 188
save_embeddings() (*in module dicee.static_funcs*), 158
save_embeddings_as_csv (*dicee.config.Namespace attribute*), 130
save_experiment() (*dicee.analyse_experiments.Experiment method*), 122
save_model_at_every_epoch (*dicee.config.Namespace attribute*), 131
save_numpy_ndarray() (*in module dicee*), 188
save_numpy_ndarray() (*in module dicee.read_preprocess_save_load_kg.util*), 104
save_numpy_ndarray() (*in module dicee.static_funcs*), 158
save_pickle() (*in module dicee*), 187
save_pickle() (*in module dicee.read_preprocess_save_load_kg.util*), 104
save_pickle() (*in module dicee.static_funcs*), 157
save_queries() (*dicee.query_generator.QueryGenerator method*), 155
save_queries() (*dicee.QueryGenerator method*), 207
save_queries_and_answers() (*dicee.query_generator.QueryGenerator static method*), 155
save_queries_and_answers() (*dicee.QueryGenerator static method*), 207
save_trained_model() (*dicee.Execute method*), 195
save_trained_model() (*dicee.executer.Execute method*), 147
scalar_batch_NN() (*dicee.LFMult method*), 181
scalar_batch_NN() (*dicee.models.function_space.LFMult method*), 36
scalar_batch_NN() (*dicee.models.LFMult method*), 98
scaler (*dicee.callbacks.Perturb attribute*), 129
score() (*dicee.CMult method*), 164
score() (*dicee.ComplEx static method*), 174
score() (*dicee.DistMult method*), 165
score() (*dicee.Keci method*), 168
score() (*dicee.models.clifford.CMult method*), 22
score() (*dicee.models.clifford.Keci method*), 25
score() (*dicee.models.CMult method*), 86
score() (*dicee.models.ComplEx static method*), 70
score() (*dicee.models.complex.ComplEx static method*), 31
score() (*dicee.models.DistMult method*), 65
score() (*dicee.models.Keci method*), 85
score() (*dicee.models.octonion.OMult method*), 37
score() (*dicee.models.OMult method*), 80
score() (*dicee.models.QMult method*), 75
score() (*dicee.models.quaternion.QMult method*), 42
score() (*dicee.models.real.DistMult method*), 44
score() (*dicee.models.real.TransE method*), 45
score() (*dicee.models.TransE method*), 65
score() (*dicee.OMult method*), 180
score() (*dicee.QMult method*), 179
score() (*dicee.TransE method*), 168

score_func (*dicee.models.FMult2 attribute*), 97
score_func (*dicee.models.function_space.FMult2 attribute*), 34
scoring_technique (*dicee.analyse_experiments.Experiment attribute*), 122
scoring_technique (*dicee.config.Namespace attribute*), 131
search() (*dicee.scripts.serve.NeuralSearcher method*), 108
search_embeddings() (*in module dicee.scripts.serve*), 108
seed (*dicee.query_generator.QueryGenerator attribute*), 154
seed (*dicee.QueryGenerator attribute*), 206
select_model() (*in module dicee*), 188
select_model() (*in module dicee.static_funcs*), 158
selected_optimizer (*dicee.BaseKGE attribute*), 186
selected_optimizer (*dicee.models.base_model.BaseKGE attribute*), 19
selected_optimizer (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
sequential_vocabulary_construction() (*dicee.read_preprocess_save_load_kg.PreprocessKG method*), 105
sequential_vocabulary_construction() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 101
set_global_seed() (*dicee.query_generator.QueryGenerator method*), 155
set_global_seed() (*dicee.QueryGenerator method*), 206
set_model_eval_mode() (*dicee.abstracts.BaseInteractiveKGE method*), 117
set_model_train_mode() (*dicee.abstracts.BaseInteractiveKGE method*), 117
setup() (*dicee.CVDataModule method*), 204
setup() (*dicee.dataset_classes.CVDataModule method*), 141
Shallom (*class in dicee*), 180
Shallom (*class in dicee.models*), 65
Shallom (*class in dicee.models.real*), 45
shallom (*dicee.models.real.Shallom attribute*), 45
shallom (*dicee.models.Shallom attribute*), 65
shallom (*dicee.Shallom attribute*), 180
shallom_width (*dicee.models.real.Shallom attribute*), 45
shallom_width (*dicee.models.Shallom attribute*), 65
shallom_width (*dicee.Shallom attribute*), 180
single_hop_query_answering() (*dicee.KGE method*), 193
single_hop_query_answering() (*dicee.knowledge_graph_embeddings.KGE method*), 153
sparql_endpoint (*dicee.config.Namespace attribute*), 130
sparql_endpoint (*dicee.knowledge_graph.KG attribute*), 148
start() (*dicee.DICE_Trainer method*), 190
start() (*dicee.Execute method*), 196
start() (*dicee.executer.Execute method*), 147
start() (*dicee.read_preprocess_save_load_kg.PreprocessKG method*), 105
start() (*dicee.read_preprocess_save_load_kg.preprocess.PreprocessKG method*), 100
start() (*dicee.read_preprocess_save_load_kg.read_from_disk.ReadFromDisk method*), 101
start() (*dicee.read_preprocess_save_load_kg.ReadFromDisk method*), 106
start() (*dicee.trainer.DICE_Trainer method*), 114
start() (*dicee.trainer.dice_trainer.DICE_Trainer method*), 110
start_time (*dicee.callbacks.PrintCallback attribute*), 124
start_time (*dicee.Execute attribute*), 195
start_time (*dicee.executer.Execute attribute*), 146
storage_path (*dicee.config.Namespace attribute*), 130
storage_path (*dicee.DICE_Trainer attribute*), 189
storage_path (*dicee.trainer.DICE_Trainer attribute*), 114
storage_path (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 109
store (*dicee.AllvsAll attribute*), 200
store (*dicee.dataset_classes.AllvsAll attribute*), 137
store (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
store (*dicee.KvsSampleDataset attribute*), 201
store() (*in module dicee*), 188
store() (*in module dicee.static_funcs*), 158
store_ensemble() (*dicee.abstracts.AbstractPPECallback method*), 121
strategy (*dicee.abstracts.AbstractTrainer attribute*), 115
swa (*dicee.config.Namespace attribute*), 132

T

T() (*dicee.DualE method*), 173
T() (*dicee.models.DualE method*), 100
T() (*dicee.models.dualE.DualE method*), 33
t_conorm() (*dicee.KGE method*), 193
t_conorm() (*dicee.knowledge_graph_embeddings.KGE method*), 153
t_norm() (*dicee.KGE method*), 193

t_norm() (*dicee.knowledge_graph_embeddings.KGE method*), 153
target_dim (*dicee.AllvsAll attribute*), 200
target_dim (*dicee.dataset_classes.AllvsAll attribute*), 137
target_dim (*dicee.dataset_classes.MultiLabelDataset attribute*), 134
target_dim (*dicee.dataset_classes.OnevsAllDataset attribute*), 135
target_dim (*dicee.knowledge_graph.KG attribute*), 149
target_dim (*dicee.MultiLabelDataset attribute*), 197
target_dim (*dicee.OnevsAllDataset attribute*), 198
temperature (*dicee.BytE attribute*), 184
temperature (*dicee.models.transformers.BytE attribute*), 47
tensor_t_norm() (*dicee.KGE method*), 193
tensor_t_norm() (*dicee.knowledge_graph_embeddings.KGE method*), 153
test_dataloader() (*dicee.models.base_model.BaseKGELightning method*), 14
test_dataloader() (*dicee.models.BaseKGELightning method*), 56
test_epoch_end() (*dicee.models.base_model.BaseKGELightning method*), 14
test_epoch_end() (*dicee.models.BaseKGELightning method*), 56
test_h1 (*dicee.analyse_experiments.Experiment attribute*), 122
test_h3 (*dicee.analyse_experiments.Experiment attribute*), 122
test_h10 (*dicee.analyse_experiments.Experiment attribute*), 122
test_mrr (*dicee.analyse_experiments.Experiment attribute*), 122
test_path (*dicee.query_generator.QueryGenerator attribute*), 154
test_path (*dicee.QueryGenerator attribute*), 206
timeit() (*in module dicee*), 187, 196
timeit() (*in module dicee.read_preprocess_save_load_kg.util*), 103
timeit() (*in module dicee.static_funcs*), 157
timeit() (*in module dicee.static_preprocess_funcs*), 160
to() (*dicee.KGE method*), 190
to() (*dicee.knowledge_graph_embeddings.KGE method*), 150
to_df() (*dicee.analyse_experiments.Experiment method*), 122
topk (*dicee.BytE attribute*), 184
topk (*dicee.models.transformers.BytE attribute*), 47
torch_ordered_shaped_bpe_entities (*dicee.dataset_classes.MultiLabelDataset attribute*), 134
torch_ordered_shaped_bpe_entities (*dicee.MultiLabelDataset attribute*), 197
TorchDDPTrainer (*class in dicee.trainer.torch_trainer_ddp*), 112
TorchTrainer (*class in dicee.trainer.torch_trainer*), 110
train() (*dicee.KGE method*), 194
train() (*dicee.knowledge_graph_embeddings.KGE method*), 154
train() (*dicee.trainer.torch_trainer_ddp.DDPTrainer method*), 113
train() (*dicee.trainer.torch_trainer_ddp.NodeTrainer method*), 112
train_data (*dicee.AllvsAll attribute*), 200
train_data (*dicee.dataset_classes.AllvsAll attribute*), 137
train_data (*dicee.dataset_classes.KvsAll attribute*), 136
train_data (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
train_data (*dicee.dataset_classes.MultiClassClassificationDataset attribute*), 135
train_data (*dicee.dataset_classes.OnevsAllDataset attribute*), 135
train_data (*dicee.KvsAll attribute*), 199
train_data (*dicee.KvsSampleDataset attribute*), 201
train_data (*dicee.MultiClassClassificationDataset attribute*), 198
train_data (*dicee.OnevsAllDataset attribute*), 198
train_dataloader() (*dicee.CVDataModule method*), 203
train_dataloader() (*dicee.dataset_classes.CVDataModule method*), 140
train_dataloader() (*dicee.models.base_model.BaseKGELightning method*), 16
train_dataloader() (*dicee.models.BaseKGELightning method*), 57
train_dataloaders (*dicee.trainer.torch_trainer.TorchTrainer attribute*), 110
train_dataset_loader (*dicee.trainer.torch_trainer_ddp.DDPTrainer attribute*), 113
train_dataset_loader (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
train_h1 (*dicee.analyse_experiments.Experiment attribute*), 122
train_h3 (*dicee.analyse_experiments.Experiment attribute*), 122
train_h10 (*dicee.analyse_experiments.Experiment attribute*), 122
train_indices_target (*dicee.dataset_classes.MultiLabelDataset attribute*), 134
train_indices_target (*dicee.MultiLabelDataset attribute*), 197
train_k_vs_all() (*dicee.KGE method*), 194
train_k_vs_all() (*dicee.knowledge_graph_embeddings.KGE method*), 154
train_mrr (*dicee.analyse_experiments.Experiment attribute*), 122
train_path (*dicee.query_generator.QueryGenerator attribute*), 154
train_path (*dicee.QueryGenerator attribute*), 206
train_set (*dicee.BPE_NegativeSamplingDataset attribute*), 197
train_set (*dicee.dataset_classes.BPE_NegativeSamplingDataset attribute*), 134

train_set (*dicee.dataset_classes.MultiLabelDataset attribute*), 134
train_set (*dicee.dataset_classes.NegSampleDataset attribute*), 138
train_set (*dicee.dataset_classes.TriplePredictionDataset attribute*), 139
train_set (*dicee.MultiLabelDataset attribute*), 197
train_set (*dicee.NegSampleDataset attribute*), 201
train_set (*dicee.TriplePredictionDataset attribute*), 202
train_set_idx (*dicee.CVDataModule attribute*), 203
train_set_idx (*dicee.dataset_classes.CVDataModule attribute*), 140
train_set_target (*dicee.knowledge_graph.KG attribute*), 149
train_target (*dicee.AllvsAll attribute*), 200
train_target (*dicee.dataset_classes.AllvsAll attribute*), 137
train_target (*dicee.dataset_classes.KvsAll attribute*), 136
train_target (*dicee.dataset_classes.KvsSampleDataset attribute*), 138
train_target (*dicee.KvsAll attribute*), 199
train_target (*dicee.KvsSampleDataset attribute*), 201
train_target_indices (*dicee.knowledge_graph.KG attribute*), 149
train_triples() (*dicee.KGE method*), 194
train_triples() (*dicee.knowledge_graph_embeddings.KGE method*), 154
trained_model (*dicee.Execute attribute*), 195
trained_model (*dicee.executer.Execute attribute*), 146
trainer (*dicee.config.Namespace attribute*), 131
trainer (*dicee.DICE_Trainer attribute*), 189
trainer (*dicee.Execute attribute*), 195
trainer (*dicee.executer.Execute attribute*), 146
trainer (*dicee.trainer.DICE_Trainer attribute*), 113
trainer (*dicee.trainer.dice_trainer.DICE_Trainer attribute*), 109
trainer (*dicee.trainer.torch_trainer_ddp.NodeTrainer attribute*), 112
training_step (*dicee.trainer.torch_trainer.TorchTrainer attribute*), 110
training_step() (*dicee.BytE method*), 184
training_step() (*dicee.models.base_model.BaseKGELightning method*), 13
training_step() (*dicee.models.BaseKGELightning method*), 54
training_step() (*dicee.models.transformers.BytE method*), 47
training_step_outputs (*dicee.models.base_model.BaseKGELightning attribute*), 13
training_step_outputs (*dicee.models.BaseKGELightning attribute*), 54
training_technique (*dicee.knowledge_graph.KG attribute*), 149
TransE (*class in dicee*), 168
TransE (*class in dicee.models*), 65
TransE (*class in dicee.models.real*), 44
transfer_batch_to_device() (*dicee.CVDataModule method*), 204
transfer_batch_to_device() (*dicee.dataset_classes.CVDataModule method*), 141
transformer (*dicee.BytE attribute*), 184
transformer (*dicee.models.transformers.BytE attribute*), 47
transformer (*dicee.models.transformers.GPT attribute*), 52
trapezoid() (*dicee.models.FMult2 method*), 97
trapezoid() (*dicee.models.function_space.FMult2 method*), 35
tri_score() (*dicee.LFMult method*), 181
tri_score() (*dicee.models.function_space.LFMult method*), 36
tri_score() (*dicee.models.function_space.LFMult1 method*), 35
tri_score() (*dicee.models.LFMult method*), 98
tri_score() (*dicee.models.LFMult1 method*), 97
triple_score() (*dicee.KGE method*), 193
triple_score() (*dicee.knowledge_graph_embeddings.KGE method*), 152
TriplePredictionDataset (*class in dicee*), 202
TriplePredictionDataset (*class in dicee.dataset_classes*), 139
tuned_embedding_dim (*dicee.models.FMult2 attribute*), 97
tuned_embedding_dim (*dicee.models.function_space.FMult2 attribute*), 34
tuple2list() (*dicee.query_generator.QueryGenerator method*), 155
tuple2list() (*dicee.QueryGenerator method*), 206

U

unlabelled_size (*dicee.callbacks.PseudoLabellingCallback attribute*), 126
unmap() (*dicee.query_generator.QueryGenerator method*), 155
unmap() (*dicee.QueryGenerator method*), 207
unmap_query() (*dicee.query_generator.QueryGenerator method*), 155
unmap_query() (*dicee.QueryGenerator method*), 207

V

val_aswa (*dicee.callbacks.ASWA attribute*), 127
val_dataloader() (*dicee.models.base_model.BaseKGELightning method*), 15
val_dataloader() (*dicee.models.BaseKGELightning method*), 56
val_h1 (*dicee.analyse_experiments.Experiment attribute*), 122
val_h3 (*dicee.analyse_experiments.Experiment attribute*), 122
val_h10 (*dicee.analyse_experiments.Experiment attribute*), 122
val_mrr (*dicee.analyse_experiments.Experiment attribute*), 122
val_path (*dicee.query_generator.QueryGenerator attribute*), 154
val_path (*dicee.QueryGenerator attribute*), 206
validate_knowledge_graph() (*in module dicee.sanity_checkers*), 156
vocab_preparation() (*dicee.evaluator.Evaluator method*), 145
vocab_size (*dicee.models.transformers.GPTConfig attribute*), 51
vocab_to_parquet() (*in module dicee*), 188
vocab_to_parquet() (*in module dicee.static_funcs*), 159
vtp_score() (*dicee.LFMult method*), 181
vtp_score() (*dicee.models.function_space.LFMult method*), 36
vtp_score() (*dicee.models.function_space.LFMult1 method*), 35
vtp_score() (*dicee.models.LFMult method*), 98
vtp_score() (*dicee.models.LFMult1 method*), 98

W

weight (*dicee.BytE attribute*), 184
weight (*dicee.models.transformers.BytE attribute*), 47
weight (*dicee.models.transformers.GPT attribute*), 52
weight (*dicee.models.transformers.LayerNorm attribute*), 48
weight_decay (*dicee.BaseKGE attribute*), 186
weight_decay (*dicee.config.Namespace attribute*), 131
weight_decay (*dicee.models.base_model.BaseKGE attribute*), 19
weight_decay (*dicee.models.BaseKGE attribute*), 60, 63, 67, 71, 77, 91, 94
weights (*dicee.models.FMult attribute*), 96
weights (*dicee.models.function_space.FMult attribute*), 33
weights (*dicee.models.function_space.GFMult attribute*), 34
weights (*dicee.models.GFMult attribute*), 96
write_links() (*dicee.query_generator.QueryGenerator method*), 155
write_links() (*dicee.QueryGenerator method*), 207
write_report() (*dicee.Execute method*), 196
write_report() (*dicee.executer.Execute method*), 147

X

x_values (*dicee.LFMult attribute*), 181
x_values (*dicee.models.function_space.LFMult attribute*), 35
x_values (*dicee.models.LFMult attribute*), 98